



## TOWN OF YEMASSEE PLANNING COMMISSION MEETING

**Tuesday, April 4, 2023 - 3:00PM**

**Yemassee Municipal Complex, 101 Town Cir, Yemassee, SC 29945-3363**

---

- I. Call to Order**
- II. Roll Call**
- III. Public Comments**
  - a. Every member of the public who is recognized to speak shall address the Chairman and in speaking, avoid disrespect to the Committee, Staff, and other members of the meeting. State your name and address for the record. Comments are limited to Two (2) Minutes.
- IV. Old Business**
  - a. Approval of the March 7, 2023, Planning Commission Meeting Minutes
- V. Public Hearings**
  - a. **Ironline Metals (Zoning Map Amendment Application):** A request by Conor Blanelly of Ward Edwards, Inc., on behalf of the property owner Ironline Metals, LLC. for approval of a Zoning Map Amendment for approximately 102.4 acres of land located at the intersection of U.S. Highway 17A and Jinks St. The application seeks rezoning of three parcels from their current zonings; 204-01-05-005 (Residential ¼ Acre), 204-01-05-013 (Office Commercial District) and 203-00-00-046 (Conservation Preservation District) to a zoning of Planned Unit Development within the Highway Corridor Overlay District (HCOD).
- II. New Business**
  - a. **Rosalyn Smith (Annexation Request / Initial Briefing):** A request for a recommendation of approval on Request for an Annexation of One Parcel of Land of Approximately 1.39 Acres of land, located on Cochran St and further identified by Hampton County TMS: 198-00-00-095 via the 100% Petition and Ordinance Method with a concurrent Zoning Map Amendment requesting a rezoning from the current zoning of General Development District pursuant to the Hampton County Zoning Ordinance to General Residential (GR) pursuant to the Town of Yemassee Zoning Ordinance.
  - b. **Comprehensive Plan Update** - Matthew Garnes, Town Administrator
- VI. Adjournment**

Colin J. Moore

*Mayor*

Peggy Bing-O'Banner

*Mayor Pro Tempore*

Matthew Garnes

*Town Administrator*



***Council Members***

Alfred Washington

Stacy Pinckney

David Paul Murray

## *Planning Commission Agenda Item*

**Subject:** Consideration of an Ordinance Amending the Town of Yemassee Zoning Map to rezone three parcels of land located near the intersection of U.S. Highway 17A & Jinks St in Hampton County, and further identified by Hampton County Tax Map Numbers: 204-01-05-005, 204-01-05-013 and 203-00-0046 from their respective zonings to Planned Unit Development.

**Meeting Date:** April 4, 2023

**Submitted by:** Matthew Garnes, Town Administrator

### **Attachments:**

	Draft Ordinance		Resolution		Other
√	Support Documents		Motion		

---

**Summary:** Attached is a request for public hearing of a Zoning Map Amendment for the three parcels of land owned by Ironline Metals, LLC. seeking a re-zoning from their current zoning designations to Planned Unit Development. In March, Town Council approved first reading and scheduled a public hearing for the request at their April 2023 meeting. Today, Planning Commission will conduct a Public Hearing on the request. Adjacent property owners have been notified by certified mail, legal notice placed in the newspaper and the property has been posted since March 7, 2023.

### **Recommended Action:**

---

#### **Commission Action:**

- ☐ Approved as Recommended
- ☐ Approved with Modifications
- ☐ Disapproved
- ☐ Tabled to Time Certain





**TOWN OF YEMASSEE**  
**ZONING MAP/TEXT AMENDMENT APPLICATION**

Town of Yemassee

Town of Yemassee  
Attn: Administration Department  
101 Town Circle  
Yemassee, SC 29945-3363  
(843)589-2565 Ext. 3  
www.townofyemassee.org

MAR-2 2023

Received

Applicant		Property Owner	
Name: Ironline Metals		Name: Ironline Metals, LLC	
Phone: 502-315-1722		Phone: 502-315-1722	
Mailing Address: 1515 Ormsby Station Ct. Louisville, KY 40223		Mailing Address: 1515 Ormsby Station Ct. Louisville, KY 40223	
E-mail: tim@ironlinemetals.com		E-mail: tim@ironlinemetals.com	
Town Business License # (if applicable):			
<b>Project Information</b>			
Project Name: Pine Street Development		Acreage: 104.4	
Project Location: NW of the intersection of US Hwy 17A & Jink St.		Comprehensive Plan Amendment    Yes <input checked="" type="checkbox"/> No	
Existing Zoning: Office Commercial District and Residential 1/4 acre		Proposed Zoning: PUD	
Type of Amendment:    Text <input checked="" type="checkbox"/> Map			
Tax Map Number(s): 204-01-05-013, 204-01-05-005, 204-01-05-046			
Project Description: The proposed development is to include a combination of residential and light industrial uses, to provide quality economic development and housing opportunities within the Town of Yemassee.			
<b>Minimum Requirements for Submittal</b>			
<input type="checkbox"/> 1. Two (2) full sized copies and digital files of the maps and/or plans depicting the subject property.			
<input type="checkbox"/> 3. Project Narrative and digital file describing reason for application and compliance with the criteria in Article 8 of the DSO.			
<input type="checkbox"/> 4. An Application Review Fee as determined by the Town of Yemassee Schedule of Rates & Fees. Checks made payable to the Town of Yemassee.			
<b>Note:</b> A Pre-Application Meeting is required prior to Application submittal.			
<b>Disclaimer:</b> The Town of Yemassee assumes no legal or financial liability to the applicant or any third party whatsoever by approving the plans associated with this permit.			
I hereby acknowledge by my signature below that the foregoing application is complete and accurate and that I am the owner of the subject property. As applicable, I authorize the subject property to be posted and inspected.			
Property Owner Signature: <i>Tim Garna</i>		Date: February 8, 2023	
Applicant Signature: <i>Tim Garna</i>		Date: February 8, 2023	
<b>For Office Use</b>			
Application Number: ZONE -03-23-1023		Date Received: 3/7/23	
Received By: M. Garna		Date Approved:	

## **Project Narrative**

**Project:** **Ironline Metals**  
Town of Yemassee, SC

**Date:** February 28, 2023

**Owner:** **Ironline Metals, LLC**  
1515 Ormsby Court  
Louisville, KY 40223

**Parcel:**  
Property ID: 204-01-05-013, 104-01-05-005  
Acreage: 102.4 Acres

### **Existing Conditions**

The existing site is mostly undeveloped, with an existing dirt road bisecting the property. The existing road is Jinks Street off US-17, and turns into Pine Street prior to the intersection of Lacey street.

### **Proposed Construction**

The developer is proposing to add a steel manufacturing facility at the front portion of the property. The subject property has undergone an annexation into the Town of Yemassee limits and rezoned to a PUD to help facilitate the current proposed and forthcoming proposed uses. The existing Jinks Street and Pine Street will be improved with the right-of-way to a full access paved 24' wide road. A new access along US-21 with a deceleration lane is proposed to all a separate means of access to the steel facility for larger truck traffic. Other site infrastructure improvements and proposed to support the steel manufacturing facility, which should encompass approximately 11.9 acres of the overall 102.4 acre site.

### **Tree Removal & Landscaping**

To support the proposed development, some tree removal will be necessary. The proposed layout was designed in a manner to both preserve and accentuate the existing specimen trees onsite. Proposed landscaping can be seen with special attention to screening the proposed facility.

### **Erosion Control**

Erosion control practices for the site will include silt fencing, inlet protection, temporary/permanent seeding, dust control measures, a concrete washout station, and sediment tubes.

### **Wetlands**

Wetlands were identified onsite by an environmental consultant. A minor portion of these wetlands, less than 0.5 acres, is being proposed to be impacted and mitigated for through the USACOE Nationwide program.

### **Phasing**

The Ironline facility is proposed to be completed in a single phase. Future development is to include single family residential development, under a separate submission.

### **Stormwater**

The property currently drains to a large wetland system along the eastern portion of the property. Conveyance ditches help direct offsite stormwater runoff from the western wetland to the mentioned eastern low lying wetland area, ultimately discharging to the Combahee River. A drainage pipe system has been designed to route the western ditch runoff to the eastern outfall around the proposed development. All runoff from the proposed development will drain to a series of dry-detention and wet-detention ponds, to promote pollutant removal and meet the local and state stormwater requirements, prior to discharging along the existing outfall path at a rate less than that of existing conditions.

### **Water & Sewer Utilities**



An existing gravity sewer main runs along Jinks Street and Pine street that has the depth and capacity to accommodate the proposed development.

A water main is proposed along Jinks Street and Pine Street, to connect to the existing water system along US-17 and Lacey Street. The proposed water main connection will be utilized to serve the proposed development.



**TOWN OF YEMASSEE  
PLANNED UNIT DEVELOPMENT  
(PUD) MASTER PLAN APPLICATION**

Town of Yemassee  
Attn: Administration Department  
101 Town Cir  
Yemassee, SC 29945-3363  
(843) 589-2565 Ext. 3  
<http://www.townofyemassee.org>

Applicant		Property Owner	
Name: Ironline Metals, LLC c/o Ward Edwards, Inc.		Name: Ironline Metals, LLC	
Phone: 757-814-0824		Phone: 502-315-1722	
Mailing Address: PO Box 381, Bluffton, SC 29910		Mailing Address: 1515 Ormsby Station Court Louisville KY 40223	
E-mail: cblaney@wardedwards.com		E-mail: tim@ironlinemetals.com	
Town Business License # (if applicable):			
<b>Project Information</b>			
Project Name: Ironline Metals		<input checked="" type="checkbox"/> New	<input type="checkbox"/> Amendment
Project Location: US Hwy 17A to the Southeast, Lacy St to the Southwest, Jenks St intersects		Acreage: 102.4	
PUD Name: Pine Street PUD			
Tax Map Number(s): 204-01-05-013, 204-01-05-005, 204-01-05-046			
Project Description: The developer is proposing to add a steel manufacturing building at the corner of Jenks Street and US-21. The existing Jenks Street would be improved/paved within the right of way at a 24' width, and a new access point along US-21 is proposed for larger truck traffic. Truck access through the building is anticipated to allow for the loading/ unloading of steel/ equipment. The project area is approximately 11.86 acres of the 102.4 acres of land. The remaining portion of uplands is anticipated for a future phase of residential housing.			
<b>Minimum Requirements for Submittal</b>			
<input checked="" type="checkbox"/> 1. Two (2) full sized copies and digital files of the Master Plan. <input checked="" type="checkbox"/> 2. Recorded deed and plat showing proof of property ownership. <input checked="" type="checkbox"/> 3. Project Narrative describing reason for application and compliance with the criteria in the DSO. <input checked="" type="checkbox"/> 4. An Application Review Fee as determined by the Town of Yemassee Schedule of Rates & Fees. Checks made payable to the Town of Yemassee.			
<b>Note:</b> An approved PUD Concept Plan Application is required prior to submittal			
<b>Disclaimer:</b> The Town of Yemassee assumes no legal or financial liability to the applicant or any third party whatsoever by approving the plans associated with this permit.			
I hereby acknowledge by my signature below that the foregoing application is complete and accurate and that I am the owner of the subject property. As applicable, I authorize the subject property to be posted and inspected.			
Property Owner Signature: 		Date: 3/1/23	
Applicant Signature: 		Date: 3/1/23	
<b>For Office Use</b>			
Application Number:		Date Received:	
Received By:		Date Approved:	




## TOWN OF YEMASSEE PLANNED UNIT DEVELOPMENT (PUD) MASTER PLAN APPLICATION PROCESS NARRATIVE

The following Process Narrative is intended to provide Applicants with an understanding of the respective application process, procedures and Development Standards Ordinance (DSO) requirements for obtaining application approval in the Town of Yemassee. While intended to explain the process, it is not intended to repeal, eliminate or otherwise limit any requirements, regulations or provisions of the Town of Yemassee's Development Standards Ordinance. Compliance with these procedures will minimize delays and assure expeditious application review.

<b>Step 1. Approved PUD Concept Plan</b>	<b>Applicant &amp; Staff</b>
Prior to the filing of a Planned Unit Development (PUD) Master Plan Application, the Applicant is required to have received approval of a PUD Concept Plan by the Planning Commission and Town Council.	
<b>Step 2. Application Check-In Meeting</b>	<b>Applicant &amp; Staff</b>
Upon receiving input from Staff after the Concept Plan application, the Applicant shall submit the PUD Master Plan Application and required submittal materials to the Zoning Administrator.	
<b>Step 3. Review by Zoning Administrator &amp; Planning Commission</b>	<b>Staff</b>
If the Zoning Administrator determines that the PUD Master Plan Application is complete, it shall be forwarded to the Planning Commission. The Commission shall review the application and prepare written comments for review with the Applicant.	
<b>Step 4. Planning Commission Meeting (Initial Presentation)</b>	<b>Applicant &amp; Staff</b>
A public meeting shall be held with the Applicant to review the Staff Report and discuss the application. The Applicant will be directed to address any comments, if any, and resubmit the application materials. If applicable, upon resubmittal, the application materials will be reviewed for compliance with the Staff Report and, if all comments are addressed, the application is placed on the next available Planning Commission (PC) Meeting agenda for a Public Hearing.	
<b>Step 5. Planning Commission Meeting (Public Hearing)</b>	<b>Applicant, Staff &amp; Planning Commission</b>
The PC shall review the PUD Master Plan Application for compliance with the criteria and provisions in the DSO. The PC may approve, approve with conditions, or deny the application.	
<b>Step 6. PUD Master Plan Approval</b>	<b>Staff</b>
If the Planning Commission approves the PUD Master Plan Application, the Zoning Administrator shall issue an approval letter to the Applicant.	
<b>Step 7. Invitation to submit Development Plan Application</b>	<b>Staff</b>
After the application is approved by the Planning Commission, the applicant will be provided with a Development Plan Application.	





PROPOSED ZONING  
CHANGE AREA  
ZONE-03-23-1023

The map displays a grid of residential lots in the Ponderosa area. Key streets shown include Ponderosa Dr, Ponderosa Rd, Salka Hachie Rd, Pine St, and Agency St. Most lots are labeled 'Residential' with acreage such as 1/2 Acre or 1 Acre. A large area on the right side of the map is labeled 'General Residential' and 'Ge Re'. The map is oriented with North at the top.

Residential  
1/4 Acre

Office  
Commercial  
District

Residential  
1/4 Acre

Residential  
1/4 Acre

Mixed Use

Residential  
1/4 Acre

Residential  
1/4 Acre  
~~Residential  
1/4 Acre~~

Conservation  
Preservation  
District






**ZONING  
DEPARTMENT**

**PROPOSED  
ZONING  
CHANGE  
AREA**

- LEGEND**
- ROADS
- YEMASSEE ZONING**
- ZONING DESCRIPTION**
- GENERAL RESIDENTIAL
  - MIXED USE
  - OFFICE COMMERCIAL DISTRICT
  - RESIDENTIAL 1/4 ACRE
  - RESIDENTIAL 1/2 ACRE
  - CONSERVATION PRESERVATION DISTRICT
- PARCELS**
- HYDROLOGY**
- LAKE/POND
  - RESERVOIR
  - STREAM/RIVER
- COUNTIES**
- PARCELS
  - PARCELS
- PROPOSED ZONING CHANGE HAMPTON**




**DATE CREATED:**  
3/14/2023

**PREPARED BY:**  
SPATIAL ENGINEERING, INC.

**DATE UPDATED:**  
3/14/2023

**CARTOGRAPHY BY:**  
GOVI HINES, GISP

0 0.02 0.04 0.07  
MILES



**DISCLAIMER:**

The GIS maps and data distributed by the Town of Yemassee are derived from a variety of public and private sector sources considered to be dependable, but the accuracy, completeness, and currency thereof are not guaranteed. The Town of Yemassee makes no warranties, expressed or implied, as to the accuracy, completeness, currency, reliability, or suitability for any particular purpose of information or data contained in or generated from the town's Geographic Information Systems database. Additionally, the Town of Yemassee or any agent, servant, or employee thereof assume no liability associated with the use of this data, and assume no responsibility to maintain it in any matter or form.

Esri, HERE, Garmin, GeoTechnology, Inc., USGS, EPA  
Conservation  
Preservation  
District



PLANNED UNIT DEVELOPMENT  
AND  
***INITIAL MASTER PLAN***

FOR

**PINE STREET**

Town of Yemassee, South Carolina

FOR

**RAMSEY DEVELOPMENT**

BY

**WITMER - JONES – KEEFER, LTD.**

23 PROMENADE STREET, SUITE 201

**DRAFT**

February 28, 2023



**PLANNED UNIT DEVELOPMENT  
AND  
INITIAL MASTER PLAN  
PINE STREET**

**TABLE OF CONTENTS**

**SECTION I – SITE DEVELOPMENT**

A.	The Property	page 1
B.	Planned Unit Development and Development Agreement Process	page 2
C.	Master Plan and Initial Master	page 2
D.	Environmental Protection	page 3
E.	Cultural and Historical Resources	page 4
F.	Water and Sewer Service	page 4
G.	Utility Service	page 4
H.	Roadways and Traffic	page 5
I.	Parking	page 6
J.	Stormwater Management	page 7

**SECTION II - LAND USE**

A.	Introduction and Narrative	page 7
B.	Allowed Land Uses	page 8
C.	Allowed Density	page 8
D.	Definitions of Land Use Terms and Density Terms	page 9

**SECTION III - EXEMPTIONS**

A.	TOWN OF YEMASSEE ZONING ORDINANCE ADOPTED MARCH 9, 2007	page 12
----	---	---------

## LIST OF APPENDICES

Appendix A	Site Location Map
Appendix B	Site Survey and Topography map
Appendix C	Freshwater Wetlands Delineation
Appendix D	USDA Soils Data
Appendix E	Aerial Site Map
Appendix F	USGS Quadrangle Map
Appendix G	FEMA Map
Appendix H	Master Plan and Initial Master Plan
Appendix I	Development Schedule
Appendix J	Intent to serve letters
Appendix K	Traffic Impact Analysis
Appendix L	Water, Sewer and Stormwater Master Plan

DRAFT

## PINE STREET PLANNED UNIT DEVELOPMENT MASTER PLAN

### SECTION I – SITE DEVELOPMENT

#### A. THE PROPERTY

The Pine Street Planned Unit Development (PUD) is located in Yemassee, South Carolina with frontage on Highway 21 / US 17. The tract is located approximately 1 mile north of the Yemassee Hwy and is approximately 104.45 acres. A site location map is provided in Appendix A.

The Pine Street Tract is currently owned by Iron Line Metals (“Owner”), its successors or assigns. The Owner proposes that this property be zoned and developed as a PUD in accordance with the Town of Yemassee Zoning Ordinance (ZO) in effect at the time of submittal to Town of Yemassee. The PUD designation will be utilized to encourage unified planning and development, promote economical and efficient land use, foster a harmonious variety of uses, encourage creative design, and produce a better environment.

The Pine Street Tract (TM# 204-01-05-046, 204-01-05-005, 204-01-05-005, 204-01-05-013); is currently vacant undeveloped land. The property has approximately 700 linear feet frontage on Highway 17/21 to the south and has access from Pine Street to the North. Jinks Road bisects the property connection Highway 17 to Pines street and Old Salkehatchie Highway. A site survey is included as Appendix B. See section I.C. and Appendix H for detail related to the Master Plan.

The property encompasses approximately 104.45 acres which consist of +/-66.95 acres non-jurisdictional freshwater wetlands, and 37.5 acres of upland. The property does not contain any saltwater marsh critical areas and has no frontage on critical areas. The U.S. Army Corps of Engineers (USACE) wetland verification are pending. Appendix C. Preliminary soil data has been evaluated using available on site soil data and USDA soils information. The soils are expected to be acceptable and suitable for the proposed site development. USDA soils data is included as Appendix D.

The **2.5** acres of Pine Street fronting Highway 17/21 is currently zoned **Office Commercial District**; the additional **55.64** acres located in the Town of Yemassee is currently zoned **Single Family Residential ¼ acre District**; and remaining **46.31** acres located in Hampton County is zoned Rural Development. The adjacent land uses to the north is Hampton County Rural Development; to the west are residential properties and Light industrial zoning; and residential property to the east. Pine Street will be

developed in 2-3 phases over an approximately 5 year period. An aerial overlay map of the PUD and surrounding area is included as Appendix E.

Based on a review of the USGS Jasper quadrangle map and preliminary site surveys, site elevations range from approximately 8-38 feet above mean sea level. A portion of the Topo survey is included as Appendix B. The site is currently forested and drainage flows north-east towards the existing wetland A.

Based on a review of FEMA Maps, all of the PUD property occurs outside of a designated flood zone areas A portion of FEMA Map is included as Appendix G.

## **B. PLANNED UNIT DEVELOPMENT(PUD)**

The PUD overlay zone was adopted by the Town of Yemassee Council to *‘encourage flexibility in land planning that will result in improved design, character, and quality of new homogenous and mixed use developments; to promote the most appropriate use of land ; to facilitate the provision of streets and utilities; and to preserve the natural and scenic features and open space.’*

## **C. MASTER PLAN**

Pine Street is an approximately 104.45 acre tract of land located in Town of Yemassee, South Carolina. It is anticipated that the property will be developed over a period of 5 years, in accordance with the Master Plan set forth in this document or amended in the future. The Master Plan sets forth the general scope of the development including number of units, phasing, development standards, open space and other issues. In addition to the Master Plan, development of the property is controlled by other provisions of the PUD. The Master Plan included in Appendix H.

The goal of the development is to provide quality economic development and housing opportunities within the Town of Yemassee. PUD designation is necessary to accommodate the mix of land uses and provide for the responsible planning and development of the property over time.

The Pine Street Master Plan, prepared by Witmer-Jones-Keefer, shows a general access locations and areas designated for Light Industrial and Residential Development. Proposed land uses in the Light Industrial and Residential development areas are detailed under Section 2 - Land Use Designation and Definitions.

The Pine Street PUD property is a 104.45 acre property with 11.48 acres Light Industrial Tract ‘1’; 46.5 acre Residential Tract ‘2-3’ and 46.31 acres Wetland preservation Tract 4.

Appropriate buffers shall be provided between incompatible land uses. Buffer widths shall meet the required of the latest adopted version of the Town of Yemassee Zoning Ordinance (ZO).

Development is planned to occur in accordance with the Development Schedule presented in Appendix I which is preliminary and subject to change based on market conditions.

The proposed Master Plan will maintain open space requirements per Town of Yemassee zoning ordinance. The open space and amenities will be owned and maintained in the manner approved with appropriate covenants and restrictions by the developer, homeowner's association, or other legally designated entity. Property deeded to a governmental entity becomes the maintenance responsibility of that entity.

Activities along any external property lines of the PUD shall conform to the setback, buffer, screening as described in Section II.D.3 of the PUD. Height requirements shall conform to the latest adopted version of the Town of Yemassee Zoning Ordinance (ZO)

The Master Plan constitute a request for a waiver from the current Town of Yemassee ZO . However, activities in the PUD shall conform to all other Town of Yemassee Ordinances and Regulations where differences do not occur.

The provisions of the Master Plan shall apply to development in the Pine Street PUD. In the event of a conflict, the hierarchy of documents is the following: 1) PUD and Master Plan; 2) Town of Yemassee ZO and LDR in effect at the time of Final Adoption of the Pine Street PUD.

The attached Initial Master Plan provides additional detail related to street network, Open spaces, storm water management and conceptual utility layout. The Master Plan is consistent with the vision for the Pine Street PUD.

#### **D. ENVIRONMENTAL PROTECTION**

Environmental protection is a priority for the Applicant. As part of the development process, Pine Street developers will meet or exceed the stormwater management requirements of the Town of Yemassee ZO /Stormwater Regulations and the South Carolina Department of Health's Office of Ocean and Coastal Resource Management (OCRM).

Pine Street developers will prepare stormwater management plans for the tracts of land as they are developed. The plan will address the hydrological characteristics of the site as well as predevelopment conditions and post-development stormwater management facilities for flood control and sediment reduction.

Freshwater wetlands on the property are typical of the South Carolina Lowcountry. Approximately 66.95 percent of the site is non-jurisdictional freshwater wetlands. A plat indicating the freshwater wetlands on the property is included in Appendix C.

On-site wetland impacts resulting from the development of the Pine Street PUD will be permitted jointly through the USACE and OCRM. All impact mitigation will be accomplished through a combination of buffers and preservation of jurisdictional wetlands located on the property and will meet or exceed state and/or federal standards.

#### **E. CULTURAL AND HISTORICAL RESOURCES**

As part of the comprehensive study of the property, a preliminary assessment of the cultural and historical resources on the site will be prepared prior to submittal of a development plan for each of the tracts. As part of Master Plan Approval and prior to final design, the South Carolina Department of Archives and History will be contacted by the Owner to request a review of the Department's cultural resource inventory database. The Owner will follow the direction and procedures of the Department of Archives and History as appropriate and if necessary, will address all cultural resource issues with the State Historic Preservation Office. A final determination will be provided as part of Master Plan Approval.

#### **F. WATER AND SEWER SERVICE**

Water and sewer service will be provided to Pine Street by Town of Yemassee Water and Sewer Department (YW&S). Detailed planning for the water and sewer systems will commence at the time of PUD approval by Town of Yemassee. The Owner will coordinate Water and Sewer service with YW&S. YW&S will operate and maintain the water and sewer systems within their service area upon completion by the developer and acceptance by the Authority.

#### **G. UTILITY SERVICE**

Pine Street is within the service territory of Dominion Energy for electrical power. The Owner will coordinate with Dominion Energy regarding planning for the PUD.

Palmetto Rural Telephone Cooperative is able to provide telephone service to Pine Street. The Owner will coordinate with Palmetto Rural Telephone Cooperative regarding planning for the PUD.

Other utility services may be provided by legally established entities at the discretion of the Owner, provided such are in accordance with applicable franchising ordinances and licensing requirements of Town of Yemassee. See appendix J for Utility intent to serve letters.

## **H. ROADWAYS AND TRAFFIC**

Pine Street has frontage on SC Highway 17/21 to the south and access to Jinks Road to the north. Establishing safe and reasonable ingress and egress for the property is a priority for the Owner, South Carolina Department of Transportation (SCDOT), and Town of Yemassee. Full access shall be defined as access which allows any and all possible vehicular traffic movements into and out of the development. Limited access shall be defined as access which limits the movement of traffic into and out of a development (i.e., right-in, right-out). Any proposed roadway improvements shall be subject to approval by Town of Yemassee and, where appropriate, the SCDOT.

The Master Plan provides locations for potential internal access points for future interconnectivity.

As part of the access management plan for the project, the Owner will work with SCDOT and Town of Yemassee to obtain two access points from Highway 17/21; one access off Pine Street and one possible access point off Lacey Street. All proposed access points will be consistent with the Town of Yemassee and SCDOT Highway Management Access Plans and design criteria. These accesses may be relocated to accommodate traffic patterns, site specific characteristics and adjacent land uses as part of the access management plan.

Roads indicated on the Master Plan are subject to modification at the time of Development Plan approval based upon specific soil conditions, environmental concerns, physical constraints and design parameters.

The access point locations described above and shown on the Master Plan are preliminary and may be relocated during final development plans. Planning, design and construction of these accesses as well as all roadways and transportation elements shall be in accordance with SCDOT standards, Town of Yemassee Ordinances, PUD standards, or other engineering standards reasonably acceptable to the County engineer. Typical roadway sections will be submitted for review at the Development Plan approval stage.

Potential access across the jurisdictional wetlands surrounding adjacent tracts may be allowed if approved by OCRM and the USACE. Road linkages to adjacent properties may include impacts to jurisdictional wetlands.

Notwithstanding other provisions of this document and subject to approval by Town of Yemassee, roadway design standards may be modified to reduce environmental impacts and increase tree preservation provided safety concerns are not compromised. Protection and preservation of significant trees will be encouraged. Reductions of roadway and right-of-way widths may not occur unless specifically authorized by the County.

A traffic impact analysis (TIA) is included as exhibit K. The TIA indicated the following : *The results of the analysis indicate that the study intersections currently operate and are expected to continue to operate at an acceptable level of service with the proposed Pine Street Residential development.*

*Per the criteria documented in Section 5D-4 of SCDOT's Access and Roadside Management Standards (ARMS, 2008), exclusive turn lanes are not recommended at any of the study intersections or project driveways.*

#### **I. PARKING**

The total number of required parking spaces for all land uses allowed herein shall conform to the Town of Yemassee ZO in effect at the time of Final Adoption of the Pine Street PUD. Modulation of those standards may be allowed provided the applicant furnishes actual documentation that the new proposed standard meets the parking needs of the proposed land use and the Town agrees at Master Plan approval.

#### **J. STORMWATER MANAGEMENT**

Pine Street PUD shall conform to the Town of Yemassee ZO and Stormwater Management Ordinance in effect at the time of Master Plan approval for the Pine Street PUD as well as all other applicable state and federal requirements. Sufficient stormwater best management practices will be employed in the development of the PUD to ensure runoff leaving the site does not degrade water quality within surrounding wetlands and the receiving waterways. The Stormwater Master Plan is included with appendix L.



## SECTION II – LAND USE

### A. INTRODUCTION AND NARRATIVE

The Pine Street PUD has a total area of 104.45 acres, including 65.92 acres of non-jurisdictional freshwater wetlands, as indicated on the Master Plan.

The Master Plan consists of the following land use areas:

List types of proposed uses:

Approximately 11.48 upland acres are intended for Light Industrial use, approximately 46.51 upland acres are intended for residential uses and 46.31 upland acres are intended for wetland preservation, community open space use and stormwater management.

The Light Industrial includes warehouse / production space and future expansion space. (Including Manufacture light gauge steel framing products including steel studs for residential and commercial buildings).

Of the residential units, initial plans include single family homes.

The land use areas indicated on the Master Plan are not intended to be rigid exact boundary lines for future land use and improvements. The Master Plan for the Pine Street PUD shall maintain flexibility to accommodate specific soil conditions, environmental conditions, pedestrian friendly requirements, physical constraints, market conditions and design parameters and as such, the exact location of boundary lines between land uses and their subsequent location and size indicated within the planning area shall be subject to change at the time Development Permit Plan(s) are submitted for development; provided, however, that maximum densities and other conditions of this PUD between the Owner and Town of Yemassee, South Carolina, will be strictly adhered to, unless adjustment is requested by the Owner and approved by the Town of Yemassee. The boundaries of the PUD may be modified to include adjacent acreage subject to the approval of Town of Yemassee by appropriate petition/application to the County to amend the PUD.

## **B. ALLOWED LAND USES**

The following land uses shall be permitted in the Pine Street PUD. The purpose of this portion of the PUD document is to state which land uses shall be allowed within the Pine Street PUD; however, by allowing these uses this does not obligate the developer to provide the uses or facilities stated herein.

The following land uses and definitions shall be permitted in the Pine Street PUD:

List types of proposed uses:

**Tract 1** : Light Industrial (+/-11.48 acres)

**Tract 2-3**: SFR ¼ Acre District (+/-46.5 acres)

**Tract 4**: Wetland Preservation (+/- 46.31 acres)

Any easement that occurs within the property shall have the same land uses as any of the adjacent land uses. Any restrictions shall be based on the legal definition of the easement.

Design Regulations and Performance Standards will be established for each area at the time of the Master Plan approval. Unless otherwise agreed at Master Plan approval or in this PUD, the standard for uses and design criteria from the Town of Yemassee ZO will apply.

## **C. ALLOWED DENSITY**

Of the approximately 104.45 upland acres, the Master Plan for the Pine Street PUD consists of approximately 11.48 acres of Light Industrial and approximately 46.5 acres of Residential uses. The Master Plan may be modified at Master Plan approval, taking into consideration the potential need to change the exact locations of the proposed use(s) in order to address traffic considerations and in response to market conditions.

The overall Commercial use density within Tract 1 for the PUD shall not exceed total build-out cap of 200,000 square feet of light industrial or commercial space.

The Pine Street PUD is planned to include a maximum of 107 residential units, which is based on a unit density of 4 units/upland acre for Parcels 2 and 3. Overall residential density shall include both Attached and Detached Single-Family Residential. Detached guesthouses, “Mother-in-Law” Apartments, and Garage Apartments (for rent or not) on the same lot with a single family unit will be allowed as one structure per lot. The Initial Master Plan is included as appendix H.

## **D. DEFINITIONS OF LAND USE TERMS AND DENSITY TERMS**

In the absence of a term definition in this Master Plan, the definitions of the Town of Yemassee Zoning Ordinance shall apply in the interpretation of this Master Plan. The definitions below shall generally describe the allowed uses within the PUD.

### **1. Tract 1 – Light Industrial District (LID)**

5.8.1 The purpose of this District is to provide a suitable environment for and enhancing the locational flexibility of uses generally classified as research and development, assembly, high technology production, precision manufacturing, and light industry by excluding heavy manufacturing and permitting only those cleaner industries and operations which tend to be less objectionable to the community; and by requiring high performance standards and

Permitted Uses as outlined in the Town of Yemassee Zoning Ordinance section 5.8.1

### **2. Tract 2-3 – Single-Family Residential 1/4 Acre [SF]**

5.4 Single-Family Residential District 1/4 Acre is designed to provide for, homogeneous residential purposes. The intent of the District is to provide areas primarily for single-family detached dwellings, and to discourage any encroachment by uses which may be incompatible with such residential use.

Permitted Uses as outlined in the Town of Yemassee Zoning Ordinance section 5.4.1

### **3. Setbacks and Buffers**

Setbacks and buffers required by the zoning district shall apply according to the Zoning Ordinance if and when necessary. All other buffers and setbacks shall be maintained as described below:

#### **a. Setbacks and buffer standards within the Pine Street PUD shall include:**

1. Minimum buffer strips of ten (10) feet shall be maintained along all external dimensions of a PUD.

2. Buffer strips shall be in addition to the required external setback. In effect there shall be a minimum thirty (30) feet of total setbacks with the required buffer.

3. No development, parking areas, structures, or accessory buildings, except the required fence and vegetation, shall be placed in the buffer area. Buffer strips shall include vegetative cover and be maintained regularly. In addition, no development, parking areas, structures, or accessory buildings shall be placed in the setback areas.

4. The buffer shall include a vegetative screen of evergreen trees and/or shrubs that will reach six (6) feet in height within twelve (12) months of installation and form a contiguous screen within two (2) years of installation.

5. The Town of Yemassee reserves the right, if it finds substantial needs for screening of the proposed PUD activity, to include within the buffer a six (6) foot high fence made of either brick, finished concrete, mortar, wood, stone, masonry units, or a combination of the above. The fence shall be fronted by the required vegetative screen.

6. The frontline of the required side yard buffer shall begin where the private property line and the public right-of-way intersect and extend to the rear lot line. The required vegetative screen and the fence, if required, shall begin twenty (20) feet from where the private property line and the public right-of-way intersect and extend to the rear lot line.

7. Required rear yard buffer strips and the fence, if required, shall extend the entire length of the rear lot line.

8. See HCOD standards 5.17.8B (Town of Yemassee Zoning ordinance) for Buffer Requirements along the Highway 17 corridor.

#### 4. Signage Control

Signage for the Pine Street PUD shall be governed by the Town of Yemassee ZO in effect at the time of the submission of final development plans or as herein contained.

#### 5. Wetlands

This designation allows the following uses within wetlands. Freshwater wetlands on the property shall be those areas over which the applicable governmental agencies claim jurisdiction for freshwater wetlands. Unless restricted via a future Memorandum of Agreement (MOA) to the contrary, the following are permitted uses:

##### a. Buffers

- b. Conservation areas
- c. Activities in all wetland areas as permitted by the USACE and OCRM
- d. Disposal of reclaimed water as permitted by SCDHEC
- e. Stormwater management and recreational lakes
- f. Boardwalks, trails, bridges and other permitted structures
- g. Game Management

## 6. Utilities

This designation allows for utility service to serve the planned tracts of the Pine Street PUD. Utility types and facilities not germane to the development will be subject to review by the Planning Commission as part of the Master Plan review process. The following land uses shall be allowed:

- a. Potable water supply and distribution
- b. Wastewater collection, treatment and disposal
- c. Stormwater collection, treatment and detention
- d. Irrigation
- e. Communication towers (except in residential land use areas)
- f. Satellite antennas
- g. Cable television facilities
- h. Telephone facilities
- i. Power transmission and distribution
- j. Fiber optic lines
- k. Other utility services (i.e., Internet access and other telecommunication uses)

Certain community-wide infrastructure is required for the development of any large, master-planned community. This infrastructure may include, but is not limited to the following:

- a. Arterial streets and primary access roads
- b. Water supply
- c. Wastewater treatment and effluent disposal
- d. Power substations
- e. Central telephone facilities
- f. Stormwater management lagoons
- g. Natural gas supply

In the case of this Master Plan, the community-wide infrastructure may serve more than one planning tract. Infrastructure serving the community (on-site and off-site) will be approved as part of the Master Plan approval process. Infrastructure projects must receive a Town of Yemassee Development Permit prior to construction.

## SECTION III – CHANGES AND EXEMPTIONS

The Planned Unit Development constitute a request for a waiver from the current Town of Yemessee Zoning Ordinance where differences occur. However, activities in the PUD shall conform to all other Town of Yemessee Ordinances and Regulations where differences do not occur. The PUD may introduce land uses that do not exist in the current Zoning Ordinance. Based on the PUD, Pine Street requests deviations from the Zoning Ordinance.

The provisions of the PUD shall apply to development in the Pine Street PUD. In the event of a conflict, the hierarchy of documents is the following: 1) PUD; 2) Town of Yemessee Zoning Ordinance in effect at the time of Final Adoption of the Pine Street PUD.

The following clarifications or modifications to otherwise applicable standards of the Yemessee Zoning Ordinance are hereby made applicable to the Pine Street PUD:

### **Modification 1:**

Section 5.8

Light Industrial District [LID]

A. All permitted and conditional uses in the Regional Commercial District subject to the same conditions apply in the District;

Add

**20. Manufacture light gauge steel framing products including steel studs for residential and commercial buildings.**

### **Modification 2:**

5.8.5 General Requirements.

A. Minimum lot size is ~~twenty-five (25)~~ **ten (10)** acres.

C. Industrial uses shall be setback a minimum of ~~fifty (50)~~ **twenty five (25)** feet from any commercial use; ~~one hundred (100)~~ **seventy five (75)** feet from a major thoroughfare; and fifty (50) feet from another industrial use.

### **Modification 3:**

**Section 5.4 Single-Family Residential 1/4 Acre [SF]**

5.4.1 Standards for the SF District

Maximum density: ~~Three Four (4)~~ dwelling units per acre.

Minimum lot size: ~~10,890~~ **6000** square feet per dwelling unit.

Minimum front yard setback: ~~Fifteen (15)~~ **Ten (10)** feet from the street right-of-way line.

Minimum side yard setbacks: ~~Ten (10)~~ **Five (5)** feet from lot lines.

**Modification 4:**

**Section 5.17 Highway Corridor Overlay District [HCOD]**

**5.17.5** A minimum distance of ~~one thousand five hundred (1,500)~~ **four hundred (400) feet** shall be maintained between all access points onto the corridor, including private driveways, roads, and public right-of-way. Spacing will be measured from the midpoint of each driveway. If the existence of jurisdictional wetlands precludes compliance with this provision, the Planning Commission shall have discretion as to the placing of an alternative access point; however, no additional curb cuts on the subject parcel should result from having the alternative access point.

**5.17.6 D.** The minimum lot width at the building setback line for newly created parcels shall be a distance of one hundred fifty (150) feet. Newly created parcels are subject to the ~~one thousand five hundred (1,500)~~ **four hundred (400) foot** distance requirement between access points from the highway.

**5.17.7** In addition to the existing standards of the Town of Yemassee Zoning Ordinances regarding subdivisions, the following requirements pertain to the HCOD:

- A. Newly created subdivisions are subject to the ~~one thousand five hundred (1,500)~~ **four hundred (400) foot** distance requirement between access points from the highway;
- B. No subdivision of land which would create parcels fronting on the highway shall be approved unless it is established prior to subdivision approval how access will be provided to each parcel in compliance with the ~~one thousand five hundred (1,500)~~ **four hundred (400)** distance requirement, (i.e., frontage roads, shared access drives, and others);

*\*Draft format for review ; additional clarifications and modifications to be included with final approval documents based on feed back from Planning Commission, Town Council, Town Staff and the Applicant.*


## APPENDIX A

### SITE LOCATION MAP

DRAFT



APPENDIX A  
SITE LOCATION MAP




PROJECT SITE



## APPENDIX B

### SITE SURVEY

# DRAFT



LOCATION MAP

NOTES

THIS PLAT DOES NOT CERTIFY THAT THE INFORMATION SHOWN HEREON COMPLIES WITH LOCAL ZONING REGULATIONS. THIS PLAT DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF OVERLAY DISTRICTS OR SPECIAL HAZARD AREAS SUCH AS BUT NOT LIMITED TO AIRPORT AND AICUZ ZONES.

THIS PLAT REPRESENTS CONDITIONS FOUND ON 4/1/2022 AND DOES NOT REPRESENT CONDITIONS FOUND ON ANY OTHER DATE.

THIS PLAT WAS SURVEYED BASED ON REFERENCED DOCUMENTS AND WAS NOT SURVEYED IN COORDINATION WITH A TITLE EXAMINATION. THE SURVEYOR DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF EASEMENTS.

THE AREA CALCULATIONS SHOWN HEREON WERE DETERMINED BY THE COORDINATE METHOD.

THE PRESENCE OR ABSENCE OF REGULATED NATURAL RESOURCES (SUCH AS, BUT NOT LIMITED TO, CRITICAL AREAS, FRESHWATER WETLANDS, SPECIMEN TREES, AND HISTORICALLY SIGNIFICANT SITES AND CULTURAL RESOURCES) WAS NOT DETERMINED AT THIS TIME OTHER THAN THOSE SHOWN HEREON AND ACCOMPANIED BY THE CERTIFICATION OR APPROVAL OF APPROPRIATE REGULATORY AGENCY.

THIS PLAT DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF UNDERGROUND FEATURES, (INCLUDING, BUT NOT LIMITED TO UTILITIES, STORAGE TANKS, AND SIMILAR).

THE VERTICAL DATUM FOR FLOOD ZONE INFORMATION AND TOPOGRAPHY IS NAVD 1988 AND WAS DETERMINED USING THE SC VRS NETWORK.

ZONING AND SETBACKS WERE NOT DETERMINED AT THIS TIME



AREA TABLE			
Description	Perimeter	Sq. Feet	Acres
AREA A	6,698.26	2,017,285.51	46.31
AREA B	7,818.71	1,824,771.31	41.89
AREA C	4,206.48	596,822.44	13.70
AREA D	1,380.30	108,808.70	2.50
Total		4,547,687.95	104.40

LINE	BEARING	DISTANCE
L1	S 54°02'11" W	119.41'
L2	N 38°18'44" W	245.26'
L3	S 54°42'38" E	194.73'
L4	N 43°12'39" W	208.73'
L5	S 50°45'40" W	183.01'
L6	S 60°26'56" W	50.00'
L7	S 60°26'56" W	113.82'
L8	N 48°49'06" E	209.73'
L9	N 40°27'17" W	46.59'
L10	N 40°17'13" W	188.93'
L11	S 44°28'53" E	131.17'
L12	S 49°42'44" W	278.85'
L13	N 85°17'14" W	47.50'
L14	N 40°27'17" W	28.68'
L15	N 44°27'15" W	147.62'
L16	N 43°09'46" W	270.15'
L17	N 40°17'13" W	178.04'
L18	N 60°40'02" E	63.84'
L19	N 29°20'29" W	244.09'
L20	S 29°24'03" E	243.34'
L21	N 59°36'52" E	50.25'
L22	N 29°20'15" W	146.49'
L23	N 29°33'44" W	7.70'

WETLANDS AREA TABLE			
Description	Perimeter	Sq. Feet	Acres
Ditch A	294.59	1,352.19	0.03
Ditch B	1,186.4	7,907	0.18
Ditch C	1,682.5	9,786	0.22
Ditch D	1,499.7	11,460.52	0.26
Ditch E	2,034.71	13,461.15	0.31
Wetland A	8,468.70	2,717,817.99	62.39
Wetland B	172.52	1,661.23	0.04
Wetland C	1,241.41	33,650.55	0.77
Wetland D	433.22	8,261.57	0.19
Wetland E	1,362.85	105,202.51	2.42
Wetland F	295.51	4,680.65	0.11
Total		2,916,081.36	66.92

AREA TABLE			
AREA	TOTAL ACREAGE	SQ. FEET	WETLANDS ACREAGE
A	46.31	2,017,285.51	46.31
B	33.96	1,479,297	17.00
C	12.70	553,115	2.42
D	2.50	108,809	0.00
E	1.00	43,567	0.11
F	7.98	347,487	0.19

AREA TABLE			
Description	Perimeter	Sq. Feet	Acres
AREA A	6,698.26	2,017,285.51	46.31
AREA B	7,818.71	1,824,771.31	41.89
AREA C	4,206.48	596,822.44	13.70
AREA D	1,380.30	108,808.70	2.50
Total		4,547,687.95	104.40





FLOOD ZONE DETERMINATION

FLOOD ZONE (BFE)-A (BFE=NOT DETERMINED) AND X  
COMMUNITY NAME: HAMPTON CO. UN INCORP./TOWN OF YEMASSEE  
COMMUNITY #: 450095 / 450103  
MAP #: 45049C0450C  
PANEL #: 450.02.550  
PANEL DATE: SEPTEMBER 29, 2010  
INDEX DATE: SEPTEMBER 29, 2010

THIS FLOOD ZONE DETERMINATION IS APPROXIMATE AND SHOULD BE VERIFIED BY THE APPROPRIATE BUILDING CODES OFFICE BEFORE ANY DESIGN OR CONSTRUCTION BEGINS.

I HEREBY CERTIFY TO RAMSEY DEVELOPMENT THAT TO THE BEST OF MY KNOWLEDGE, INFORMATION, AND BELIEF, THE SURVEY SHOWN HEREON WAS MADE IN ACCORDANCE WITH THE REQUIREMENTS OF THE MINIMUM STANDARDS MANUAL FOR THE PRACTICE OF LAND SURVEYING IN SOUTH CAROLINA, AND MEETS OR EXCEEDS THE REQUIREMENTS FOR A CLASS "C" SURVEY AS SPECIFIED THEREIN. ALSO THERE ARE NO ENCROACHMENTS OR PROJECTIONS AFFECTING THE PROPERTY OTHER THAN THOSE SHOWN.




BOUNDARY SURVEY OF  
CORBETT TRACT  
TAX PARCELS 204-01-05-005 AND 203-00-00-046  
YEMASSEE, HAMPTON COUNTY, SOUTH CAROLINA  
PREPARED FOR RAMSEY DEVELOPMENT

JOB # 6024

FIELD BOOK:	ELECTRONIC
FIELD CREW:	LE/PW
DRAFTER:	LE/PW
DATE OF FIELDWORK:	04/01/2022
REFERENCES	PB 21 PG 417 PB 3 PG 127 DB 484 PG 261
	PB 32 PG 4 PB 14 PG 64
	PB 5 PG 96 PB 3 PG 157

LAND CONSULTING GROUP, LLC  
POST OFFICE DRAWER 1366  
BEAUFORT, SOUTH CAROLINA 29901-1366  
(843) 575-5206





LOCATION MAP

NOTES

THIS PLAT DOES NOT CERTIFY THAT THE INFORMATION SHOWN HEREON COMPLIES WITH LOCAL ZONING REGULATIONS. THIS PLAT DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF OVERLAY DISTRICTS OR SPECIAL HAZARD AREAS SUCH AS BUT NOT LIMITED TO AIRPORT AND AICUZ ZONES.

THIS PLAT REPRESENTS CONDITIONS FOUND ON 4/1/2022 AND DOES NOT REPRESENT CONDITIONS FOUND ON ANY OTHER DATE.

THIS PLAT WAS SURVEYED BASED ON REFERENCED DOCUMENTS AND WAS NOT SURVEYED IN COORDINATION WITH A TITLE EXAMINATION. THE SURVEYOR DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF EASEMENTS.

THE AREA CALCULATIONS SHOWN HEREON WERE DETERMINED BY THE COORDINATE METHOD.

THE PRESENCE OR ABSENCE OF REGULATED NATURAL RESOURCES (SUCH AS, BUT NOT LIMITED TO, CRITICAL AREAS, FRESHWATER WETLANDS, SPECIMEN TREES, AND HISTORICALLY SIGNIFICANT SITES AND CULTURAL RESOURCES) WAS NOT DETERMINED AT THIS TIME OTHER THAN THOSE SHOWN HEREON AND ACCOMPANIED BY THE CERTIFICATION OR APPROVAL OF APPROPRIATE REGULATORY AGENCY.

THIS PLAT DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF UNDERGROUND FEATURES, (INCLUDING, BUT NOT LIMITED TO UTILITIES, STORAGE TANKS, AND SIMILAR).

THE VERTICAL DATUM FOR FLOOD ZONE INFORMATION AND TOPOGRAPHY IS NAVD 1988 AND WAS DETERMINED USING THE SC VRS NETWORK.

ZONING AND SETBACKS WERE NOT DETERMINED AT THIS TIME



AREA TABLE			
Description	Perimeter	Sq. Feet	Acres
AREA A	6,698.26	2,017,285.51	46.31
AREA B	7,818.71	1,824,771.31	41.89
AREA C	4,206.48	596,822.44	13.70
AREA D	1,380.30	108,808.70	2.50
Total		4,547,687.95	104.40

LINE	BEARING	DISTANCE
L1	S 54°02'11" W	119.41'
L2	N 38°18'44" W	245.26'
L3	S 54°42'38" E	194.73'
L4	N 43°12'39" W	208.73'
L5	S 50°45'40" W	183.01'
L6	S 60°26'56" W	50.00'
L7	S 60°26'56" W	113.82'
L8	N 48°49'06" E	209.73'
L9	N 40°27'17" W	46.59'
L10	N 40°17'13" W	188.93'
L11	S 44°28'33" E	131.17'
L12	S 49°42'44" W	278.85'
L13	N 85°17'14" W	47.50'
L14	N 40°27'17" W	28.68'
L15	N 44°27'15" W	147.62'
L16	N 43°09'46" W	270.15'
L17	N 40°17'13" W	178.04'
L18	N 60°40'02" E	63.84'
L19	N 29°20'29" W	244.09'
L20	S 29°24'03" E	243.34'
L21	N 59°36'32" E	50.25'
L22	N 29°20'15" W	146.49'
L23	N 29°33'44" W	7.70'

WETLANDS AREA TABLE			
Description	Perimeter	Sq. Feet	Acres
Ditch A	294.59	1,352.19	0.03
Ditch B	1,186.4	7,907	0.18
Ditch C	1,682.5	9,786	0.22
Ditch D	1,499.7	11,460.52	0.26
Ditch E	2,034.71	13,461.15	0.31
Wetland A	8,468.70	2,717,817.99	62.39
Wetland B	172.52	1,661.23	0.04
Wetland C	1,241.41	33,650.55	0.77
Wetland D	433.22	8,261.57	0.19
Wetland E	1,362.85	105,202.51	2.42
Wetland F	295.51	4,680.65	0.11
Total		2,916,081.36	66.92

AREA TABLE			
AREA	TOTAL ACREAGE	SQ. FEET	WETLANDS ACREAGE
A	46.31	2,017,286	46.20
B	33.96	1,479,297	17.00
C	12.70	553,115	2.42
D	2.50	108,809	0.00
E	1.00	43,567	0.11
F	7.98	347,487	0.19

AREA TABLE			
Description	Perimeter	Sq. Feet	Acres
AREA A	6,698.26	2,017,285.51	46.31
AREA B	7,818.71	1,824,771.31	41.89
AREA C	4,206.48	596,822.44	13.70
AREA D	1,380.30	108,808.70	2.50
Total		4,547,687.95	104.40







## APPENDIX C

### FRESHWATER WETLANDS DELINEATION

# DRAFT





FLOOD ZONE DETERMINATION

FLOOD ZONE (BFE): A (BFE=NOT DETERMINED) AND X  
COMMUNITY NAME: HAMPTON CO. UN. INCORP./TOWN OF YEMASSEE  
COMMUNITY #: 450035 / 450103  
MAP #: 4504300450C  
PANEL #: 450 OF 550  
PANEL DATE: SEPTEMBER 29, 2010  
INDEX DATE: SEPTEMBER 29, 2010  
THIS FLOOD ZONE DETERMINATION IS APPROXIMATE AND SHOULD BE VERIFIED BY THE APPROPRIATE BUILDING CODES OFFICE BEFORE ANY DESIGN OR CONSTRUCTION BEGINS.

I HEREBY CERTIFY TO RAMSEY DEVELOPMENT THAT TO THE BEST OF MY KNOWLEDGE, INFORMATION, AND BELIEF, THE SURVEY SHOWN HEREON WAS MADE IN ACCORDANCE WITH THE REQUIREMENTS OF THE MINIMUM STANDARDS MANUAL FOR THE PRACTICE OF LAND SURVEYING IN SOUTH CAROLINA, AND MEETS OR EXCEEDS THE REQUIREMENTS FOR A CLASS "C" SURVEY AS SPECIFIED THEREIN, ALSO THERE ARE NO ENCROACHMENTS OR PROJECTIONS AFFECTING THE PROPERTY OTHER THAN THOSE SHOWN.

LORICK V. FANNING, PLS 19882




WETLANDS SURVEY OF  
CORBETT TRACT  
TAX PARCELS 204-01-05-005 AND 203-00-00-046  
YEMASSEE, HAMPTON COUNTY, SOUTH CAROLINA  
PREPARED FOR RAMSEY DEVELOPMENT  
SHEET 2 OF 2

JOB # 6024

FIELD BOOK: ELECTRONIC  
FIELD CREW: LF/PW  
DRAFTER: LF/PW  
DATE OF FIELDWORK: 04/01/2022  
REFERENCES  
PB 21 PG 417 PB 3 PG 127 DB 484 PG 261  
PB 32 PG 4 PB 14 PG 64  
PB 5 PG 96 PB 3 PG 157

LAND CONSULTING GROUP, LLC  
POST OFFICE DRAWER 1366  
BEAUFORT, SOUTH CAROLINA 29901-1366  
(843) 575-5206



LOCATION MAP

## NOTES

THIS PLAT DOES NOT CERTIFY THAT THE INFORMATION SHOWN HEREON COMPLIES WITH LOCAL ZONING REGULATIONS. THIS PLAT DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF OVERLAY DISTRICTS OR SPECIAL HAZARD AREAS SUCH AS BUT NOT LIMITED TO AIRPORT AND AICUZ ZONES.

THIS PLAT REPRESENTS CONDITIONS FOUND ON 4/1/2022 AND DOES NOT REPRESENT CONDITIONS FOUND ON ANY OTHER DATE.

THIS PLAT WAS SURVEYED BASED ON REFERENCED DOCUMENTS AND WAS NOT SURVEYED IN COORDINATION WITH A TITLE EXAMINATION. THE SURVEYOR DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF EASEMENTS.

THE AREA CALCULATIONS SHOWN HEREON WERE DETERMINED BY THE COORDINATE METHOD.

THE PRESENCE OR ABSENCE OF REGULATED NATURAL RESOURCES (SUCH AS, BUT NOT LIMITED TO, CRITICAL AREAS, FRESHWATER WETLANDS, SPECIMEN TREES, AND HISTORICALLY SIGNIFICANT SITES AND CULTURAL RESOURCES) WAS NOT DETERMINED AT THIS TIME OTHER THAN THOSE SHOWN HEREON AND ACCOMPANIED BY THE CERTIFICATION OR APPROVAL OF APPROPRIATE REGULATORY AGENCY.

THIS PLAT DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF UNDERGROUND FEATURES, (INCLUDING, BUT NOT LIMITED TO UTILITIES, STORAGE TANKS, AND SIMILAR).

THE VERTICAL DATUM FOR FLOOD ZONE INFORMATION AND TOPOGRAPHY IS NAVD 1988 AND WAS DETERMINED USING THE SC VRS NETWORK.

ZONING AND SETBACKS WERE NOT DETERMINED AT THIS TIME

AREA TABLE			
Description	Perimeter	Sq. Feet	Acres
AREA A	6,698.26	2,017,285.51	46.31
AREA B	7,818.71	1,824,771.31	41.89
AREA C	4,206.48	596,822.44	13.70
AREA D	1,380.30	108,808.70	2.50
Total		4,547,687.95	104.40

LINE	BEARING	DISTANCE
L1	S 54°02'11" W	119.41'
L2	N 38°18'44" W	245.26'
L3	S 54°42'38" E	194.73'
L4	N 43°12'39" W	208.73'
L5	S 50°45'40" W	183.01'
L6	S 60°26'56" W	50.00'
L7	S 60°26'56" W	113.82'
L8	N 48°49'06" E	209.73'
L9	N 40°27'17" W	46.59'
L10	N 40°17'13" W	188.93'
L11	S 44°28'33" E	131.17'
L12	S 49°42'44" W	278.85'
L13	N 85°17'14" W	47.50'
L14	N 40°27'17" W	28.68'
L15	N 44°27'15" W	147.62'
L16	N 43°09'46" W	270.15'
L17	N 40°17'13" W	178.04'
L18	N 60°40'02" E	63.84'
L19	N 29°20'29" W	244.09'
L20	S 29°24'03" E	243.34'
L21	N 59°36'32" E	50.25'
L22	N 29°20'15" W	146.49'
L23	N 29°33'44" W	7.70'

WETLANDS AREA TABLE			
Description	Perimeter	Sq. Feet	Acres
Ditch A	294.59	1,352.19	0.03
Ditch B	1,186.4	7,907	0.18
Ditch C	1,682.5	9,786	0.22
Ditch D	1,499.7	11,460.52	0.26
Ditch E	2,034.71	13,461.15	0.31
Wetland A	8,468.70	2,717,817.99	62.39
Wetland B	172.52	1,661.23	0.04
Wetland C	1,241.41	33,650.55	0.77
Wetland D	433.22	8,261.57	0.19
Wetland E	1,362.85	105,202.51	2.42
Wetland F	295.51	4,680.65	0.11
Total		2,916,081.36	66.92

AREA TABLE			
AREA/TOTAL	ACREAGE	SQ. FEET	WETLANDS ACREAGE
A	46.31	2,017,286	46.20
B	33.96	1,479,297	17.00
C	12.70	553,115	2.42
D	2.50	108,809	0.00
E	1.00	43,567	0.11
F	7.98	347,487	0.19

AREA TABLE			
Description	Perimeter	Sq. Feet	Acres
AREA A	6,698.26	2,017,285.51	46.31
AREA B	7,818.71	1,824,771.31	41.89
AREA C	4,206.48	596,822.44	13.70
AREA D	1,380.30	108,808.70	2.50
Total		4,547,687.95	104.40

LINE	BEARING	DISTANCE
L24	N 67°42'26" E	48.34'
L25	N 54°21'03" E	48.16'
L26	N 51°56'55" E	37.48'
L27	S 24°45'48" E	10.12'
L28	S 54°10'28" W	43.47'
L29	S 53°39'09" W	41.93'
L30	S 69°33'31" W	47.29'
L31	S 45°26'11" E	20.80'
L32	N 80°47'05" E	16.25'
L33	S 85°54'34" E	33.94'
L34	N 35°39'44" E	8.66'
L35	N 16°42'56" W	10.01'
L36	N 71°04'53" W	20.57'
L37	N 58°10'23" W	23.55'
L38	S 72°04'53" W	24.22'
L39	S 17°29'54" W	14.53'
L40	S 59°00'43" E	27.91'
L41	S 03°43'59" W	18.54'
L42	N 85°21'48" W	28.81'
L43	N 71°24'10" W	24.80'
L44	S 31°17'53" W	64.38'
L45	N 87°55'49" W	38.43'
L46	N 39°46'17" W	39.56'
L47	N 23°22'06" E	49.29'
L48	N 80°03'53" E	62.15'
L49	N 45°48'46" E	36.64'
L50	S 09°47'09" W	7.63'
L51	S 36°37'00" E	35.07'
L52	N 47°22'00" E	7.33'
L53	N 49°20'42" E	124.90'
L54	N 46°45'02" E	87.15'
L55	N 46°54'03" E	131.98'
L56	N 51°53'20" E	158.18'
L57	N 49°11'48" E	134.60'
L58	N 52°35'15" E	44.45'
L59	S 26°15'28" E	10.24'
L60	S 44°58'35" W	44.45'
L61	S 49°15'06" W	129.16'
L62	S 52°49'21" W	160.08'
L63	S 45°15'56" W	128.29'
L64	S 46°36'31" W	96.13'
L65	S 49°23'09" W	123.17'
L66	S 47°28'45" W	71.50'
L67	N 43°12'39" W	16.72'
L68	S 75°42'22" E	39.79'
L69	S 47°42'55" E	28.12'
L70	S 30°00'38" W	34.07'
L71	S 65°30'03" W	26.16'
L72	N 40°10'52" W	28.21'
L73	S 67°00'10" W	30.17'
L74	S 25°46'25" W	31.86'
L75	S 89°35'21" W	18.54'
L76	N 52°40'38" W	37.56'
L77	S 80°42'07" W	31.23'
L78	N 71°39'20" W	29.80'
L79	N 32°15'32" W	38.93'
L80	N 84°05'10" W	11.13'
L81	S 05°55'48" E	19.67'
L82	S 05°15'18" E	48.07'
L83	S 57°24'44" W	42.50'
L84	S 83°21'44" W	12.57'
L85	N 37°53'20" W	25.30'
L86	N 17°42'44" E	6.92'
L87	N 26°07'09" E	34.76'
L88	N 44°59'37" W	17.32'
L89	S 55°25'46" E	30.30'
L90	N 28°48'00" E	3.50'
L91	N 48°18'36" W	29.18'
L92	N 47°12'22" E	11.99'
L93	N 59°28'59" E	53.34'
L94	N 51°49'16" E	52.38'
L95	N 53°30'51" E	128.47'
L96	N 67°02'28" E	19.22'
L97	N 64°50'13" E	43.63'
L98	N 69°36'55" E	39.80'
L99	S 83°16'17" E	24.23'
L100	S 15°20'50" E	22.83'
L101	S 05°13'27" E	15.41'
L102	S 55°44'53" W	34.59'
L103	S 65°09'54" W	32.60'
L104	S 53°37'04" W	37.93'
L105	S 37°41'27" W	30.65'
L106	S 08°25'45" W	21.73'
L107	S 63°23'37" E	17.39'
L108	N 64°47'59" W	52.39'
L109	N 80°14'52" W	21.35'
L110	N 02°49'10" W	28.63'
L111	N 10°53'49" E	57.42'
L112	N 34°56'36" W	53.29'
L113	N 18°41'36" W	48.42'
L114	N 17°13'24" E	71.54'
L115	N 11°28'09" E	40.93'
L116	N 60°11'12" E	56.68'
L117	N 84°41'06" E	46.26'
L118	N 68°00'42" E	48.12'
L119	N 69°25'09" E	68.12'
L120	N 57°59'53" E	98.97'

LINE	BEARING	DISTANCE
L121	N 62°44'02" E	39.83'
L122	S 28°51'37" E	173.30'
L123	N 41°01'08" W	198.85'
L124	N 28°51'37" W	172.06'
L125	N 60°31'54" E	31.30'
L126	N 29°20'29" W	6.54'
L127	S 28°51'37" E	152.55'
L128	N 57°43'22" E	13.88'
L129	N 28°51'37" W	112.46'
L130	S 77°06'49" W	23.30'
L131	S 06°19'37" W	32.81'
L132	S 23°43'28" E	31.29'
L133	S 20°12'57" E	16.72'
L134	S 27°21'57" E	26.91'
L135	N 89°48'01" E	38.14'
L136	N 28°51'37" W	51.89'
L137	S 17°30'58" W	91.85'
L138	S 55°06'41" W	50.28'
L139	N 48°40'20" E	77.22'
L140	N 51°01'32" E	49.92'
L141	N 48°42'14" E	22.63'
L142	N 44°09'09" E	71.27'
L143	N 56°18'05" E	123.64'
L144	N 55°02'21" E	127.02'
L145	N 29°27'04" W	21.80'
L146	S 52°09'46" W	132.15'
L147	S 55°24'42" W	121.99'
L148	S 43°33'57" W	74.50'
L149	N 48°40'20" E	10.51'
L150	N 48°33'00" E	19.15'
L151	N 48°05'39" E	45.23'
L152	N 47°33'09" E	109.69'
L153	N 47°54'31" E	177.29'
L154	N 48°53'08" E	299.37'
L155	N 37°44'23" W	5.32'
L156	N 49°34'21" W	147.54'
L157	S 49°55'40" W	154.36'
L158	N 49°01'31" W	180.73'
L159	N 48°14'40" W	104.12'
L160	N 48°03'39" W	81.49'
L161	N 48°47'37" W	57.76'
L162	N 46°54'27" W	23.59'
L163	N 29°57'09" E	10.47'
L164	N 52°46'00" E	42.70'
L165	N 48°31'33" E	54.35'
L166	N 47°53'14" E	75.10'
L167	N 50°09'57" E	38.95'
L168	S 51°07'42" W	52.42'
L169	S 47°43'47" W	114.58'
L170	S 49°42'14" W	67.40'
L171	S 24°44'26" E	11.95'
L172	N 49°06'34" E	69.43'
L173	N 64°50'13" W	43.63'
L174	N 66°59'07" W	19.27'
L175	N 41°02'25" W	7.50'
L176	S 60°18'38" W	26.47'
L177	N 68°02'09" W	13.85'
L178	S 18°18'02" W	47.62'
L179	N 40°17'55" W	5.11'
L180	N 42°44'49" E	17.27'
L181	N 42°29'37" E	41.02'
L182	N 55°14'43" E	94.12'
L183	N 65°02'02" E	96.37'
L184	N 37°44'23" W	48.67'
L185	N 37°44'23" W	30.86'
L186	N 58°42'59" W	44.05'
L187	N 48°05'58" W	65.98'
L188	N 84°02'31" W	84.41'
L189	S 74°43'05" W	42.71'
L190	N 59°13'14" W	50.94'
L191	N 75°20'46" W	79.62'
L192	N 58°20'14" W	39.13'
L193	N 59°00'08" W	70.01'
L194	N 65°59'10" W	43.06'
L195	N 69°48'56" W	57.58'
L196	S 83°49'20" W	21.93'
L197	N 89°16'04" W	56.19'
L198	N 82°23'31" W	33.71'
L199	N 83°53'07" W	52.94'
L200	N 67°08'43" W	37.88'
L201	N 31°37'32" W	33.98'
L202	N 57°59'02" W	34.05'
L203	N 50°38'56" W	49.85'
L204	N 80°14'41" E	49.81'
L205	N 84°50'10" E	90.19'
L206	N 13°57'00" W	9.38'
L207	N 43°37'58" W	27.53'
L208	N 24°58'57" E	15.46'
L209	N 26°10'53" W	38.00'
L210	N 72°37'44" W	26.77'

LINE	BEARING	DISTANCE
L211	S 12°35'50" W	22.53'
L212	S 70°37'46" W	15.17'
L213	S 28°12'22" W	15.21'
L214	N 31°43'46" W	48.99'
L215	N 66°57'01" W	18.56'
L216	S 32°22'14" W	35.28'
L217	S 87°47'53" W	23.97'
L218	S 60°27'38" W	16.22'
L219	S 69°35'37" W	33.67'
L220	S 70°54'06" W	33.52'
L221	N 27°37'01" W	18.76'
L222	N 46°36'54" E	37.96'
L223	N 20°51'33" E	16.68'
L224	N 11°20'48" W	17.41'
L225	S 67°48'46" W	24.02'
L226	S 00°57'36" E	10.68'
L227	S 45°38'50" W	29.67'
L228	S 73°20'13" W	43.98'
L229	S 77°39'01" W	34.83'
L230	S 85°39'05" W	24.95'
L231	N 85°04'23" W	75.44'
L232	S 21°47'35" W	64.92'
L233	S 49°38'29" W	52.62'
L234	S 65°03'20" W	34.38'
L235	S 44°57'01" W	17.74'
L236	S 46°35'03" W	30.33'
L237	S 66°21'45" W	39.86'
L238	N 41°58'04" W	16.72'
L239	S 80°10'31" W	12.87'
L240	S 69°04'06" W	33.97'
L241	S 71°25'38" W	29.44'
L242	N 54°29'25" W	21.03'
L243	N 12°36'01" E	20.88'
L244	N 21°59'15" W	20.69'
L245	N 68°16'45" E	13.02'
L246	S 85°08'44" E	40.97'
L247	S 89°13'03" E	32.58'
L248	S 56°49'52" E	21.71'
L249	N 49°49'45" W	26.63'
L250	N 72°54'43" W	20.31'
L251	N 71°19'32" W	28.99'
L252	N 48°05'06" W	12.52'
L253	N 07°47'46" E	40.74'
L254	N 09°09'04" E	33.15'
L255	N 05°46'53" W	40.80'
L256	N 04°33'13" W	34.21'
L257	N 60°01'45" W	3

## APPENDIX D

### USDA SOILS DATA

DRAFT






United States  
Department of  
Agriculture

**NRCS**

Natural  
Resources  
Conservation  
Service

A product of the National  
Cooperative Soil Survey,  
a joint effort of the United  
States Department of  
Agriculture and other  
Federal agencies, State  
agencies including the  
Agricultural Experiment  
Stations, and local  
participants


# Custom Soil Resource Report for Hampton County, South Carolina



October 27, 2022



# Custom Soil Resource Report Soil Map



# Custom Soil Resource Report

## MAP LEGEND

### Area of Interest (AOI)

 Area of Interest (AOI)

### Soils

 Soil Map Unit Polygons

 Soil Map Unit Lines

 Soil Map Unit Points

### Special Point Features

 Blowout

 Borrow Pit

 Clay Spot

 Closed Depression

 Gravel Pit

 Gravelly Spot

 Landfill

 Lava Flow

 Marsh or swamp

 Mine or Quarry

 Miscellaneous Water

 Perennial Water

 Rock Outcrop


 Saline Spot

 Sandy Spot

 Severely Eroded Spot


 Sinkhole

 Slide or Slip

 Sodic Spot

 Spoil Area

 Stony Spot

 Very Stony Spot

 Wet Spot

 Other

 Special Line Features

### Water Features

 Streams and Canals

### Transportation

 Rails

 Interstate Highways

 US Routes

 Major Roads

 Local Roads

### Background

 Aerial Photography

## MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:20,000.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service

Web Soil Survey URL:

Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Hampton County, South Carolina

Survey Area Data: Version 22, Sep 7, 2022

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Feb 21, 2021—Feb 23, 2021

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

## Map Unit Legend

Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI
Ar	Argent fine sandy loam, ponded	56.5	53.2%
Br	Brookman clay loam, ponded	1.0	0.9%
EpB	Emporia loamy sand, 2 to 6 percent slopes	26.5	24.9%
Gr	Grifton-Osier complex, frequently flooded	6.3	5.9%
Na	Nakina fine sandy loam, occasionally flooded	13.4	12.6%
Oe	Osier loamy sand	2.7	2.5%
<b>Totals for Area of Interest</b>		<b>106.3</b>	<b>100.0%</b>

## Map Unit Descriptions

The map units delineated on the detailed soil maps in a soil survey represent the soils or miscellaneous areas in the survey area. The map unit descriptions, along with the maps, can be used to determine the composition and properties of a unit.

A map unit delineation on a soil map represents an area dominated by one or more major kinds of soil or miscellaneous areas. A map unit is identified and named according to the taxonomic classification of the dominant soils. Within a taxonomic class there are precisely defined limits for the properties of the soils. On the landscape, however, the soils are natural phenomena, and they have the characteristic variability of all natural phenomena. Thus, the range of some observed properties may extend beyond the limits defined for a taxonomic class. Areas of soils of a single taxonomic class rarely, if ever, can be mapped without including areas of other taxonomic classes. Consequently, every map unit is made up of the soils or miscellaneous areas for which it is named and some minor components that belong to taxonomic classes other than those of the major soils.

Most minor soils have properties similar to those of the dominant soil or soils in the map unit, and thus they do not affect use and management. These are called noncontrasting, or similar, components. They may or may not be mentioned in a particular map unit description. Other minor components, however, have properties and behavioral characteristics divergent enough to affect use or to require different management. These are called contrasting, or dissimilar, components. They generally are in small areas and could not be mapped separately because of the scale used. Some small areas of strongly contrasting soils or miscellaneous areas are identified by a special symbol on the maps. If included in the database for a given area, the contrasting minor components are identified in the map unit descriptions along with some characteristics of each. A few areas of minor components may not have been observed, and consequently they are not mentioned in the descriptions, especially where the pattern was so complex that it was impractical to make enough observations to identify all the soils and miscellaneous areas on the landscape.



## Custom Soil Resource Report

The presence of minor components in a map unit in no way diminishes the usefulness or accuracy of the data. The objective of mapping is not to delineate pure taxonomic classes but rather to separate the landscape into landforms or landform segments that have similar use and management requirements. The delineation of such segments on the map provides sufficient information for the development of resource plans. If intensive use of small areas is planned, however, onsite investigation is needed to define and locate the soils and miscellaneous areas.

An identifying symbol precedes the map unit name in the map unit descriptions. Each description includes general facts about the unit and gives important soil properties and qualities.

Soils that have profiles that are almost alike make up a *soil series*. Except for differences in texture of the surface layer, all the soils of a series have major horizons that are similar in composition, thickness, and arrangement.

Soils of one series can differ in texture of the surface layer, slope, stoniness, salinity, degree of erosion, and other characteristics that affect their use. On the basis of such differences, a soil series is divided into *soil phases*. Most of the areas shown on the detailed soil maps are phases of soil series. The name of a soil phase commonly indicates a feature that affects use or management. For example, Alpha silt loam, 0 to 2 percent slopes, is a phase of the Alpha series.

Some map units are made up of two or more major soils or miscellaneous areas. These map units are complexes, associations, or undifferentiated groups.

A *complex* consists of two or more soils or miscellaneous areas in such an intricate pattern or in such small areas that they cannot be shown separately on the maps. The pattern and proportion of the soils or miscellaneous areas are somewhat similar in all areas. Alpha-Beta complex, 0 to 6 percent slopes, is an example.

An *association* is made up of two or more geographically associated soils or miscellaneous areas that are shown as one unit on the maps. Because of present or anticipated uses of the map units in the survey area, it was not considered practical or necessary to map the soils or miscellaneous areas separately. The pattern and relative proportion of the soils or miscellaneous areas are somewhat similar. Alpha-Beta association, 0 to 2 percent slopes, is an example.

An *undifferentiated group* is made up of two or more soils or miscellaneous areas that could be mapped individually but are mapped as one unit because similar interpretations can be made for use and management. The pattern and proportion of the soils or miscellaneous areas in a mapped area are not uniform. An area can be made up of only one of the major soils or miscellaneous areas, or it can be made up of all of them. Alpha and Beta soils, 0 to 2 percent slopes, is an example.

Some surveys include *miscellaneous areas*. Such areas have little or no soil material and support little or no vegetation. Rock outcrop is an example.

## Hampton County, South Carolina

### Ar—Argent fine sandy loam, ponded

#### Map Unit Setting

*National map unit symbol:* 4cc7

*Elevation:* 10 to 150 feet

*Mean annual precipitation:* 50 to 64 inches

*Mean annual air temperature:* 63 to 68 degrees F

*Frost-free period:* 220 to 250 days

*Farmland classification:* Farmland of statewide importance

#### Map Unit Composition

*Argent and similar soils:* 100 percent

*Estimates are based on observations, descriptions, and transects of the mapunit.*

#### Description of Argent

##### Setting

*Landform:* Depressions, marine terraces

*Landform position (three-dimensional):* Tread

*Down-slope shape:* Concave, linear

*Across-slope shape:* Concave, linear

*Parent material:* Clayey marine deposits

##### Typical profile

*A - 0 to 5 inches:* fine sandy loam

*Btg - 5 to 58 inches:* clay

*BCg - 58 to 65 inches:* clay

##### Properties and qualities

*Slope:* 0 to 2 percent

*Depth to restrictive feature:* More than 80 inches

*Drainage class:* Poorly drained

*Runoff class:* Negligible

*Capacity of the most limiting layer to transmit water (Ksat):* Moderately low to moderately high (0.06 to 0.20 in/hr)

*Depth to water table:* About 0 to 12 inches

*Frequency of flooding:* None

*Frequency of ponding:* Occasional

*Available water supply, 0 to 60 inches:* High (about 9.4 inches)

##### Interpretive groups

*Land capability classification (irrigated):* None specified

*Land capability classification (nonirrigated):* 6w

*Hydrologic Soil Group:* C/D

*Hydric soil rating:* Yes

## **Br—Brookman clay loam, ponded**

### **Map Unit Setting**

*National map unit symbol:* 4ccj

*Elevation:* 10 to 150 feet

*Mean annual precipitation:* 50 to 64 inches

*Mean annual air temperature:* 63 to 68 degrees F

*Frost-free period:* 220 to 250 days

*Farmland classification:* Farmland of statewide importance

### **Map Unit Composition**

*Brookman and similar soils:* 100 percent

*Estimates are based on observations, descriptions, and transects of the mapunit.*

### **Description of Brookman**

#### **Setting**

*Landform:* Depressions, marine terraces

*Landform position (three-dimensional):* Tread

*Down-slope shape:* Concave, linear

*Across-slope shape:* Concave, linear

*Parent material:* Clayey marine deposits

#### **Typical profile**

*A - 0 to 4 inches:* clay loam

*Btg1 - 4 to 11 inches:* clay loam

*Btg2 - 11 to 44 inches:* clay

*Btg3 - 44 to 62 inches:* clay loam

*Cg - 62 to 80 inches:* sand

#### **Properties and qualities**

*Slope:* 0 to 2 percent

*Depth to restrictive feature:* More than 80 inches

*Drainage class:* Very poorly drained

*Runoff class:* Negligible

*Capacity of the most limiting layer to transmit water (Ksat):* Moderately high to high  
(0.57 to 1.98 in/hr)

*Depth to water table:* About 0 to 12 inches

*Frequency of flooding:* None

*Frequency of ponding:* Occasional

*Available water supply, 0 to 60 inches:* High (about 10.7 inches)

#### **Interpretive groups**

*Land capability classification (irrigated):* None specified

*Land capability classification (nonirrigated):* 7w

*Hydrologic Soil Group:* B/D

*Hydric soil rating:* Yes

## **EpB—Emporia loamy sand, 2 to 6 percent slopes**

### **Map Unit Setting**

*National map unit symbol:* 4cct  
*Elevation:* 10 to 150 feet  
*Mean annual precipitation:* 50 to 64 inches  
*Mean annual air temperature:* 63 to 68 degrees F  
*Frost-free period:* 220 to 250 days  
*Farmland classification:* All areas are prime farmland

### **Map Unit Composition**

*Emporia and similar soils:* 100 percent  
*Estimates are based on observations, descriptions, and transects of the mapunit.*

### **Description of Emporia**

#### **Setting**

*Landform:* Marine terraces  
*Landform position (three-dimensional):* Tread  
*Down-slope shape:* Convex  
*Across-slope shape:* Convex  
*Parent material:* Loamy marine deposits

#### **Typical profile**

*Ap - 0 to 11 inches:* loamy sand  
*Bt1 - 11 to 31 inches:* sandy clay loam  
*Bt2 - 31 to 45 inches:* sandy clay loam  
*BC - 45 to 60 inches:* clay loam

#### **Properties and qualities**

*Slope:* 2 to 6 percent  
*Depth to restrictive feature:* More than 80 inches  
*Drainage class:* Well drained  
*Runoff class:* Low  
*Capacity of the most limiting layer to transmit water (Ksat):* Very low to moderately high (0.00 to 0.57 in/hr)  
*Depth to water table:* About 36 inches  
*Frequency of flooding:* None  
*Frequency of ponding:* None  
*Available water supply, 0 to 60 inches:* Moderate (about 7.2 inches)

#### **Interpretive groups**

*Land capability classification (irrigated):* None specified  
*Land capability classification (nonirrigated):* 2e  
*Hydrologic Soil Group:* C  
*Hydric soil rating:* No



## **Gr—Grifton-Osier complex, frequently flooded**

### **Map Unit Setting**

*National map unit symbol:* 4cd0

*Elevation:* 10 to 150 feet

*Mean annual precipitation:* 50 to 64 inches

*Mean annual air temperature:* 63 to 68 degrees F

*Frost-free period:* 220 to 250 days

*Farmland classification:* Not prime farmland

### **Map Unit Composition**

*Grifton and similar soils:* 60 percent

*Osier and similar soils:* 40 percent

*Estimates are based on observations, descriptions, and transects of the mapunit.*

### **Description of Grifton**

#### **Setting**

*Landform:* Depressions, marine terraces

*Landform position (three-dimensional):* Tread

*Down-slope shape:* Concave, linear

*Across-slope shape:* Concave, linear

*Parent material:* Loamy marine deposits

#### **Typical profile**

*Ap - 0 to 6 inches:* fine sandy loam

*E - 6 to 13 inches:* fine sandy loam

*Btg - 13 to 48 inches:* sandy clay loam

*Cg - 48 to 65 inches:* loamy sand

#### **Properties and qualities**

*Slope:* 0 to 2 percent

*Depth to restrictive feature:* More than 80 inches

*Drainage class:* Poorly drained

*Runoff class:* Very high

*Capacity of the most limiting layer to transmit water (Ksat):* Moderately high to high  
(0.57 to 1.98 in/hr)

*Depth to water table:* About 0 to 12 inches

*Frequency of flooding:* FrequentNone

*Frequency of ponding:* None

*Available water supply, 0 to 60 inches:* Moderate (about 8.1 inches)

#### **Interpretive groups**

*Land capability classification (irrigated):* None specified

*Land capability classification (nonirrigated):* 7w

*Hydrologic Soil Group:* B/D

*Hydric soil rating:* Yes

### **Description of Osier**

#### **Setting**

*Landform:* Depressions, marine terraces

## Custom Soil Resource Report

*Landform position (three-dimensional):* Tread  
*Down-slope shape:* Concave, linear  
*Across-slope shape:* Concave, linear  
*Parent material:* Sandy alluvium

### Typical profile

*A - 0 to 19 inches:* loamy sand  
*Cg1 - 19 to 35 inches:* sand  
*Cg2 - 35 to 70 inches:* coarse sand

### Properties and qualities

*Slope:* 0 to 2 percent  
*Depth to restrictive feature:* More than 80 inches  
*Drainage class:* Poorly drained  
*Runoff class:* Very high  
*Capacity of the most limiting layer to transmit water (Ksat):* High to very high (5.95 to 19.98 in/hr)  
*Depth to water table:* About 0 to 12 inches  
*Frequency of flooding:* Rare  
*Frequency of ponding:* None  
*Available water supply, 0 to 60 inches:* Low (about 3.4 inches)

### Interpretive groups

*Land capability classification (irrigated):* None specified  
*Land capability classification (nonirrigated):* 5w  
*Hydrologic Soil Group:* A/D  
*Hydric soil rating:* Yes

## Na—Nakina fine sandy loam, occasionally flooded

### Map Unit Setting

*National map unit symbol:* 4cd5  
*Elevation:* 10 to 150 feet  
*Mean annual precipitation:* 50 to 64 inches  
*Mean annual air temperature:* 63 to 68 degrees F  
*Frost-free period:* 220 to 250 days  
*Farmland classification:* Farmland of statewide importance

### Map Unit Composition

*Nakina and similar soils:* 100 percent  
*Estimates are based on observations, descriptions, and transects of the mapunit.*

### Description of Nakina

#### Setting

*Landform:* Depressions, marine terraces  
*Landform position (three-dimensional):* Tread  
*Down-slope shape:* Concave, linear  
*Across-slope shape:* Concave, linear  
*Parent material:* Loamy marine deposits

**Typical profile**

*A - 0 to 15 inches:* fine sandy loam  
*Btg - 15 to 43 inches:* sandy clay loam  
*BCg - 43 to 60 inches:* sandy loam

**Properties and qualities**

*Slope:* 0 to 2 percent  
*Depth to restrictive feature:* More than 80 inches  
*Drainage class:* Very poorly drained  
*Runoff class:* Very high  
*Capacity of the most limiting layer to transmit water (Ksat):* Moderately high to high  
(0.57 to 5.95 in/hr)  
*Depth to water table:* About 0 to 12 inches  
*Frequency of flooding:* OccasionalNone  
*Frequency of ponding:* None  
*Available water supply, 0 to 60 inches:* High (about 9.3 inches)

**Interpretive groups**

*Land capability classification (irrigated):* None specified  
*Land capability classification (nonirrigated):* 6w  
*Hydrologic Soil Group:* A/D  
*Hydric soil rating:* Yes

**Oe—Osier loamy sand**

**Map Unit Setting**

*National map unit symbol:* 4cdd  
*Elevation:* 10 to 150 feet  
*Mean annual precipitation:* 50 to 64 inches  
*Mean annual air temperature:* 63 to 68 degrees F  
*Frost-free period:* 220 to 250 days  
*Farmland classification:* Not prime farmland

**Map Unit Composition**

*Osier and similar soils:* 100 percent  
*Estimates are based on observations, descriptions, and transects of the mapunit.*

**Description of Osier**

**Setting**

*Landform:* Depressions, marine terraces  
*Landform position (three-dimensional):* Tread  
*Down-slope shape:* Concave, linear  
*Across-slope shape:* Concave, linear  
*Parent material:* Sandy alluvium

**Typical profile**

*A - 0 to 19 inches:* loamy sand  
*Cg1 - 19 to 35 inches:* sand  
*Cg2 - 35 to 70 inches:* coarse sand

## Custom Soil Resource Report

### Properties and qualities

*Slope:* 0 to 2 percent

*Depth to restrictive feature:* More than 80 inches

*Drainage class:* Poorly drained

*Runoff class:* Very high

*Capacity of the most limiting layer to transmit water (Ksat):* High to very high (5.95 to 19.98 in/hr)

*Depth to water table:* About 0 to 12 inches

*Frequency of flooding:* RareNone

*Frequency of ponding:* None

*Available water supply, 0 to 60 inches:* Low (about 3.4 inches)

### Interpretive groups

*Land capability classification (irrigated):* None specified

*Land capability classification (nonirrigated):* 5w

*Hydrologic Soil Group:* A/D


*Hydric soil rating:* Yes

## APPENDIX E

### AERIAL SITE MAP

DRAFT





P.O. BOX 381, BLUFFTON, SOUTH CAROLINA 29910  
PH (843) 837-5250 / FAX (843) 837-2558  
[WWW.WARDEDWARDS.COM](http://WWW.WARDEDWARDS.COM)

## VICINITY MAP

### PINE STREET DEVELOPMENT

LOCATION: YEMASSEE, SC  
DATE: 10/25/2022  
PROJECT #: 210148


SCALE: 1"=1,000'



## APPENDIX F

### USGS QUADRANGLE MAP

DRAFT



P.O. BOX 381, BLUFFTON, SOUTH CAROLINA 29910  
 PH (843) 837-5250 / FAX (843) 837-2558  
 WWW.WARDEDWARDS.COM

## QUAD MAP

### PINE STREET DEVELOPMENT

LOCATION: YEMASSEE, SC  
 DATE: 10/25/2022  
 PROJECT #: 210148

SCALE: 1"=2000'



## APPENDIX G

### FEMA MAP

DRAFT

# National Flood Hazard Layer FIRMMette



80°50'44"W 32°42'26"N



0 250 500 1,000 1,500 2,000 Feet 1:6,000

Basemap: USGS National Map: Orthoimagery: Data refreshed October, 2020

## Legend

SEE FIS REPORT FOR DETAILED LEGEND AND INDEX MAP FOR FIRM PANEL LAYOUT

SPECIAL FLOOD HAZARD AREAS		Without Base Flood Elevation (BFE) Zone A, V, A99
		With BFE or Depth Zone AE, AO, AH, VE, AR
		Regulatory Floodway
OTHER AREAS OF FLOOD HAZARD		0.2% Annual Chance Flood Hazard, Areas of 1% annual chance flood with average depth less than one foot or with drainage areas of less than one square mile Zone X
		Future Conditions 1% Annual Chance Flood Hazard Zone X
		Area with Reduced Flood Risk due to Levee. See Notes. Zone X
		Area with Flood Risk due to Levee Zone D
OTHER AREAS		NO SCREEN Area of Minimal Flood Hazard Zone X
		Effective LOMRs
GENERAL STRUCTURES		Area of Undetermined Flood Hazard Zone D
		Channel, Culvert, or Storm Sewer
OTHER FEATURES		Levee, Dike, or Floodwall
		Cross Sections with 1% Annual Chance Water Surface Elevation
OTHER FEATURES		Coastal Transect
		Base Flood Elevation Line (BFE)
OTHER FEATURES		Limit of Study
		Jurisdiction Boundary
OTHER FEATURES		Coastal Transect Baseline
		Profile Baseline
MAP PANELS		Digital Data Available
		No Digital Data Available
MAP PANELS		Unmapped
		The pin displayed on the map is an approximate point selected by the user and does not represent an authoritative property location.



This map complies with FEMA's standards for the use of digital flood maps if it is not void as described below. The basemap shown complies with FEMA's basemap accuracy standards

The flood hazard information is derived directly from the authoritative NFHL web services provided by FEMA. This map was exported on **10/27/2022 at 5:25 PM** and does not reflect changes or amendments subsequent to this date and time. The NFHL and effective information may change or become superseded by new data over time.


This map image is void if the one or more of the following map elements do not appear: basemap imagery, flood zone labels, legend, scale bar, map creation date, community identifiers, FIRM panel number, and FIRM effective date. Map images for unmapped and unmodernized areas cannot be used for regulatory purposes.

## APPENDIX H

### PUD MASTER PLAN AND INITIAL MASTER PLAN

# DRAFT





LEGEND

PRIMARY ACCESS POINT

SECONDARY ACCESS POINT

WETLAND

SUMMARY BY PARCEL			
	UPLAND (ACRES)	WETLAND (ACRES)	TOTAL (ACRES)
PARCEL 1	10.73	.75	11.48
PARCEL 2	10.01	2.69	12.7
PARCEL 3	16.76	17.2	33.8
PARCEL 4	0.11	46.2	46.31
TOTAL	37.5	66.95	104.45







APPENDIX I

DEVELOPMENT SCHEDULE

The following is a Preliminary Development Schedule for Pine Street PUD that is subject to change based on market conditions and other factors:

Year	Commercial (sq ft)	Residential (dwelling units)
Phase 1 – 2023-2025	100,000	50 DU's
Phase 2 -2026-2028	50,000	57 DU's

## APPENDIX J

### INTENT TO SERVE LETTERS

DRAFT

## RE: Ironline Metals - Letter of Intent to Serve Request

Matt Sigman <matt.sigman@prtc.us>

Thu 11/10/2022 1:13 PM

To: Shelly Snyder <ssnyder@wardedwards.com>

Cc: Conor Blaney <cblaney@wardedwards.com>

Good afternoon, Shelly

After reviewing this conceptual plan with our engineering manager, he wanted me to pass this along to you.

"In reference Pine Street Residential subdivision. We have existing fiber cable on Pine St, Lacey St, and Hwy 17A. We will be able to accommodate any future build in this area with our existing fiber facilities."

Please let me know if you have any additional questions.

Thank you,

Matt Sigman

Business Development Manager

Palmetto Rural Telephone Cooperative, Inc.

Desk: [843-538-9381](tel:843-538-9381)

Mobile: [843-217-3653](tel:843-217-3653)

Business Direct: [843-538-SALE](tel:843-538-SALE)(7253)

Email: [matt.sigman@prtc.coop](mailto:matt.sigman@prtc.coop)

Business Direct: [busdirect@prtc.coop](mailto:busdirect@prtc.coop)

[292 Robertson Blvd.](#)

Walterboro, SC 29488







## **Letter of Power Availability**

Nov 16, 2022

### **Correspondence Sent Electronically**

Shelly Snyder  
Ward Edwards Engineering  
Bluffton, S.C.

Re: Ironline Metals, Yemassee, S.C.

Ms. Snyder:

I am pleased to inform you that Dominion Energy will be able to provide electric service to the above referenced project. Electric service will be provided in accordance with Dominion Energy General Terms and Conditions, other documents on file with the South Carolina Public Service Commission, and the company's standard operating policies and procedures. To begin engineering work for the project, the following information will need to be provided:

- 1.) Detailed utility site plan in AutoCAD format showing water, sewer, and storm drainage, as well as the requested service point/transformer locations.
- 2.) Additional drawings that indicate wetland boundaries, tree survey with barricade plan and buffer zones (if required), as well as any existing or additional easements that will also be needed.
- 3.) Electric load breakdown by type with riser diagrams and desired metering specifications.
- 4.) The anticipated timeline for each phase of the development.
- 5.) Dominion Energy has specific requirements for electric service to new water and sewer pump-stations. If your project requires these facilities, please contact me for more details.

Dominion Energy construction standards and specifications are available here:  
<https://www.dominionenergy.com/south-carolina/start-stop-service/new-construction>

If you have any questions, please contact me at 843-540-1315.

Sincerely,

*Parks Moss*

Parks Moss  
Senior Key Account Manager  
Dominion Energy South Carolina



## Natural Gas Letter of Availability

11/16/2022  
Shelly Snyder  
Ironline Metals  
Yemassee, SC

I am pleased to inform you that Dominion Energy South Carolina will be able to provide natural gas service to the above referenced. Natural gas service can be provided in accordance with Dominion Energy's General Terms and Conditions, other documents on file with the South Carolina Public Service Commission, and the company's standard operating policies and procedures. **In order to begin the design process for the project, the following information will need to be provided:**

1. Site Plan / Cad File / PDF
2. Total natural gas BTU load of each piece of equipment per building
3. Delivery pressure
4. Estimated wanted by date for gas line installation
6. Permanent account established, please call 1-877-937-7234
7. All required Contribution in Aid of Construction must be received before scheduling can be arranged.

Thank you in advance for this information and I look forward to working with your company.

For more information or questions, don't hesitate to contact me.

Sincerely,

*Ryan Hooks*

**Account Manager – Natural Gas**  
**Dominion Energy South Carolina**

**81 May River Rd. Bluffton, SC 29910**  
**P (843) 576-8911 • M (843) 412-5178**  
[michael.r.hooks@dominionenergy.com](mailto:michael.r.hooks@dominionenergy.com)

## APPENDIX K

### TRAFFIC IMPACT ANALYSIS

DRAFT



# PINE STREET RESIDENTIAL

2023  
January

Project No:  
171002659

DRAFT


PREPARED FOR:

WARD EDWARDS  
ENGINEERING

PO BOX 381, BLUFFTON, SC 29910

## TRAFFIC IMPACT ANALYSIS

ALONG PINE STREET  
IN HAMPTON COUNTY, SOUTH CAROLINA





# PINE STREET RESIDENTIAL TRAFFIC IMPACT ANALYSIS

The conclusions in the Report titled "Pine Street Residential Traffic Impact Analysis" are Stantec's professional opinion, as of the time of the Report, and concerning the scope described in the Report. The opinions in the document are based on conditions and information existing at the time the document was published and do not take into account any subsequent changes. The Report relates solely to the specific project for which Stantec was retained and the stated purpose for which the Report was prepared. The Report is not to be used or relied on for any variation or extension of the project, or for any other project or purpose, and any unauthorized use or reliance is at the recipient's own risk.

Stantec has assumed all information received from Ward Edwards Engineering (the "Client") and third parties in the preparation of the Report to be correct. While Stantec has exercised a customary level of judgement or due diligence in the use of such information, Stantec assumes no responsibility for the consequence of any error or omission contained therein.

This Report is intended solely for use by the Client in accordance with Stantec's contract with the Client. While the Report may be provided to applicable authorities having jurisdiction and others for whom the Client is responsible, Stantec does not warrant the services to any third party. The report may not be relied upon by any other party without the express written consent of Stantec, which may be withheld at Stantec's discretion.

Prepared by: 

Prasad Chame

Reviewed by: 

Stuart Day, PE, PTOE



Approved by: 

Josh Mitchell, PE

January 2023

# TABLE OF CONTENTS



<b>EXECUTIVE SUMMARY</b> .....	<b>I</b>
<b>1.0 INTRODUCTION</b> .....	<b>1.1</b>
1.1 PROJECT BACKGROUND.....	1.1
1.2 EXISTING ROADWAY CONDITIONS.....	1.1
<b>2.0 DRIVEWAY SPACING REVIEW</b> .....	<b>2.1</b>
<b>3.0 PROJECT TRAFFIC</b> .....	<b>3.1</b>
3.1 PROPOSED LAND USES.....	3.1
3.2 TRIP GENERATION ESTIMATES.....	3.1
3.3 TRIP DISTRIBUTION & ASSIGNMENT.....	3.1
3.3.1 New External Traffic.....	3.1
<b>4.0 TRAFFIC VOLUME DEVELOPMENT</b> .....	<b>4.1</b>
4.1 EXISTING TRAFFIC VOLUMES.....	4.1
4.2 FUTURE TRAFFIC PROJECTIONS.....	4.1
<b>5.0 TRAFFIC IMPACT ANALYSIS</b> .....	<b>5.1</b>
5.1 TURN LANE ANALYSIS.....	5.1
5.1.1 Right-Turn Lanes.....	5.1
5.1.2 Left-Turn Lanes.....	5.2
5.2 INTERSECTION LOS ANALYSIS.....	5.3
<b>6.0 SUMMARY OF FINDINGS AND RECOMMENDATIONS</b> .....	<b>6.1</b>

## LIST OF TABLES

Table 2.1 – Minimum Driveway Spacing*.....	2.1
Table 3.1 – Trip Generation Estimates.....	3.1
Table 5.1 – Right-Turn Lane Criteria Warrants.....	5.1
Table 5.2 – Left-Turn Lane Criteria Warrants.....	5.2
Table 5.3 – HCM 6 <sup>th</sup> Edition Intersection LOS Criteria.....	5.3
Table 5.4 – Peak Hour Intersection Analysis Results.....	5.4

## LIST OF EXHIBITS

Exhibit 1.1 – Pine Street Residential Location Map.....	1.2
Exhibit 1.2 – Pine Street Residential Site Plan.....	1.3
Exhibit 3.1 – Residential Project Traffic Distribution and Assignment.....	3.2
Exhibit 3.2 – Light Industrial Project Traffic Distribution and Assignment.....	3.3
Exhibit 3.3 – Peak Hour Project Traffic Volumes.....	3.4
Exhibit 4.1 – 2022 Existing Peak Hour Traffic Volumes.....	4.2
Exhibit 4.2 – 2025 No Build Peak Hour Traffic Volumes.....	4.3
Exhibit 4.3 – 2025 Build Peak Hour Traffic Volumes.....	4.4

## LIST OF APPENDICES

Appendix A	Trip Generation Worksheets
Appendix B	Traffic Volume Data
Appendix C	Traffic Volume Development Worksheets
Appendix D	Analysis Worksheets: 2022 Existing Conditions
Appendix E	Analysis Worksheets: 2025 No Build Conditions
Appendix F	Analysis Worksheets: 2025 Build Conditions
Appendix G	Turn Lane Analysis Worksheets



## EXECUTIVE SUMMARY

A traffic impact analysis was conducted for the Pine Street Residential development in accordance with SCDOT and Town of Yemassee guidelines.

The proposed Pine Street Residential development (which is anticipated to be constructed by 2025) is located on Pine Street, north of US 21, and will consist of 71 single-family detached housing units and an approximately 100,000 square-foot light industrial building.

Access to the development will be provided via one new proposed access along US 21, servicing the light industrial building, which meets SCDOT's access spacing criteria, as well as via driveways along existing Pine Street, will serve as the access for the development.

For the purposes of the analysis, the intersection of US 21 & Pine Street is also referred to as Project Driveway #1, the intersection of Salkehatchie Road & Pine Street is also referred to as Project Driveway #2, and the new proposed access along US 21 is referred to as Project Driveway #3.

The extent of the roadway network analyzed consisted of the four (4) intersections of:

1. US 21 & Salkehatchie Road;
2. US 21 & Pine Street (Project Driveway #1);
3. Salkehatchie Road & Pine Street (Project Driveway #2);  
and
4. US 21 & Project Driveway #3.

The operation of each of the study area intersections (in terms of average vehicular delay and level of service) was analyzed with and without the project traffic anticipated to be generated by the Pine Street Residential development.

The results of the analysis indicate that the study intersections currently operate and are expected to continue to operate at an acceptable level of service with the proposed Pine Street Residential development.

Per the criteria documented in *Section 5D-4* of SCDOT's *Access and Roadside Management Standards (ARMS, 2008)*, exclusive turn lanes are not recommended at any of the study intersections or project driveways.





## 1.0 INTRODUCTION

### 1.1 PROJECT BACKGROUND

The purpose of this report is to document the procedures and findings of a traffic impact analysis for the proposed Pine Street Residential development in accordance with SCDOT and Town of Yemassee guidelines. The proposed Pine Street Residential development is located along US 21 and along Pine Street, north of US 21, as shown in **Exhibit 1.1**, and will consist of 71 single-family detached housing units and an approximately 100,000 square-foot light industrial building with anticipated completion by 2025.

Access to the development will be provided via one new proposed access along US 21, servicing the light industrial building, along with driveways along existing Pine Street, will serve as the access for the development, as shown in **Exhibit 1.2**. For the purposes of the analysis, the intersection of US 21 & Pine Street is also referred to as Project Driveway #1, the intersection of Salkehatchie Road & Pine Street is also referred to as Project Driveway #2, and the new proposed access along US 21 is referred to as Project Driveway #3.

The traffic impact analysis considers the weekday AM peak hour (between 7:00 AM and 9:00 AM) and the weekday PM peak hour (between 4:00 PM and 6:00 PM) as the study time frames.

The extent of the roadway network analyzed consisted of the four (4) intersections of:

1. US 21 & Salkehatchie Road;
2. US 21 & Pine Street (Project Driveway #1);
3. Salkehatchie Road & Pine Street (Project Driveway #2); and
4. US 21 & Project Driveway #3.

### 1.2 EXISTING ROADWAY CONDITIONS

US 21 is a two-lane arterial that primarily serves commercial and residential land uses. The posted speed limit is 45-miles per hour (mph) north of Pine Street, while the posted speed limit south of Lacey Street is 35-mph. The speed limit changes from 45-mph to 35-mph between Pine Street and Lacey Street. The average annual daily traffic (AADT) in 2021 was 1,650 vehicles/day. Based upon existing turning movement counts, the percentage of heavy vehicles along US 21 is approximately 13%.

Salkehatchie Road is a two-lane major collector that primarily serves residential and commercial land uses. The posted speed limit is 30-mph. The AADT in 2021 was 850 vehicles/day. Based upon existing turning movement counts, the percentage of heavy vehicles along Salkehatchie Road is approximately 2%.

Pine Street is a two-lane local road that primarily serves residential land uses. Based upon existing turning movement counts, the percentage of heavy vehicles along Pine Street is approximately 5%.



Exhibit 1.1 – Pine Street Residential Location Map






Exhibit 1.2 – Pine Street Residential Site Plan





## 2.0 DRIVEWAY SPACING REVIEW

Access to the development will be provided via one new proposed access along US 21, servicing the light industrial building, along with driveways along existing Pine Street, will serve as the access for the development.

As shown in **Exhibit 1.2**, For the purposes of the analysis, the intersection of US 21 & Pine Street is also referred to as Project Driveway #1, the intersection of Salkehatchie Road & Pine Street is also referred to as Project Driveway #2, and the new proposed access along US 21 is referred to as Project Driveway #3.

Since the intersections of US 21 & Pine Street and Salkehatchie Road & Pine Street currently exist, a driveway spacing was not performed for Project Driveways #1 and #2. However, a driveway spacing was performed for Project Driveway #3, since it is a new proposed access along US 21.

A review of the driveway spacing of the proposed driveway was completed based on information contained in SCDOT's *Access & Roadside Management Standards (ARMS)* manual (2008), shown in the adapted **Table 2.1**.

Table 2.1 – Minimum Driveway Spacing\*

Posted Speed Limit (mph)	AADT ≥ 2000; or Driveways Generating > 50 Peak Hour Trips	AADT < 2000
30	160 ft	75 ft
35	220 ft	125 ft
40	275 ft	175 ft
45	325 ft	225 ft
≥ 50	400 ft	275 ft

\*Figure 3-7 of *Access & Roadside Management Standards, 2008, SCDOT*

Based upon the 45-mph speed limit and the driveway spacing criteria of *ARMS*, a **minimum of 325 feet** is required for full access along US 21.

**Project Driveway #3** is proposed to be located along US 21, approximately 430 feet east of the intersection of US 21 & Pine Street, which meets the spacing criteria and approximately 4,700 feet west of the intersection of US 21 & Rum Bluff Road, which meets the spacing criteria.



## 3.0 PROJECT TRAFFIC

### 3.1 PROPOSED LAND USES

Project traffic in this analysis is defined as the vehicle trips anticipated to be generated by the proposed Pine Street Residential development. These trips were distributed and assigned throughout the study roadway network.

The Pine Street Residential development is proposed to consist of 71 single-family detached housing units and an approximately 100,000 square-foot light industrial building.

### 3.2 TRIP GENERATION ESTIMATES

The trip generation potential for the development was estimated using information contained in ITE's *Trip Generation Manual*, 11<sup>th</sup> Edition (2021) reference. The estimates utilized land use codes (LUC) 210 – Single-Family Detached Housing, and LUC 110 – General Light Industrial.

Due to the nature of the proposed Pine Street Residential development, internal capture trips and pass-by trips were not considered in the trip generation estimates.

The trip generation estimates for the development are shown below in **Table 3.1**, and documented in **Appendix A**.

### 3.3 TRIP DISTRIBUTION & ASSIGNMENT

#### 3.3.1 New External Traffic

New external traffic expected to be generated by the Pine Street Residential development was distributed and assigned to the roadway network based upon existing travel patterns in

the area. Since the proposed Pine Street Residential development will also consist of a 100,000 square-foot light industrial building, the residential and light industrial trips were distributed and assigned separately considering the nature of the trips attracted to/generated from these land uses. The general distribution of the residential project trips was assumed to be:

- ❖ 30% to/from the north via Salkehatchie Road;
- ❖ 10% to/from the south via Salkehatchie Road;
- ❖ 30% to/from the east via US 21; and
- ❖ 30% to/from the west via US 21.

The assignment of new external project traffic anticipated to be generated by the residential trips of the Pine Street Residential development is illustrated in **Exhibit 3.1**.

The general distribution of the light industrial project trips was assumed to be:

- ❖ 50% to/from the east via US 21; and
- ❖ 50% to/from the west via US 21.

The assignment of new external project traffic anticipated to be generated by the residential trips of the Pine Street Residential development is illustrated in **Exhibit 3.2**.

The AM and PM peak hour project traffic volumes are illustrated in **Exhibit 3.3**.

**Table 3.1 – Trip Generation Estimates**


Land Use	ITE LUC	Scale	Daily	Weekday AM Peak Period		Weekday PM Peak Period	
				Enter	Exit	Enter	Exit
Single-Family Detached Housing	210	71 Dwelling Units	736	14	41	45	27
General Light Industrial	110	100,000 Sq. Ft.	426	63	9	5	35
New, External Trips			1,162	77	50	50	62



Exhibit 3.1 - Project Traffic Distribution and Assignment  
(Residential)



Project Traffic Volume Assignment Legend		
00% - Inbound Trip Percentage	● TWSC	🚦 SIGNAL
(00%) - Outbound Trip Percentage		





### Exhibit 3.2 - Project Traffic Distribution and Assignment (Light Industrial)




#### Project Traffic Volume Assignment Legend

00% - Inbound Trip Percentage  
(00%) - Outbound Trip Percentage



TWSC SIGNAL








### Exhibit 3.3 - Peak Hour Project Traffic Volumes



Traffic Volumes Legend		
000 - AM Peak Hour Project Traffic	● TWSC	🚦 SIGNAL
(000) - AM Peak Hour Pass-By Traffic		





## 4.0 TRAFFIC VOLUME DEVELOPMENT

### 4.1 EXISTING TRAFFIC VOLUMES

The traffic impact analysis considers the weekday AM peak hour (between 7:00 AM and 9:00 AM) and the weekday PM peak hour (between 4:00 PM and 6:00 PM) as the study time frames. The extent of the existing roadway network to be studied consists of the three (3) intersections of:

1. US 21 & Salkehatchie Road;
2. US 21 & Pine Street (Project Driveway #1); and
3. Salkehatchie Road & Pine Street (Project Driveway #2).

Existing 2022 traffic volumes were collected at these study area intersections during the AM and PM peak periods listed above.

The raw traffic volume counts are provided in **Appendix B** and the 2022 existing AM and PM peak hour traffic volumes are illustrated in **Exhibit 4.1**.

### 4.2 FUTURE TRAFFIC PROJECTIONS

Future 2025 No Build traffic volumes were developed by adding *background traffic growth* to the collected existing study area peak hour volumes. *Background traffic growth* is growth anticipated to occur in the study area regardless of the proposed Pine Street Residential development.

To develop an annual background growth rate for use in the analysis, historical count data along US 21 (SCDOT count stations #103 & #105) and Salkehatchie Road (SCDOT count stations #271 & #273) was reviewed over the past 5 years. It was determined that the roadways have experienced a collective annual growth of less than 1%. Therefore, in an effort to be conservative, a 1% annual growth rate was utilized to develop anticipated *background traffic growth* through the anticipated 2025 buildout year.

Future 2025 No Build AM and PM peak hour traffic volumes, illustrated in **Exhibit 4.2**, were developed by adding the *background traffic growth* (assuming 1% annual growth of the existing traffic volumes) to the 2022 existing AM and PM peak hour traffic volumes.

Future 2025 Build AM and PM peak hour traffic volumes, illustrated in **Exhibit 4.3**, were developed by adding the Pine Street Residential project traffic (shown in **Exhibit 3.2**) volumes to the 2025 No Build traffic volumes.

Volume development worksheets for each intersection are documented in **Appendix C**.



## Exhibit 4.1 - 2022 Existing Peak Hour Traffic Volumes




### Traffic Volumes Legend

000 - AM Peak Hour Volumes  
(000) - PM Peak Hour Volumes

● TWSC

■ SIGNAL






## Exhibit 4.2 - 2025 No Build Peak Hour Traffic Volumes



### Traffic Volumes Legend

000 - AM Peak Hour Volumes  
(000) - PM Peak Hour Volumes







## Exhibit 4.3 - 2025 Build Peak Hour Traffic Volumes




### Traffic Volumes Legend

000 - AM Peak Hour Volumes  
(000) - PM Peak Hour Volumes

TWSC

SIGNAL





## 5.0 TRAFFIC IMPACT ANALYSIS

A traffic impact analysis was conducted for the Pine Street Residential development which analyzed the need for turn lanes at the project driveway and study intersections according to *Highway Capacity Manual (HCM) 6<sup>th</sup> Edition* methodologies.

### 5.1 TURN LANE ANALYSIS

#### 5.1.1 Right-Turn Lanes

The need for exclusive right-turn lanes is based upon the criteria documented in Section 9.5.1.1 of SCDOT's *Roadway Design Manual* (2021), which consists of nine considerations, listed below:

1. At a free-flowing leg of any unsignalized intersection on a two-lane urban or rural highway which satisfies the criteria in Figure 9.5-A;
2. at a free-flowing leg of any unsignalized intersection on a high-speed (50 mph or greater), four-lane urban or rural highway which satisfies the criteria in Figure 9.5-B;
3. at the free-flowing leg of any unsignalized intersection on a six-lane urban or rural highway;
4. at any intersection where a capacity analysis determines a right-turn lane is necessary to meet the overall level-of-service criteria;
5. as a general rule, at any signalized intersection where the projected right-turning volume is greater than 300 vehicles per hour and where there are greater than 300 vehicles per hour per lane on the mainline (A traffic analysis will be required if the turning volumes are greater than 300 vehicles per hour);
6. for uniformity of intersection design along the highway if other intersections have right-turn lanes;
7. at any intersection where the mainline is curved to the left and where the mainline curve requires superelevation;
8. at railroad crossings where the railroad is paralleled to the facility and is located close to the intersection and where a right-turn lane would be desirable to store queued vehicles avoiding interference with the movement of through traffic; or
9. at any intersection where the crash experience, existing traffic operations, sight distance restrictions (e.g., intersection beyond a crest vertical curve), or engineering judgement indicates a significant conflict related to right-turning vehicles;

Table 5.1 details whether the previously mentioned criteria are satisfied for Project Driveway #1 and at the study intersections of Salkehatchie Road & Pine Street (Project Driveway #2) and US 21 & Salkehatchie Road. An "✖" indicates that the criteria is not met; a "✓" indicates that it is met; and "N/A" indicates that the criteria is not applicable.

Table 5.1 – Right-Turn Lane Criteria Warrants

Crit- eria	PD #1	PD #3	Pine St & Salke- hatchie Rd	US 21 & Salke- hatchie Rd	Reference/ Note
1	✖	✖	✖	✖	Appendix G
2	N/A	N/A	N/A	N/A	Not a four-lane highway
3	N/A	N/A	N/A	N/A	Not a six-lane highway
4	✖	✖	✖	✖	Table 5.4
5	N/A	N/A	N/A	N/A	Not signalized
6	✖	✖	✖	✖	Not typically provided
7	✖	✖	✖	✖	Mainline not curved
8	✖	✖	✖	✖	No railroad crossing
9	N/A	N/A	N/A	N/A	Crash data not reviewed

Based on SCDOT's *Roadway Design Manual* considerations, exclusive right-turn lanes are **not recommended** at any of the study intersections.

Worksheets documenting the turn-lane analysis are provided in **Appendix G**.



## 5.1.2 Left-Turn Lanes

The need for exclusive left-turn lanes is based upon the criteria documented in Section 9.5.1.2 of SCDOT's *Roadway Design Manual* (2021), which consists of nine considerations, listed below:

1. At any unsignalized intersection on principal, high-speed rural highways with other arterials or collectors;
2. at any unsignalized intersection on a two-lane urban or rural highway that satisfies the criteria in Figures 9.5-C, 9.5-D, 9.5-E, 9.5-F, or 9.5-G;
3. at any intersection where a capacity analysis determines a left-turn lane is necessary to meet the level of service criteria;
4. at any signalized intersection where the left-turn volume is 300 vehicles per hour or more, conduct a traffic review to determine if dual left-turn lanes are required;
5. as a general rule, at any intersection where the left-turning volume is 100 vehicles per hour (for a single turn lane) or 300 vehicles per hour (for a dual turn lane);
6. at all entrances to major residential, commercial, and industrial developments;
7. at all median crossovers;
8. for uniformity of intersection design along the highway if other intersections have left-turn lanes (i.e., to satisfy driver expectancy); or
9. at any intersection where the crash experience, existing traffic operations, sight distance restrictions (e.g., intersection beyond a crest vertical curve), or engineering judgement indicates a significant conflict related to left-turning vehicles;

Table 5.2 below details whether the previously mentioned criteria are satisfied for Project Driveway #1 and at the study intersections of Salkehatchie Road & Pine Street (Project Driveway #2) and US 21 & Salkehatchie Road. An "✖" indicates that the criteria is not met; a "✓" indicates that it is met; and "N/A" indicates that the criteria is not applicable.

Table 5.2 – Left-Turn Lane Criteria Warrants

Crit- eria	PD #1	PD #3	Pine St & Salke- hatchie Rd	US 21 & Salke- hatchie Rd	Reference/ Note
1	N/A	N/A	N/A	N/A	Not an arterial or collector
2	✖	✖	✖*	✖	Appendix G
3	✖	✖	✖	✖	Table 5.4
4	N/A	N/A	N/A	N/A	Not signalized
5	✖	✖	✖	✖	Exhibit 4.3
6	✖	✖	✖	✖	Not a major development
7	✖	✖	✖	✖	No median crossover
8	✖	✖	✖	✖	Not typically provided
9	N/A	N/A	N/A	N/A	No crash data reviewed

\*Since Section 9.5.1.2 of SCDOT's *Roadway Design Manual* (2021) does not provide turn-lane criteria figure for roadways with speed limit 30 mph, Figure 9.5-G was used for analysis.

Based on SCDOT's *Roadway Design Manual* considerations, exclusive left-turn lanes are **not recommended** at any of the study intersections.

Worksheets documenting the turn-lane analysis are provided in **Appendix G**.



## 5.2 INTERSECTION LOS ANALYSIS

Using the existing and projected peak hour traffic volumes previously discussed, intersection analysis was conducted for the study and project driveway intersections considering 2022 Existing Conditions, 2025 No Build Conditions, and 2025 Build Conditions. The analysis was conducted using the Transportation Research Board's *Highway Capacity Manual (HCM) 6<sup>th</sup> Edition* methodologies of the *Synchro*, Version 11 software for stop-controlled intersection analysis.

Intersection level of service (LOS) grades range from LOS A to LOS F, which are directly related to the level of control delay at the intersection and characterize the operational conditions of the intersection traffic flow. LOS A operations typically represent ideal, free-flow conditions where vehicles experience little to no delays, and LOS F operations typically represent poor, forced-flow (bumper-to-bumper) conditions with high vehicular delays, and are generally considered undesirable. **Table 5.3** summarizes the HCM 6<sup>th</sup> Edition control delay thresholds associated with each LOS grade for unsignalized intersections. Level of service A through D is considered to be acceptable LOS, while LOS E and F is considered to be undesirable.

**Table 5.3 – HCM 6<sup>th</sup> Edition Intersection LOS Criteria**

LOS	Control Delay per Vehicle (s) Unsignalized
A	≤ 10
B	> 10 and ≤ 15
C	> 15 and ≤ 25
D	> 25 and ≤ 35
E	> 35 and ≤ 50
F	> 50

As part of the intersection analysis, SCDOT's default *Synchro* parameters were utilized. The existing 2022 traffic counts' peak hour factors (PHF) were utilized in the analysis of existing conditions. Future-year 2025 conditions were analyzed utilizing existing PHF, but with a minimum PHF of 0.90 and maximum PHF of 0.95 considered. The existing 2022 heavy vehicle percentages, as previously discussed, were utilized in the analysis, with a minimum percentage of 2% considered.

Existing lane geometry was utilized for the analysis of 2022 Existing Conditions and 2025 No Build Conditions. The 2025 Build Conditions were analyzed both with existing lane geometry and with any proposed improvements resulting from this impact analysis (including any proposed exclusive turn lanes per the results of **Section 5.1**) to illustrate their anticipated impact on traffic operations.

The results of the intersection analysis for existing and future-year conditions for the weekday AM and PM peak hour time periods are summarized in **Table 5.4**.

For two-way stop-controlled (TWSC) intersections, the LOS and delay results are evaluated for the worst-case minor-street approaches only, per *HCM 6<sup>th</sup> Edition* methodologies for TWSC intersections.

As shown in **Table 5.4**, the results of the analysis indicate that the study intersections currently operate and are expected to continue to operate at an acceptable LOS with the proposed Pine Street Residential development.

Worksheets documenting the intersection analyses are provided in **Appendix D** for 2022 Existing Conditions, **Appendix E** for 2025 No Build Conditions, and **Appendix F** for 2025 Build Conditions.





Table 5.4 – Peak Hour Intersection Analysis Results

Intersection	Control	LOS/Delay (seconds/vehicle)					
		AM Peak Hour			PM Peak Hour		
		2022 Existing	2025 No Build	2025 Build	2022 Existing	2025 No Build	2025 Build
1 US 21 & Salkehatchie Road	TWSC	B/10.3 (EB)	B/10.3 (EB)	B/10.9 (EB)	B/10.8 (WB)	B/10.8 (WB)	B/11.1 (WB)
2 US 21 & Pine Street (Project Driveway #1)	TWSC	--	--	A/9.5 (SB)	--	--	B/11.0 (SB)
3 Salkehatchie Road & Pine Street (Project Driveway #2)	TWSC	A/8.7 (WB)	A/8.7 (WB)	A/8.7 (WB)	A/8.6 (WB)	A/8.6 (WB)	A/8.7 (WB)
4 US 21 & Project Driveway #3	TWSC	--	--	A/9.6 (SB)	--	--	A/9.6 (SB)



## 6.0 SUMMARY OF FINDINGS AND RECOMMENDATIONS

A traffic impact analysis was conducted for the Pine Street Residential development in accordance with SCDOT and Town of Yemassee guidelines.

The proposed Pine Street Residential development (which is anticipated to be constructed by 2025) is located on Pine Street, north of US 21, and will consist of 71 single-family detached housing units and an approximately 100,000 square-foot light industrial building.

Access to the development will be provided via one new proposed access along US 21, servicing the light industrial building, which meets SCDOT's access spacing criteria, as well as via driveways along existing Pine Street, will serve as the access for the development.

For the purposes of the analysis, the intersection of US 21 & Pine Street is also referred to as Project Driveway #1, the intersection of Salkehatchie Road & Pine Street is also referred to as Project Driveway #2, and the new proposed access along US 21 is referred to as Project Driveway #3.

The extent of the roadway network analyzed consisted of the four (4) intersections of:

1. US 21 & Salkehatchie Road;
2. US 21 & Pine Street (Project Driveway #1);
3. Salkehatchie Road & Pine Street (Project Driveway #2);  
and
4. US 21 & Project Driveway #3.

The operation of each of the study area intersections (in terms of average vehicular delay and level of service) was analyzed with and without the project traffic anticipated to be generated by the Pine Street Residential development.

The results of the analysis indicate that the study intersections currently operate and are expected to continue to operate at an acceptable level of service with the proposed Pine Street Residential development.

Per the criteria documented in *Section 5D-4* of SCDOT's *Access and Roadside Management Standards (ARMS, 2008)*, exclusive turn lanes are not recommended at any of the study intersections or project driveways.



# **PINE STREET RESIDENTIAL TRAFFIC IMPACT ANALYSIS APPENDICES**



## Appendix A TRIP GENERATION WORKSHEETS



# TRIP GENERATION ESTIMATES

## Pine St Residential TIA

Weekday Daily																					
TRIP GENERATION CHARACTERISTICS						DIRECT. DISTRIB.		GROSS TRIPS			INTERNAL CAPTURE TRIPS				PASS-BY CAPTURE TRIPS				NEW EXTERNAL TRIPS		
Land Use	Ed.	LUC	Scale	Unit	Equation/Rate	In	Out	In	Out	Total	%	In	Out	Trips	%	In	Out	Trips	In	Out	Total
Single-Family Detached Housing General Light Industrial	11th	210	71	DU	$\text{Ln(T)} = 0.92 \text{ Ln(X)} + 2.68$	50%	50%	368	368	736	0%	0	0	0	0%	0	0	0	368	368	736
	11th	110	100	DU	$\text{T} = 3.76(\text{X}) + 50.47$	50%	50%	213	213	426	0%	0	0	0	0%	0	0	0	213	213	426
Total:								581	581	1,162	0%	0	0	0	0%	0	0	0	581	581	1,162

Weekday AM Peak Hour																					
TRIP GENERATION CHARACTERISTICS						DIRECT. DISTRIB.		GROSS TRIPS			INTERNAL CAPTURE TRIPS				PASS-BY CAPTURE TRIPS				NEW EXTERNAL TRIPS		
Land Use	Ed.	LUC	Scale	Unit	Equation/Rate	In	Out	In	Out	Total	%	In	Out	Trips	%	In	Out	Trips	In	Out	Total
Single-Family Detached Housing General Light Industrial	11th	210	71	DU	$\text{Ln(T)} = 0.91 \text{ Ln(X)} + 0.12$	26%	74%	14	41	55	0%	0	0	0	0%	0	0	0	14	41	55
	11th	110	100	DU	$\text{T} = 0.68 \text{ (X)} + 3.81$	88%	12%	63	9	72	0%	0	0	0	0%	0	0	0	63	9	72
Total:								77	50	127	0%	0	0	0	0%	0	0	0	77	50	127

Weekday PM Peak Hour																					
TRIP GENERATION CHARACTERISTICS						DIRECT. DISTRIB.		GROSS TRIPS			INTERNAL CAPTURE TRIPS				PASS-BY CAPTURE TRIPS				NEW EXTERNAL TRIPS		
Land Use	Ed.	LUC	Scale	Unit	Equation/Rate	In	Out	In	Out	Total	%	In	Out	Trips	%	In	Out	Trips	In	Out	Total
Single-Family Detached Housing	11th	210	71	DU	$\text{Ln(T)} = 0.94 \text{ Ln(X)} + 0.27$	63%	37%	45	27	72	0%	0	0	0	0%	0	0	0	45	27	72
General Light Industrial	11th	110	100	DU	$\text{Ln(T)} = 0.72 \text{ Ln(X)} + 0.38$	14%	86%	5	35	40	0%	0	0	0	0%	0	0	0	5	35	40
Total:								50	62	112	0%	0	0	0	0%	0	0	0	50	62	112



## Appendix B TRAFFIC VOLUME DATA

# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201

*We can't say we're the Best, but you Can!*

File Name : Pine St @ Salkehatchie Rd

Site Code :

Start Date : 11/03/2022

Page No : 1

Groups Printed- Passenger Vehicles - Heavy Vehicles - Buses

	Salkehatchie Rd Southbound				Pine St Westbound				Salkehatchie Rd Northbound				Eastbound					
Start Time	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Int. Total	
07:00	0	10	0	0	0	0	0	0	0	7	0	0	0	0	0	0	0	17
07:15	0	11	0	0	1	0	2	0	0	5	1	0	0	0	0	0	0	20
07:30	1	7	0	0	1	0	2	0	0	8	0	0	0	0	0	0	0	19
07:45	1	11	0	0	0	0	0	0	0	11	0	0	0	0	0	0	0	23
Total	2	39	0	0	2	0	4	0	0	31	1	0	0	0	0	0	0	79
08:00	1	14	0	0	0	0	2	0	0	8	0	0	0	0	0	0	0	25
08:15	1	13	0	0	1	0	0	0	0	11	0	0	0	0	0	0	0	26
08:30	1	6	0	0	0	0	1	0	0	3	0	0	0	0	0	0	0	11
08:45	0	7	0	0	0	0	1	0	0	3	0	0	0	0	0	0	0	11
Total	3	40	0	0	1	0	4	0	0	25	0	0	0	0	0	0	0	73
16:00	2	12	0	0	0	0	2	0	0	12	0	0	0	0	0	0	0	28
16:15	1	7	0	0	0	0	3	0	0	16	1	0	0	0	0	0	0	28
16:30	1	7	0	0	0	0	2	0	0	10	0	0	0	0	0	0	0	20
16:45	1	5	0	0	1	0	1	0	0	5	1	0	0	0	0	0	0	14
Total	5	31	0	0	1	0	8	0	0	43	2	0	0	0	0	0	0	90
17:00	0	8	0	0	0	0	1	0	0	14	0	0	0	0	0	0	0	23
17:15	1	5	0	0	0	0	1	0	0	11	1	0	0	0	0	0	0	19
17:30	0	7	0	0	0	0	1	0	0	21	0	0	0	0	0	0	0	29
17:45	3	9	0	0	0	0	2	0	0	11	0	0	0	0	0	0	0	25
Total	4	29	0	0	0	0	5	0	0	57	1	0	0	0	0	0	0	96
Grand Total	14	139	0	0	4	0	21	0	0	156	4	0	0	0	0	0	0	338
Apprch %	9.2	90.8	0	0	16	0	84	0	0	97.5	2.5	0	0	0	0	0	0	
Total %	4.1	41.1	0	0	1.2	0	6.2	0	0	46.2	1.2	0	0	0	0	0	0	
Passenger Vehicles	14	137	0	0	4	0	19	0	0	151	4	0	0	0	0	0	0	329
% Passenger Vehicles	100	98.6	0	0	100	0	90.5	0	0	96.8	100	0	0	0	0	0	0	97.3
Heavy Vehicles	0	2	0	0	0	0	1	0	0	2	0	0	0	0	0	0	0	5
% Heavy Vehicles	0	1.4	0	0	0	0	4.8	0	0	1.3	0	0	0	0	0	0	0	1.5
Buses	0	0	0	0	0	0	1	0	0	3	0	0	0	0	0	0	0	4
% Buses	0	0	0	0	0	0	4.8	0	0	1.9	0	0	0	0	0	0	0	1.2

# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201


*We can't say we're the Best, but you Can!*

File Name : Pine St @ Salkehatchie Rd

Site Code :

Start Date : 11/03/2022

Page No : 2





# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201

*We can't say we're the Best, but you Can!*


File Name : Pine St @ Salkehatchie Rd

Site Code :

Start Date : 11/03/2022

Page No : 3

	Salkehatchie Rd Southbound					Pine St Westbound					Salkehatchie Rd Northbound					Eastbound					
Start Time	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Int. Total
Peak Hour Analysis From 07:00 to 08:45 - Peak 1 of 1																					
Peak Hour for Entire Intersection Begins at 07:30																					
07:30	1	7	0	0	8	1	0	2	0	3	0	8	0	0	8	0	0	0	0	0	19
07:45	1	11	0	0	12	0	0	0	0	0	0	11	0	0	11	0	0	0	0	0	23
08:00	1	14	0	0	15	0	0	2	0	2	0	8	0	0	8	0	0	0	0	0	25
08:15	1	13	0	0	14	1	0	0	0	1	0	11	0	0	11	0	0	0	0	0	26
Total Volume	4	45	0	0	49	2	0	4	0	6	0	38	0	0	38	0	0	0	0	0	93
% App. Total	8.2	91.8	0	0		33.3	0	66.7	0		0	100	0	0		0	0	0	0		
PHF	1.00	.804	.000	.000	.817	.500	.000	.500	.000	.500	.000	.864	.000	.000	.864	.000	.000	.000	.000	.000	.894
Passenger Vehicles	4	43	0	0	47	2	0	4	0	6	0	36	0	0	36	0	0	0	0	0	89
% Passenger Vehicles																					
Heavy Vehicles	0	2	0	0	2	0	0	0	0	0	0	2	0	0	2	0	0	0	0	0	4
% Heavy Vehicles	0	4.4	0	0	4.1	0	0	0	0	0	0	5.3	0	0	5.3	0	0	0	0	0	4.3
Buses	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
% Buses	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0



# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201

*We can't say we're the Best, but you Can!*


File Name : Pine St @ Salkehatchie Rd

Site Code :

Start Date : 11/03/2022

Page No : 4

	Salkehatchie Rd Southbound					Pine St Westbound					Salkehatchie Rd Northbound					Eastbound					
Start Time	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Int. Total
Peak Hour Analysis From 16:00 to 17:45 - Peak 1 of 1																					
Peak Hour for Entire Intersection Begins at 17:00																					
17:00	0	8	0	0	8	0	0	1	0	1	0	14	0	0	14	0	0	0	0	0	23
17:15	1	5	0	0	6	0	0	1	0	1	0	11	1	0	12	0	0	0	0	0	19
17:30	0	7	0	0	7	0	0	1	0	1	0	21	0	0	21	0	0	0	0	0	29
17:45	3	9	0	0	12	0	0	2	0	2	0	11	0	0	11	0	0	0	0	0	25
Total Volume	4	29	0	0	33	0	0	5	0	5	0	57	1	0	58	0	0	0	0	0	96
% App. Total	12.1	87.9	0	0		0	0	100	0		0	98.3	1.7	0		0	0	0	0	0	
PHF	.333	.806	.000	.000	.688	.000	.000	.625	.000	.625	.000	.679	.250	.000	.690	.000	.000	.000	.000	.000	.828
Passenger Vehicles	4	29	0	0	33	0	0	5	0	5	0	56	1	0	57	0	0	0	0	0	95
% Passenger Vehicles																					
Heavy Vehicles	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
% Heavy Vehicles	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Buses	0	0	0	0	0	0	0	0	0	0	0	1	0	0	1	0	0	0	0	0	1
% Buses	0	0	0	0	0	0	0	0	0	0	0	1.8	0	0	1.7	0	0	0	0	0	1.0



# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201

*We can't say we're the Best, but you Can!*

File Name : US 21 @ Pine St

Site Code :

Start Date : 11/03/2022

Page No : 1

Groups Printed- Passenger Vehicles - Heavy Vehicles - Buses

Start Time	Pine St Southbound				US 21 Westbound				Northbound				US 21 Eastbound				Int. Total
	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Left	Thru	Right	Peds	
07:00	0	0	0	0	0	23	0	0	0	0	0	0	0	8	0	0	31
07:15	0	0	0	0	0	21	0	0	0	0	0	0	0	9	0	0	30
07:30	0	0	0	0	0	17	0	0	0	0	0	0	0	12	0	0	29
07:45	0	0	0	0	0	32	0	0	0	0	0	0	0	13	0	0	45
Total	0	0	0	0	0	93	0	0	0	0	0	0	0	42	0	0	135
08:00	0	0	0	0	0	23	0	0	0	0	0	0	0	11	0	0	34
08:15	0	0	0	0	0	16	0	0	0	0	0	0	0	8	0	0	24
08:30	0	0	0	0	0	14	0	0	0	0	0	0	0	10	0	0	24
08:45	0	0	0	0	0	22	0	0	0	0	0	0	0	11	0	0	33
Total	0	0	0	0	0	75	0	0	0	0	0	0	0	40	0	0	115
16:00	0	0	0	0	0	21	0	0	0	0	0	0	0	31	0	0	52
16:15	0	0	0	0	0	19	0	0	0	0	0	0	0	25	0	0	44
16:30	0	0	0	0	0	13	0	0	0	0	0	0	0	29	0	0	42
16:45	0	0	0	0	0	21	0	0	0	0	0	0	0	29	0	0	50
Total	0	0	0	0	0	74	0	0	0	0	0	0	0	114	0	0	188
17:00	0	0	0	0	0	14	0	0	0	0	0	0	0	32	0	0	46
17:15	0	0	0	0	0	21	0	0	0	0	0	0	0	27	0	0	48
17:30	0	0	0	0	0	13	0	0	0	0	0	0	0	37	0	0	50
17:45	0	0	0	0	0	32	0	0	0	0	0	0	0	25	0	0	57
Total	0	0	0	0	0	80	0	0	0	0	0	0	0	121	0	0	201
Grand Total	0	0	0	0	0	322	0	0	0	0	0	0	0	317	0	0	639
Apprch %	0	0	0	0	0	100	0	0	0	0	0	0	0	100	0	0	
Total %	0	0	0	0	0	50.4	0	0	0	0	0	0	0	49.6	0	0	
Passenger Vehicles	0	0	0	0	0	276	0	0	0	0	0	0	0	290	0	0	566
% Passenger Vehicles	0	0	0	0	0	85.7	0	0	0	0	0	0	0	91.5	0	0	88.6
Heavy Vehicles	0	0	0	0	0	45	0	0	0	0	0	0	0	26	0	0	71
% Heavy Vehicles	0	0	0	0	0	14	0	0	0	0	0	0	0	8.2	0	0	11.1
Buses	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0	0	2
% Buses	0	0	0	0	0	0.3	0	0	0	0	0	0	0	0.3	0	0	0.3

# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201


*We can't say we're the Best, but you Can!*

File Name : US 21 @ Pine St

Site Code :

Start Date : 11/03/2022

Page No : 2





# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201

*We can't say we're the Best, but you Can!*


File Name : US 21 @ Pine St

Site Code :

Start Date : 11/03/2022

Page No : 3

	Pine St Southbound					US 21 Westbound					Northbound					US 21 Eastbound					
Start Time	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Int. Total
Peak Hour Analysis From 07:00 to 08:45 - Peak 1 of 1																					
Peak Hour for Entire Intersection Begins at 07:15																					
07:15	0	0	0	0	0	0	21	0	0	21	0	0	0	0	0	0	9	0	0	9	30
07:30	0	0	0	0	0	0	17	0	0	17	0	0	0	0	0	0	12	0	0	12	29
07:45	0	0	0	0	0	0	32	0	0	32	0	0	0	0	0	0	13	0	0	13	45
08:00	0	0	0	0	0	0	23	0	0	23	0	0	0	0	0	0	11	0	0	11	34
Total Volume	0	0	0	0	0	0	93	0	0	93	0	0	0	0	0	0	45	0	0	45	138
% App. Total	0	0	0	0	0	0	100	0	0	100	0	0	0	0	0	0	100	0	0	100	100
PHF	.000	.000	.000	.000	.000	.000	.727	.000	.000	.727	.000	.000	.000	.000	.000	.000	.865	.000	.000	.865	.767
Passenger Vehicles	0	0	0	0	0	0	78	0	0	78	0	0	0	0	0	0	40	0	0	40	118
% Passenger Vehicles																					
Heavy Vehicles	0	0	0	0	0	0	15	0	0	15	0	0	0	0	0	0	5	0	0	5	20
% Heavy Vehicles	0	0	0	0	0	0	16.1	0	0	16.1	0	0	0	0	0	0	11.1	0	0	11.1	14.5
Buses	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
% Buses	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0



# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201

*We can't say we're the Best, but you Can!*


File Name : US 21 @ Pine St

Site Code :

Start Date : 11/03/2022

Page No : 4

	Pine St Southbound					US 21 Westbound					Northbound					US 21 Eastbound					
Start Time	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Int. Total
Peak Hour Analysis From 16:00 to 17:45 - Peak 1 of 1																					
Peak Hour for Entire Intersection Begins at 17:00																					
17:00	0	0	0	0	0	0	14	0	0	14	0	0	0	0	0	0	32	0	0	32	46
17:15	0	0	0	0	0	0	21	0	0	21	0	0	0	0	0	0	27	0	0	27	48
17:30	0	0	0	0	0	0	13	0	0	13	0	0	0	0	0	0	37	0	0	37	50
17:45	0	0	0	0	0	0	32	0	0	32	0	0	0	0	0	0	25	0	0	25	57
Total Volume	0	0	0	0	0	0	80	0	0	80	0	0	0	0	0	0	121	0	0	121	201
% App. Total	0	0	0	0	0	0	100	0	0	100	0	0	0	0	0	0	100	0	0	100	
PHF	.000	.000	.000	.000	.000	.000	.625	.000	.000	.625	.000	.000	.000	.000	.000	.000	.818	.000	.000	.818	.882
Passenger Vehicles	0	0	0	0	0	0	77	0	0	77	0	0	0	0	0	0	111	0	0	111	188
% Passenger Vehicles																					
Heavy Vehicles	0	0	0	0	0	0	3	0	0	3	0	0	0	0	0	0	10	0	0	10	13
% Heavy Vehicles	0	0	0	0	0	0	3.8	0	0	3.8	0	0	0	0	0	0	8.3	0	0	8.3	6.5
Buses	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
% Buses	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0





# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201

*We can't say we're the Best, but you Can!*

File Name : US 21 @ Salkehatchie Rd

Site Code :

Start Date : 11/03/2022

Page No : 1

Groups Printed- Passenger Vehicles - Heavy Vehicles - Buses

Start Time	US 21 Southbound				Salkehatchie Rd Westbound				US 21 Northbound				Salkehatchie Rd Eastbound				Int. Total
	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Left	Thru	Right	Peds	
07:00	5	9	2	0	0	4	2	0	1	6	0	0	1	8	0	0	38
07:15	7	11	1	0	2	0	3	0	1	2	0	0	0	5	5	0	37
07:30	7	6	2	7	1	4	3	0	0	5	3	0	1	5	2	0	46
07:45	9	22	3	3	1	4	1	0	0	5	6	2	2	9	1	0	68
Total	28	48	8	10	4	12	9	0	2	18	9	2	4	27	8	0	189
08:00	8	14	2	1	1	5	5	0	0	5	3	1	4	8	5	0	62
08:15	6	12	3	0	0	4	2	0	4	2	1	0	2	7	2	0	45
08:30	4	9	1	0	1	3	4	0	1	6	0	0	2	4	3	0	38
08:45	2	6	2	0	1	3	1	0	0	6	1	0	4	8	1	0	35
Total	20	41	8	1	3	15	12	0	5	19	5	1	12	27	11	0	180
16:00	4	12	4	1	2	8	4	0	4	15	0	0	7	8	3	0	72
16:15	3	5	5	0	2	12	7	0	3	12	4	0	3	6	1	0	63
16:30	2	12	6	0	4	5	4	0	3	14	0	0	4	4	2	0	60
16:45	2	11	7	2	0	3	12	0	3	12	0	0	4	2	2	0	60
Total	11	40	22	3	8	28	27	0	13	53	4	0	18	20	8	0	255
17:00	1	10	3	0	4	11	6	0	7	21	4	0	5	4	2	0	78
17:15	12	5	7	0	0	4	14	0	0	11	0	0	5	1	2	0	61
17:30	4	5	6	0	1	12	11	0	8	9	2	0	6	2	6	0	72
17:45	10	13	2	0	0	7	7	0	3	12	1	1	4	5	0	0	65
Total	27	33	18	0	5	34	38	0	18	53	7	1	20	12	10	0	276
Grand Total	86	162	56	14	20	89	86	0	38	143	25	4	54	86	37	0	900
Apprch %	27	50.9	17.6	4.4	10.3	45.6	44.1	0	18.1	68.1	11.9	1.9	30.5	48.6	20.9	0	
Total %	9.6	18	6.2	1.6	2.2	9.9	9.6	0	4.2	15.9	2.8	0.4	6	9.6	4.1	0	
Passenger Vehicles	83	127	56	14	19	87	82	0	37	121	25	4	54	85	37	0	831
% Passenger Vehicles	96.5	78.4	100	100	95	97.8	95.3	0	97.4	84.6	100	100	100	98.8	100	0	92.3
Heavy Vehicles	3	35	0	0	1	0	4	0	0	20	0	0	0	1	0	0	64
% Heavy Vehicles	3.5	21.6	0	0	5	0	4.7	0	0	14	0	0	0	1.2	0	0	7.1
Buses	0	0	0	0	0	2	0	0	1	2	0	0	0	0	0	0	5
% Buses	0	0	0	0	0	2.2	0	0	2.6	1.4	0	0	0	0	0	0	0.6

# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201


*We can't say we're the Best, but you Can!*

File Name : US 21 @ Salkehatchie Rd

Site Code :

Start Date : 11/03/2022

Page No : 2





# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201

*We can't say we're the Best, but you Can!*


File Name : US 21 @ Salkehatchie Rd

Site Code :

Start Date : 11/03/2022

Page No : 3

	US 21 Southbound					Salkehatchie Rd Westbound					US 21 Northbound					Salkehatchie Rd Eastbound					
Start Time	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Int. Total
Peak Hour Analysis From 07:00 to 08:45 - Peak 1 of 1																					
Peak Hour for Entire Intersection Begins at 07:30																					
07:30	7	6	2	7	22	1	4	3	0	8	0	5	3	0	8	1	5	2	0	8	46
07:45	9	22	3	3	37	1	4	1	0	6	0	5	6	2	13	2	9	1	0	12	68
08:00	8	14	2	1	25	1	5	5	0	11	0	5	3	1	9	4	8	5	0	17	62
08:15	6	12	3	0	21	0	4	2	0	6	4	2	1	0	7	2	7	2	0	11	45
Total Volume	30	54	10	11	105	3	17	11	0	31	4	17	13	3	37	9	29	10	0	48	221
% App. Total	28.6	51.4	9.5	10.5		9.7	54.8	35.5	0		10.8	45.9	35.1	8.1		18.8	60.4	20.8	0		
PHF	.833	.614	.833	.393	.709	.750	.850	.550	.000	.705	.250	.850	.542	.375	.712	.563	.806	.500	.000	.706	.813
Passenger Vehicles	28	41	10	11	90	3	17	11	0	31	4	11	13	3	31	9	28	10	0	47	199
% Passenger Vehicles																					
Heavy Vehicles	2	13	0	0	15	0	0	0	0	0	0	6	0	0	6	0	1	0	0	1	22
% Heavy Vehicles	6.7	24.1	0	0	14.3	0	0	0	0	0	0	35.3	0	0	16.2	0	3.4	0	0	2.1	10.0
Buses	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
% Buses	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0



# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201

*We can't say we're the Best, but you Can!*


File Name : US 21 @ Salkehatchie Rd

Site Code :

Start Date : 11/03/2022

Page No : 4

	US 21 Southbound					Salkehatchie Rd Westbound					US 21 Northbound					Salkehatchie Rd Eastbound					
Start Time	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Int. Total
Peak Hour Analysis From 16:00 to 17:45 - Peak 1 of 1																					
Peak Hour for Entire Intersection Begins at 17:00																					
17:00	1	10	3	0	14	4	11	6	0	21	7	21	4	0	32	5	4	2	0	11	78
17:15	12	5	7	0	24	0	4	14	0	18	0	11	0	0	11	5	1	2	0	8	61
17:30	4	5	6	0	15	1	12	11	0	24	8	9	2	0	19	6	2	6	0	14	72
17:45	10	13	2	0	25	0	7	7	0	14	3	12	1	1	17	4	5	0	0	9	65
Total Volume	27	33	18	0	78	5	34	38	0	77	18	53	7	1	79	20	12	10	0	42	276
% App. Total	34.6	42.3	23.1	0		6.5	44.2	49.4	0		22.8	67.1	8.9	1.3		47.6	28.6	23.8	0		
PHF	.563	.635	.643	.000	.780	.313	.708	.679	.000	.802	.563	.631	.438	.250	.617	.833	.600	.417	.000	.750	.885
Passenger Vehicles	27	30	18	0	75	5	34	37	0	76	17	46	7	1	71	20	12	10	0	42	264
% Passenger Vehicles																					
Heavy Vehicles	0	3	0	0	3	0	0	1	0	1	0	7	0	0	7	0	0	0	0	0	11
% Heavy Vehicles	0	9.1	0	0	3.8	0	0	2.6	0	1.3	0	13.2	0	0	8.9	0	0	0	0	0	4.0
Buses	0	0	0	0	0	0	0	0	0	0	1	0	0	0	1	0	0	0	0	0	1
% Buses	0	0	0	0	0	0	0	0	0	0	5.6	0	0	0	1.3	0	0	0	0	0	0.4







## Appendix C TRAFFIC VOLUME DEVELOPMENT WORKSHEETS

# 1 - Salkehatchie Rd & US 21

Traffic Control: TWSC

Date Counted: 11/3/2022

## TOTAL PROJECT TRAFFIC

IN OUT IN OUT

AM 77 50 PM 50 62

AM PEAK HOUR 7:30 AM - 8:30 AM	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
2022 Existing Traffic Volumes	9	29	10	3	17	11	4	17	13	30	54	10
Years to Buildout	3	3	3	3	3	3	3	3	3	3	3	3
Yearly Growth Rate	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%
Background Traffic	0	1	0	0	1	0	0	1	0	1	2	0
Vested Traffic												
2025 No Build Traffic Volumes	9	30	10	3	18	11	4	18	13	31	56	10
Inbound Residential Project Traffic %				10%			5%	25%				
Outbound Residential Project Traffic %	5%								10%		25%	
Inbound Industrial Project Traffic %							50%					
Outbound Industrial Project Traffic %									50%			
2025 Project Traffic	0	0	2	0	0	1	1	35	0	4	15	0
2025 Build Traffic Volumes	9	30	12	3	18	12	5	53	13	35	71	10

PM PEAK HOUR 5:00 PM - 6:00 PM	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
2022 Existing Traffic Volumes	20	12	10	5	34	38	18	53	7	27	33	18
Years to Buildout	3	3	3	3	3	3	3	3	3	3	3	3
Yearly Growth Rate	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%
Background Traffic	1	0	0	0	1	1	1	2	0	1	1	1
Vested Traffic												
2025 No Build Traffic Volumes	21	12	10	5	35	39	19	55	7	28	34	19
Inbound Project Traffic %				10%			5%	25%				
Outbound Project Traffic %	5%									10%	25%	
Inbound Industrial Project Traffic %							50%					
Outbound Industrial Project Traffic %									50%			
2025 Project Traffic	0	0	1	0	0	5	2	14	0	3	24	0
2025 Build Traffic Volumes	21	12	11	5	35	44	21	69	7	31	58	19



## 2 - US 21 & Pine Street/Project Driveway #1

<div> <div>Traffic Control: TWSC</div> <div>Date Counted: 11/3/2022</div> </div> <div> <div>TOTAL PROJECT TRAFFIC</div> <div> <div>IN</div> <div>OUT</div> </div> <div> <div>IN</div> <div>OUT</div> </div> </div>												
AM PEAK HOUR 7:15 AM - 8:15 AM	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
2022 Existing Traffic Volumes	0	45	0	0	93	0	0	0	0	0	0	0
Years to Buildout	3	3	3	3	3	3	3	3	3	3	3	3
Yearly Growth Rate	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%
Background Traffic	0	1	0	0	3	0	0	0	0	0	0	0
Vested Traffic												
2025 No Build Traffic Volumes	0	46	0	0	96	0	0	0	0	0	0	0
Inbound Project Traffic %	35%			30%						30%		
Outbound Project Traffic %										35%		
Inbound Industrial Project Traffic %	25%	25%										
Outbound Industrial Project Traffic %				25%						25%	25%	
2025 Project Traffic	21	15	0	0	2	20	0	0	0	15	0	17
2025 Build Traffic Volumes	21	61	0	0	98	20	0	0	0	15	0	17

PM PEAK HOUR 5:00 PM - 6:00 PM	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
2022 Existing Traffic Volumes	0	121	0	0	80	0	0	0	0	0	0	0
Years to Buildout	3	3	3	3	3	3	3	3	3	3	3	3
Yearly Growth Rate	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%
Background Traffic	0	4	0	0	2	0	0	0	0	0	0	0
Vested Traffic												
2025 No Build Traffic Volumes	0	125	0	0	82	0	0	0	0	0	0	0
Inbound Project Traffic %	35%			30%						30%		
Outbound Project Traffic %										35%		
Inbound Industrial Project Traffic %	25%	25%										
Outbound Industrial Project Traffic %				25%						25%	25%	
2025 Project Traffic	17	1	0	0	9	15	0	0	0	17	0	18
2025 Build Traffic Volumes	17	126	0	0	91	15	0	0	0	17	0	18

### 3 - Salkehatchie Rd & Pine Street/Project Driveway #2

Traffic Control: TWSC

Date Counted: 11/3/2022

#### TOTAL PROJECT TRAFFIC

				AM			PM					
				IN			OUT					
				77			50			62		
AM PEAK HOUR 7:30 AM - 8:30 AM	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
2022 Existing Traffic Volumes	0	0	0	2	0	4	0	38	0	4	45	0
Years to Buildout	3	3	3	3	3	3	3	3	3	3	3	3
Yearly Growth Rate	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%
Background Traffic	0	0	0	0	0	0	0	1	0	0	1	0
Vested Traffic												
2025 No Build Traffic Volumes	0	0	0	2	0	4	0	39	0	4	46	0
Inbound Project Traffic %							5%			30%		
Outbound Project Traffic %				5%			30%					
Inbound Industrial Project Traffic %												
Outbound Industrial Project Traffic %												
2025 Project Traffic	0	0	0	2	0	12	0	0	1	4	0	0
2025 Build Traffic Volumes	0	0	0	4	0	16	0	39	1	8	46	0

PM PEAK HOUR 5:00 PM - 6:00 PM	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
2022 Existing Traffic Volumes	0	0	0	0	0	5	0	57	1	4	29	0
Years to Buildout	3	3	3	3	3	3	3	3	3	3	3	3
Yearly Growth Rate	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%
Background Traffic	0	0	0	0	0	0	0	2	0	0	1	0
Vested Traffic												
2025 No Build Traffic Volumes	0	0	0	0	0	5	0	59	1	4	30	0
Inbound Project Traffic %							5%			30%		
Outbound Project Traffic %				5%			30%					
Inbound Industrial Project Traffic %												
Outbound Industrial Project Traffic %												
2025 Project Traffic	0	0	0	1	0	8	0	0	2	14	0	0
2025 Build Traffic Volumes	0	0	0	1	0	13	0	59	3	18	30	0



#### 4 - US 21 & Project Driveway #3





TOTAL PROJECT TRAFFIC												
Traffic Control: TWSC				IN			OUT					
Date Counted: 11/3/2022				AM			PM					
				77			50			62		
AM PEAK HOUR 7:15 AM - 8:15 AM	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
2022 Existing Traffic Volumes	0	45	0	0	93	0	0	0	0	0	0	0
Years to Buildout	3	3	3	3	3	3	3	3	3	3	3	3
Yearly Growth Rate	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%
Background Traffic	0	1	0	0	3	0	0	0	0	0	0	0
Vested Traffic												
2025 No Build Traffic Volumes	0	46	0	0	96	0	0	0	0	0	0	0
Inbound Project Traffic %				30%								
Outbound Project Traffic %	30%											
Inbound Industrial Project Traffic %	25%			25%		25%						
Outbound Industrial Project Traffic %	25%									25%		25%
2025 Project Traffic	15	15	0	0	20	16	0	0	0	2	0	2
2025 Build Traffic Volumes	15	61	0	0	116	16	0	0	0	2	0	2




PM PEAK HOUR 5:00 PM - 6:00 PM	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
2022 Existing Traffic Volumes	0	121	0	0	80	0	0	0	0	0	0	0
Years to Buildout	3	3	3	3	3	3	3	3	3	3	3	3
Yearly Growth Rate	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%
Background Traffic	0	4	0	0	2	0	0	0	0	0	0	0
Vested Traffic												
2025 No Build Traffic Volumes	0	125	0	0	82	0	0	0	0	0	0	0
Inbound Project Traffic %				30%								
Outbound Project Traffic %	30%											
Inbound Industrial Project Traffic %	25%			25%		25%						
Outbound Industrial Project Traffic %	25%									25%		25%
2025 Project Traffic	1	17	0	0	15	1	0	0	0	9	0	9
2025 Build Traffic Volumes	1	142	0	0	97	1	0	0	0	9	0	9



## Appendix D ANALYSIS WORKSHEETS: 2022 EXISTING CONDITIONS

Intersection												
Int Delay, s/veh	5.1											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	9	29	10	3	17	11	4	17	13	30	54	10
Future Vol, veh/h	9	29	10	3	17	11	4	17	13	30	54	10
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	89	89	89	89	89	89	89	89	89	89	89	89
Heavy Vehicles, %	14	14	14	16	16	16	2	2	2	2	2	2
Mvmt Flow	10	33	11	3	19	12	4	19	15	34	61	11
Major/Minor	Minor2		Minor1			Major1			Major2			
Conflicting Flow All	185	177	67	192	175	27	72	0	0	34	0	0
Stage 1	135	135	-	35	35	-	-	-	-	-	-	-
Stage 2	50	42	-	157	140	-	-	-	-	-	-	-
Critical Hdwy	7.24	6.64	6.34	7.26	6.66	6.36	4.12	-	-	4.12	-	-
Critical Hdwy Stg 1	6.24	5.64	-	6.26	5.66	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.24	5.64	-	6.26	5.66	-	-	-	-	-	-	-
Follow-up Hdwy	3.626	4.126	3.426	3.644	4.144	3.444	2.218	-	-	2.218	-	-
Pot Cap-1 Maneuver	750	695	964	738	694	1010	1528	-	-	1578	-	-
Stage 1	840	762	-	946	839	-	-	-	-	-	-	-
Stage 2	934	837	-	813	755	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	711	678	964	689	677	1010	1528	-	-	1578	-	-
Mov Cap-2 Maneuver	711	678	-	689	677	-	-	-	-	-	-	-
Stage 1	837	745	-	943	836	-	-	-	-	-	-	-
Stage 2	899	834	-	751	738	-	-	-	-	-	-	-
Approach	EB		WB			NB			SB			
HCM Control Delay, s	10.3		9.9			0.9			2.3			
HCM LOS	B		A									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR					
Capacity (veh/h)	1528	-	-	729	768	1578	-	-				
HCM Lane V/C Ratio	0.003	-	-	0.074	0.045	0.021	-	-				
HCM Control Delay (s)	7.4	0	-	10.3	9.9	7.3	0	-				
HCM Lane LOS	A	A	-	B	A	A	A	-				
HCM 95th %tile Q(veh)	0	-	-	0.2	0.1	0.1	-	-				










Intersection						
Int Delay, s/veh	0.9					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	2	4	38	0	4	45
Future Vol, veh/h	2	4	38	0	4	45
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	89	89	89	89	89	89
Heavy Vehicles, %	2	2	5	5	4	4
Mvmt Flow	2	4	43	0	4	51

Major/Minor	Minor1	Major1	Major2		
Conflicting Flow All	102	43	0	0	43
Stage 1	43	-	-	-	-
Stage 2	59	-	-	-	-
Critical Hdwy	6.42	6.22	-	-	4.14
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	3.318	-	-	2.236
Pot Cap-1 Maneuver	896	1027	-	-	1553
Stage 1	979	-	-	-	-
Stage 2	964	-	-	-	-
Platoon blocked, %			-	-	-
Mov Cap-1 Maneuver	893	1027	-	-	1553
Mov Cap-2 Maneuver	893	-	-	-	-
Stage 1	979	-	-	-	-
Stage 2	961	-	-	-	-

Approach	WB	NB	SB
HCM Control Delay, s	8.7	0	0.6
HCM LOS	A		

Minor Lane/Major Mvmt	NBT	NBRWBLn1	SBL	SBT
Capacity (veh/h)	-	-	978	1553
HCM Lane V/C Ratio	-	-	0.007	0.003
HCM Control Delay (s)	-	-	8.7	7.3
HCM Lane LOS	-	-	A	A
HCM 95th %tile Q(veh)	-	-	0	0

Intersection												
Int Delay, s/veh	5.8											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	20	12	10	5	34	38	18	53	7	27	33	18
Future Vol, veh/h	20	12	10	5	34	38	18	53	7	27	33	18
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	83	83	83	83	83	83	83	83	83	83	83	83
Heavy Vehicles, %	4	4	4	9	9	9	2	2	2	2	2	2
Mvmt Flow	24	14	12	6	41	46	22	64	8	33	40	22
Major/Minor	Minor2		Minor1			Major1			Major2			
Conflicting Flow All	273	233	51	242	240	68	62	0	0	72	0	0
Stage 1	117	117	-	112	112	-	-	-	-	-	-	-
Stage 2	156	116	-	130	128	-	-	-	-	-	-	-
Critical Hdwy	7.14	6.54	6.24	7.19	6.59	6.29	4.12	-	-	4.12	-	-
Critical Hdwy Stg 1	6.14	5.54	-	6.19	5.59	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.14	5.54	-	6.19	5.59	-	-	-	-	-	-	-
Follow-up Hdwy	3.536	4.036	3.336	3.581	4.081	3.381	2.218	-	-	2.218	-	-
Pot Cap-1 Maneuver	675	664	1011	698	649	976	1541	-	-	1528	-	-
Stage 1	883	795	-	876	789	-	-	-	-	-	-	-
Stage 2	842	796	-	857	777	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	594	639	1011	659	625	976	1541	-	-	1528	-	-
Mov Cap-2 Maneuver	594	639	-	659	625	-	-	-	-	-	-	-
Stage 1	870	778	-	863	777	-	-	-	-	-	-	-
Stage 2	749	784	-	813	760	-	-	-	-	-	-	-
Approach	EB		WB			NB			SB			
HCM Control Delay, s	10.8		10.4			1.7			2.6			
HCM LOS	B		B									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR					
Capacity (veh/h)	1541	-	-	674	763	1528	-	-				
HCM Lane V/C Ratio	0.014	-	-	0.075	0.122	0.021	-	-				
HCM Control Delay (s)	7.4	0	-	10.8	10.4	7.4	0	-				
HCM Lane LOS	A	A	-	B	B	A	A	-				
HCM 95th %tile Q(veh)	0	-	-	0.2	0.4	0.1	-	-				

Intersection						
Int Delay, s/veh	0.8					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	0	5	57	1	4	29
Future Vol, veh/h	0	5	57	1	4	29
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	0	6	63	1	4	32

Major/Minor	Minor1	Major1	Major2		
Conflicting Flow All	104	64	0	0	64
Stage 1	64	-	-	-	-
Stage 2	40	-	-	-	-
Critical Hdwy	6.42	6.22	-	-	4.12
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	3.318	-	-	2.218
Pot Cap-1 Maneuver	894	1000	-	-	1538
Stage 1	959	-	-	-	-
Stage 2	982	-	-	-	-
Platoon blocked, %			-	-	-
Mov Cap-1 Maneuver	891	1000	-	-	1538
Mov Cap-2 Maneuver	891	-	-	-	-
Stage 1	959	-	-	-	-
Stage 2	979	-	-	-	-





Approach	WB	NB	SB
HCM Control Delay, s	8.6	0	0.9
HCM LOS	A		




Minor Lane/Major Mvmt	NBT	NBRWBLn1	SBL	SBT
Capacity (veh/h)	-	- 1000	1538	-
HCM Lane V/C Ratio	-	- 0.006	0.003	-
HCM Control Delay (s)	-	- 8.6	7.3	0
HCM Lane LOS	-	- A	A	A
HCM 95th %tile Q(veh)	-	- 0	0	-









## Appendix E ANALYSIS WORKSHEETS: 2025 NO BUILD CONDITIONS

Intersection												
Int Delay, s/veh	5											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	9	30	10	3	18	11	4	18	13	31	56	10
Future Vol, veh/h	9	30	10	3	18	11	4	18	13	31	56	10
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	14	14	14	16	16	16	2	2	2	2	2	2
Mvmt Flow	10	33	11	3	20	12	4	20	14	34	62	11
Major/Minor	Minor2		Minor1			Major1			Major2			
Conflicting Flow All	187	178	68	193	176	27	73	0	0	34	0	0
Stage 1	136	136	-	35	35	-	-	-	-	-	-	-
Stage 2	51	42	-	158	141	-	-	-	-	-	-	-
Critical Hdwy	7.24	6.64	6.34	7.26	6.66	6.36	4.12	-	-	4.12	-	-
Critical Hdwy Stg 1	6.24	5.64	-	6.26	5.66	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.24	5.64	-	6.26	5.66	-	-	-	-	-	-	-
Follow-up Hdwy	3.626	4.126	3.426	3.644	4.144	3.444	2.218	-	-	2.218	-	-
Pot Cap-1 Maneuver	748	695	963	737	693	1010	1527	-	-	1578	-	-
Stage 1	839	761	-	946	839	-	-	-	-	-	-	-
Stage 2	932	837	-	812	754	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	708	678	963	688	676	1010	1527	-	-	1578	-	-
Mov Cap-2 Maneuver	708	678	-	688	676	-	-	-	-	-	-	-
Stage 1	836	744	-	943	836	-	-	-	-	-	-	-
Stage 2	896	834	-	750	737	-	-	-	-	-	-	-
Approach	EB		WB			NB			SB			
HCM Control Delay, s	10.3		9.9			0.8			2.3			
HCM LOS	B		A									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	WBLn1	SBL	SBT	SBR				
Capacity (veh/h)	1527	-	-	728	764	1578	-	-				
HCM Lane V/C Ratio	0.003	-	-	0.075	0.047	0.022	-	-				
HCM Control Delay (s)	7.4	0	-	10.3	9.9	7.3	0	-				
HCM Lane LOS	A	A	-	B	A	A	A	-				
HCM 95th %tile Q(veh)	0	-	-	0.2	0.1	0.1	-	-				

Intersection						
Int Delay, s/veh	0.9					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	2	4	39	0	4	46
Future Vol, veh/h	2	4	39	0	4	46
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	5	5	4	4
Mvmt Flow	2	4	43	0	4	51
Major/Minor	Minor1	Major1	Major2			
Conflicting Flow All	102	43	0	0	43	0
Stage 1	43	-	-	-	-	-
Stage 2	59	-	-	-	-	-
Critical Hdwy	6.42	6.22	-	-	4.14	-
Critical Hdwy Stg 1	5.42	-	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-	-
Follow-up Hdwy	3.518	3.318	-	-	2.236	-
Pot Cap-1 Maneuver	896	1027	-	-	1553	-
Stage 1	979	-	-	-	-	-
Stage 2	964	-	-	-	-	-
Platoon blocked, %			-	-		-
Mov Cap-1 Maneuver	893	1027	-	-	1553	-
Mov Cap-2 Maneuver	893	-	-	-	-	-
Stage 1	979	-	-	-	-	-
Stage 2	961	-	-	-	-	-
Approach	WB	NB		SB		
HCM Control Delay, s	8.7	0		0.6		
HCM LOS	A					
Minor Lane/Major Mvmt	NBT	NBRWBLn1	SBL	SBT		
Capacity (veh/h)	-	-	978	1553	-	
HCM Lane V/C Ratio	-	-	0.007	0.003	-	
HCM Control Delay (s)	-	-	8.7	7.3	0	
HCM Lane LOS	-	-	A	A	A	
HCM 95th %tile Q(veh)	-	-	0	0	-	



Intersection												
Int Delay, s/veh	5.7											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	21	12	10	5	35	39	19	55	7	28	34	19
Future Vol, veh/h	21	12	10	5	35	39	19	55	7	28	34	19
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	4	4	4	9	9	9	2	2	2	2	2	2
Mvmt Flow	23	13	11	6	39	43	21	61	8	31	38	21




Major/Minor	Minor2		Minor1		Major1		Major2	
Conflicting Flow All	259	222	49	230	228	65	59	0
Stage 1	111	111	-	107	107	-	-	-
Stage 2	148	111	-	123	121	-	-	-
Critical Hdwy	7.14	6.54	6.24	7.19	6.59	6.29	4.12	-
Critical Hdwy Stg 1	6.14	5.54	-	6.19	5.59	-	-	-
Critical Hdwy Stg 2	6.14	5.54	-	6.19	5.59	-	-	-
Follow-up Hdwy	3.536	4.036	3.336	3.581	4.081	3.381	2.218	-
Pot Cap-1 Maneuver	690	673	1014	710	659	980	1545	-
Stage 1	889	800	-	882	793	-	-	-
Stage 2	850	800	-	864	782	-	-	-
Platoon blocked, %								-
Mov Cap-1 Maneuver	612	649	1014	673	636	980	1545	-
Mov Cap-2 Maneuver	612	649	-	673	636	-	-	-
Stage 1	877	783	-	870	782	-	-	-
Stage 2	761	789	-	822	766	-	-	-

Approach	EB	WB	NB	SB
HCM Control Delay, s	10.6	10.3	1.7	2.6
HCM LOS	B	B		

Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR
Capacity (veh/h)	1545	-	-	686	773	1532	-
HCM Lane V/C Ratio	0.014	-	-	0.07	0.114	0.02	-
HCM Control Delay (s)	7.4	0	-	10.6	10.3	7.4	0
HCM Lane LOS	A	A	-	B	B	A	A
HCM 95th %tile Q(veh)	0	-	-	0.2	0.4	0.1	-

Intersection						
Int Delay, s/veh	0.7					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	0	5	59	1	4	30
Future Vol, veh/h	0	5	59	1	4	30
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	0	6	66	1	4	33
Major/Minor	Minor1	Major1	Major2			
Conflicting Flow All	108	67	0	0	67	0
Stage 1	67	-	-	-	-	-
Stage 2	41	-	-	-	-	-
Critical Hdwy	6.42	6.22	-	-	4.12	-
Critical Hdwy Stg 1	5.42	-	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-	-
Follow-up Hdwy	3.518	3.318	-	-	2.218	-
Pot Cap-1 Maneuver	889	997	-	-	1535	-
Stage 1	956	-	-	-	-	-
Stage 2	981	-	-	-	-	-
Platoon blocked, %			-	-		-
Mov Cap-1 Maneuver	886	997	-	-	1535	-
Mov Cap-2 Maneuver	886	-	-	-	-	-
Stage 1	956	-	-	-	-	-
Stage 2	978	-	-	-	-	-
Approach	WB	NB		SB		
HCM Control Delay, s	8.6	0		0.9		
HCM LOS	A					
Minor Lane/Major Mvmt	NBT	NBRWBLn1	SBL	SBT		
Capacity (veh/h)	-	-	997	1535	-	
HCM Lane V/C Ratio	-	-	0.006	0.003	-	
HCM Control Delay (s)	-	-	8.6	7.4	0	
HCM Lane LOS	-	-	A	A	A	
HCM 95th %tile Q(veh)	-	-	0	0	-	






## Appendix F ANALYSIS WORKSHEETS: 2025 BUILD CONDITIONS



Intersection												
Int Delay, s/veh	4.4											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations		↕			↕			↕			↕	
Traffic Vol, veh/h	9	30	12	3	18	12	5	53	13	35	71	10
Future Vol, veh/h	9	30	12	3	18	12	5	53	13	35	71	10
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	14	14	14	16	16	16	2	2	2	2	2	2
Mvmt Flow	10	33	13	3	20	13	6	59	14	39	79	11
Major/Minor	Minor2		Minor1		Major1		Major2					
Conflicting Flow All	258	248	85	264	246	66	90	0	0	73	0	0
Stage 1	163	163	-	78	78	-	-	-	-	-	-	-
Stage 2	95	85	-	186	168	-	-	-	-	-	-	-
Critical Hdwy	7.24	6.64	6.34	7.26	6.66	6.36	4.12	-	-	4.12	-	-
Critical Hdwy Stg 1	6.24	5.64	-	6.26	5.66	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.24	5.64	-	6.26	5.66	-	-	-	-	-	-	-
Follow-up Hdwy	3.626	4.126	3.426	3.644	4.144	3.444	2.218	-	-	2.218	-	-
Pot Cap-1 Maneuver	671	634	942	661	633	960	1505	-	-	1527	-	-
Stage 1	812	741	-	897	803	-	-	-	-	-	-	-
Stage 2	883	802	-	784	734	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	630	614	942	610	613	960	1505	-	-	1527	-	-
Mov Cap-2 Maneuver	630	614	-	610	613	-	-	-	-	-	-	-
Stage 1	809	721	-	893	800	-	-	-	-	-	-	-
Stage 2	846	799	-	717	714	-	-	-	-	-	-	-
Approach	EB		WB		NB		SB					
HCM Control Delay, s	10.9		10.4		0.5		2.2					
HCM LOS	B		B									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	WBLn1	SBL	SBT	SBR				
Capacity (veh/h)	1505	-	-	672	705	1527	-	-				
HCM Lane V/C Ratio	0.004	-	-	0.084	0.052	0.025	-	-				
HCM Control Delay (s)	7.4	0	-	10.9	10.4	7.4	0	-				
HCM Lane LOS	A	A	-	B	B	A	A	-				
HCM 95th %tile Q(veh)	0	-	-	0.3	0.2	0.1	-	-				

Intersection

Int Delay, s/veh 2

Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	21	61	98	20	15	17
Future Vol, veh/h	21	61	98	20	15	17
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	11	11	16	16	2	2
Mvmt Flow	23	68	109	22	17	19




Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	131	0	0 234 120
Stage 1	-	-	- 120 -
Stage 2	-	-	- 114 -
Critical Hdwy	4.21	-	- 6.42 6.22
Critical Hdwy Stg 1	-	-	- 5.42 -
Critical Hdwy Stg 2	-	-	- 5.42 -
Follow-up Hdwy	2.299	-	- 3.518 3.318
Pot Cap-1 Maneuver	1400	-	- 754 931
Stage 1	-	-	- 905 -
Stage 2	-	-	- 911 -
Platoon blocked, %		-	-
Mov Cap-1 Maneuver	1400	-	- 741 931
Mov Cap-2 Maneuver	-	-	- 741 -
Stage 1	-	-	- 890 -
Stage 2	-	-	- 911 -

Approach	EB	WB	SB
HCM Control Delay, s	2	0	9.5
HCM LOS			A

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1
Capacity (veh/h)	1400	-	-	-	831
HCM Lane V/C Ratio	0.017	-	-	-	0.043
HCM Control Delay (s)	7.6	0	-	-	9.5
HCM Lane LOS	A	A	-	-	A
HCM 95th %tile Q(veh)	0.1	-	-	-	0.1

HCM 6th TWSC  
3: Salkehatchie Rd & Pine St

2025 Build Conditions  
AM Peak Hour

Intersection						
Int Delay, s/veh	2					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	4	16	39	1	8	46
Future Vol, veh/h	4	16	39	1	8	46
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	5	5	4	4
Mvmt Flow	4	18	43	1	9	51

Major/Minor	Minor1	Major1	Major2		
Conflicting Flow All	113	44	0	0	44
Stage 1	44	-	-	-	-
Stage 2	69	-	-	-	-
Critical Hdwy	6.42	6.22	-	-	4.14
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	3.318	-	-	2.236
Pot Cap-1 Maneuver	884	1026	-	-	1552
Stage 1	978	-	-	-	-
Stage 2	954	-	-	-	-
Platoon blocked, %			-	-	-
Mov Cap-1 Maneuver	879	1026	-	-	1552
Mov Cap-2 Maneuver	879	-	-	-	-
Stage 1	978	-	-	-	-
Stage 2	948	-	-	-	-




Approach	WB	NB	SB
HCM Control Delay, s	8.7	0	1.1
HCM LOS	A		





Minor Lane/Major Mvmt	NBT	NBRWBLn1	SBL	SBT
Capacity (veh/h)	-	-	993	1552
HCM Lane V/C Ratio	-	-	0.022	0.006
HCM Control Delay (s)	-	-	8.7	7.3
HCM Lane LOS	-	-	A	A
HCM 95th %tile Q(veh)	-	-	0.1	0



HCM 6th TWSC  
4: US 21 & Project Driveway #3




2025 Build Conditions  
AM Peak Hour

Intersection						
Int Delay, s/veh	0.7					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	15	61	116	16	2	2
Future Vol, veh/h	15	61	116	16	2	2
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	11	11	16	16	16	11
Mvmt Flow	17	68	129	18	2	2
Major/Minor	Major1	Major2		Minor2		
Conflicting Flow All	147	0	-	0	240	138
Stage 1	-	-	-	-	138	-
Stage 2	-	-	-	-	102	-
Critical Hdwy	4.21	-	-	-	6.56	6.31
Critical Hdwy Stg 1	-	-	-	-	5.56	-
Critical Hdwy Stg 2	-	-	-	-	5.56	-
Follow-up Hdwy	2.299	-	-	-	3.644	3.399
Pot Cap-1 Maneuver	1381	-	-	-	719	887
Stage 1	-	-	-	-	855	-
Stage 2	-	-	-	-	888	-
Platoon blocked, %		-	-	-		
Mov Cap-1 Maneuver	1381	-	-	-	710	887
Mov Cap-2 Maneuver	-	-	-	-	710	-
Stage 1	-	-	-	-	844	-
Stage 2	-	-	-	-	888	-
Approach	EB	WB		SB		
HCM Control Delay, s	1.5	0		9.6		
HCM LOS	A					
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	
Capacity (veh/h)	1381	-	-	-	789	
HCM Lane V/C Ratio	0.012	-	-	-	0.006	
HCM Control Delay (s)	7.6	0	-	-	9.6	
HCM Lane LOS	A	A	-	-	A	
HCM 95th %tile Q(veh)	0	-	-	-	0	

Intersection												
Int Delay, s/veh	5.3											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	21	12	11	5	35	44	21	69	7	31	58	19
Future Vol, veh/h	21	12	11	5	35	44	21	69	7	31	58	19
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	4	4	4	9	9	9	2	2	2	2	2	2
Mvmt Flow	23	13	12	6	39	49	23	77	8	34	64	21
Major/Minor	Minor2		Minor1		Major1		Major2					
Conflicting Flow All	314	274	75	282	280	81	85	0	0	85	0	0
Stage 1	143	143	-	127	127	-	-	-	-	-	-	-
Stage 2	171	131	-	155	153	-	-	-	-	-	-	-
Critical Hdwy	7.14	6.54	6.24	7.19	6.59	6.29	4.12	-	-	4.12	-	-
Critical Hdwy Stg 1	6.14	5.54	-	6.19	5.59	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.14	5.54	-	6.19	5.59	-	-	-	-	-	-	-
Follow-up Hdwy	3.536	4.036	3.336	3.581	4.081	3.381	2.218	-	-	2.218	-	-
Pot Cap-1 Maneuver	635	630	981	656	617	960	1512	-	-	1512	-	-
Stage 1	855	775	-	860	778	-	-	-	-	-	-	-
Stage 2	826	784	-	831	758	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	555	605	981	618	592	960	1512	-	-	1512	-	-
Mov Cap-2 Maneuver	555	605	-	618	592	-	-	-	-	-	-	-
Stage 1	841	756	-	846	766	-	-	-	-	-	-	-
Stage 2	732	771	-	787	740	-	-	-	-	-	-	-
Approach	EB		WB		NB		SB					
HCM Control Delay, s	11.1		10.5		1.6		2.1					
HCM LOS	B		B									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR					
Capacity (veh/h)	1512	-	-	639	743	1512	-	-				
HCM Lane V/C Ratio	0.015	-	-	0.077	0.126	0.023	-	-				
HCM Control Delay (s)	7.4	0	-	11.1	10.5	7.4	0	-				
HCM Lane LOS	A	A	-	B	B	A	A	-				
HCM 95th %tile Q(veh)	0	-	-	0.2	0.4	0.1	-	-				

Intersection

Int Delay, s/veh 2.4




Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	17	125	82	17	26	27
Future Vol, veh/h	17	125	82	17	26	27
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	8	8	4	4	80	80
Mvmt Flow	19	139	91	19	29	30

Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	110	0	0 278 101
Stage 1	-	-	- 101 -
Stage 2	-	-	- 177 -
Critical Hdwy	4.18	-	- 7.2 7
Critical Hdwy Stg 1	-	-	- 6.2 -
Critical Hdwy Stg 2	-	-	- 6.2 -
Follow-up Hdwy	2.272	-	- 4.22 4.02
Pot Cap-1 Maneuver	1443	-	- 573 778
Stage 1	-	-	- 760 -
Stage 2	-	-	- 696 -
Platoon blocked, %	-	-	-
Mov Cap-1 Maneuver	1443	-	- 565 778
Mov Cap-2 Maneuver	-	-	- 565 -
Stage 1	-	-	- 749 -
Stage 2	-	-	- 696 -

Approach	EB	WB	SB
HCM Control Delay, s	0.9	0	11
HCM LOS			B




Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1
Capacity (veh/h)	1443	-	-	-	657
HCM Lane V/C Ratio	0.013	-	-	-	0.09
HCM Control Delay (s)	7.5	0	-	-	11
HCM Lane LOS	A	A	-	-	B
HCM 95th %tile Q(veh)	0	-	-	-	0.3



Intersection						
Int Delay, s/veh	2.1					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	1	13	59	3	18	30
Future Vol, veh/h	1	13	59	3	18	30
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	1	14	66	3	20	33
Major/Minor	Minor1	Major1		Major2		
Conflicting Flow All	141	68	0	0	69	0
Stage 1	68	-	-	-	-	-
Stage 2	73	-	-	-	-	-
Critical Hdwy	6.42	6.22	-	-	4.12	-
Critical Hdwy Stg 1	5.42	-	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-	-
Follow-up Hdwy	3.518	3.318	-	-	2.218	-
Pot Cap-1 Maneuver	852	995	-	-	1532	-
Stage 1	955	-	-	-	-	-
Stage 2	950	-	-	-	-	-
Platoon blocked, %			-	-		-
Mov Cap-1 Maneuver	841	995	-	-	1532	-
Mov Cap-2 Maneuver	841	-	-	-	-	-
Stage 1	955	-	-	-	-	-
Stage 2	938	-	-	-	-	-
Approach	WB	NB		SB		
HCM Control Delay, s	8.7	0		2.8		
HCM LOS	A					
Minor Lane/Major Mvmt	NBT	NBRWBLn1	SBL	SBT		
Capacity (veh/h)	-	-	982	1532	-	
HCM Lane V/C Ratio	-	-	0.016	0.013	-	
HCM Control Delay (s)	-	-	8.7	7.4	0	
HCM Lane LOS	-	-	A	A	A	
HCM 95th %tile Q(veh)	-	-	0	0	-	

HCM 6th TWSC  
4: US 21 & Project Driveway #3

2025 Build Conditions  
PM Peak Hour

Intersection						
Int Delay, s/veh	0.7					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	1	142	97	1	9	9
Future Vol, veh/h	1	142	97	1	9	9
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	8	8	4	4	4	8
Mvmt Flow	1	158	108	1	10	10
Major/Minor	Major1	Major2		Minor2		
Conflicting Flow All	109	0	-	0	269	109
Stage 1	-	-	-	-	109	-
Stage 2	-	-	-	-	160	-
Critical Hdwy	4.18	-	-	-	6.44	6.28
Critical Hdwy Stg 1	-	-	-	-	5.44	-
Critical Hdwy Stg 2	-	-	-	-	5.44	-
Follow-up Hdwy	2.272	-	-	-	3.536	3.372
Pot Cap-1 Maneuver	1445	-	-	-	716	929
Stage 1	-	-	-	-	911	-
Stage 2	-	-	-	-	864	-
Platoon blocked, %		-	-	-		
Mov Cap-1 Maneuver	1445	-	-	-	715	929
Mov Cap-2 Maneuver	-	-	-	-	715	-
Stage 1	-	-	-	-	910	-
Stage 2	-	-	-	-	864	-
Approach	EB	WB		SB		
HCM Control Delay, s	0.1	0		9.6		
HCM LOS	A					
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	
Capacity (veh/h)	1445	-	-	-	808	
HCM Lane V/C Ratio	0.001	-	-	-	0.025	
HCM Control Delay (s)	7.5	0	-	-	9.6	
HCM Lane LOS	A	A	-	-	A	
HCM 95th %tile Q(veh)	0	-	-	-	0.1	



## Appendix G TURN LANE ANALYSIS WORKSHEETS



### Study Area Information

County:	Hampton County	Date:	11/10/2022
SCDOT Engineering District:	District 7	Analyst:	PC
Analysis Year:	2025	Agency:	Stantec Consulting Services Inc.

Intersection:	US 21 & Salkhatchie Road		
Left Turn Movement:	Northbound Left-Turn Lane		
Right Turn Movement:	Southbound Right-Turn Lane		

Posted Speed Limit:	35	mph	Median:	Undivided
# of Approach Lanes:	1		Urban or Rural?	Rural

### Volume Information & Calculations

#### Left Turn Lane Volume Calculations

Movement		Volume (vph)	
		AM	PM
Advancing	Left	5	21
	Through	53	69
	Right	13	7
Opposing	Left	35	31
	Through	71	58
	Right	10	19

	AM	PM
Advancing Volume:	71	97
Opposing Volume:	116	108
Left Turn Volume:	5	21

% Left Turns in Advancing Volume:	7.0%	21.6%
-----------------------------------	------	-------

#### Right Turn Lane Volume Calculations

Movement		Volume (vph)	
		AM	PM
Advancing	Left	35	31
	Through	71	58
	Right	10	19

Adjustment to Right Turn Volume <sup>1</sup>	Include?	No
--	----------	----

	AM	PM
Advancing Volume:	116	108
Right Turn Volume:	10	19

### Turn Lane Warrant Met?

Left Turn Lane Warrant		Right Turn Lane Warrant	
Applicable Warrant Chart:	Fig 9.5-G	Applicable Warrant Chart:	Fig 9.5-A
Warrant Satisfied:	No	Warrant Satisfied:	No

### Recommended Turn Lane Length


Left Turn Lane		Right Turn Lane	
Turning Truck%:	2%	Turning Truck%:	2%
Storage Length (ft):	N/A	Storage Length:	N/A
Taper Length (ft):	N/A	Taper Length:	N/A
Total Left Turn Lane (ft):	N/A	Total Left Turn Lane:	N/A

Consider providing dual-turn lanes if the turning volumes are greater than 300 vehicles per hour. A traffic analysis will be required if the turning volumes are greater than 300 vehicles per hour.

The traffic designer should review the design to determine if longer turn lane lengths are required.


# GUIDELINES FOR RIGHT-TURN LANES AT UNSIGNALIZED INTERSECTIONS ON TWO-LANE HIGHWAYS

Figure 9.5-A, (SCDOT ROADWAY DESIGN MANUAL 2021)



# VOLUME GUIDELINES FOR LEFT-TURN LANES AT UNSIGNALALIZED INTERSECTIONS ON TWO-LANE HIGHWAYS (40 mph)

Figure 9.5-G, (SCDOT ROADWAY DESIGN MANUAL 2021)





### Study Area Information

County:	Hampton County	Date:	11/10/2022
SCDOT Engineering District:	District 7	Analyst:	PC
Analysis Year:	2025	Agency:	Stantec Consulting Services Inc.
Intersection:	US 21 & Pine St (Project Driveway #1)		
Left Turn Movement:	Eastbound Left-Turn Lane		
Right Turn Movement:	Westbound Right-Turn Lane		
Posted Speed Limit:	45	Median:	Undivided
# of Approach Lanes:	1	Urban or Rural?	Rural

### Volume Information & Calculations

#### Left Turn Lane Volume Calculations

Movement		Volume (vph)	
		AM	PM
Advancing	Left	21	17
	Through	61	126
	Right	0	0
Opposing	Left	0	0
	Through	98	91
	Right	20	15

	AM	PM
Advancing Volume:	82	143
Opposing Volume:	118	106
Left Turn Volume:	21	17

% Left Turns in Advancing Volume: 25.6% 11.9%

#### Right Turn Lane Volume Calculations

Movement		Volume (vph)	
		AM	PM
Advancing	Left	0	0
	Through	98	91
	Right	20	15

Adjustment to Right Turn Volume<sup>1</sup> Include? No

	AM	PM
Advancing Volume:	118	106
Right Turn Volume:	20	15

### Turn Lane Warrant Met?

<b>Left Turn Lane Warrant</b> Applicable Warrant Chart: <b>Fig 9.5-F</b> Warrant Satisfied: <b>No</b>	<b>Right Turn Lane Warrant</b> Applicable Warrant Chart: <b>Fig 9.5-A</b> Warrant Satisfied: <b>No</b>
---	--

### Recommended Turn Lane Length

Turning Truck%: 20%

Turning Truck%: 20%


<b>Left Turn Lane</b> Storage Length (ft): N/A ft Taper Length (ft): N/A ft Total Left Turn Lane (ft): N/A ft	<b>Right Turn Lane</b> Storage Length: N/A ft Taper Length: N/A ft Total Left Turn Lane: N/A ft
--	--

Consider providing dual-turn lanes if the turning volumes are greater than 300 vehicles per hour. A traffic analysis will be required if the turning volumes are greater than 300 vehicles per hour.

The traffic designer should review the design to determine if longer turn lane lengths are required.


# GUIDELINES FOR RIGHT-TURN LANES AT UNSIGNALIZED INTERSECTIONS ON TWO-LANE HIGHWAYS

Figure 9.5-A, (SCDOT ROADWAY DESIGN MANUAL 2021)



# VOLUME GUIDELINES FOR LEFT-TURN LANES AT UNSIGNALALIZED INTERSECTIONS ON TWO-LANE HIGHWAYS (45 mph)

Figure 9.5-F, (SCDOT ROADWAY DESIGN MANUAL 2021)





### Study Area Information

County:	Hampton County	Date:	11/10/2022
SCDOT Engineering District:	District 7	Analyst:	PC
Analysis Year:	2025	Agency:	Stantec Consulting Services Inc.
Intersection:	Salkhatchie Rd & Pine St (Project Driveway #2)		
Left Turn Movement:	Southbound Left-Turn Lane		
Right Turn Movement:	Northbound Right-Turn Lane		
Posted Speed Limit:	35	Median:	Undivided
# of Approach Lanes:	1	Urban or Rural?	Rural

### Volume Information & Calculations

#### Left Turn Lane Volume Calculations

Movement		Volume (vph)				
		AM	PM		AM	PM
Advancing	Left	8	18	Advancing Volume:	54	48
	Through	46	30	Opposing Volume:	40	62
	Right	0	0	Left Turn Volume:	8	18
Opposing	Left	0	0			
	Through	39	59			
	Right	1	3			

% Left Turns in Advancing Volume: 14.8% 37.5%

#### Right Turn Lane Volume Calculations

Movement		Volume (vph)				
		AM	PM		AM	PM
Advancing	Left	0	0	Adjustment to Right Turn Volume <sup>1</sup>	Include?	No
	Through	39	59	Advancing Volume:	40	62
	Right	1	3	Right Turn Volume:	1	3

### Turn Lane Warrant Met?

Left Turn Lane Warrant		Right Turn Lane Warrant	
Applicable Warrant Chart:	Fig 9.5-G	Applicable Warrant Chart:	Fig 9.5-A
Warrant Satisfied:	No	Warrant Satisfied:	No

### Recommended Turn Lane Length


Left Turn Lane		Right Turn Lane	
Turning Truck%:	80%	Turning Truck%:	80%
Storage Length (ft):	N/A	Storage Length:	N/A
Taper Length (ft):	N/A	Taper Length:	N/A
Total Left Turn Lane (ft):	N/A	Total Left Turn Lane:	N/A

Consider providing dual-turn lanes if the turning volumes are greater than 300 vehicles per hour. A traffic analysis will be required if the turning volumes are greater than 300 vehicles per hour.

The traffic designer should review the design to determine if longer turn lane lengths are required.


# GUIDELINES FOR RIGHT-TURN LANES AT UNSIGNALIZED INTERSECTIONS ON TWO-LANE HIGHWAYS

Figure 9.5-A, (SCDOT ROADWAY DESIGN MANUAL 2021)



# VOLUME GUIDELINES FOR LEFT-TURN LANES AT UNSIGNALALIZED INTERSECTIONS ON TWO-LANE HIGHWAYS (40 mph)

Figure 9.5-G, (SCDOT ROADWAY DESIGN MANUAL 2021)





### Study Area Information

County:	Hampton County	Date:	11/10/2022
SCDOT Engineering District:	District 7	Analyst:	PC
Analysis Year:	2025	Agency:	Stantec Consulting Services Inc.
Intersection: US 21 & Project Driveway #3			
Left Turn Movement: Eastbound Left-Turn Lane			
Right Turn Movement: Westbound Right-Turn Lane			
Posted Speed Limit:	45 mph	Median:	Undivided
# of Approach Lanes:	1	Urban or Rural?	Rural

### Volume Information & Calculations

#### Left Turn Lane Volume Calculations

Movement		Volume (vph)	
		AM	PM
Advancing	Left	15	1
	Through	61	142
	Right	0	0
Opposing	Left	0	0
	Through	116	97
	Right	16	1

	AM	PM
Advancing Volume:	76	143
Opposing Volume:	132	98
Left Turn Volume:	15	1

% Left Turns in Advancing Volume: 19.7% 0.7%

#### Right Turn Lane Volume Calculations

Movement		Volume (vph)	
		AM	PM
Advancing	Left	0	0
	Through	116	97
	Right	16	1

Adjustment to Right Turn Volume<sup>1</sup> Include? No

	AM	PM
Advancing Volume:	132	98
Right Turn Volume:	16	1

### Turn Lane Warrant Met?

<b>Left Turn Lane Warrant</b> Applicable Warrant Chart: <b>Fig 9.5-F</b> Warrant Satisfied: <b>No</b>	<b>Right Turn Lane Warrant</b> Applicable Warrant Chart: <b>Fig 9.5-A</b> Warrant Satisfied: <b>No</b>
---	--

### Recommended Turn Lane Length

Turning Truck%: 20%

Turning Truck%: 20%


<b>Left Turn Lane</b> Storage Length (ft): N/A ft Taper Length (ft): N/A ft Total Left Turn Lane (ft): N/A ft	<b>Right Turn Lane</b> Storage Length: N/A ft Taper Length: N/A ft Total Left Turn Lane: N/A ft
--	--

Consider providing dual-turn lanes if the turning volumes are greater than 300 vehicles per hour. A traffic analysis will be required if the turning volumes are greater than 300 vehicles per hour.

The traffic designer should review the design to determine if longer turn lane lengths are required.


# GUIDELINES FOR RIGHT-TURN LANES AT UNSIGNALIZED INTERSECTIONS ON TWO-LANE HIGHWAYS

Figure 9.5-A, (SCDOT ROADWAY DESIGN MANUAL 2021)



# VOLUME GUIDELINES FOR LEFT-TURN LANES AT UNSIGNALALIZED INTERSECTIONS ON TWO-LANE HIGHWAYS (45 mph)

Figure 9.5-F, (SCDOT ROADWAY DESIGN MANUAL 2021)






## APPENDIX L

DRAFT

WATER, SEWER AND STORMWATER MASTER PLAN





SITE DATA TABLE

Parcel	Upland (Acres)	Wetland (Acres)	Total (Acres)
Parcel 1	10.73	.75	11.48
Parcel 2	10.01	2.69	12.7
Parcel 3	16.76	17.2	33.8
Parcel 4	0.11	46.2	46.31
TOTAL	37.5	66.95	104.45

SUMMARY BY PARCEL

Parcel	Upland (Acres)	Wetland (Acres)	Total (Acres)
Parcel 1	10.73	.75	11.48
Parcel 2	10.01	2.69	12.7
Parcel 3	16.76	17.2	33.8
Parcel 4	0.11	46.2	46.31
TOTAL	37.5	66.95	104.45

LAND USE KEY



SITE DEVELOPMENT PLANS  
FOR  
PINE STREET RESIDENTIAL  
YEMASSEE, SOUTH CAROLINA

DATE:	FEB. 27 2023
PROJECT NO.:	22024.01
DRAWN BY:	KJ
CHECKED BY:	DK


PRELIMINARY  
SUBMITTAL PLAN,  
NOT FOR  
CONSTRUCTION

REVISIONS:

DRAWING TITLE  
STORMWATER  
MASTERPLAN

DRAWING NUMBER


...











SITE DATA TABLE

Parcel	Area (Acres)	Wetland (Acres)	Total (Acres)
Parcel 1	10.73	.75	11.48
Parcel 2	10.01	2.69	12.7
Parcel 3	16.76	17.2	33.8
Parcel 4	0.11	46.2	46.31
TOTAL	37.5	66.95	104.45

SUMMARY BY PARCEL

Parcel	Area (Acres)	Wetland (Acres)	Total (Acres)
Parcel 1	10.73	.75	11.48
Parcel 2	10.01	2.69	12.7
Parcel 3	16.76	17.2	33.8
Parcel 4	0.11	46.2	46.31
TOTAL	37.5	66.95	104.45

LAND USE KEY



SITE DEVELOPMENT PLANS  
FOR  
PINE STREET RESIDENTIAL  
YEMASSEE, SOUTH CAROLINA

DATE: FEB. 27 2023  
PROJECT NO.: 22024.01  
DRAWN BY: KJ  
CHECKED BY: DK


PRELIMINARY  
SUBMITTAL PLAN,  
NOT FOR  
CONSTRUCTION

REVISIONS:  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

DRAWING TITLE  
SEWER  
MASTERPLAN

DRAWING NUMBER

....





# National Flood Hazard Layer FIRMette



80°50'44"W 32°42'26"N



0 250 500 1,000 1,500 2,000 Feet 1:6,000

Basemap: USGS National Map: Orthoimagery: Data refreshed October, 2020

## Legend

SEE FIS REPORT FOR DETAILED LEGEND AND INDEX MAP FOR FIRM PANEL LAYOUT

SPECIAL FLOOD HAZARD AREAS		Without Base Flood Elevation (BFE) Zone A, V, A99
		With BFE or Depth Zone AE, AO, AH, VE, AR
		Regulatory Floodway
OTHER AREAS OF FLOOD HAZARD		0.2% Annual Chance Flood Hazard, Areas of 1% annual chance flood with average depth less than one foot or with drainage areas of less than one square mile Zone X
		Future Conditions 1% Annual Chance Flood Hazard Zone X
		Area with Reduced Flood Risk due to Levee. See Notes. Zone X
		Area with Flood Risk due to Levee Zone D
OTHER AREAS		NO SCREEN Area of Minimal Flood Hazard Zone X
		Effective LOMRs
GENERAL STRUCTURES		Area of Undetermined Flood Hazard Zone D
		Channel, Culvert, or Storm Sewer
OTHER FEATURES		Levee, Dike, or Floodwall
		Cross Sections with 1% Annual Chance Water Surface Elevation
OTHER FEATURES		Coastal Transect
		Base Flood Elevation Line (BFE)
OTHER FEATURES		Limit of Study
		Jurisdiction Boundary
OTHER FEATURES		Coastal Transect Baseline
		Profile Baseline
OTHER FEATURES		Hydrographic Feature
		Digital Data Available
MAP PANELS		No Digital Data Available
		Unmapped



The pin displayed on the map is an approximate point selected by the user and does not represent an authoritative property location.

This map complies with FEMA's standards for the use of digital flood maps if it is not void as described below. The basemap shown complies with FEMA's basemap accuracy standards

The flood hazard information is derived directly from the authoritative NFHL web services provided by FEMA. This map was exported on **10/27/2022 at 5:25 PM** and does not reflect changes or amendments subsequent to this date and time. The NFHL and effective information may change or become superseded by new data over time.

This map image is void if the one or more of the following map elements do not appear: basemap imagery, flood zone labels, legend, scale bar, map creation date, community identifiers, FIRM panel number, and FIRM effective date. Map images for unmapped and unmodernized areas cannot be used for regulatory purposes.










United States  
Department of  
Agriculture

NRCS

Natural  
Resources  
Conservation  
Service

A product of the National  
Cooperative Soil Survey,  
a joint effort of the United  
States Department of  
Agriculture and other  
Federal agencies, State  
agencies including the  
Agricultural Experiment  
Stations, and local  
participants


# Custom Soil Resource Report for Hampton County, South Carolina



October 27, 2022



# Custom Soil Resource Report Soil Map



# Custom Soil Resource Report

## MAP LEGEND

### Area of Interest (AOI)

 Area of Interest (AOI)

### Soils

 Soil Map Unit Polygons

 Soil Map Unit Lines

 Soil Map Unit Points

### Special Point Features

 Blowout

 Borrow Pit

 Clay Spot

 Closed Depression

 Gravel Pit

 Gravelly Spot


 Landfill

 Lava Flow

 Marsh or swamp

 Mine or Quarry


 Miscellaneous Water

 Perennial Water

 Rock Outcrop


 Saline Spot

 Sandy Spot

 Severely Eroded Spot

 Sinkhole

 Slide or Slip

 Sodic Spot

 Spoil Area

 Stony Spot

 Very Stony Spot

 Wet Spot

 Other

 Special Line Features

### Water Features

 Streams and Canals

### Transportation

 Rails

 Interstate Highways

 US Routes

 Major Roads

 Local Roads

### Background

 Aerial Photography

## MAP INFORMATION

The soil surveys that comprise your AOI were mapped at 1:20,000.

Warning: Soil Map may not be valid at this scale.

Enlargement of maps beyond the scale of mapping can cause misunderstanding of the detail of mapping and accuracy of soil line placement. The maps do not show the small areas of contrasting soils that could have been shown at a more detailed scale.

Please rely on the bar scale on each map sheet for map measurements.

Source of Map: Natural Resources Conservation Service  
Web Soil Survey URL:  
Coordinate System: Web Mercator (EPSG:3857)

Maps from the Web Soil Survey are based on the Web Mercator projection, which preserves direction and shape but distorts distance and area. A projection that preserves area, such as the Albers equal-area conic projection, should be used if more accurate calculations of distance or area are required.

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Hampton County, South Carolina  
Survey Area Data: Version 22, Sep 7, 2022

Soil map units are labeled (as space allows) for map scales 1:50,000 or larger.

Date(s) aerial images were photographed: Feb 21, 2021—Feb 23, 2021

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.



## Map Unit Legend

Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI
Ar	Argent fine sandy loam, ponded	56.5	53.2%
Br	Brookman clay loam, ponded	1.0	0.9%
EpB	Emporia loamy sand, 2 to 6 percent slopes	26.5	24.9%
Gr	Grifton-Osier complex, frequently flooded	6.3	5.9%
Na	Nakina fine sandy loam, occasionally flooded	13.4	12.6%
Oe	Osier loamy sand	2.7	2.5%
<b>Totals for Area of Interest</b>		<b>106.3</b>	<b>100.0%</b>

## Map Unit Descriptions

The map units delineated on the detailed soil maps in a soil survey represent the soils or miscellaneous areas in the survey area. The map unit descriptions, along with the maps, can be used to determine the composition and properties of a unit.

A map unit delineation on a soil map represents an area dominated by one or more major kinds of soil or miscellaneous areas. A map unit is identified and named according to the taxonomic classification of the dominant soils. Within a taxonomic class there are precisely defined limits for the properties of the soils. On the landscape, however, the soils are natural phenomena, and they have the characteristic variability of all natural phenomena. Thus, the range of some observed properties may extend beyond the limits defined for a taxonomic class. Areas of soils of a single taxonomic class rarely, if ever, can be mapped without including areas of other taxonomic classes. Consequently, every map unit is made up of the soils or miscellaneous areas for which it is named and some minor components that belong to taxonomic classes other than those of the major soils.

Most minor soils have properties similar to those of the dominant soil or soils in the map unit, and thus they do not affect use and management. These are called noncontrasting, or similar, components. They may or may not be mentioned in a particular map unit description. Other minor components, however, have properties and behavioral characteristics divergent enough to affect use or to require different management. These are called contrasting, or dissimilar, components. They generally are in small areas and could not be mapped separately because of the scale used. Some small areas of strongly contrasting soils or miscellaneous areas are identified by a special symbol on the maps. If included in the database for a given area, the contrasting minor components are identified in the map unit descriptions along with some characteristics of each. A few areas of minor components may not have been observed, and consequently they are not mentioned in the descriptions, especially where the pattern was so complex that it was impractical to make enough observations to identify all the soils and miscellaneous areas on the landscape.

## Custom Soil Resource Report

The presence of minor components in a map unit in no way diminishes the usefulness or accuracy of the data. The objective of mapping is not to delineate pure taxonomic classes but rather to separate the landscape into landforms or landform segments that have similar use and management requirements. The delineation of such segments on the map provides sufficient information for the development of resource plans. If intensive use of small areas is planned, however, onsite investigation is needed to define and locate the soils and miscellaneous areas.

An identifying symbol precedes the map unit name in the map unit descriptions. Each description includes general facts about the unit and gives important soil properties and qualities.

Soils that have profiles that are almost alike make up a *soil series*. Except for differences in texture of the surface layer, all the soils of a series have major horizons that are similar in composition, thickness, and arrangement.

Soils of one series can differ in texture of the surface layer, slope, stoniness, salinity, degree of erosion, and other characteristics that affect their use. On the basis of such differences, a soil series is divided into *soil phases*. Most of the areas shown on the detailed soil maps are phases of soil series. The name of a soil phase commonly indicates a feature that affects use or management. For example, Alpha silt loam, 0 to 2 percent slopes, is a phase of the Alpha series.

Some map units are made up of two or more major soils or miscellaneous areas. These map units are complexes, associations, or undifferentiated groups.

A *complex* consists of two or more soils or miscellaneous areas in such an intricate pattern or in such small areas that they cannot be shown separately on the maps. The pattern and proportion of the soils or miscellaneous areas are somewhat similar in all areas. Alpha-Beta complex, 0 to 6 percent slopes, is an example.

An *association* is made up of two or more geographically associated soils or miscellaneous areas that are shown as one unit on the maps. Because of present or anticipated uses of the map units in the survey area, it was not considered practical or necessary to map the soils or miscellaneous areas separately. The pattern and relative proportion of the soils or miscellaneous areas are somewhat similar. Alpha-Beta association, 0 to 2 percent slopes, is an example.

An *undifferentiated group* is made up of two or more soils or miscellaneous areas that could be mapped individually but are mapped as one unit because similar interpretations can be made for use and management. The pattern and proportion of the soils or miscellaneous areas in a mapped area are not uniform. An area can be made up of only one of the major soils or miscellaneous areas, or it can be made up of all of them. Alpha and Beta soils, 0 to 2 percent slopes, is an example.

Some surveys include *miscellaneous areas*. Such areas have little or no soil material and support little or no vegetation. Rock outcrop is an example.

## Hampton County, South Carolina

### Ar—Argent fine sandy loam, ponded

#### Map Unit Setting

*National map unit symbol:* 4cc7

*Elevation:* 10 to 150 feet

*Mean annual precipitation:* 50 to 64 inches

*Mean annual air temperature:* 63 to 68 degrees F

*Frost-free period:* 220 to 250 days

*Farmland classification:* Farmland of statewide importance

#### Map Unit Composition

*Argent and similar soils:* 100 percent

*Estimates are based on observations, descriptions, and transects of the mapunit.*

#### Description of Argent

##### Setting

*Landform:* Depressions, marine terraces

*Landform position (three-dimensional):* Tread

*Down-slope shape:* Concave, linear

*Across-slope shape:* Concave, linear

*Parent material:* Clayey marine deposits

##### Typical profile

*A - 0 to 5 inches:* fine sandy loam

*Btg - 5 to 58 inches:* clay

*BCg - 58 to 65 inches:* clay

##### Properties and qualities

*Slope:* 0 to 2 percent

*Depth to restrictive feature:* More than 80 inches

*Drainage class:* Poorly drained

*Runoff class:* Negligible

*Capacity of the most limiting layer to transmit water (Ksat):* Moderately low to moderately high (0.06 to 0.20 in/hr)

*Depth to water table:* About 0 to 12 inches

*Frequency of flooding:* None

*Frequency of ponding:* Occasional

*Available water supply, 0 to 60 inches:* High (about 9.4 inches)

##### Interpretive groups

*Land capability classification (irrigated):* None specified

*Land capability classification (nonirrigated):* 6w

*Hydrologic Soil Group:* C/D

*Hydric soil rating:* Yes



## **Br—Brookman clay loam, ponded**

### **Map Unit Setting**

*National map unit symbol:* 4ccj

*Elevation:* 10 to 150 feet

*Mean annual precipitation:* 50 to 64 inches

*Mean annual air temperature:* 63 to 68 degrees F

*Frost-free period:* 220 to 250 days

*Farmland classification:* Farmland of statewide importance

### **Map Unit Composition**

*Brookman and similar soils:* 100 percent

*Estimates are based on observations, descriptions, and transects of the mapunit.*

### **Description of Brookman**

#### **Setting**

*Landform:* Depressions, marine terraces

*Landform position (three-dimensional):* Tread

*Down-slope shape:* Concave, linear

*Across-slope shape:* Concave, linear

*Parent material:* Clayey marine deposits

#### **Typical profile**

*A - 0 to 4 inches:* clay loam

*Btg1 - 4 to 11 inches:* clay loam

*Btg2 - 11 to 44 inches:* clay

*Btg3 - 44 to 62 inches:* clay loam

*Cg - 62 to 80 inches:* sand

#### **Properties and qualities**

*Slope:* 0 to 2 percent

*Depth to restrictive feature:* More than 80 inches

*Drainage class:* Very poorly drained

*Runoff class:* Negligible

*Capacity of the most limiting layer to transmit water (Ksat):* Moderately high to high  
(0.57 to 1.98 in/hr)

*Depth to water table:* About 0 to 12 inches

*Frequency of flooding:* None

*Frequency of ponding:* Occasional

*Available water supply, 0 to 60 inches:* High (about 10.7 inches)

#### **Interpretive groups**

*Land capability classification (irrigated):* None specified

*Land capability classification (nonirrigated):* 7w

*Hydrologic Soil Group:* B/D

*Hydric soil rating:* Yes

## **EpB—Emporia loamy sand, 2 to 6 percent slopes**

### **Map Unit Setting**

*National map unit symbol:* 4cct  
*Elevation:* 10 to 150 feet  
*Mean annual precipitation:* 50 to 64 inches  
*Mean annual air temperature:* 63 to 68 degrees F  
*Frost-free period:* 220 to 250 days  
*Farmland classification:* All areas are prime farmland

### **Map Unit Composition**

*Emporia and similar soils:* 100 percent  
*Estimates are based on observations, descriptions, and transects of the mapunit.*

### **Description of Emporia**

#### **Setting**

*Landform:* Marine terraces  
*Landform position (three-dimensional):* Tread  
*Down-slope shape:* Convex  
*Across-slope shape:* Convex  
*Parent material:* Loamy marine deposits

#### **Typical profile**

*Ap - 0 to 11 inches:* loamy sand  
*Bt1 - 11 to 31 inches:* sandy clay loam  
*Bt2 - 31 to 45 inches:* sandy clay loam  
*BC - 45 to 60 inches:* clay loam

#### **Properties and qualities**

*Slope:* 2 to 6 percent  
*Depth to restrictive feature:* More than 80 inches  
*Drainage class:* Well drained  
*Runoff class:* Low  
*Capacity of the most limiting layer to transmit water (Ksat):* Very low to moderately high (0.00 to 0.57 in/hr)  
*Depth to water table:* About 36 inches  
*Frequency of flooding:* None  
*Frequency of ponding:* None  
*Available water supply, 0 to 60 inches:* Moderate (about 7.2 inches)

#### **Interpretive groups**

*Land capability classification (irrigated):* None specified  
*Land capability classification (nonirrigated):* 2e  
*Hydrologic Soil Group:* C  
*Hydric soil rating:* No

## **Gr—Grifton-Osier complex, frequently flooded**

### **Map Unit Setting**

*National map unit symbol:* 4cd0

*Elevation:* 10 to 150 feet

*Mean annual precipitation:* 50 to 64 inches

*Mean annual air temperature:* 63 to 68 degrees F

*Frost-free period:* 220 to 250 days

*Farmland classification:* Not prime farmland

### **Map Unit Composition**

*Grifton and similar soils:* 60 percent

*Osier and similar soils:* 40 percent

*Estimates are based on observations, descriptions, and transects of the mapunit.*

### **Description of Grifton**

#### **Setting**

*Landform:* Depressions, marine terraces

*Landform position (three-dimensional):* Tread

*Down-slope shape:* Concave, linear

*Across-slope shape:* Concave, linear

*Parent material:* Loamy marine deposits

#### **Typical profile**

*Ap - 0 to 6 inches:* fine sandy loam

*E - 6 to 13 inches:* fine sandy loam

*Btg - 13 to 48 inches:* sandy clay loam

*Cg - 48 to 65 inches:* loamy sand

#### **Properties and qualities**

*Slope:* 0 to 2 percent

*Depth to restrictive feature:* More than 80 inches

*Drainage class:* Poorly drained

*Runoff class:* Very high

*Capacity of the most limiting layer to transmit water (Ksat):* Moderately high to high  
(0.57 to 1.98 in/hr)

*Depth to water table:* About 0 to 12 inches

*Frequency of flooding:* FrequentNone

*Frequency of ponding:* None

*Available water supply, 0 to 60 inches:* Moderate (about 8.1 inches)

#### **Interpretive groups**

*Land capability classification (irrigated):* None specified

*Land capability classification (nonirrigated):* 7w

*Hydrologic Soil Group:* B/D

*Hydric soil rating:* Yes

### **Description of Osier**

#### **Setting**

*Landform:* Depressions, marine terraces



## Custom Soil Resource Report

*Landform position (three-dimensional):* Tread  
*Down-slope shape:* Concave, linear  
*Across-slope shape:* Concave, linear  
*Parent material:* Sandy alluvium

### Typical profile

*A - 0 to 19 inches:* loamy sand  
*Cg1 - 19 to 35 inches:* sand  
*Cg2 - 35 to 70 inches:* coarse sand

### Properties and qualities

*Slope:* 0 to 2 percent  
*Depth to restrictive feature:* More than 80 inches  
*Drainage class:* Poorly drained  
*Runoff class:* Very high  
*Capacity of the most limiting layer to transmit water (Ksat):* High to very high (5.95 to 19.98 in/hr)  
*Depth to water table:* About 0 to 12 inches  
*Frequency of flooding:* Rare  
*Frequency of ponding:* None  
*Available water supply, 0 to 60 inches:* Low (about 3.4 inches)

### Interpretive groups

*Land capability classification (irrigated):* None specified  
*Land capability classification (nonirrigated):* 5w  
*Hydrologic Soil Group:* A/D  
*Hydric soil rating:* Yes

## Na—Nakina fine sandy loam, occasionally flooded

### Map Unit Setting

*National map unit symbol:* 4cd5  
*Elevation:* 10 to 150 feet  
*Mean annual precipitation:* 50 to 64 inches  
*Mean annual air temperature:* 63 to 68 degrees F  
*Frost-free period:* 220 to 250 days  
*Farmland classification:* Farmland of statewide importance

### Map Unit Composition

*Nakina and similar soils:* 100 percent  
*Estimates are based on observations, descriptions, and transects of the mapunit.*

### Description of Nakina

#### Setting

*Landform:* Depressions, marine terraces  
*Landform position (three-dimensional):* Tread  
*Down-slope shape:* Concave, linear  
*Across-slope shape:* Concave, linear  
*Parent material:* Loamy marine deposits

**Typical profile**

*A - 0 to 15 inches:* fine sandy loam  
*Btg - 15 to 43 inches:* sandy clay loam  
*BCg - 43 to 60 inches:* sandy loam

**Properties and qualities**

*Slope:* 0 to 2 percent  
*Depth to restrictive feature:* More than 80 inches  
*Drainage class:* Very poorly drained  
*Runoff class:* Very high  
*Capacity of the most limiting layer to transmit water (Ksat):* Moderately high to high  
(0.57 to 5.95 in/hr)  
*Depth to water table:* About 0 to 12 inches  
*Frequency of flooding:* OccasionalNone  
*Frequency of ponding:* None  
*Available water supply, 0 to 60 inches:* High (about 9.3 inches)

**Interpretive groups**

*Land capability classification (irrigated):* None specified  
*Land capability classification (nonirrigated):* 6w  
*Hydrologic Soil Group:* A/D  
*Hydric soil rating:* Yes

**Oe—Osier loamy sand**

**Map Unit Setting**

*National map unit symbol:* 4cdd  
*Elevation:* 10 to 150 feet  
*Mean annual precipitation:* 50 to 64 inches  
*Mean annual air temperature:* 63 to 68 degrees F  
*Frost-free period:* 220 to 250 days  
*Farmland classification:* Not prime farmland

**Map Unit Composition**

*Osier and similar soils:* 100 percent  
*Estimates are based on observations, descriptions, and transects of the mapunit.*

**Description of Osier**

**Setting**

*Landform:* Depressions, marine terraces  
*Landform position (three-dimensional):* Tread  
*Down-slope shape:* Concave, linear  
*Across-slope shape:* Concave, linear  
*Parent material:* Sandy alluvium

**Typical profile**

*A - 0 to 19 inches:* loamy sand  
*Cg1 - 19 to 35 inches:* sand  
*Cg2 - 35 to 70 inches:* coarse sand

## Custom Soil Resource Report

### Properties and qualities

*Slope:* 0 to 2 percent

*Depth to restrictive feature:* More than 80 inches

*Drainage class:* Poorly drained

*Runoff class:* Very high

*Capacity of the most limiting layer to transmit water (Ksat):* High to very high (5.95 to 19.98 in/hr)

*Depth to water table:* About 0 to 12 inches

*Frequency of flooding:* RareNone

*Frequency of ponding:* None

*Available water supply, 0 to 60 inches:* Low (about 3.4 inches)

### Interpretive groups


*Land capability classification (irrigated):* None specified

*Land capability classification (nonirrigated):* 5w

*Hydrologic Soil Group:* A/D

*Hydric soil rating:* Yes





P.O. BOX 381, BLUFFTON, SOUTH CAROLINA 29910  
PH (843) 837-5250 / FAX (843) 837-2558  
[WWW.WARDEDWARDS.COM](http://WWW.WARDEDWARDS.COM)

## VICINITY MAP

### PINE STREET DEVELOPMENT

LOCATION: YEMASSEE, SC  
DATE: 10/25/2022  
PROJECT #: 210148

SCALE: 1"=1,000'



Our ref: 12591408-00 | Pine Street Industrial Building

October 06, 2022

Mr. Tim Huber  
Ironline LLC  
300 Technology Drive  
Walterboro, South Carolina 29488

## Report of Subsurface Exploration and Geotechnical Evaluation

Dear Mr. Huber:

**GHD** is pleased to present the results of our subsurface exploration and geotechnical evaluation for the above-referenced project. Our services were performed in general accordance with our Proposal No. 12591408 dated August 10, 2022.

### 1. Site Description / Project Understanding

GHD has received project information via email correspondence with you beginning July 29, 2022. Project information provided to us and referenced in our evaluation includes a preliminary site plan drawing titled 'Conceptual Plan for Pine Street Residential' prepared by Witmer-Jones-Keefer, Ltd. and dated July 7, 2022.

The subject property is an approximately rectangular shaped parcel located in the northeast quadrant of the intersection of Highway 17/21 and Pine Street in Yemassee, South Carolina. The south approximate half (2.5 acres) of the property is identified by street address as 311 US Highway 21 and includes an existing single multi-family residence structure fronting on Highway 17/21 in the southwest corner, a concrete parking slab adjacent to the highway right-of-way in the central portion, and the balance is cleared of significant vegetation with visual evidence of widespread past ground disturbance. Multiple small piles of miscellaneous household debris, multiple abandoned vehicles, and several used vehicle tires were observed at widespread locations throughout this south portion of the overall property. In addition, review of historic aerial images available through Google Earth reveals that the concrete parking slab adjacent to the highway (described above) was associated with a structure (visible in a 1994 aerial image) that has been demolished and removed in the past. Further, it is our understanding that it has been reported that there may be buried debris within the south portion of the subject property.

The north portion of the subject property was observed to be vegetated with moderate density mature trees and moderate to dense underbrush. Two approximately parallel southwest/northeast oriented drainage ditches cross the subject property diagonally, one separating the south and north approximate halves and the second, further north, subdividing the northern portion into approximately equal halves. In addition, the two ditches detailed above are connected by a generally north/south oriented ditch in the central portion of the overall site.

We observed that the property is generally flat but with multiple isolated lower elevated areas throughout much of both the south and north portions. At the time of our clearing for drill rig access and excavation of the test pits, as well as at the time our soil test borings were performed, we observed significant flow of water within the drainage ditches described above as well as ponded surface water within the isolated lower elevated areas.



The conceptual site plan provided to us indicates that the existing multi-unit residence structure is to be removed and that new development is to include an industrial building having initial footprint dimensions of 200 feet by 500 feet and with an anticipated future expansion along the east side of an additional width of approximately 100 feet. As requested, our evaluation addresses the entire anticipated 300 feet by 500 feet footprint of the future building. The conceptual plan also indicates that the development will include paved entrances, drives and parking along the north, west and south sides of the proposed building.

Details of the proposed new structure have not been provided to us for reference in our analyses and evaluation. It is our assumption, and our evaluation is based upon our assumption, that the structure will be of some conventional combination of concrete masonry unit (CMU), steel frame, and/or wood frame design and that the preferred foundation system will be conventional shallow spread column/continuous wall footings and soil supported concrete floor slabs. We have assumed, as stated in our proposal to perform these services, for the purpose of our analyses, that the maximum design loads for isolated column footings and/or continuous strip foundations will not exceed 60 kips and 3.5 kips per linear foot, respectively. Further, we anticipate fill thicknesses of not greater than approximately 18 inches will be required in order to bring the building floor slab to the desired elevation.

With regard to paved access drives and parking areas, we anticipate that heavy duty pavements will be required for the main entrances and access drives and that light duty pavements will be sufficient for the parking areas.

It is our understanding that the purposes of this geotechnical site investigation are generally to explore and evaluate the underlying in situ soils and groundwater conditions to provide site preparation and shallow foundation design recommendations for the proposed new structure (including potential 'static' settlement estimates, seismic design parameters, and potential liquefaction induced settlement estimates) as well as site preparation and preliminary cross-section design recommendations for conventional asphalt pavements.

## 2. Subsurface Exploration

Our scope of services has included eight (8) soil test borings at widely dispersed locations throughout the footprint area of the proposed new structure and four (4) hand-auger borings at widely dispersed locations throughout the paved portions of the site as indicated on the preliminary conceptual site plan provided to us, as well as test pit excavations at thirteen (13) locations within the south portion of the property.

The locations of the soil test borings, hand-auger borings, and test pit excavations in **Figure 1**. A GHD professional positioned the explorations in the field utilizing a hand-held GPS device. Given the method of locating the explorations in the field, the locations indicated on **Figure 1** should be considered approximate.

### 2.1 SPT Soil Test Borings

The eight soil test borings (designated B-1 through B-8) were performed on September 14 and 15, 2022. Current International Building Code (IBC) requirements dictate that the geotechnical evaluation/foundation design process include a seismic analysis; which requires at least one boring be performed to sufficient depth to provide the necessary subsurface soils parameter information. Therefore, one of the borings (B-6) was advanced to a depth of 50 feet below the existing ground surface. The other borings were each advanced to a depth of 25 feet. The borings were advanced utilizing mud-rotary drilling equipment/methods. Closely spaced soil sampling was performed in the upper ten feet and at five-foot intervals thereafter in each boring. During the sampling procedure, Standard Penetration Tests (SPT's) were conducted in general accordance with ASTM D1586 to obtain the standard penetration value of the soil. The standard penetration value (N) is defined as the number of blows of a 140-pound hammer, falling thirty inches, required to advance the split spoon sampler one foot. The sampler is lowered to the bottom of the drill hole and the number of blows

recorded for each of three successive increments of six inches penetration. The “N” value is obtained by adding the second and third incremental values. The “N” values are reported on each boring log. The results of the SPT testing indicate the relative density and comparative consistency of the soils, and thereby provide a basis for estimating relative strength and compressibility of the soil profile components. The logs of each of the soil test borings are presented as **Appendix A, Soil Test Boring Logs**.

## 2.2 Hand-auger Borings

The four (4) hand-auger borings (designated HA-1 through HA-4) were performed on September 20, 2022. Each hand-auger boring was manually advanced to a depth of approximately 4 feet below the existing ground surface using a steel auger. The soils encountered were examined by retrieving samples of the auger cuttings at regular depth intervals during boring advancement. Our personnel visually classified the soils encountered in the field. The logs of the hand-auger borings are presented as **Appendix B, Hand-Auger Boring Logs**.

## 2.3 Test Pits

The test pit excavations (designated TP-1 through TP-13, but with five (A – E) excavations in close proximity to each other at location TP-3 and three (A-C) at TP-9) were performed on September 7, 2022 to depths varying from approximately 3.5 to 11 feet below the existing ground surface. The soils encountered at each test pit location were examined and visually classified during the excavation of each test pit and representative samples of the various strata encountered were collected. The logs of the test pits are presented as **Appendix C, Test Pit Logs**.

## 2.4 Soil Sample Handling

The soils from each soil boring sample/SPT test, selected hand-auger boring cuttings, and the representative test pit excavation samples were placed in individual containers, properly sealed and marked for identification, and transported to our laboratory for analysis and/or final classification by a GHD staff professional in accordance with the Unified Soil Classification System (USCS).

## 2.5 Laboratory Analyses

Selected samples of the soils obtained from the test pit excavations were tested in our laboratory to determine their percent fines (ASTM D1140) and natural moisture content (ASTM D2216). The laboratory data was used to aid in the classification of the soils in accordance with ASTM D2487 and to determine their engineering characteristics. The laboratory test results are included in the logs of test pit excavations in **Appendix C**.

# 3. Subsurface Stratigraphy/Conditions Encountered

A GHD professional developed the final boring log and test pit excavation log information from the field logs and visual review of the soil samples delivered to our laboratory. Similar soils were grouped into strata, with each stratum described in general accordance with the nomenclature used in ASTM D2487. Although indicated on the boring and test pit logs as distinct changes, the transition from one soil type or stratum to another may be gradual or may occur at slightly differing elevations than indicated between soil samples. Soil conditions may also vary from our findings at locations in areas of the site not explored.

The following discussion of the subsurface conditions encountered highlights the generalized major subsurface stratification encountered during our fieldwork. For more detailed descriptions of the subsurface conditions encountered at each location, please refer to the **Appendices A, B and C** to this report. The logs include the SPT “N” values (soil test borings), Unified Soil Classification System (USCS) symbols and groundwater levels at the time of our study.



### **3.1 Subsurface Soil Stratigraphy**

The specific soil types, stratifications and consistencies encountered varied significantly both with depth within individual explorations and between the exploration locations. However, a generalized description of the soil profile encountered throughout the majority of the overall property includes a thin surface veneer of organic topsoil, a surficial layer of clayey to very clayey fine sand (SC), sometimes including fine roots, to depths of approximately 1.5 to 2.5 feet, then varied strata of clays with varying fine sand content and fine sands of varying clay content (CL, CH, SC, SP-SC, SP) through the depth of the explorations.

Within the south portion of the property that had been previously cleared of significant vegetation, and from within which a previous structure had apparently been removed, our test pit excavations identified as TP-3 (A – E), TP-9 (A- C), and TP-11 all encountered significant quantities of miscellaneous household and/or construction debris to depths varying from approximately 1.5 to 3.5 feet below the existing ground surface, abandoned shallow concrete foundations, and an undocumented sewer pipe. The deeper soils at those three locations generally consisted of fine very sandy clay (CL). Within the remainder of the south portion of the property the explorations encountered surficial grass root mass and/or topsoil underlain by a shallow layer of clayey fine sand (SC) then fine very sandy clay (CL) or underlain directly by the fine very sandy clay.

### **3.2 Groundwater**

The depth to groundwater in the soil test borings measured after a stabilization period in excess of 24 hours varied from approximately 1 to 3 feet below the existing ground surface. No groundwater was encountered at the hand-auger locations. At test pit location TP-1, although moist soils were encountered beginning at depths of approximately 7 to 9 feet below the existing ground surface, no significant water inflow was observed.

The soil conditions observed at the exploration locations generally consisted of relatively permeable surficial and shallow subgrade soils having moderate clay content directly underlain by much less permeable very sandy clay or very clayey sand. These soil conditions are conducive to development of a ‘perched’ water condition within the near surface soils. A ‘perched’ condition occurs when surface water is not readily drained from the site and becomes ponded and/or permeates an upper more permeable soil strata while an underlying relatively impervious stratum prevents any further downward migration of the water, thus creating the ‘perched’ condition. The magnitude of ‘perched’ water is related to surficial soil permeability, lateral surface drainage onto and across the subject site, and the amount and duration of recent precipitation. The ‘perched groundwater’ may often be non-existent.

In general, we believe the variation in depth to stabilized groundwater levels in our soil test borings can be somewhat correlated to the topographic variation across the site. Also, there are a number of possible reasons why the groundwater depths vary, including localized perching within surficial sandy soils above clayey soils with low permeability and the effects of drainage feature installations and ground surface grading modifications within and/or in the vicinity of the site. We also expect groundwater levels will fluctuate depending upon the season, recent rainfall quantities in the area, and other factors.

## **4. Conclusions and Recommendations**

### **4.1 General**

The following conclusions and recommendations are based on the project characteristics previously described, the data obtained in our field explorations, and our experience with similar subsurface conditions and development projects. If the final design grades are to be significantly different from our understanding as stated earlier, or if subsurface conditions different from those disclosed by the soil test borings, hand-auger borings, and/or test pit excavations are encountered during site preparation, we should be notified so that we

might review the following preliminary recommendations in light of such additional information and/or changed conditions.

In general, it is our opinion that the subsurface conditions encountered by the soil test borings are suitable for support of the proposed structures using conventional shallow foundations following implementation of the site preparation and design recommendations discussed in the following sections of this report.

Further, our analyses indicate that, if liquefaction did occur, the magnitude of potential total settlement of the subgrade soils within the site could be on the order of 1 inch or less. Therefore, 'improvement' of the subsurface soils to a degree sufficient to reduce the magnitude of potential liquefaction induced settlement of the proposed structure to a lesser magnitude would likely not be warranted.

## **4.2 Site Preparation Recommendations**

### **4.2.1 Moisture Control**

Our explorations encountered moisture sensitive clayey soils at or very near the existing ground surface throughout the proposed structure/pavement areas. Strict moisture control will need to be maintained to avoid destabilization of the surficial and/or shallow subgrade soils during site preparation in these areas. Failure to control moisture in clayey soils may result in the need for removal and replacement of otherwise stable soils. Moisture control methods should also be implemented even where more favourable soils are located within the upper two feet. Moisture control methods should include, but are not necessarily be limited to:

- Staging the work to avoid excessive exposure to inclement weather;
- Installing drainage features such as ditches and ponds prior to initiating site clearing and grubbing;
- Maintaining positive drainage at the end of each work day or prior to inclement weather;
- Using a smooth drum roller or bulldozer to seal areas to facilitate runoff;
- And minimizing/limiting rubber-tired vehicle traffic by utilizing low contact pressure or tracked equipment whenever possible across the work area.

We highly recommend that surface water across the area be managed prior to, during and after stripping and grubbing operations to avoid excessive surface moisture which can lead to an unstable working surface and thus, undue mixing of the organic debris with the underlying soils. Therefore, it may be necessary to drain ponded surface water and to reduce the moisture content of the surficial and shallow subgrade soils prior to initiating general site preparation procedures.

### **4.2.2 Stripping and Grubbing / Uncontrolled Fill/Backfill Removal**

Site preparation should include the complete clearing, stripping and removal of all vegetation (including trees, underbrush, grasses/weeds, etc.), surficial topsoil, surficial and subgrade soils containing organic material and/or other debris, and other deleterious materials from within and to a minimum distance of five (5) feet beyond the perimeter of the structure footprints and pavement areas.

The depth to which topsoil, organic laden soils, miscellaneous debris, abandoned foundations and utilities, etc. was encountered at our exploration locations was generally on the order of a few inches to approximately 3.5 feet. It should be anticipated that the required depth of removal of deleterious materials and/or abandoned structures/utilities may be greater within un-explored portions of the site. During site clearing and earthwork operations, and while excavating for site utilities and foundations, the excavated and exposed soils should be observed for the presence of excessive organic and/or deleterious materials and debris that could be detrimental to building foundations, floor slabs and/or pavements. We recommend that an experienced soils engineering technician be present on site during the stripping, grubbing and uncontrolled fill/backfill removal process in order to determine which surficial and/or subgrade soils must be removed and replaced.



### 4.2.3 Exposed Subgrade Soils Proofrolling

After stripping and grubbing, and removal of debris/deleterious materials where necessary, GHD should inspect the disturbed surficial soils in structural (building and pavement) areas. Where practical, structural areas of the site should be proofrolled utilizing a loaded tri-axle dump truck, or other heavily loaded construction equipment. The purpose of the proofrolling will be to detect any areas where unstable soils are present. Materials that yield excessively during the proofrolling should be investigated via shallow test pits to verify the absence of organic laden soils, debris, or other deleterious materials. Where deleterious materials are not present, prior to fill placement, the soils should be over-excavated and replaced with structural fill soils meeting the material type and compaction requirements as outlined herein. GHD can recommend the nature and extent of any such remedial work.

### 4.2.4 Backfill/Fill Placement

#### 4.2.4.1 Building Footprint Areas

All fill within the proposed building footprint area should be inorganic, granular soils (clean to silty/clayey sands) with a maximum of 25 percent silt and/or clay. Backfill/fill should be placed in level lifts not to exceed 12 inches loose thickness and compacted to a minimum of 95 percent of the soil's "Modified" Proctor maximum dry density as determined by ASTM D1557.

#### 4.2.4.2 Conventional (Non-Permeable) Pavement Areas

Below 24 inches of Subgrade Elevation: All backfill/fill placed in conventional non-permeable paved parking and access drive areas at depths of 24 inches or deeper below pavement base should be inorganic, granular soils (clean to silty/clayey sands) with a maximum of 30 percent passing the No. 200 sieve. All backfill placed in undercut areas deeper than 24 inches below the pavement base course should be placed in level lifts not to exceed 12 inches in loose thickness and should be compacted to a minimum of 95 percent of the soil's maximum dry density as determined by ASTM D1557.

Upper 24 inches of Subgrade: Fill/backfill for the upper 24 inches in conventional non-permeable paved parking and access drive areas should be inorganic, granular soil (clean to silty / clayey sands) with a maximum of 20 percent passing the No. 200 sieve. Backfill/Fill within the upper 24 inches of the subgrade should be placed in level lifts not to exceed 12 inches in loose thickness and should be compacted to a minimum of 98 percent of the soil's maximum dry density as determined by ASTM D1557.

#### 4.2.4.3 General

In-place density tests should be performed on each lift by an experienced engineering technician working under the direction of a licensed geotechnical engineer to verify that the recommended degree of compaction has been achieved.

The top surface of the fill should extend a minimum of 3 feet beyond the perimeters of the structures/pavements and fill slopes should not exceed 2 horizontal to 1 vertical to prevent possible erosion or undermining of slabs, shallow footings and/or pavements. Shallower slopes may be dictated by site grading requirements.

## 4.3 Shallow Foundation / Floor Slab Design and Construction

### 4.3.1 Foundation Design / Dimensioning

When structural loads comply with the earlier stated assumed criteria, the footings may be proportioned for a maximum allowable bearing pressure of 2000 pounds per square foot (psf). To provide an adequate factor of

safety against a shearing failure in the subsoils: (1) all foundations should be founded at a depth of not less than 18 inches below the adjacent ground surface or floor slab elevation; (2) continuous footings should be at least 18 inches wide; and (3) isolated foundations should not be less than 24 inches in their least dimension.

### **4.3.2 Foundation Construction**

All foundation elements should be excavated, formed if necessary, and have their concrete cast in the dry. Care should also be taken when scheduling the excavation of foundations to avoid inclement weather as rain will make it necessary to control stormwater and/or 'perched' water that may infiltrate the exposed bearing soils. Any sandy soils at the bottom of the foundation excavations disturbed during the excavation process should be re-densified prior to placement of reinforcement steel. Any disturbed and/or softened clayey/silty soils should be removed and replaced with properly compacted structural fill or graded aggregate prior to placement of reinforcement steel. If this issue is encountered during construction, the geotechnical engineer should be consulted to evaluate the field conditions and to determine the extent of the required undercutting and appropriate alternatives for backfill. We also recommend that probing and/or dynamic cone penetrometer (DCP) testing be performed in the foundation excavations where the footings bear in or just above in-situ soils.

### **4.3.3 Floor Slab Design Recommendations**

A modulus of subgrade reaction of 200 psi/inch may be used for design of the floor slabs bearing on properly compacted structural fill. We recommend the placement of a vapor barrier below the floor slab(s). We suggest the use of polyethylene sheeting of at least 10-mil thickness for this purpose. Nevertheless, selection of the vapor barrier should consider the anticipated moisture conditions, flooring types and other applicable considerations.

The structural fill soils as specified herein for use in constructing the building pad are considered to be relatively free-draining soils. It is our opinion that these soils would be classified as "drainable" and that an additional aggregate material to act as a capillary barrier immediately below the floor slab would not be required.

Note that all downspouts/roof drains should be positioned such that stormwater is directed away from the structure and that the site should be constructed to meet the construction grading requirements.

### **4.3.4 Settlement**

Column and continuous wall foundations designed and constructed in the recommended manner are estimated to be subject to a maximum potential total settlement of less than about 0.5 inch, in the absence of a significant seismic event.

## **4.4 Seismic Considerations**

### **4.4.1 Liquefaction Potential**

The subject property is located within an active seismic zone with its center in the Charleston, South Carolina area. Although the area has not experienced significant earthquake events in the recent past, evidence of seismic event induced liquefaction has been found and geologists have mapped this area as having the potential for recurrence(s) of such an event. Considerable research is ongoing to better determine which local soils are truly liquefiable and the magnitude of settlement that might occur as a result of their liquefaction during a significant seismic event.

Based on our review of soil and groundwater conditions at the subject site, we believe there is a risk for liquefaction settlement to occur during a significant seismic event. Utilizing 'LiquefyPro' modelling software, we have performed a liquefaction analysis of the subject site considering the 'general' subsurface soil and groundwater conditions encountered and, in reference to the 2018 International Building Code (2018 IBC),



utilizing the Maximum Considered Earthquake Geometric Mean ( $MCE_G$ ) and Peak Ground Acceleration ( $PGAM$ ) which considers the soil characteristics of the site (Site Class effects). As previously stated, our analysis of the potential magnitude of settlement due to liquefaction indicates that following completion of the site preparation recommendations detailed above, settlement would be on the order of 1.0 inch or less within the area of the proposed structure. The potential liquefaction induced settlement would be due generally to the consolidation of the loose to medium dense saturated sand soils below the water table encountered at various depths below the existing ground surface. Due to the depth below the ground surface to the upper boundary of liquefiable soils, we estimate that differential liquefaction induced settlement within the building footprint would be on the order of 25 percent or less of the total.

#### 4.4.2 Seismic Design Parameters

Based upon the soil conditions encountered, our procedure for determining the site specific seismic design parameters follows that which is outlined in the 2018 International Building Code with reference to ASCE 7-16 for a default Seismic Site Class “D”. Values for Spectral Response Acceleration for short periods (0.2 seconds),  $S_s$ , and for long periods (1 second),  $S_1$ , were obtained from the Applied Technology Council (ATC) ‘Hazards by Location’ online tool which queries the United States Geological Survey (USGS) web servers and retrieves the seismic design variables in a report format. The values are expressed as a multiple of the acceleration of gravity. The design parameters generated are presented in **Appendix D, Seismic Design Parameters**.

### 4.5 Pavement Recommendations

The following pavement design guidelines are made without the benefit of specific traffic information and/or reference to any local minimum section standards, and are intended as a general guide for the design engineer’s evaluation. Site design decisions may dictate alterations to certain aspects of these guidelines.

#### 4.5.1 Conventional (Non-Pervious) Pavements

The following recommendations assume that site preparation procedures, including removal and replacement of unsuitable near surface soils/debris and proper proofrolling of subgrade soils detailed in earlier sections of this report, will have been completed where necessary. All conventional asphalt pavements and base courses should be constructed in accordance with the guidelines of the latest applicable South Carolina Department of Transportation Specifications.

**Entrance Drives & Truck Corridors:** We recommend an asphalt pavement section consisting of 3½ inches of asphaltic concrete (2 inches intermediate course + 1½ inches surface course) over 8 inches of graded aggregate base course. The pavement section should be underlain by a 24-inch sand subbase (with a maximum of 20 percent by weight passing the No. 200 sieve).

**Personal Vehicle Corridors & Parking Areas:** We recommend an asphalt pavement section consisting of 2 inches of asphaltic concrete (Type C) over 6 inches of graded aggregate base course. The pavement section should be underlain by a 24-inch sand subbase (with a maximum of 20 percent by weight passing the No. 200 sieve).

**Suitability of In Situ Soils:** Beneath the surficial organic debris/topsoil and shallow subgrade soils consisting of fine sand of varying clay content and/or very sandy clay, our explorations generally encountered unsuitable clay of varying fine sand content and/or very clayey fine sand at depths of less than 24 inches below the existing ground surface. These unsuitable soils will require removal and replacement with suitable select fill as detailed above to the depths necessary to provide the 24-inch sand subbase included in the recommended pavement section.

## 5. Limitations

*This report: has been prepared by GHD for Ironline LLC and may only be used and relied on by Ironline LLC and their selected consultants for the purposes agreed between GHD and Ironline LLC as set out in this report.*

*GHD otherwise disclaims responsibility to any person other than Ironline LLC arising in connection with this report. GHD also excludes implied warranties and conditions, to the extent legally permissible.*

*The services undertaken by GHD in connection with preparing this report were limited to those specifically detailed in the report and are subject to the scope limitations set out in the report.*

*The opinions, conclusions and any recommendations in this report are based on conditions encountered and information reviewed at the date of preparation of the report. GHD has no responsibility or obligation to update this report to account for events or changes occurring subsequent to the date that the report was prepared.*

*The opinions, conclusions and any recommendations in this report are based on assumptions made by GHD described in this report). GHD disclaims liability arising from any of the assumptions being incorrect.*

*GHD's scope of work for this project has not included investigation, detection, or evaluation related to the presence of any biological pollutants. The term 'biological pollutants' includes, but is not limited to, mold, fungi, spores, bacteria, and viruses, and the by products of any such biological organisms. Further, evaluation or review to determine compliance with State and/or Federal regulatory requirements, assessment of potential contamination migration from or onto the subject site, and/or any similar environmental analyses were beyond the scope of this study.*

*This report has been prepared with the intent that it not be separated. Information from this report should not be distributed or made available to designers or contractors in partial form. This report should be made available to prospective contractors for information only, and not as a warranty of subsurface conditions.*

## 6. Closure

We appreciate the opportunity to work with you on this project. We trust that the information provided in the report is clear and understandable. Should it require any clarification or amplification, however, please contact us at (843) 815-5120.

Regards

  
W. Chuck Rushing, P.E.  
843.815.0263  
Chuck.Rushing@ghd.com



  
Sean M. McCubbins, LEED® AP  
843.815.0268  
Sean.McCubbins@ghd.com



# Appendix A

## **Soil Test Boring Logs**

# Key to Soil Classification

## Correlation of Penetration Resistance with Relative Density and Consistency

<u>Sands and Gravels</u>		<u>Silts and Clays</u>	
No. of <u>Blows, N</u>	Relative <u>Density</u>	No. of <u>Blows, N</u>	Relative <u>Density</u>
0 – 4	Very loose	0 – 2	Very soft
5 – 10	Loose	3 – 4	Soft
11 – 30	Medium dense	5 – 8	Firm
31 – 50	Dense	9 – 15	Stiff
Over 50	Very dense	16 – 30	Very stiff
		31 – 50	Hard
		Over 50	Very hard

## Particle Size Identification (Unified Classification System)

Boulders:	Diameter exceeds 8 inches
Cobbles:	3 to 8 inches diameter
Gravel:	<b>Coarse</b> - 3/4 to 3 inches diameter <b>Fine</b> - 4.76 mm to 3/4 inch diameter
Sand:	<b>Coarse</b> - 2.0 mm to 4.76 mm diameter <b>Medium</b> - 0.42 mm to 2.0 mm diameter <b>Fine</b> - 0.074 mm to 0.42 mm diameter
Silt and Clay:	Less than 0.07 mm (particles cannot be seen with naked eye)



## Modifiers




The modifiers provide our estimate of the amount of silt, clay or sand size particles in the soil sample.

Approximate Content	Modifiers
≤ 5%:	Trace
5% to 12%:	Slightly silty, slightly clayey, slightly sandy
12% to 30%:	Silty, clayey, sandy
30% to 50%:	Very silty, very clayey, very sandy






Field Moisture Description	
Saturated:	Usually liquid; very wet, usually from below the groundwater table
Wet:	Semisolid; requires drying to attain optimum moisture
Moist:	Solid; at or near optimum moisture
Dry:	Requires additional water to attain optimum moisture










PROJECT:  <i>Pine Street Industrial Building</i>										LOG OF BORING:  B-1					
DATE DRILLED: <i>September 14, 2022</i>					DRILLER: <i>A. Nelson</i>					GROUND ELEVATION:					
DRILLING METHOD: <i>Mud Rotary</i>					BORING DEPTH: <i>25.00 Feet</i>					Notes:					
WATER LEVEL:					WATER LEVEL (24-HRS): <i>3'</i>										
ANALYSIS					Depth feet	BLOW COUNTS	GROUND WATER	GRAPHIC LOG	USCS	GEOLOGIC DESCRIPTION					
Moisture Content	% Passing 200 Sieve	Organic Content	Liquid Limit	Plasticity Index											
					0						4" Topsoil				
					1.4	11			SC		Medium dense tan to tan orange and brown clayey fine SAND				
					2.8	7			CL		Firm gray orange tan and brown fine very sandy CLAY with soft lense at 4' - 5.5'				
					4.2										
					5.6	3									
					7	8									
					8.4										
					9.8	3			CH		Soft light gray CLAY				
					11.2										
					12.6				SP		Medium dense tan fine to medium SAND				
					14										
					15.4	19									
					16.8										
					18.2										
					19.6	9			SP-SC		Loose tannish gray slightly clayey fine SAND				
					21										
					22.4										
					23.8				SC		Loose dark gray very clayey fine SAND				
					25.2	5					Boring terminated at 25 feet				
					26.6										
					28										
					29.4										
					30.8										
					32.2										
					33.6										
					35										
					36.4										
					37.8										
					39.2										
					40.6										
					42										
					43.4										
					44.8										
					46.2										
					47.6										
					49										
					50.4										
					51.8										
					53.2										




PROJECT:  <i>Pine Street Industrial Building</i>										LOG OF BORING:  B-2					
DATE DRILLED: <i>September 14, 2022</i>					DRILLER: <i>A. Nelson</i>					GROUND ELEVATION:					
DRILLING METHOD: <i>Mud Rotary</i>					BORING DEPTH: <i>25.00 Feet</i>					Notes:					
WATER LEVEL:					WATER LEVEL (24-HRS): <i>2.5'</i>										
ANALYSIS					Depth feet	BLOW COUNTS	GROUND WATER	GRAPHIC LOG	USCS	GEOLOGIC DESCRIPTION					
Moisture Content	% Passing 200 Sieve	Organic Content	Liquid Limit	Plasticity Index											
					0						4" Topsoil				
					1.4	6			SC	Loose gray and dark gray clayey fine SAND with fine roots					
					2.8	8			CL	Firm gray tan and orange fine very sandy CLAY					
					4.2	8			SC	Loose gray very clayey fine SAND					
					5.6	8									
					7	20			SC	Medium dense light gray and tan clayey fine SAND					
					8.4	11									
					9.8										
					11.2										
					12.6										
					14										
					15.4	11									
					16.8										
					18.2				SC	Loose dark gray very clayey fine SAND					
					19.6	5									
					21										
					22.4				SC	Medium dense dark gray and gray clayey fine SAND					
					23.8										
					25.2	12				Boring terminated at 25 feet					
					26.6										
					28										
					29.4										
					30.8										
					32.2										
					33.6										
					35										
					36.4										
					37.8										
					39.2										
					40.6										
					42										
					43.4										
					44.8										
					46.2										
					47.6										
					49										
					50.4										
					51.8										
					53.2										





PROJECT:  <i>Pine Street Industrial Building</i>										LOG OF BORING:  B-3					
DATE DRILLED: <i>September 14, 2022</i>					DRILLER: <i>A. Nelson</i>					GROUND ELEVATION:					
DRILLING METHOD: <i>Mud Rotary</i>					BORING DEPTH: <i>25.00 Feet</i>					Notes:					
WATER LEVEL:					WATER LEVEL (24-HRS): <i>2.5'</i>										
ANALYSIS					Depth feet	BLOW COUNTS	GROUND WATER	GRAPHIC LOG	USCS	GEOLOGIC DESCRIPTION					
Moisture Content	% Passing 200 Sieve	Organic Content	Liquid Limit	Plasticity Index											
					0						4" Topsoil				
					1.4	5			SC	Loose dark gray and brown clayey fine SAND with decayed organics					
					2.8	8			CL	Firm brown gray and orange fine very sandy CLAY					
					4.2										
					5.6	7									
					7	8									
					8.4				CH	Firm light gray CLAY with thin clayey fine sand seams					
					9.8	6									
					11.2										
					12.6										
					14										
					15.4	5									
					16.8				SC	Loose to medium dense dark gray slightly clayey fine SAND					
					18.2										
					19.6	10									
					21										
					22.4										
					23.8										
					25.2	15				Boring terminated at 25 feet					
					26.6										
					28										
					29.4										
					30.8										
					32.2										
					33.6										
					35										
					36.4										
					37.8										
					39.2										
					40.6										
					42										
					43.4										
					44.8										
					46.2										
					47.6										
					49										
					50.4										
					51.8										
					53.2										


PROJECT:  <i>Pine Street Industrial Building</i>									LOG OF BORING:  B-4	
DATE DRILLED: <i>September 15, 2022</i>					DRILLER: <i>A. Nelson</i>				GROUND ELEVATION:	
DRILLING METHOD: <i>Mud Rotary</i>					BORING DEPTH: <i>25.00 Feet</i>				Notes:	
WATER LEVEL:					WATER LEVEL (24-HRS): <i>2.5'</i>					
ANALYSIS					Depth feet	BLOW COUNTS	GROUND WATER	GRAPHIC LOG	USCS	GEOLOGIC DESCRIPTION
Moisture Content	% Passing 200 Sieve	Organic Content	Liquid Limit	Plasticity Index						
					0					4" Topsoil
					1.4	5			SC	Loose gray tan orange and brown very clayey fine SAND with fine roots
					2.8	13			CL	
					4.2					Stiff brown tan and orange fine very sandy CLAY
					5.6	9				
					7	33			SC	Dense gray light gray orange and tan very clayey fine SAND
					8.4				CH	Stiff gray CLAY with thin clayey fine sand seams
					9.8	15				
					11.2					
					12.6					
					14					
					15.4	9				
					16.8					
					18.2				CH	Stiff greenish gray CLAY
					19.6	9				
					21					
					22.4				SC	Medium dense dark gray very clayey fine SAND
					23.8					
					25.2	12				Boring terminated at 25 feet
					26.6					
					28					
					29.4					
					30.8					
					32.2					
					33.6					
					35					
					36.4					
					37.8					
					39.2					
					40.6					
					42					
					43.4					
					44.8					
					46.2					
					47.6					
					49					
					50.4					
					51.8					
					53.2					











PROJECT:  <i>Pine Street Industrial Building</i>									LOG OF BORING:  B-5		
DATE DRILLED: <i>September 15, 2022</i>					DRILLER: <i>A. Nelson</i>				GROUND ELEVATION:		
DRILLING METHOD: <i>Mud Rotary</i>					BORING DEPTH: <i>25.00 Feet</i>				Notes:		
WATER LEVEL:					WATER LEVEL (24-HRS): <i>3'</i>						
ANALYSIS					Depth feet	BLOW COUNTS	GROUND WATER	GRAPHIC LOG	USCS	GEOLOGIC DESCRIPTION	
Moisture Content	% Passing 200 Sieve	Organic Content	Liquid Limit	Plasticity Index							
					0					6" Topsoil	
					1.4	4			SC	Very loose gray tan orange and light gray clayey fine SAND	
					2.8	10			SC	Loose gray tan and orange very clayey fine SAND	
					4.2						
					5.6	12				CL	Stiff to very stiff gray and tan fine very sandy CLAY
					7	21					
					8.4					SC	Medium dense tan and orange clayey fine SAND
					9.8	14					
					11.2						
					12.6						
					14						
					15.4	11					
					16.8						
					18.2					SC	Loose to medium dense gray and dark gray clayey fine SAND
					19.6	9					
					21						
					22.4						
					23.8						
					25.2	16					Boring terminated at 25 feet
					26.6						
					28						
					29.4						
					30.8						
					32.2						
					33.6						
					35						
					36.4						
					37.8						
					39.2						
					40.6						
42											
43.4											
44.8											
46.2											
47.6											
49											
50.4											
51.8											
53.2											

PROJECT:  <i>Pine Street Industrial Building</i>								LOG OF BORING:  B-6		
DATE DRILLED: <i>September 15, 2022</i>					DRILLER: <i>A. Nelson</i>			GROUND ELEVATION:		
DRILLING METHOD: <i>Mud Rotary</i>					BORING DEPTH: <i>50.00 Feet</i>			Notes:		
WATER LEVEL:					WATER LEVEL (24-HRS): <i>3'</i>					
ANALYSIS					Depth feet	BLOW COUNTS	GROUND WATER	GRAPHIC LOG	USCS	GEOLOGIC DESCRIPTION
Moisture Content	% Passing 200 Sieve	Organic Content	Liquid Limit	Plasticity Index						
					0					6" Topsoil
					1.4	4			SC	Very loose gray brown and tan very clayey fine SAND with fine roots
					2.8	9			SC	
					4.2					Loose to medium dense gray tan orange and red very clayey fine SAND
					5.6	7				
					7	17				
					8.4	10			CL	Stiff greenish gray fine very sandy CLAY
					9.8					
					11.2					
					12.6				SP-SC	Medium dense light gray and tan slightly clayey fine SAND
					14	11			SC	Loose gray and dark gray very clayey fine SAND
					15.4					
					16.8					
					18.2					
					19.6	9				
					21					
					22.4				SC	Medium dense dark greenish gray very clayey fine SAND with thin clay seams
					23.8					
					25.2	12				
					26.6					
					28					
					29.4					
					30.8	14				
					32.2					
					33.6				SC	Medium dense dark gray clayey fine SAND
					35	17				Medium dense dark gray very clayey fine SAND
					36.4					
					37.8					
					39.2					
					40.6	15				
					42					
					43.4				SC	
					44.8	12				
					46.2					
					47.6					
					49					
					50.4	17				Boring terminated at 50 feet
					51.8					
					53.2					



PROJECT:  <i>Pine Street Industrial Building</i>									LOG OF BORING:  B-7	
DATE DRILLED: <i>September 15, 2022</i>						DRILLER: <i>A. Nelson</i>			GROUND ELEVATION:	
DRILLING METHOD: <i>Mud Rotary</i>						BORING DEPTH: <i>25.00 Feet</i>			Notes:	
WATER LEVEL:						WATER LEVEL (24-HRS): <i>1'</i>				
ANALYSIS					Depth feet	BLOW COUNTS	GROUND WATER	GRAPHIC LOG	USCS	GEOLOGIC DESCRIPTION
Moisture Content	% Passing 200 Sieve	Organic Content	Liquid Limit	Plasticity Index						
					0					4" Topsoil
					1.4	6			SC	Loose gray light gray tan orange and red clayey fine SAND with fine roots
					2.8	15			CL	
					4.2					Stiff to firm gray orange and red fine very sandy CLAY
					5.6	8				
					7	18			CH	Very stiff light gray and gray CLAY with thin clayey fine sand seams
					8.4				SC	Medium dense light gray and tan clayey fine SAND
					9.8	22				
					11.2					
					12.6				SC	Medium dense gray very clayey fine SAND
					14	14				
					15.4					
					16.8					
					18.2				SC	Medium dense dark gray clayey fine SAND
					19.6	12				
					21					
					22.4					
					23.8					
					25.2	12				
					26.6					Boring terminated at 25 feet
					28					
					29.4					
					30.8					
					32.2					
					33.6					
					35					
					36.4					
					37.8					
					39.2					
					40.6					
					42					
					43.4					
					44.8					
					46.2					
					47.6					
					49					
					50.4					
					51.8					
					53.2					

PROJECT:  <i>Pine Street Industrial Building</i>									LOG OF BORING:  B-8	
DATE DRILLED: <i>September 15, 2022</i>						DRILLER: <i>A. Nelson</i>			GROUND ELEVATION:	
DRILLING METHOD: <i>Mud Rotary</i>						BORING DEPTH: <i>25.00 Feet</i>			Notes:	
WATER LEVEL:						WATER LEVEL (24-HRS): <i>2'</i>				
ANALYSIS					Depth feet	BLOW COUNTS	GROUND WATER	GRAPHIC LOG	USCS	GEOLOGIC DESCRIPTION
Moisture Content	% Passing 200 Sieve	Organic Content	Liquid Limit	Plasticity Index						
					0					4" Topsoil
					1.4	10			SC	Loose gray tan and orange very clayey fine SAND
					2.8	19			CL	Very stiff to stiff gray tan and red fine sandy CLAY
					4.2				SP- SC	Medium dense light gray and tan slightly clayey fine SAND
					5.6	14				
					7	16				
					8.4				SP	Medium dense gray fine to medium SAND with thin slightly clayey fine sand seams
					9.8	12				
					11.2					
					12.6					Loose to medium dense gray and dark gray clayey fine SAND
					14	12				
					15.4					
					16.8					
					18.2	8				
					19.6					
					21					
					22.4					
					23.8					
					25.2	18				Boring terminated at 25 feet
					26.6					
					28					
					29.4					
					30.8					
					32.2					
					33.6					
					35					
					36.4					
					37.8					
					39.2					
					40.6					
					42					
					43.4					
					44.8					
					46.2					
					47.6					
					49					
					50.4					
					51.8					
					53.2					



# Appendix B

## **Hand-auger Boring Logs**

## B-1 Log of Hand-Auger Borings

Project: Pine Street Industrial Building

Date: September 20, 2022

Personnel: C. Rushing

Reference No: 12591408-00

Location: See Figure

Location	Depth Below Ground Surface	Soil Description
HA-1	0 – 6"	Topsoil
	6" – 14"	Gray and brown slightly clayey fine SAND (SP-SC)
	14" – 22"	Gray orange and tan very clayey fine SAND (SC)
	22" – 48"	Gray orange tan and red fine very sandy CLAY (CL)
HA-2	0 – 14"	Topsoil and roots
	14" – 18"	Gray orange and tan very clayey fine SAND (SC)
	18" – 48"	Gray orange tan and red fine very sandy CLAY (CL)
HA-3	0 – 4"	Topsoil
	4" – 8"	Tan clayey fine SAND (SC)
	8" – 14"	Gray orange and tan very clayey fine SAND (SC)
	14" – 48"	Gray orange tan and red fine very sandy CLAY (CL)
HA-4	0 – 3"	Topsoil
	3" – 8"	Gray orange and tan very clayey fine SAND (SC)
	8" – 48"	Gray orange tan and red fine very sandy CLAY (CL)

Comments: \_\_\_\_\_



# Appendix C

## **Test Pit Excavation Logs**

## C-1 Log of Test Pits

Project: Pine Street Industrial Building

Date: September 7, 2022

Personnel: C. Rushing

Reference No: 12591408-00

Location: See Figure 1

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-1	0 – 2"	Topsoil		
	2" – 14"	Gray to tan slightly clayey fine SAND (SP-SC)		
	14" – 32"	Gray and tan very clayey fine SAND (SC)		
	32" – 8.5'	Gray orange and tan fine very sandy CLAY (CL) <Water inflow at 8.5'>	35.1	67.9
	8.5' – 11'	Light gray and tan clayey fine AND (SC)	23.6	16.8
Test pit terminated at 11'				

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-2	0 – 4"	Topsoil		
	4" – 4'	Gray orange and tan fine very sandy CLAY (CL)		
Test pit terminated at 4'				



## C-1 Log of Test Pits

Project: Pine Street Industrial Building

Date: September 7, 2022

Personnel: C. Rushing

Reference No: 12591408-00

Location: See Figure 1

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-3 (A-E)	0 – 6"	Topsoil		
	6" – 2.5'	Gray and tan slightly clayey fine SAND (SP-SC) and debris (shingles/metal/PVC/bricks)		
	2.5' – 6'	Gray orange and tan fine very sandy CLAY (CL)		
Test pit terminated at 6'				

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-4	0 – 4"	Topsoil		
	4" – 4'	Gray orange and tan fine very sandy CLAY (CL)		
Test pit terminated at 4'				

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-5	0 – 3"	Topsoil		
	3" – 10"	Gray slightly clayey fine SAND (SP-SC)		
	10" – 4'	Gray orange and tan fine very sandy CLAY (CL)	30.6	65.4
Test pit terminated at 4'				

## C-1 Log of Test Pits

Project: Pine Street Industrial Building

Date: September 7, 2022

Personnel: C. Rushing

Reference No: 12591408-00

Location: See Figure 1

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-6	0 – 4"	Topsoil		
	4" – 14"	Gray to tan slightly clayey fine SAND (SP-SC)		
	14" – 3'	Gray and tan very clayey fine SAND (SC)		
	3' – 5'	Gray orange and tan fine very sandy CLAY (CL)		
Test pit terminated at 5'				

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-7	0 – 5"	Topsoil		
	5" – 14"	Gray slightly clayey fine SAND (SP-SC)		
	14" – 4'	Gray orange and tan fine very sandy CLAY (CL)		
Test pit terminated at 4'				

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-8	0 – 8"	Topsoil and debris (bricks/plastic/gravel)		
	8" – 16"	Gray slightly clayey fine SAND (SP-SC)		
	16" – 4'	Gray orange and tan fine very sandy CLAY (CL)		
Test pit terminated at 4'				



## C-1 Log of Test Pits

Project: Pine Street Industrial Building

Date: September 7, 2022

Personnel: C. Rushing

Reference No: 12591408-00

Location: See Figure 1

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-9 (A-C)	0 – 14"	Topsoil and debris (bricks/plastic/gravel/clay pipe/strip foundation)		
	14" – 20"	Gray slightly clayey fine SAND (SP-SC)		
	20" – 4'	Gray orange and tan fine very sandy CLAY (CL)		
Test pit terminated at 4'				

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-10	0 – 4"	Topsoil		
	4" – 14"	Gray slightly clayey fine SAND (SP-SC) with few bricks and roots		
	14" – 3'	Gray orange and tan fine very sandy CLAY (CL)	33.8	66.0
Test pit terminated at 4'				
<i>Note: Test pit located under current debris pile</i>				

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-11	0 – 4"	Topsoil		
	4" – 16"	Gray and tan slightly clayey fine SAND (SP-SC)		
	16" – 3.5'	Gray orange and tan fine very sandy CLAY (CL)		
Test pit terminated at 3.5'				
<i>Note: Encountered cast iron pipe oriented parallel to highway at 3.5'</i>				

## C-1 Log of Test Pits

Project: Pine Street Industrial Building

Date: September 7, 2022

Personnel: C. Rushing

Reference No: 12591408-00

Location: See Figure 1

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-12	0 – 2"	Topsoil		
	2" – 14"	Tan slightly clayey fine SAND (SP-SC)		
	14" – 4'	Gray orange and tan fine very sandy CLAY (CL)		
Test pit terminated at 4'				

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-13	0 – 2"	Topsoil		
	2" – 16"	Tan slightly clayey fine SAND (SP-SC)		
	16" – 4'	Gray orange and tan fine very sandy CLAY (CL)		
Test pit terminated at 4'				



# Appendix D

## **Seismic Design Parameters**

⚠ This is a beta release of the new ATC Hazards by Location website. Please [contact us](#) with feedback.

ℹ The ATC Hazards by Location website will not be updated to support ASCE 7-22. [Find out why.](#)



## Hazards by Location

### Search Information

**Address:** 311 US-17 ALT, Yemassee, SC 29945, USA

**Coordinates:** 32.6985622, -80.84510920000001

**Elevation:** 16 ft

**Timestamp:** 2022-10-05T17:46:28.305Z

**Hazard Type:** Seismic


**Reference Document:** ASCE7-16

**Risk Category:** II


**Site Class:** D-default



### MCER Horizontal Response Spectrum



### Design Horizontal Response Spectrum



### Basic Parameters

Name	Value	Description
$S_S$	0.587	MCE <sub>R</sub> ground motion (period=0.2s)
$S_1$	0.184	MCE <sub>R</sub> ground motion (period=1.0s)
$S_{MS}$	0.781	Site-modified spectral acceleration value
$S_{M1}$	0.41	Site-modified spectral acceleration value
$S_{DS}$	0.52	Numeric seismic design value at 0.2s SA
$S_{D1}$	0.273	Numeric seismic design value at 1.0s SA

### Additional Information

Name	Value	Description
SDC	D	Seismic design category



$F_a$	1.331	Site amplification factor at 0.2s
$F_v$	2.233	Site amplification factor at 1.0s
$CR_S$	0.899	Coefficient of risk (0.2s)
$CR_1$	0.908	Coefficient of risk (1.0s)
PGA	0.344	$MCE_G$ peak ground acceleration
$F_{PGA}$	1.256	Site amplification factor at PGA
$PGA_M$	0.432	Site modified peak ground acceleration
$T_L$	8	Long-period transition period (s)
SsRT	0.587	Probabilistic risk-targeted ground motion (0.2s)
SsUH	0.653	Factored uniform-hazard spectral acceleration (2% probability of exceedance in 50 years)
SsD	1.5	Factored deterministic acceleration value (0.2s)
S1RT	0.184	Probabilistic risk-targeted ground motion (1.0s)
S1UH	0.202	Factored uniform-hazard spectral acceleration (2% probability of exceedance in 50 years)
S1D	0.6	Factored deterministic acceleration value (1.0s)
PGAd	0.5	Factored deterministic acceleration value (PGA)

*The results indicated here DO NOT reflect any state or local amendments to the values or any delineation lines made during the building code adoption process. Users should confirm any output obtained from this tool with the local Authority Having Jurisdiction before proceeding with design.*

*Please note that the ATC Hazards by Location website will not be updated to support ASCE 7-22. [Find out why.](#)*

## Disclaimer

Hazard loads are provided by the U.S. Geological Survey [Seismic Design Web Services](#).

While the information presented on this website is believed to be correct, ATC and its sponsors and contributors assume no responsibility or liability for its accuracy. The material presented in the report should not be used or relied upon for any specific application without competent examination and verification of its accuracy, suitability and applicability by engineers or other licensed professionals. ATC does not intend that the use of this information replace the sound judgment of such competent professionals, having experience and knowledge in the field of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the results of the report provided by this website. Users of the information from this website assume all liability arising from such use. Use of the output of this website does not imply approval by the governing building code bodies responsible for building code approval and interpretation for the building site described by latitude/longitude location in the report.

# Appendix E

**Figure**





- |   |   |   |
|---|---|---|
| <b>B-#</b> Designation / approximate location of Standard Penetration Test (SPT) Boring | <b>HA-#</b> Designation / approximate location of Hand-Auger Boring | <b>TP-#</b> Designation / approximate location of Test Pit Excavation |
|---|---|---|

# Figure 1: Location Plan

Pine Street Industrial Building



# PINE STREET RESIDENTIAL

2023  
January

Project No:  
171002659

DRAFT


PREPARED FOR:

WARD EDWARDS  
ENGINEERING

PO BOX 381, BLUFFTON, SC 29910

## TRAFFIC IMPACT ANALYSIS

ALONG PINE STREET  
IN HAMPTON COUNTY, SOUTH CAROLINA







# PINE STREET RESIDENTIAL TRAFFIC IMPACT ANALYSIS


The conclusions in the Report titled "Pine Street Residential Traffic Impact Analysis" are Stantec's professional opinion, as of the time of the Report, and concerning the scope described in the Report. The opinions in the document are based on conditions and information existing at the time the document was published and do not take into account any subsequent changes. The Report relates solely to the specific project for which Stantec was retained and the stated purpose for which the Report was prepared. The Report is not to be used or relied on for any variation or extension of the project, or for any other project or purpose, and any unauthorized use or reliance is at the recipient's own risk.

Stantec has assumed all information received from Ward Edwards Engineering (the "Client") and third parties in the preparation of the Report to be correct. While Stantec has exercised a customary level of judgement or due diligence in the use of such information, Stantec assumes no responsibility for the consequence of any error or omission contained therein.

This Report is intended solely for use by the Client in accordance with Stantec's contract with the Client. While the Report may be provided to applicable authorities having jurisdiction and others for whom the Client is responsible, Stantec does not warrant the services to any third party. The report may not be relied upon by any other party without the express written consent of Stantec, which may be withheld at Stantec's discretion.

Prepared by: 

Prasad Chame

Reviewed by: 

Stuart Day, PE, PTOE



Approved by: 

Josh Mitchell, PE

January 2023

# TABLE OF CONTENTS



<b>EXECUTIVE SUMMARY</b> .....	<b>I</b>
<b>1.0 INTRODUCTION</b> .....	<b>1.1</b>
1.1 PROJECT BACKGROUND.....	1.1
1.2 EXISTING ROADWAY CONDITIONS.....	1.1
<b>2.0 DRIVEWAY SPACING REVIEW</b> .....	<b>2.1</b>
<b>3.0 PROJECT TRAFFIC</b> .....	<b>3.1</b>
3.1 PROPOSED LAND USES.....	3.1
3.2 TRIP GENERATION ESTIMATES.....	3.1
3.3 TRIP DISTRIBUTION & ASSIGNMENT.....	3.1
3.3.1 New External Traffic.....	3.1
<b>4.0 TRAFFIC VOLUME DEVELOPMENT</b> .....	<b>4.1</b>
4.1 EXISTING TRAFFIC VOLUMES.....	4.1
4.2 FUTURE TRAFFIC PROJECTIONS.....	4.1
<b>5.0 TRAFFIC IMPACT ANALYSIS</b> .....	<b>5.1</b>
5.1 TURN LANE ANALYSIS.....	5.1
5.1.1 Right-Turn Lanes.....	5.1
5.1.2 Left-Turn Lanes.....	5.2
5.2 INTERSECTION LOS ANALYSIS.....	5.3
<b>6.0 SUMMARY OF FINDINGS AND RECOMMENDATIONS</b> .....	<b>6.1</b>

## LIST OF TABLES

Table 2.1 – Minimum Driveway Spacing*.....	2.1
Table 3.1 – Trip Generation Estimates.....	3.1
Table 5.1 – Right-Turn Lane Criteria Warrants.....	5.1
Table 5.2 – Left-Turn Lane Criteria Warrants.....	5.2
Table 5.3 – HCM 6 <sup>th</sup> Edition Intersection LOS Criteria.....	5.3
Table 5.4 – Peak Hour Intersection Analysis Results.....	5.4

## LIST OF EXHIBITS

Exhibit 1.1 – Pine Street Residential Location Map.....	1.2
Exhibit 1.2 – Pine Street Residential Site Plan.....	1.3
Exhibit 3.1 – Residential Project Traffic Distribution and Assignment.....	3.2
Exhibit 3.2 – Light Industrial Project Traffic Distribution and Assignment.....	3.3
Exhibit 3.3 – Peak Hour Project Traffic Volumes.....	3.4
Exhibit 4.1 – 2022 Existing Peak Hour Traffic Volumes.....	4.2
Exhibit 4.2 – 2025 No Build Peak Hour Traffic Volumes.....	4.3
Exhibit 4.3 – 2025 Build Peak Hour Traffic Volumes.....	4.4

## LIST OF APPENDICES

Appendix A	Trip Generation Worksheets
Appendix B	Traffic Volume Data
Appendix C	Traffic Volume Development Worksheets
Appendix D	Analysis Worksheets: 2022 Existing Conditions
Appendix E	Analysis Worksheets: 2025 No Build Conditions
Appendix F	Analysis Worksheets: 2025 Build Conditions
Appendix G	Turn Lane Analysis Worksheets





## EXECUTIVE SUMMARY

A traffic impact analysis was conducted for the Pine Street Residential development in accordance with SCDOT and Town of Yemassee guidelines.

The proposed Pine Street Residential development (which is anticipated to be constructed by 2025) is located on Pine Street, north of US 21, and will consist of 71 single-family detached housing units and an approximately 100,000 square-foot light industrial building.

Access to the development will be provided via one new proposed access along US 21, servicing the light industrial building, which meets SCDOT's access spacing criteria, as well as via driveways along existing Pine Street, will serve as the access for the development.

For the purposes of the analysis, the intersection of US 21 & Pine Street is also referred to as Project Driveway #1, the intersection of Salkehatchie Road & Pine Street is also referred to as Project Driveway #2, and the new proposed access along US 21 is referred to as Project Driveway #3.

The extent of the roadway network analyzed consisted of the four (4) intersections of:

1. US 21 & Salkehatchie Road;
2. US 21 & Pine Street (Project Driveway #1);
3. Salkehatchie Road & Pine Street (Project Driveway #2);  
and
4. US 21 & Project Driveway #3.

The operation of each of the study area intersections (in terms of average vehicular delay and level of service) was analyzed with and without the project traffic anticipated to be generated by the Pine Street Residential development.

The results of the analysis indicate that the study intersections currently operate and are expected to continue to operate at an acceptable level of service with the proposed Pine Street Residential development.

Per the criteria documented in *Section 5D-4* of SCDOT's *Access and Roadside Management Standards (ARMS, 2008)*, exclusive turn lanes are not recommended at any of the study intersections or project driveways.



## 1.0 INTRODUCTION

### 1.1 PROJECT BACKGROUND

The purpose of this report is to document the procedures and findings of a traffic impact analysis for the proposed Pine Street Residential development in accordance with SCDOT and Town of Yemassee guidelines. The proposed Pine Street Residential development is located along US 21 and along Pine Street, north of US 21, as shown in **Exhibit 1.1**, and will consist of 71 single-family detached housing units and an approximately 100,000 square-foot light industrial building with anticipated completion by 2025.

Access to the development will be provided via one new proposed access along US 21, servicing the light industrial building, along with driveways along existing Pine Street, will serve as the access for the development, as shown in **Exhibit 1.2**. For the purposes of the analysis, the intersection of US 21 & Pine Street is also referred to as Project Driveway #1, the intersection of Salkehatchie Road & Pine Street is also referred to as Project Driveway #2, and the new proposed access along US 21 is referred to as Project Driveway #3.

The traffic impact analysis considers the weekday AM peak hour (between 7:00 AM and 9:00 AM) and the weekday PM peak hour (between 4:00 PM and 6:00 PM) as the study time frames.

The extent of the roadway network analyzed consisted of the four (4) intersections of:

1. US 21 & Salkehatchie Road;
2. US 21 & Pine Street (Project Driveway #1);
3. Salkehatchie Road & Pine Street (Project Driveway #2); and
4. US 21 & Project Driveway #3.

### 1.2 EXISTING ROADWAY CONDITIONS

US 21 is a two-lane arterial that primarily serves commercial and residential land uses. The posted speed limit is 45-miles per hour (mph) north of Pine Street, while the posted speed limit south of Lacey Street is 35-mph. The speed limit changes from 45-mph to 35-mph between Pine Street and Lacey Street. The average annual daily traffic (AADT) in 2021 was 1,650 vehicles/day. Based upon existing turning movement counts, the percentage of heavy vehicles along US 21 is approximately 13%.

Salkehatchie Road is a two-lane major collector that primarily serves residential and commercial land uses. The posted speed limit is 30-mph. The AADT in 2021 was 850 vehicles/day. Based upon existing turning movement counts, the percentage of heavy vehicles along Salkehatchie Road is approximately 2%.

Pine Street is a two-lane local road that primarily serves residential land uses. Based upon existing turning movement counts, the percentage of heavy vehicles along Pine Street is approximately 5%.





Exhibit 1.1 – Pine Street Residential Location Map






Exhibit 1.2 – Pine Street Residential Site Plan







## 2.0 DRIVEWAY SPACING REVIEW

Access to the development will be provided via one new proposed access along US 21, servicing the light industrial building, along with driveways along existing Pine Street, will serve as the access for the development.

As shown in **Exhibit 1.2**, For the purposes of the analysis, the intersection of US 21 & Pine Street is also referred to as Project Driveway #1, the intersection of Salkehatchie Road & Pine Street is also referred to as Project Driveway #2, and the new proposed access along US 21 is referred to as Project Driveway #3.

Since the intersections of US 21 & Pine Street and Salkehatchie Road & Pine Street currently exist, a driveway spacing was not performed for Project Driveways #1 and #2. However, a driveway spacing was performed for Project Driveway #3, since it is a new proposed access along US 21.

A review of the driveway spacing of the proposed driveway was completed based on information contained in SCDOT's *Access & Roadside Management Standards (ARMS)* manual (2008), shown in the adapted **Table 2.1**.

Table 2.1 – Minimum Driveway Spacing\*

Posted Speed Limit (mph)	AADT ≥ 2000; or Driveways Generating > 50 Peak Hour Trips	AADT < 2000
30	160 ft	75 ft
35	220 ft	125 ft
40	275 ft	175 ft
45	325 ft	225 ft
≥ 50	400 ft	275 ft

\*Figure 3-7 of *Access & Roadside Management Standards, 2008, SCDOT*

Based upon the 45-mph speed limit and the driveway spacing criteria of *ARMS*, a **minimum of 325 feet** is required for full access along US 21.

**Project Driveway #3** is proposed to be located along US 21, approximately 430 feet east of the intersection of US 21 & Pine Street, which meets the spacing criteria and approximately 4,700 feet west of the intersection of US 21 & Rum Bluff Road, which meets the spacing criteria.



## 3.0 PROJECT TRAFFIC

### 3.1 PROPOSED LAND USES

Project traffic in this analysis is defined as the vehicle trips anticipated to be generated by the proposed Pine Street Residential development. These trips were distributed and assigned throughout the study roadway network.

The Pine Street Residential development is proposed to consist of 71 single-family detached housing units and an approximately 100,000 square-foot light industrial building.

### 3.2 TRIP GENERATION ESTIMATES

The trip generation potential for the development was estimated using information contained in ITE's *Trip Generation Manual*, 11<sup>th</sup> Edition (2021) reference. The estimates utilized land use codes (LUC) 210 – Single-Family Detached Housing, and LUC 110 – General Light Industrial.

Due to the nature of the proposed Pine Street Residential development, internal capture trips and pass-by trips were not considered in the trip generation estimates.

The trip generation estimates for the development are shown below in **Table 3.1**, and documented in **Appendix A**.

### 3.3 TRIP DISTRIBUTION & ASSIGNMENT

#### 3.3.1 New External Traffic

New external traffic expected to be generated by the Pine Street Residential development was distributed and assigned to the roadway network based upon existing travel patterns in

the area. Since the proposed Pine Street Residential development will also consist of a 100,000 square-foot light industrial building, the residential and light industrial trips were distributed and assigned separately considering the nature of the trips attracted to/generated from these land uses. The general distribution of the residential project trips was assumed to be:

- ❖ 30% to/from the north via Salkehatchie Road;
- ❖ 10% to/from the south via Salkehatchie Road;
- ❖ 30% to/from the east via US 21; and
- ❖ 30% to/from the west via US 21.

The assignment of new external project traffic anticipated to be generated by the residential trips of the Pine Street Residential development is illustrated in **Exhibit 3.1**.

The general distribution of the light industrial project trips was assumed to be:

- ❖ 50% to/from the east via US 21; and
- ❖ 50% to/from the west via US 21.

The assignment of new external project traffic anticipated to be generated by the residential trips of the Pine Street Residential development is illustrated in **Exhibit 3.2**.

The AM and PM peak hour project traffic volumes are illustrated in **Exhibit 3.3**.

**Table 3.1 – Trip Generation Estimates**

Land Use	ITE LUC	Scale	Daily	Weekday AM Peak Period		Weekday PM Peak Period	
				Enter	Exit	Enter	Exit
Single-Family Detached Housing	210	71 Dwelling Units	736	14	41	45	27
General Light Industrial	110	100,000 Sq. Ft.	426	63	9	5	35
New, External Trips			1,162	77	50	50	62





### Exhibit 3.1 - Project Traffic Distribution and Assignment (Residential)



**Project Traffic Volume Assignment Legend**


00% - Inbound Trip Percentage  
(00%) - Outbound Trip Percentage



TWSC



SIGNAL





### Exhibit 3.2 - Project Traffic Distribution and Assignment (Light Industrial)




#### Project Traffic Volume Assignment Legend

00% - Inbound Trip Percentage  
(00%) - Outbound Trip Percentage



TWSC SIGNAL








### Exhibit 3.3 - Peak Hour Project Traffic Volumes



#### Traffic Volumes Legend

000 - AM Peak Hour Project Traffic  
(000) - AM Peak Hour Pass-By Traffic





## 4.0 TRAFFIC VOLUME DEVELOPMENT

### 4.1 EXISTING TRAFFIC VOLUMES

The traffic impact analysis considers the weekday AM peak hour (between 7:00 AM and 9:00 AM) and the weekday PM peak hour (between 4:00 PM and 6:00 PM) as the study time frames. The extent of the existing roadway network to be studied consists of the three (3) intersections of:

1. US 21 & Salkehatchie Road;
2. US 21 & Pine Street (Project Driveway #1); and
3. Salkehatchie Road & Pine Street (Project Driveway #2).

Existing 2022 traffic volumes were collected at these study area intersections during the AM and PM peak periods listed above.

The raw traffic volume counts are provided in **Appendix B** and the 2022 existing AM and PM peak hour traffic volumes are illustrated in **Exhibit 4.1**.

### 4.2 FUTURE TRAFFIC PROJECTIONS

Future 2025 No Build traffic volumes were developed by adding *background traffic growth* to the collected existing study area peak hour volumes. *Background traffic growth* is growth anticipated to occur in the study area regardless of the proposed Pine Street Residential development.

To develop an annual background growth rate for use in the analysis, historical count data along US 21 (SCDOT count stations #103 & #105) and Salkehatchie Road (SCDOT count stations #271 & #273) was reviewed over the past 5 years. It was determined that the roadways have experienced a collective annual growth of less than 1%. Therefore, in an effort to be conservative, a 1% annual growth rate was utilized to develop anticipated *background traffic growth* through the anticipated 2025 buildout year.

Future 2025 No Build AM and PM peak hour traffic volumes, illustrated in **Exhibit 4.2**, were developed by adding the *background traffic growth* (assuming 1% annual growth of the existing traffic volumes) to the 2022 existing AM and PM peak hour traffic volumes.

Future 2025 Build AM and PM peak hour traffic volumes, illustrated in **Exhibit 4.3**, were developed by adding the Pine Street Residential project traffic (shown in **Exhibit 3.2**) volumes to the 2025 No Build traffic volumes.

Volume development worksheets for each intersection are documented in **Appendix C**.






## Exhibit 4.1 - 2022 Existing Peak Hour Traffic Volumes



### Traffic Volumes Legend

000 - AM Peak Hour Volumes  
(000) - PM Peak Hour Volumes






## Exhibit 4.2 - 2025 No Build Peak Hour Traffic Volumes



### Traffic Volumes Legend

000 - AM Peak Hour Volumes  
(000) - PM Peak Hour Volumes







## Exhibit 4.3 - 2025 Build Peak Hour Traffic Volumes




### Traffic Volumes Legend

000 - AM Peak Hour Volumes  
(000) - PM Peak Hour Volumes

TWSC

SIGNAL





## 5.0 TRAFFIC IMPACT ANALYSIS

A traffic impact analysis was conducted for the Pine Street Residential development which analyzed the need for turn lanes at the project driveway and study intersections according to *Highway Capacity Manual (HCM) 6<sup>th</sup> Edition* methodologies.

### 5.1 TURN LANE ANALYSIS

#### 5.1.1 Right-Turn Lanes

The need for exclusive right-turn lanes is based upon the criteria documented in Section 9.5.1.1 of SCDOT's *Roadway Design Manual* (2021), which consists of nine considerations, listed below:

1. At a free-flowing leg of any unsignalized intersection on a two-lane urban or rural highway which satisfies the criteria in Figure 9.5-A;
2. at a free-flowing leg of any unsignalized intersection on a high-speed (50 mph or greater), four-lane urban or rural highway which satisfies the criteria in Figure 9.5-B;
3. at the free-flowing leg of any unsignalized intersection on a six-lane urban or rural highway;
4. at any intersection where a capacity analysis determines a right-turn lane is necessary to meet the overall level-of-service criteria;
5. as a general rule, at any signalized intersection where the projected right-turning volume is greater than 300 vehicles per hour and where there are greater than 300 vehicles per hour per lane on the mainline (A traffic analysis will be required if the turning volumes are greater than 300 vehicles per hour);
6. for uniformity of intersection design along the highway if other intersections have right-turn lanes;
7. at any intersection where the mainline is curved to the left and where the mainline curve requires superelevation;
8. at railroad crossings where the railroad is paralleled to the facility and is located close to the intersection and where a right-turn lane would be desirable to store queued vehicles avoiding interference with the movement of through traffic; or
9. at any intersection where the crash experience, existing traffic operations, sight distance restrictions (e.g., intersection beyond a crest vertical curve), or engineering judgement indicates a significant conflict related to right-turning vehicles;

Table 5.1 details whether the previously mentioned criteria are satisfied for Project Driveway #1 and at the study intersections of Salkehatchie Road & Pine Street (Project Driveway #2) and US 21 & Salkehatchie Road. An "✖" indicates that the criteria is not met; a "✓" indicates that it is met; and "N/A" indicates that the criteria is not applicable.

Table 5.1 – Right-Turn Lane Criteria Warrants

Crit- eria	PD #1	PD #3	Pine St & Salke- hatchie Rd	US 21 & Salke- hatchie Rd	Reference/ Note
1	✖	✖	✖	✖	Appendix G
2	N/A	N/A	N/A	N/A	Not a four-lane highway
3	N/A	N/A	N/A	N/A	Not a six-lane highway
4	✖	✖	✖	✖	Table 5.4
5	N/A	N/A	N/A	N/A	Not signalized
6	✖	✖	✖	✖	Not typically provided
7	✖	✖	✖	✖	Mainline not curved
8	✖	✖	✖	✖	No railroad crossing
9	N/A	N/A	N/A	N/A	Crash data not reviewed

Based on SCDOT's *Roadway Design Manual* considerations, exclusive right-turn lanes are **not recommended** at any of the study intersections.

Worksheets documenting the turn-lane analysis are provided in **Appendix G**.





## 5.1.2 Left-Turn Lanes

The need for exclusive left-turn lanes is based upon the criteria documented in Section 9.5.1.2 of SCDOT's *Roadway Design Manual* (2021), which consists of nine considerations, listed below:

1. *At any unsignalized intersection on principal, high-speed rural highways with other arterials or collectors;*
2. *at any unsignalized intersection on a two-lane urban or rural highway that satisfies the criteria in Figures 9.5-C, 9.5-D, 9.5-E, 9.5-F, or 9.5-G;*
3. *at any intersection where a capacity analysis determines a left-turn lane is necessary to meet the level of service criteria;*
4. *at any signalized intersection where the left-turn volume is 300 vehicles per hour or more, conduct a traffic review to determine if dual left-turn lanes are required;*
5. *as a general rule, at any intersection where the left-turning volume is 100 vehicles per hour (for a single turn lane) or 300 vehicles per hour (for a dual turn lane);*
6. *at all entrances to major residential, commercial, and industrial developments;*
7. *at all median crossovers;*
8. *for uniformity of intersection design along the highway if other intersections have left-turn lanes (i.e., to satisfy driver expectancy); or*
9. *at any intersection where the crash experience, existing traffic operations, sight distance restrictions (e.g., intersection beyond a crest vertical curve), or engineering judgement indicates a significant conflict related to left-turning vehicles;*

Table 5.2 below details whether the previously mentioned criteria are satisfied for Project Driveway #1 and at the study intersections of Salkehatchie Road & Pine Street (Project Driveway #2) and US 21 & Salkehatchie Road. An "✖" indicates that the criteria is not met; a "✓" indicates that it is met; and "N/A" indicates that the criteria is not applicable.

Table 5.2 – Left-Turn Lane Criteria Warrants

Crit- eria	PD #1	PD #3	Pine St & Salke- hatchie Rd	US 21 & Salke- hatchie Rd	Reference/ Note
1	N/A	N/A	N/A	N/A	Not an arterial or collector
2	✖	✖	✖*	✖	Appendix G
3	✖	✖	✖	✖	Table 5.4
4	N/A	N/A	N/A	N/A	Not signalized
5	✖	✖	✖	✖	Exhibit 4.3
6	✖	✖	✖	✖	Not a major development
7	✖	✖	✖	✖	No median crossover
8	✖	✖	✖	✖	Not typically provided
9	N/A	N/A	N/A	N/A	No crash data reviewed

\*Since Section 9.5.1.2 of SCDOT's *Roadway Design Manual* (2021) does not provide turn-lane criteria figure for roadways with speed limit 30 mph, Figure 9.5-G was used for analysis.

Based on SCDOT's *Roadway Design Manual* considerations, exclusive left-turn lanes are **not recommended** at any of the study intersections.

Worksheets documenting the turn-lane analysis are provided in **Appendix G**.



## 5.2 INTERSECTION LOS ANALYSIS

Using the existing and projected peak hour traffic volumes previously discussed, intersection analysis was conducted for the study and project driveway intersections considering 2022 Existing Conditions, 2025 No Build Conditions, and 2025 Build Conditions. The analysis was conducted using the Transportation Research Board's *Highway Capacity Manual (HCM) 6<sup>th</sup> Edition* methodologies of the *Synchro*, Version 11 software for stop-controlled intersection analysis.

Intersection level of service (LOS) grades range from LOS A to LOS F, which are directly related to the level of control delay at the intersection and characterize the operational conditions of the intersection traffic flow. LOS A operations typically represent ideal, free-flow conditions where vehicles experience little to no delays, and LOS F operations typically represent poor, forced-flow (bumper-to-bumper) conditions with high vehicular delays, and are generally considered undesirable. **Table 5.3** summarizes the HCM 6<sup>th</sup> Edition control delay thresholds associated with each LOS grade for unsignalized intersections. Level of service A through D is considered to be acceptable LOS, while LOS E and F is considered to be undesirable.

**Table 5.3 – HCM 6<sup>th</sup> Edition Intersection LOS Criteria**

LOS	Control Delay per Vehicle (s) Unsignalized
A	≤ 10
B	> 10 and ≤ 15
C	> 15 and ≤ 25
D	> 25 and ≤ 35
E	> 35 and ≤ 50
F	> 50

As part of the intersection analysis, SCDOT's default *Synchro* parameters were utilized. The existing 2022 traffic counts' peak hour factors (PHF) were utilized in the analysis of existing conditions. Future-year 2025 conditions were analyzed utilizing existing PHF, but with a minimum PHF of 0.90 and maximum PHF of 0.95 considered. The existing 2022 heavy vehicle percentages, as previously discussed, were utilized in the analysis, with a minimum percentage of 2% considered.

Existing lane geometry was utilized for the analysis of 2022 Existing Conditions and 2025 No Build Conditions. The 2025 Build Conditions were analyzed both with existing lane geometry and with any proposed improvements resulting from this impact analysis (including any proposed exclusive turn lanes per the results of **Section 5.1**) to illustrate their anticipated impact on traffic operations.

The results of the intersection analysis for existing and future-year conditions for the weekday AM and PM peak hour time periods are summarized in **Table 5.4**.

For two-way stop-controlled (TWSC) intersections, the LOS and delay results are evaluated for the worst-case minor-street approaches only, per *HCM 6<sup>th</sup> Edition* methodologies for TWSC intersections.

As shown in **Table 5.4**, the results of the analysis indicate that the study intersections currently operate and are expected to continue to operate at an acceptable LOS with the proposed Pine Street Residential development.

Worksheets documenting the intersection analyses are provided in **Appendix D** for 2022 Existing Conditions, **Appendix E** for 2025 No Build Conditions, and **Appendix F** for 2025 Build Conditions.





Table 5.4 – Peak Hour Intersection Analysis Results

Intersection	Control	LOS/Delay (seconds/vehicle)					
		AM Peak Hour			PM Peak Hour		
		2022 Existing	2025 No Build	2025 Build	2022 Existing	2025 No Build	2025 Build
1 US 21 & Salkehatchie Road	TWSC	B/10.3 (EB)	B/10.3 (EB)	B/10.9 (EB)	B/10.8 (WB)	B/10.8 (WB)	B/11.1 (WB)
2 US 21 & Pine Street (Project Driveway #1)	TWSC	--	--	A/9.5 (SB)	--	--	B/11.0 (SB)
3 Salkehatchie Road & Pine Street (Project Driveway #2)	TWSC	A/8.7 (WB)	A/8.7 (WB)	A/8.7 (WB)	A/8.6 (WB)	A/8.6 (WB)	A/8.7 (WB)
4 US 21 & Project Driveway #3	TWSC	--	--	A/9.6 (SB)	--	--	A/9.6 (SB)



## 6.0 SUMMARY OF FINDINGS AND RECOMMENDATIONS

A traffic impact analysis was conducted for the Pine Street Residential development in accordance with SCDOT and Town of Yemassee guidelines.

The proposed Pine Street Residential development (which is anticipated to be constructed by 2025) is located on Pine Street, north of US 21, and will consist of 71 single-family detached housing units and an approximately 100,000 square-foot light industrial building.

Access to the development will be provided via one new proposed access along US 21, servicing the light industrial building, which meets SCDOT's access spacing criteria, as well as via driveways along existing Pine Street, will serve as the access for the development.

For the purposes of the analysis, the intersection of US 21 & Pine Street is also referred to as Project Driveway #1, the intersection of Salkehatchie Road & Pine Street is also referred to as Project Driveway #2, and the new proposed access along US 21 is referred to as Project Driveway #3.

The extent of the roadway network analyzed consisted of the four (4) intersections of:

1. US 21 & Salkehatchie Road;
2. US 21 & Pine Street (Project Driveway #1);
3. Salkehatchie Road & Pine Street (Project Driveway #2);  
and
4. US 21 & Project Driveway #3.

The operation of each of the study area intersections (in terms of average vehicular delay and level of service) was analyzed with and without the project traffic anticipated to be generated by the Pine Street Residential development.

The results of the analysis indicate that the study intersections currently operate and are expected to continue to operate at an acceptable level of service with the proposed Pine Street Residential development.

Per the criteria documented in *Section 5D-4* of SCDOT's *Access and Roadside Management Standards (ARMS, 2008)*, exclusive turn lanes are not recommended at any of the study intersections or project driveways.





# **PINE STREET RESIDENTIAL TRAFFIC IMPACT ANALYSIS APPENDICES**



## Appendix A TRIP GENERATION WORKSHEETS



# TRIP GENERATION ESTIMATES

## Pine St Residential TIA

Weekday Daily																					
TRIP GENERATION CHARACTERISTICS						DIRECT. DISTRIB.		GROSS TRIPS			INTERNAL CAPTURE TRIPS				PASS-BY CAPTURE TRIPS				NEW EXTERNAL TRIPS		
Land Use	Ed.	LUC	Scale	Unit	Equation/Rate	In	Out	In	Out	Total	%	In	Out	Trips	%	In	Out	Trips	In	Out	Total
Single-Family Detached Housing General Light Industrial	11th	210	71	DU	$\text{Ln(T)} = 0.92 \text{ Ln(X)} + 2.68$	50%	50%	368	368	736	0%	0	0	0	0%	0	0	0	368	368	736
	11th	110	100	DU	$T = 3.76(X) + 50.47$	50%	50%	213	213	426	0%	0	0	0	0%	0	0	0	213	213	426
	Total:						581	581	1,162	0%	0	0	0	0%	0	0	0	581	581	1,162	

Weekday AM Peak Hour																					
TRIP GENERATION CHARACTERISTICS						DIRECT. DISTRIB.		GROSS TRIPS			INTERNAL CAPTURE TRIPS				PASS-BY CAPTURE TRIPS				NEW EXTERNAL TRIPS		
Land Use	Ed.	LUC	Scale	Unit	Equation/Rate	In	Out	In	Out	Total	%	In	Out	Trips	%	In	Out	Trips	In	Out	Total
Single-Family Detached Housing General Light Industrial	11th	210	71	DU	$\text{Ln(T)} = 0.91 \text{ Ln(X)} + 0.12$	26%	74%	14	41	55	0%	0	0	0	0%	0	0	0	14	41	55
	11th	110	100	DU	$\text{T} = 0.68 (\text{X}) + 3.81$	88%	12%	63	9	72	0%	0	0	0	0%	0	0	0	63	9	72
	Total:							77	50	127	0%	0	0	0	0%	0	0	0	77	50	127

Weekday PM Peak Hour																					
TRIP GENERATION CHARACTERISTICS						DIRECT. DISTRIB.		GROSS TRIPS			INTERNAL CAPTURE TRIPS				PASS-BY CAPTURE TRIPS				NEW EXTERNAL TRIPS		
Land Use	Ed.	LUC	Scale	Unit	Equation/Rate	In	Out	In	Out	Total	%	In	Out	Trips	%	In	Out	Trips	In	Out	Total
Single-Family Detached Housing General Light Industrial	11th	210	71	DU	$\text{Ln(T)} = 0.94 \text{ Ln(X)} + 0.27$	63%	37%	45	27	72	0%	0	0	0	0%	0	0	0	45	27	72
	11th	110	100	DU	$\text{Ln(T)} = 0.72 \text{ Ln(X)} + 0.38$	14%	86%	5	35	40	0%	0	0	0	0%	0	0	0	5	35	40
	Total:							50	62	112	0%	0	0	0	0%	0	0	0	50	62	112



## Appendix B TRAFFIC VOLUME DATA



# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201

*We can't say we're the Best, but you Can!*

File Name : Pine St @ Salkehatchie Rd

Site Code :

Start Date : 11/03/2022

Page No : 1

Groups Printed- Passenger Vehicles - Heavy Vehicles - Buses

	Salkehatchie Rd Southbound				Pine St Westbound				Salkehatchie Rd Northbound				Eastbound					
Start Time	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Int. Total	
07:00	0	10	0	0	0	0	0	0	0	7	0	0	0	0	0	0	0	17
07:15	0	11	0	0	1	0	2	0	0	5	1	0	0	0	0	0	0	20
07:30	1	7	0	0	1	0	2	0	0	8	0	0	0	0	0	0	0	19
07:45	1	11	0	0	0	0	0	0	0	11	0	0	0	0	0	0	0	23
Total	2	39	0	0	2	0	4	0	0	31	1	0	0	0	0	0	0	79
08:00	1	14	0	0	0	0	2	0	0	8	0	0	0	0	0	0	0	25
08:15	1	13	0	0	1	0	0	0	0	11	0	0	0	0	0	0	0	26
08:30	1	6	0	0	0	0	1	0	0	3	0	0	0	0	0	0	0	11
08:45	0	7	0	0	0	0	1	0	0	3	0	0	0	0	0	0	0	11
Total	3	40	0	0	1	0	4	0	0	25	0	0	0	0	0	0	0	73
16:00	2	12	0	0	0	0	2	0	0	12	0	0	0	0	0	0	0	28
16:15	1	7	0	0	0	0	3	0	0	16	1	0	0	0	0	0	0	28
16:30	1	7	0	0	0	0	2	0	0	10	0	0	0	0	0	0	0	20
16:45	1	5	0	0	1	0	1	0	0	5	1	0	0	0	0	0	0	14
Total	5	31	0	0	1	0	8	0	0	43	2	0	0	0	0	0	0	90
17:00	0	8	0	0	0	0	1	0	0	14	0	0	0	0	0	0	0	23
17:15	1	5	0	0	0	0	1	0	0	11	1	0	0	0	0	0	0	19
17:30	0	7	0	0	0	0	1	0	0	21	0	0	0	0	0	0	0	29
17:45	3	9	0	0	0	0	2	0	0	11	0	0	0	0	0	0	0	25
Total	4	29	0	0	0	0	5	0	0	57	1	0	0	0	0	0	0	96
Grand Total	14	139	0	0	4	0	21	0	0	156	4	0	0	0	0	0	0	338
Apprch %	9.2	90.8	0	0	16	0	84	0	0	97.5	2.5	0	0	0	0	0	0	
Total %	4.1	41.1	0	0	1.2	0	6.2	0	0	46.2	1.2	0	0	0	0	0	0	
Passenger Vehicles	14	137	0	0	4	0	19	0	0	151	4	0	0	0	0	0	0	329
% Passenger Vehicles	100	98.6	0	0	100	0	90.5	0	0	96.8	100	0	0	0	0	0	0	97.3
Heavy Vehicles	0	2	0	0	0	0	1	0	0	2	0	0	0	0	0	0	0	5
% Heavy Vehicles	0	1.4	0	0	0	0	4.8	0	0	1.3	0	0	0	0	0	0	0	1.5
Buses	0	0	0	0	0	0	1	0	0	3	0	0	0	0	0	0	0	4
% Buses	0	0	0	0	0	0	4.8	0	0	1.9	0	0	0	0	0	0	0	1.2

# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201


*We can't say we're the Best, but you Can!*

File Name : Pine St @ Salkehatchie Rd

Site Code :

Start Date : 11/03/2022

Page No : 2





# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201

*We can't say we're the Best, but you Can!*


File Name : Pine St @ Salkehatchie Rd

Site Code :

Start Date : 11/03/2022

Page No : 3

	Salkehatchie Rd Southbound					Pine St Westbound					Salkehatchie Rd Northbound					Eastbound					
Start Time	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Int. Total
Peak Hour Analysis From 07:00 to 08:45 - Peak 1 of 1																					
Peak Hour for Entire Intersection Begins at 07:30																					
07:30	1	7	0	0	8	1	0	2	0	3	0	8	0	0	8	0	0	0	0	0	19
07:45	1	11	0	0	12	0	0	0	0	0	0	11	0	0	11	0	0	0	0	0	23
08:00	1	14	0	0	15	0	0	2	0	2	0	8	0	0	8	0	0	0	0	0	25
08:15	1	13	0	0	14	1	0	0	0	1	0	11	0	0	11	0	0	0	0	0	26
Total Volume	4	45	0	0	49	2	0	4	0	6	0	38	0	0	38	0	0	0	0	0	93
% App. Total	8.2	91.8	0	0		33.3	0	66.7	0		0	100	0	0		0	0	0	0	0	
PHF	1.00	.804	.000	.000	.817	.500	.000	.500	.000	.500	.000	.864	.000	.000	.864	.000	.000	.000	.000	.000	.894
Passenger Vehicles	4	43	0	0	47	2	0	4	0	6	0	36	0	0	36	0	0	0	0	0	89
% Passenger Vehicles																					
Heavy Vehicles	0	2	0	0	2	0	0	0	0	0	0	2	0	0	2	0	0	0	0	0	4
% Heavy Vehicles	0	4.4	0	0	4.1	0	0	0	0	0	0	5.3	0	0	5.3	0	0	0	0	0	4.3
Buses	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
% Buses	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0



# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201

*We can't say we're the Best, but you Can!*


File Name : Pine St @ Salkehatchie Rd

Site Code :

Start Date : 11/03/2022

Page No : 4

	Salkehatchie Rd Southbound					Pine St Westbound					Salkehatchie Rd Northbound					Eastbound					
Start Time	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Int. Total
Peak Hour Analysis From 16:00 to 17:45 - Peak 1 of 1																					
Peak Hour for Entire Intersection Begins at 17:00																					
17:00	0	8	0	0	8	0	0	1	0	1	0	14	0	0	14	0	0	0	0	0	23
17:15	1	5	0	0	6	0	0	1	0	1	0	11	1	0	12	0	0	0	0	0	19
17:30	0	7	0	0	7	0	0	1	0	1	0	21	0	0	21	0	0	0	0	0	29
17:45	3	9	0	0	12	0	0	2	0	2	0	11	0	0	11	0	0	0	0	0	25
Total Volume	4	29	0	0	33	0	0	5	0	5	0	57	1	0	58	0	0	0	0	0	96
% App. Total	12.1	87.9	0	0		0	0	100	0		0	98.3	1.7	0		0	0	0	0	0	
PHF	.333	.806	.000	.000	.688	.000	.000	.625	.000	.625	.000	.679	.250	.000	.690	.000	.000	.000	.000	.000	.828
Passenger Vehicles	4	29	0	0	33	0	0	5	0	5	0	56	1	0	57	0	0	0	0	0	95
% Passenger Vehicles																					
Heavy Vehicles	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
% Heavy Vehicles	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
Buses	0	0	0	0	0	0	0	0	0	0	0	1	0	0	1	0	0	0	0	0	1
% Buses	0	0	0	0	0	0	0	0	0	0	0	1.8	0	0	1.7	0	0	0	0	0	1.0



# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201

*We can't say we're the Best, but you Can!*

File Name : US 21 @ Pine St

Site Code :

Start Date : 11/03/2022

Page No : 1

Groups Printed- Passenger Vehicles - Heavy Vehicles - Buses

Start Time	Pine St Southbound				US 21 Westbound				Northbound				US 21 Eastbound				Int. Total
	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Left	Thru	Right	Peds	
07:00	0	0	0	0	0	23	0	0	0	0	0	0	0	8	0	0	31
07:15	0	0	0	0	0	21	0	0	0	0	0	0	0	9	0	0	30
07:30	0	0	0	0	0	17	0	0	0	0	0	0	0	12	0	0	29
07:45	0	0	0	0	0	32	0	0	0	0	0	0	0	13	0	0	45
Total	0	0	0	0	0	93	0	0	0	0	0	0	0	42	0	0	135
08:00	0	0	0	0	0	23	0	0	0	0	0	0	0	11	0	0	34
08:15	0	0	0	0	0	16	0	0	0	0	0	0	0	8	0	0	24
08:30	0	0	0	0	0	14	0	0	0	0	0	0	0	10	0	0	24
08:45	0	0	0	0	0	22	0	0	0	0	0	0	0	11	0	0	33
Total	0	0	0	0	0	75	0	0	0	0	0	0	0	40	0	0	115
16:00	0	0	0	0	0	21	0	0	0	0	0	0	0	31	0	0	52
16:15	0	0	0	0	0	19	0	0	0	0	0	0	0	25	0	0	44
16:30	0	0	0	0	0	13	0	0	0	0	0	0	0	29	0	0	42
16:45	0	0	0	0	0	21	0	0	0	0	0	0	0	29	0	0	50
Total	0	0	0	0	0	74	0	0	0	0	0	0	0	114	0	0	188
17:00	0	0	0	0	0	14	0	0	0	0	0	0	0	32	0	0	46
17:15	0	0	0	0	0	21	0	0	0	0	0	0	0	27	0	0	48
17:30	0	0	0	0	0	13	0	0	0	0	0	0	0	37	0	0	50
17:45	0	0	0	0	0	32	0	0	0	0	0	0	0	25	0	0	57
Total	0	0	0	0	0	80	0	0	0	0	0	0	0	121	0	0	201
Grand Total	0	0	0	0	0	322	0	0	0	0	0	0	0	317	0	0	639
Apprch %	0	0	0	0	0	100	0	0	0	0	0	0	0	100	0	0	
Total %	0	0	0	0	0	50.4	0	0	0	0	0	0	0	49.6	0	0	
Passenger Vehicles	0	0	0	0	0	276	0	0	0	0	0	0	0	290	0	0	566
% Passenger Vehicles	0	0	0	0	0	85.7	0	0	0	0	0	0	0	91.5	0	0	88.6
Heavy Vehicles	0	0	0	0	0	45	0	0	0	0	0	0	0	26	0	0	71
% Heavy Vehicles	0	0	0	0	0	14	0	0	0	0	0	0	0	8.2	0	0	11.1
Buses	0	0	0	0	0	1	0	0	0	0	0	0	0	1	0	0	2
% Buses	0	0	0	0	0	0.3	0	0	0	0	0	0	0	0.3	0	0	0.3



# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201


*We can't say we're the Best, but you Can!*

File Name : US 21 @ Pine St

Site Code :

Start Date : 11/03/2022

Page No : 2



# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201

*We can't say we're the Best, but you Can!*


File Name : US 21 @ Pine St

Site Code :

Start Date : 11/03/2022

Page No : 3

	Pine St Southbound					US 21 Westbound					Northbound					US 21 Eastbound					
Start Time	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Int. Total
Peak Hour Analysis From 07:00 to 08:45 - Peak 1 of 1																					
Peak Hour for Entire Intersection Begins at 07:15																					
07:15	0	0	0	0	0	0	21	0	0	21	0	0	0	0	0	0	9	0	0	9	30
07:30	0	0	0	0	0	0	17	0	0	17	0	0	0	0	0	0	12	0	0	12	29
07:45	0	0	0	0	0	0	32	0	0	32	0	0	0	0	0	0	13	0	0	13	45
08:00	0	0	0	0	0	0	23	0	0	23	0	0	0	0	0	0	11	0	0	11	34
Total Volume	0	0	0	0	0	0	93	0	0	93	0	0	0	0	0	0	45	0	0	45	138
% App. Total	0	0	0	0	0	0	100	0	0	100	0	0	0	0	0	0	100	0	0	100	100
PHF	.000	.000	.000	.000	.000	.000	.727	.000	.000	.727	.000	.000	.000	.000	.000	.000	.865	.000	.000	.865	.767
Passenger Vehicles	0	0	0	0	0	0	78	0	0	78	0	0	0	0	0	0	40	0	0	40	118
% Passenger Vehicles																					
Heavy Vehicles	0	0	0	0	0	0	15	0	0	15	0	0	0	0	0	0	5	0	0	5	20
% Heavy Vehicles	0	0	0	0	0	0	16.1	0	0	16.1	0	0	0	0	0	0	11.1	0	0	11.1	14.5
Buses	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
% Buses	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0



# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201

*We can't say we're the Best, but you Can!*


File Name : US 21 @ Pine St

Site Code :

Start Date : 11/03/2022

Page No : 4

	Pine St Southbound					US 21 Westbound					Northbound					US 21 Eastbound					
Start Time	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Int. Total
Peak Hour Analysis From 16:00 to 17:45 - Peak 1 of 1																					
Peak Hour for Entire Intersection Begins at 17:00																					
17:00	0	0	0	0	0	0	14	0	0	14	0	0	0	0	0	0	32	0	0	32	46
17:15	0	0	0	0	0	0	21	0	0	21	0	0	0	0	0	0	27	0	0	27	48
17:30	0	0	0	0	0	0	13	0	0	13	0	0	0	0	0	0	37	0	0	37	50
17:45	0	0	0	0	0	0	32	0	0	32	0	0	0	0	0	0	25	0	0	25	57
Total Volume	0	0	0	0	0	0	80	0	0	80	0	0	0	0	0	0	121	0	0	121	201
% App. Total	0	0	0	0	0	0	100	0	0	100	0	0	0	0	0	0	100	0	0	100	100
PHF	.000	.000	.000	.000	.000	.000	.625	.000	.000	.625	.000	.000	.000	.000	.000	.000	.818	.000	.000	.818	.882
Passenger Vehicles	0	0	0	0	0	0	77	0	0	77	0	0	0	0	0	0	111	0	0	111	188
% Passenger Vehicles																					
Heavy Vehicles	0	0	0	0	0	0	3	0	0	3	0	0	0	0	0	0	10	0	0	10	13
% Heavy Vehicles	0	0	0	0	0	0	3.8	0	0	3.8	0	0	0	0	0	0	8.3	0	0	8.3	6.5
Buses	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
% Buses	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0





# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201

*We can't say we're the Best, but you Can!*

File Name : US 21 @ Salkehatchie Rd

Site Code :

Start Date : 11/03/2022

Page No : 1

Groups Printed- Passenger Vehicles - Heavy Vehicles - Buses

Start Time	US 21 Southbound				Salkehatchie Rd Westbound				US 21 Northbound				Salkehatchie Rd Eastbound				Int. Total
	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Left	Thru	Right	Peds	Left	Thru	Right	Peds	
07:00	5	9	2	0	0	4	2	0	1	6	0	0	1	8	0	0	38
07:15	7	11	1	0	2	0	3	0	1	2	0	0	0	5	5	0	37
07:30	7	6	2	7	1	4	3	0	0	5	3	0	1	5	2	0	46
07:45	9	22	3	3	1	4	1	0	0	5	6	2	2	9	1	0	68
Total	28	48	8	10	4	12	9	0	2	18	9	2	4	27	8	0	189
08:00	8	14	2	1	1	5	5	0	0	5	3	1	4	8	5	0	62
08:15	6	12	3	0	0	4	2	0	4	2	1	0	2	7	2	0	45
08:30	4	9	1	0	1	3	4	0	1	6	0	0	2	4	3	0	38
08:45	2	6	2	0	1	3	1	0	0	6	1	0	4	8	1	0	35
Total	20	41	8	1	3	15	12	0	5	19	5	1	12	27	11	0	180
16:00	4	12	4	1	2	8	4	0	4	15	0	0	7	8	3	0	72
16:15	3	5	5	0	2	12	7	0	3	12	4	0	3	6	1	0	63
16:30	2	12	6	0	4	5	4	0	3	14	0	0	4	4	2	0	60
16:45	2	11	7	2	0	3	12	0	3	12	0	0	4	2	2	0	60
Total	11	40	22	3	8	28	27	0	13	53	4	0	18	20	8	0	255
17:00	1	10	3	0	4	11	6	0	7	21	4	0	5	4	2	0	78
17:15	12	5	7	0	0	4	14	0	0	11	0	0	5	1	2	0	61
17:30	4	5	6	0	1	12	11	0	8	9	2	0	6	2	6	0	72
17:45	10	13	2	0	0	7	7	0	3	12	1	1	4	5	0	0	65
Total	27	33	18	0	5	34	38	0	18	53	7	1	20	12	10	0	276
Grand Total	86	162	56	14	20	89	86	0	38	143	25	4	54	86	37	0	900
Apprch %	27	50.9	17.6	4.4	10.3	45.6	44.1	0	18.1	68.1	11.9	1.9	30.5	48.6	20.9	0	
Total %	9.6	18	6.2	1.6	2.2	9.9	9.6	0	4.2	15.9	2.8	0.4	6	9.6	4.1	0	
Passenger Vehicles	83	127	56	14	19	87	82	0	37	121	25	4	54	85	37	0	831
% Passenger Vehicles	96.5	78.4	100	100	95	97.8	95.3	0	97.4	84.6	100	100	100	98.8	100	0	92.3
Heavy Vehicles	3	35	0	0	1	0	4	0	0	20	0	0	0	1	0	0	64
% Heavy Vehicles	3.5	21.6	0	0	5	0	4.7	0	0	14	0	0	0	1.2	0	0	7.1
Buses	0	0	0	0	0	2	0	0	1	2	0	0	0	0	0	0	5
% Buses	0	0	0	0	0	2.2	0	0	2.6	1.4	0	0	0	0	0	0	0.6

# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201


*We can't say we're the Best, but you Can!*

File Name : US 21 @ Salkehatchie Rd

Site Code :

Start Date : 11/03/2022

Page No : 2



# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201

*We can't say we're the Best, but you Can!*


File Name : US 21 @ Salkehatchie Rd

Site Code :

Start Date : 11/03/2022

Page No : 3

	US 21 Southbound					Salkehatchie Rd Westbound					US 21 Northbound					Salkehatchie Rd Eastbound					
Start Time	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Int. Total
Peak Hour Analysis From 07:00 to 08:45 - Peak 1 of 1																					
Peak Hour for Entire Intersection Begins at 07:30																					
07:30	7	6	2	7	22	1	4	3	0	8	0	5	3	0	8	1	5	2	0	8	46
07:45	9	22	3	3	37	1	4	1	0	6	0	5	6	2	13	2	9	1	0	12	68
08:00	8	14	2	1	25	1	5	5	0	11	0	5	3	1	9	4	8	5	0	17	62
08:15	6	12	3	0	21	0	4	2	0	6	4	2	1	0	7	2	7	2	0	11	45
Total Volume	30	54	10	11	105	3	17	11	0	31	4	17	13	3	37	9	29	10	0	48	221
% App. Total	28.6	51.4	9.5	10.5		9.7	54.8	35.5	0		10.8	45.9	35.1	8.1		18.8	60.4	20.8	0		
PHF	.833	.614	.833	.393	.709	.750	.850	.550	.000	.705	.250	.850	.542	.375	.712	.563	.806	.500	.000	.706	.813
Passenger Vehicles	28	41	10	11	90	3	17	11	0	31	4	11	13	3	31	9	28	10	0	47	199
% Passenger Vehicles																					
Heavy Vehicles	2	13	0	0	15	0	0	0	0	0	0	6	0	0	6	0	1	0	0	1	22
% Heavy Vehicles	6.7	24.1	0	0	14.3	0	0	0	0	0	0	35.3	0	0	16.2	0	3.4	0	0	2.1	10.0
Buses	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0
% Buses	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0	0





# SHORT COUNTS, LLC

735 Maryland St  
Columbia, SC 29201

*We can't say we're the Best, but you Can!*


File Name : US 21 @ Salkehatchie Rd

Site Code :

Start Date : 11/03/2022

Page No : 4

	US 21 Southbound					Salkehatchie Rd Westbound					US 21 Northbound					Salkehatchie Rd Eastbound					
Start Time	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Left	Thru	Right	Peds	App. Total	Int. Total
Peak Hour Analysis From 16:00 to 17:45 - Peak 1 of 1																					
Peak Hour for Entire Intersection Begins at 17:00																					
17:00	1	10	3	0	14	4	11	6	0	21	7	21	4	0	32	5	4	2	0	11	78
17:15	12	5	7	0	24	0	4	14	0	18	0	11	0	0	11	5	1	2	0	8	61
17:30	4	5	6	0	15	1	12	11	0	24	8	9	2	0	19	6	2	6	0	14	72
17:45	10	13	2	0	25	0	7	7	0	14	3	12	1	1	17	4	5	0	0	9	65
Total Volume	27	33	18	0	78	5	34	38	0	77	18	53	7	1	79	20	12	10	0	42	276
% App. Total	34.6	42.3	23.1	0		6.5	44.2	49.4	0		22.8	67.1	8.9	1.3		47.6	28.6	23.8	0		
PHF	.563	.635	.643	.000	.780	.313	.708	.679	.000	.802	.563	.631	.438	.250	.617	.833	.600	.417	.000	.750	.885
Passenger Vehicles	27	30	18	0	75	5	34	37	0	76	17	46	7	1	71	20	12	10	0	42	264
% Passenger Vehicles																					
Heavy Vehicles	0	3	0	0	3	0	0	1	0	1	0	7	0	0	7	0	0	0	0	0	11
% Heavy Vehicles	0	9.1	0	0	3.8	0	0	2.6	0	1.3	0	13.2	0	0	8.9	0	0	0	0	0	4.0
Buses	0	0	0	0	0	0	0	0	0	0	1	0	0	0	1	0	0	0	0	0	1
% Buses	0	0	0	0	0	0	0	0	0	0	5.6	0	0	0	1.3	0	0	0	0	0	0.4





## Appendix C TRAFFIC VOLUME DEVELOPMENT WORKSHEETS

# 1 - Salkehatchie Rd & US 21

Traffic Control: TWSC

Date Counted: 11/3/2022

## TOTAL PROJECT TRAFFIC

IN OUT IN OUT

AM 77 50 PM 50 62

AM PEAK HOUR 7:30 AM - 8:30 AM	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
<b>2022 Existing Traffic Volumes</b>	<b>9</b>	<b>29</b>	<b>10</b>	<b>3</b>	<b>17</b>	<b>11</b>	<b>4</b>	<b>17</b>	<b>13</b>	<b>30</b>	<b>54</b>	<b>10</b>
Years to Buildout	3	3	3	3	3	3	3	3	3	3	3	3
Yearly Growth Rate	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%
Background Traffic	0	1	0	0	1	0	0	1	0	1	2	0
Vested Traffic												
<b>2025 No Build Traffic Volumes</b>	<b>9</b>	<b>30</b>	<b>10</b>	<b>3</b>	<b>18</b>	<b>11</b>	<b>4</b>	<b>18</b>	<b>13</b>	<b>31</b>	<b>56</b>	<b>10</b>
Inbound Residential Project Traffic %				10%			5%	25%				
Outbound Residential Project Traffic %	5%									10%	25%	
Inbound Industrial Project Traffic %							50%					
Outbound Industrial Project Traffic %										50%		
2025 Project Traffic	0	0	2	0	0	1	1	35	0	4	15	0
<b>2025 Build Traffic Volumes</b>	<b>9</b>	<b>30</b>	<b>12</b>	<b>3</b>	<b>18</b>	<b>12</b>	<b>5</b>	<b>53</b>	<b>13</b>	<b>35</b>	<b>71</b>	<b>10</b>

PM PEAK HOUR 5:00 PM - 6:00 PM	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
<b>2022 Existing Traffic Volumes</b>	<b>20</b>	<b>12</b>	<b>10</b>	<b>5</b>	<b>34</b>	<b>38</b>	<b>18</b>	<b>53</b>	<b>7</b>	<b>27</b>	<b>33</b>	<b>18</b>
Years to Buildout	3	3	3	3	3	3	3	3	3	3	3	3
Yearly Growth Rate	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%
Background Traffic	1	0	0	0	1	1	1	2	0	1	1	1
Vested Traffic												
<b>2025 No Build Traffic Volumes</b>	<b>21</b>	<b>12</b>	<b>10</b>	<b>5</b>	<b>35</b>	<b>39</b>	<b>19</b>	<b>55</b>	<b>7</b>	<b>28</b>	<b>34</b>	<b>19</b>
Inbound Project Traffic %				10%			5%	25%				
Outbound Project Traffic %	5%									10%	25%	
Inbound Industrial Project Traffic %							50%					
Outbound Industrial Project Traffic %										50%		
2025 Project Traffic	0	0	1	0	0	5	2	14	0	3	24	0
<b>2025 Build Traffic Volumes</b>	<b>21</b>	<b>12</b>	<b>11</b>	<b>5</b>	<b>35</b>	<b>44</b>	<b>21</b>	<b>69</b>	<b>7</b>	<b>31</b>	<b>58</b>	<b>19</b>



## 2 - US 21 & Pine Street/Project Driveway #1

<div> <div>Traffic Control: TWSC</div> <div>Date Counted: 11/3/2022</div> </div> <div> <div>TOTAL PROJECT TRAFFIC</div> <div> <div>IN</div> <div>OUT</div> </div> <div> <div>IN</div> <div>OUT</div> </div> </div>												
AM PEAK HOUR 7:15 AM - 8:15 AM	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
2022 Existing Traffic Volumes	0	45	0	0	93	0	0	0	0	0	0	0
Years to Buildout	3	3	3	3	3	3	3	3	3	3	3	3
Yearly Growth Rate	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%
Background Traffic	0	1	0	0	3	0	0	0	0	0	0	0
Vested Traffic												
2025 No Build Traffic Volumes	0	46	0	0	96	0	0	0	0	0	0	0
Inbound Project Traffic %	35%			30%						30%		
Outbound Project Traffic %										35%		
Inbound Industrial Project Traffic %	25%	25%										
Outbound Industrial Project Traffic %				25%						25%	25%	
2025 Project Traffic	21	15	0	0	2	20	0	0	0	15	0	17
2025 Build Traffic Volumes	21	61	0	0	98	20	0	0	0	15	0	17

PM PEAK HOUR 5:00 PM - 6:00 PM	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
2022 Existing Traffic Volumes	0	121	0	0	80	0	0	0	0	0	0	0
Years to Buildout	3	3	3	3	3	3	3	3	3	3	3	3
Yearly Growth Rate	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%
Background Traffic	0	4	0	0	2	0	0	0	0	0	0	0
Vested Traffic												
2025 No Build Traffic Volumes	0	125	0	0	82	0	0	0	0	0	0	0
Inbound Project Traffic %	35%			30%						30%		
Outbound Project Traffic %										35%		
Inbound Industrial Project Traffic %	25%	25%										
Outbound Industrial Project Traffic %				25%						25%	25%	
2025 Project Traffic	17	1	0	0	9	15	0	0	0	17	0	18
2025 Build Traffic Volumes	17	126	0	0	91	15	0	0	0	17	0	18

### 3 - Salkehatchie Rd & Pine Street/Project Driveway #2

Traffic Control: TWSC

Date Counted: 11/3/2022

#### TOTAL PROJECT TRAFFIC

				AM			PM					
				IN			OUT					
				77			50			62		
AM PEAK HOUR 7:30 AM - 8:30 AM	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
2022 Existing Traffic Volumes	0	0	0	2	0	4	0	38	0	4	45	0
Years to Buildout	3	3	3	3	3	3	3	3	3	3	3	3
Yearly Growth Rate	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%
Background Traffic	0	0	0	0	0	0	0	1	0	0	1	0
Vested Traffic												
2025 No Build Traffic Volumes	0	0	0	2	0	4	0	39	0	4	46	0
Inbound Project Traffic %							5%			30%		
Outbound Project Traffic %				5%			30%					
Inbound Industrial Project Traffic %												
Outbound Industrial Project Traffic %												
2025 Project Traffic	0	0	0	2	0	12	0	0	1	4	0	0
2025 Build Traffic Volumes	0	0	0	4	0	16	0	39	1	8	46	0

PM PEAK HOUR 5:00 PM - 6:00 PM	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
2022 Existing Traffic Volumes	0	0	0	0	0	5	0	57	1	4	29	0
Years to Buildout	3	3	3	3	3	3	3	3	3	3	3	3
Yearly Growth Rate	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%
Background Traffic	0	0	0	0	0	0	0	2	0	0	1	0
Vested Traffic												
2025 No Build Traffic Volumes	0	0	0	0	0	5	0	59	1	4	30	0
Inbound Project Traffic %							5%			30%		
Outbound Project Traffic %				5%			30%					
Inbound Industrial Project Traffic %												
Outbound Industrial Project Traffic %												
2025 Project Traffic	0	0	0	1	0	8	0	0	2	14	0	0
2025 Build Traffic Volumes	0	0	0	1	0	13	0	59	3	18	30	0

#### 4 - US 21 & Project Driveway #3





TOTAL PROJECT TRAFFIC												
Traffic Control: TWSC				IN			OUT					
Date Counted: 11/3/2022				AM			PM					
				77			50			62		
AM PEAK HOUR 7:15 AM - 8:15 AM	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
2022 Existing Traffic Volumes	0	45	0	0	93	0	0	0	0	0	0	0
Years to Buildout	3	3	3	3	3	3	3	3	3	3	3	3
Yearly Growth Rate	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%
Background Traffic	0	1	0	0	3	0	0	0	0	0	0	0
Vested Traffic												
2025 No Build Traffic Volumes	0	46	0	0	96	0	0	0	0	0	0	0
Inbound Project Traffic %				30%								
Outbound Project Traffic %	30%											
Inbound Industrial Project Traffic %	25%			25%		25%						
Outbound Industrial Project Traffic %	25%									25%		25%
2025 Project Traffic	15	15	0	0	20	16	0	0	0	2	0	2
2025 Build Traffic Volumes	15	61	0	0	116	16	0	0	0	2	0	2




PM PEAK HOUR 5:00 PM - 6:00 PM	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
2022 Existing Traffic Volumes	0	121	0	0	80	0	0	0	0	0	0	0
Years to Buildout	3	3	3	3	3	3	3	3	3	3	3	3
Yearly Growth Rate	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%	1%
Background Traffic	0	4	0	0	2	0	0	0	0	0	0	0
Vested Traffic												
2025 No Build Traffic Volumes	0	125	0	0	82	0	0	0	0	0	0	0
Inbound Project Traffic %				30%								
Outbound Project Traffic %	30%											
Inbound Industrial Project Traffic %	25%			25%		25%						
Outbound Industrial Project Traffic %	25%									25%		25%
2025 Project Traffic	1	17	0	0	15	1	0	0	0	9	0	9
2025 Build Traffic Volumes	1	142	0	0	97	1	0	0	0	9	0	9





## Appendix D ANALYSIS WORKSHEETS: 2022 EXISTING CONDITIONS

Intersection												
Int Delay, s/veh	5.1											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	9	29	10	3	17	11	4	17	13	30	54	10
Future Vol, veh/h	9	29	10	3	17	11	4	17	13	30	54	10
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	89	89	89	89	89	89	89	89	89	89	89	89
Heavy Vehicles, %	14	14	14	16	16	16	2	2	2	2	2	2
Mvmt Flow	10	33	11	3	19	12	4	19	15	34	61	11
Major/Minor	Minor2		Minor1			Major1			Major2			
Conflicting Flow All	185	177	67	192	175	27	72	0	0	34	0	0
Stage 1	135	135	-	35	35	-	-	-	-	-	-	-
Stage 2	50	42	-	157	140	-	-	-	-	-	-	-
Critical Hdwy	7.24	6.64	6.34	7.26	6.66	6.36	4.12	-	-	4.12	-	-
Critical Hdwy Stg 1	6.24	5.64	-	6.26	5.66	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.24	5.64	-	6.26	5.66	-	-	-	-	-	-	-
Follow-up Hdwy	3.626	4.126	3.426	3.644	4.144	3.444	2.218	-	-	2.218	-	-
Pot Cap-1 Maneuver	750	695	964	738	694	1010	1528	-	-	1578	-	-
Stage 1	840	762	-	946	839	-	-	-	-	-	-	-
Stage 2	934	837	-	813	755	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	711	678	964	689	677	1010	1528	-	-	1578	-	-
Mov Cap-2 Maneuver	711	678	-	689	677	-	-	-	-	-	-	-
Stage 1	837	745	-	943	836	-	-	-	-	-	-	-
Stage 2	899	834	-	751	738	-	-	-	-	-	-	-
Approach	EB		WB			NB			SB			
HCM Control Delay, s	10.3		9.9			0.9			2.3			
HCM LOS	B		A									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR					
Capacity (veh/h)	1528	-	-	729	768	1578	-	-				
HCM Lane V/C Ratio	0.003	-	-	0.074	0.045	0.021	-	-				
HCM Control Delay (s)	7.4	0	-	10.3	9.9	7.3	0	-				
HCM Lane LOS	A	A	-	B	A	A	A	-				
HCM 95th %tile Q(veh)	0	-	-	0.2	0.1	0.1	-	-				





Intersection						
Int Delay, s/veh	0.9					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	2	4	38	0	4	45
Future Vol, veh/h	2	4	38	0	4	45
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	89	89	89	89	89	89
Heavy Vehicles, %	2	2	5	5	4	4
Mvmt Flow	2	4	43	0	4	51




Major/Minor	Minor1	Major1	Major2		
Conflicting Flow All	102	43	0	0	43
Stage 1	43	-	-	-	-
Stage 2	59	-	-	-	-
Critical Hdwy	6.42	6.22	-	-	4.14
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	3.318	-	-	2.236
Pot Cap-1 Maneuver	896	1027	-	-	1553
Stage 1	979	-	-	-	-
Stage 2	964	-	-	-	-
Platoon blocked, %			-	-	-
Mov Cap-1 Maneuver	893	1027	-	-	1553
Mov Cap-2 Maneuver	893	-	-	-	-
Stage 1	979	-	-	-	-
Stage 2	961	-	-	-	-

Approach	WB	NB	SB
HCM Control Delay, s	8.7	0	0.6
HCM LOS	A		

Minor Lane/Major Mvmt	NBT	NBRWBLn1	SBL	SBT
Capacity (veh/h)	-	-	978	1553
HCM Lane V/C Ratio	-	-	0.007	0.003
HCM Control Delay (s)	-	-	8.7	7.3
HCM Lane LOS	-	-	A	A
HCM 95th %tile Q(veh)	-	-	0	0



Intersection												
Int Delay, s/veh	5.8											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	20	12	10	5	34	38	18	53	7	27	33	18
Future Vol, veh/h	20	12	10	5	34	38	18	53	7	27	33	18
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	83	83	83	83	83	83	83	83	83	83	83	83
Heavy Vehicles, %	4	4	4	9	9	9	2	2	2	2	2	2
Mvmt Flow	24	14	12	6	41	46	22	64	8	33	40	22
Major/Minor	Minor2		Minor1			Major1			Major2			
Conflicting Flow All	273	233	51	242	240	68	62	0	0	72	0	0
Stage 1	117	117	-	112	112	-	-	-	-	-	-	-
Stage 2	156	116	-	130	128	-	-	-	-	-	-	-
Critical Hdwy	7.14	6.54	6.24	7.19	6.59	6.29	4.12	-	-	4.12	-	-
Critical Hdwy Stg 1	6.14	5.54	-	6.19	5.59	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.14	5.54	-	6.19	5.59	-	-	-	-	-	-	-
Follow-up Hdwy	3.536	4.036	3.336	3.581	4.081	3.381	2.218	-	-	2.218	-	-
Pot Cap-1 Maneuver	675	664	1011	698	649	976	1541	-	-	1528	-	-
Stage 1	883	795	-	876	789	-	-	-	-	-	-	-
Stage 2	842	796	-	857	777	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	594	639	1011	659	625	976	1541	-	-	1528	-	-
Mov Cap-2 Maneuver	594	639	-	659	625	-	-	-	-	-	-	-
Stage 1	870	778	-	863	777	-	-	-	-	-	-	-
Stage 2	749	784	-	813	760	-	-	-	-	-	-	-
Approach	EB		WB			NB			SB			
HCM Control Delay, s	10.8		10.4			1.7			2.6			
HCM LOS	B		B									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR					
Capacity (veh/h)	1541	-	-	674	763	1528	-	-				
HCM Lane V/C Ratio	0.014	-	-	0.075	0.122	0.021	-	-				
HCM Control Delay (s)	7.4	0	-	10.8	10.4	7.4	0	-				
HCM Lane LOS	A	A	-	B	B	A	A	-				
HCM 95th %tile Q(veh)	0	-	-	0.2	0.4	0.1	-	-				

Intersection						
Int Delay, s/veh	0.8					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	0	5	57	1	4	29
Future Vol, veh/h	0	5	57	1	4	29
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	0	6	63	1	4	32

Major/Minor	Minor1	Major1	Major2
Conflicting Flow All	104	64	0
Stage 1	64	-	-
Stage 2	40	-	-
Critical Hdwy	6.42	6.22	-
Critical Hdwy Stg 1	5.42	-	-
Critical Hdwy Stg 2	5.42	-	-
Follow-up Hdwy	3.518	3.318	-
Pot Cap-1 Maneuver	894	1000	-
Stage 1	959	-	-
Stage 2	982	-	-
Platoon blocked, %		-	-
Mov Cap-1 Maneuver	891	1000	-
Mov Cap-2 Maneuver	891	-	-
Stage 1	959	-	-
Stage 2	979	-	-





Approach	WB	NB	SB
HCM Control Delay, s	8.6	0	0.9
HCM LOS	A		

Minor Lane/Major Mvmt	NBT	NBRWBLn1	SBL	SBT
Capacity (veh/h)	-	-	1000	1538
HCM Lane V/C Ratio	-	-	0.006	0.003
HCM Control Delay (s)	-	-	8.6	7.3
HCM Lane LOS	-	-	A	A
HCM 95th %tile Q(veh)	-	-	0	0



## Appendix E ANALYSIS WORKSHEETS: 2025 NO BUILD CONDITIONS



Intersection												
Int Delay, s/veh	5											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	9	30	10	3	18	11	4	18	13	31	56	10
Future Vol, veh/h	9	30	10	3	18	11	4	18	13	31	56	10
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	14	14	14	16	16	16	2	2	2	2	2	2
Mvmt Flow	10	33	11	3	20	12	4	20	14	34	62	11




Major/Minor	Minor2		Minor1		Major1		Major2	
Conflicting Flow All	187	178	68	193	176	27	73	0
Stage 1	136	136	-	35	35	-	-	-
Stage 2	51	42	-	158	141	-	-	-
Critical Hdwy	7.24	6.64	6.34	7.26	6.66	6.36	4.12	-
Critical Hdwy Stg 1	6.24	5.64	-	6.26	5.66	-	-	-
Critical Hdwy Stg 2	6.24	5.64	-	6.26	5.66	-	-	-
Follow-up Hdwy	3.626	4.126	3.426	3.644	4.144	3.444	2.218	-
Pot Cap-1 Maneuver	748	695	963	737	693	1010	1527	-
Stage 1	839	761	-	946	839	-	-	-
Stage 2	932	837	-	812	754	-	-	-
Platoon blocked, %								-
Mov Cap-1 Maneuver	708	678	963	688	676	1010	1527	-
Mov Cap-2 Maneuver	708	678	-	688	676	-	-	-
Stage 1	836	744	-	943	836	-	-	-
Stage 2	896	834	-	750	737	-	-	-





  

Approach	EB	WB	NB	SB
HCM Control Delay, s	10.3	9.9	0.8	2.3
HCM LOS	B	A		




  

Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR
Capacity (veh/h)	1527	-	-	728	764	1578	-
HCM Lane V/C Ratio	0.003	-	-	0.075	0.047	0.022	-
HCM Control Delay (s)	7.4	0	-	10.3	9.9	7.3	0
HCM Lane LOS	A	A	-	B	A	A	A
HCM 95th %tile Q(veh)	0	-	-	0.2	0.1	0.1	-

Intersection						
Int Delay, s/veh	0.9					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	2	4	39	0	4	46
Future Vol, veh/h	2	4	39	0	4	46
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	5	5	4	4
Mvmt Flow	2	4	43	0	4	51
Major/Minor	Minor1	Major1	Major2			
Conflicting Flow All	102	43	0	0	43	0
Stage 1	43	-	-	-	-	-
Stage 2	59	-	-	-	-	-
Critical Hdwy	6.42	6.22	-	-	4.14	-
Critical Hdwy Stg 1	5.42	-	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-	-
Follow-up Hdwy	3.518	3.318	-	-	2.236	-
Pot Cap-1 Maneuver	896	1027	-	-	1553	-
Stage 1	979	-	-	-	-	-
Stage 2	964	-	-	-	-	-
Platoon blocked, %			-	-		-
Mov Cap-1 Maneuver	893	1027	-	-	1553	-
Mov Cap-2 Maneuver	893	-	-	-	-	-
Stage 1	979	-	-	-	-	-
Stage 2	961	-	-	-	-	-
Approach	WB	NB		SB		
HCM Control Delay, s	8.7	0		0.6		
HCM LOS	A					
Minor Lane/Major Mvmt	NBT	NBRWBLn1	SBL	SBT		
Capacity (veh/h)	-	-	978	1553	-	
HCM Lane V/C Ratio	-	-	0.007	0.003	-	
HCM Control Delay (s)	-	-	8.7	7.3	0	
HCM Lane LOS	-	-	A	A	A	
HCM 95th %tile Q(veh)	-	-	0	0	-	





Intersection												
Int Delay, s/veh	5.7											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	21	12	10	5	35	39	19	55	7	28	34	19
Future Vol, veh/h	21	12	10	5	35	39	19	55	7	28	34	19
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	4	4	4	9	9	9	2	2	2	2	2	2
Mvmt Flow	23	13	11	6	39	43	21	61	8	31	38	21
Major/Minor	Minor2		Minor1			Major1			Major2			
Conflicting Flow All	259	222	49	230	228	65	59	0	0	69	0	0
Stage 1	111	111	-	107	107	-	-	-	-	-	-	-
Stage 2	148	111	-	123	121	-	-	-	-	-	-	-
Critical Hdwy	7.14	6.54	6.24	7.19	6.59	6.29	4.12	-	-	4.12	-	-
Critical Hdwy Stg 1	6.14	5.54	-	6.19	5.59	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.14	5.54	-	6.19	5.59	-	-	-	-	-	-	-
Follow-up Hdwy	3.536	4.036	3.336	3.581	4.081	3.381	2.218	-	-	2.218	-	-
Pot Cap-1 Maneuver	690	673	1014	710	659	980	1545	-	-	1532	-	-
Stage 1	889	800	-	882	793	-	-	-	-	-	-	-
Stage 2	850	800	-	864	782	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	612	649	1014	673	636	980	1545	-	-	1532	-	-
Mov Cap-2 Maneuver	612	649	-	673	636	-	-	-	-	-	-	-
Stage 1	877	783	-	870	782	-	-	-	-	-	-	-
Stage 2	761	789	-	822	766	-	-	-	-	-	-	-
Approach	EB		WB			NB			SB			
HCM Control Delay, s	10.6		10.3			1.7			2.6			
HCM LOS	B		B									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR					
Capacity (veh/h)	1545	-	-	686	773	1532	-	-				
HCM Lane V/C Ratio	0.014	-	-	0.07	0.114	0.02	-	-				
HCM Control Delay (s)	7.4	0	-	10.6	10.3	7.4	0	-				
HCM Lane LOS	A	A	-	B	B	A	A	-				
HCM 95th %tile Q(veh)	0	-	-	0.2	0.4	0.1	-	-				






Intersection						
Int Delay, s/veh	0.7					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	0	5	59	1	4	30
Future Vol, veh/h	0	5	59	1	4	30
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	0	6	66	1	4	33
Major/Minor	Minor1	Major1		Major2		
Conflicting Flow All	108	67	0	0	67	0
Stage 1	67	-	-	-	-	-
Stage 2	41	-	-	-	-	-
Critical Hdwy	6.42	6.22	-	-	4.12	-
Critical Hdwy Stg 1	5.42	-	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-	-
Follow-up Hdwy	3.518	3.318	-	-	2.218	-
Pot Cap-1 Maneuver	889	997	-	-	1535	-
Stage 1	956	-	-	-	-	-
Stage 2	981	-	-	-	-	-
Platoon blocked, %			-	-		-
Mov Cap-1 Maneuver	886	997	-	-	1535	-
Mov Cap-2 Maneuver	886	-	-	-	-	-
Stage 1	956	-	-	-	-	-
Stage 2	978	-	-	-	-	-
Approach	WB	NB		SB		
HCM Control Delay, s	8.6	0		0.9		
HCM LOS	A					
Minor Lane/Major Mvmt	NBT	NBRWBLn1		SBL	SBT	
Capacity (veh/h)	-	- 997		1535	-	
HCM Lane V/C Ratio	-	- 0.006		0.003	-	
HCM Control Delay (s)	-	- 8.6		7.4	0	
HCM Lane LOS	-	- A		A	A	
HCM 95th %tile Q(veh)	-	- 0		0	-	






## Appendix F ANALYSIS WORKSHEETS: 2025 BUILD CONDITIONS

Intersection												
Int Delay, s/veh	4.4											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	9	30	12	3	18	12	5	53	13	35	71	10
Future Vol, veh/h	9	30	12	3	18	12	5	53	13	35	71	10
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	14	14	14	16	16	16	2	2	2	2	2	2
Mvmt Flow	10	33	13	3	20	13	6	59	14	39	79	11
Major/Minor	Minor2		Minor1		Major1		Major2					
Conflicting Flow All	258	248	85	264	246	66	90	0	0	73	0	0
Stage 1	163	163	-	78	78	-	-	-	-	-	-	-
Stage 2	95	85	-	186	168	-	-	-	-	-	-	-
Critical Hdwy	7.24	6.64	6.34	7.26	6.66	6.36	4.12	-	-	4.12	-	-
Critical Hdwy Stg 1	6.24	5.64	-	6.26	5.66	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.24	5.64	-	6.26	5.66	-	-	-	-	-	-	-
Follow-up Hdwy	3.626	4.126	3.426	3.644	4.144	3.444	2.218	-	-	2.218	-	-
Pot Cap-1 Maneuver	671	634	942	661	633	960	1505	-	-	1527	-	-
Stage 1	812	741	-	897	803	-	-	-	-	-	-	-
Stage 2	883	802	-	784	734	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	630	614	942	610	613	960	1505	-	-	1527	-	-
Mov Cap-2 Maneuver	630	614	-	610	613	-	-	-	-	-	-	-
Stage 1	809	721	-	893	800	-	-	-	-	-	-	-
Stage 2	846	799	-	717	714	-	-	-	-	-	-	-
Approach	EB		WB		NB		SB					
HCM Control Delay, s	10.9		10.4		0.5		2.2					
HCM LOS	B		B									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1	WBLn1	SBL	SBT	SBR				
Capacity (veh/h)	1505	-	-	672	705	1527	-	-				
HCM Lane V/C Ratio	0.004	-	-	0.084	0.052	0.025	-	-				
HCM Control Delay (s)	7.4	0	-	10.9	10.4	7.4	0	-				
HCM Lane LOS	A	A	-	B	B	A	A	-				
HCM 95th %tile Q(veh)	0	-	-	0.3	0.2	0.1	-	-				






Intersection						
Int Delay, s/veh	2					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	21	61	98	20	15	17
Future Vol, veh/h	21	61	98	20	15	17
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	11	11	16	16	2	2
Mvmt Flow	23	68	109	22	17	19
Major/Minor	Major1	Major2		Minor2		
Conflicting Flow All	131	0	-	0	234	120
Stage 1	-	-	-	-	120	-
Stage 2	-	-	-	-	114	-
Critical Hdwy	4.21	-	-	-	6.42	6.22
Critical Hdwy Stg 1	-	-	-	-	5.42	-
Critical Hdwy Stg 2	-	-	-	-	5.42	-
Follow-up Hdwy	2.299	-	-	-	3.518	3.318
Pot Cap-1 Maneuver	1400	-	-	-	754	931
Stage 1	-	-	-	-	905	-
Stage 2	-	-	-	-	911	-
Platoon blocked, %		-	-	-		
Mov Cap-1 Maneuver	1400	-	-	-	741	931
Mov Cap-2 Maneuver	-	-	-	-	741	-
Stage 1	-	-	-	-	890	-
Stage 2	-	-	-	-	911	-
Approach	EB	WB		SB		
HCM Control Delay, s	2	0		9.5		
HCM LOS	A					
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	
Capacity (veh/h)	1400	-	-	-	831	
HCM Lane V/C Ratio	0.017	-	-	-	0.043	
HCM Control Delay (s)	7.6	0	-	-	9.5	
HCM Lane LOS	A	A	-	-	A	
HCM 95th %tile Q(veh)	0.1	-	-	-	0.1	

Intersection						
Int Delay, s/veh	2					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	4	16	39	1	8	46
Future Vol, veh/h	4	16	39	1	8	46
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	5	5	4	4
Mvmt Flow	4	18	43	1	9	51





Major/Minor	Minor1	Major1	Major2		
Conflicting Flow All	113	44	0	0	44
Stage 1	44	-	-	-	-
Stage 2	69	-	-	-	-
Critical Hdwy	6.42	6.22	-	-	4.14
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	3.318	-	-	2.236
Pot Cap-1 Maneuver	884	1026	-	-	1552
Stage 1	978	-	-	-	-
Stage 2	954	-	-	-	-
Platoon blocked, %			-	-	-
Mov Cap-1 Maneuver	879	1026	-	-	1552
Mov Cap-2 Maneuver	879	-	-	-	-
Stage 1	978	-	-	-	-
Stage 2	948	-	-	-	-

Approach	WB	NB	SB
HCM Control Delay, s	8.7	0	1.1
HCM LOS	A		

Minor Lane/Major Mvmt	NBT	NBRWBLn1	SBL	SBT
Capacity (veh/h)	-	-	993	1552
HCM Lane V/C Ratio	-	-	0.022	0.006
HCM Control Delay (s)	-	-	8.7	7.3
HCM Lane LOS	-	-	A	A
HCM 95th %tile Q(veh)	-	-	0.1	0




Intersection						
Int Delay, s/veh	0.7					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	15	61	116	16	2	2
Future Vol, veh/h	15	61	116	16	2	2
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	11	11	16	16	16	11
Mvmt Flow	17	68	129	18	2	2
Major/Minor	Major1	Major2		Minor2		
Conflicting Flow All	147	0	-	0	240	138
Stage 1	-	-	-	-	138	-
Stage 2	-	-	-	-	102	-
Critical Hdwy	4.21	-	-	-	6.56	6.31
Critical Hdwy Stg 1	-	-	-	-	5.56	-
Critical Hdwy Stg 2	-	-	-	-	5.56	-
Follow-up Hdwy	2.299	-	-	-	3.644	3.399
Pot Cap-1 Maneuver	1381	-	-	-	719	887
Stage 1	-	-	-	-	855	-
Stage 2	-	-	-	-	888	-
Platoon blocked, %		-	-	-		
Mov Cap-1 Maneuver	1381	-	-	-	710	887
Mov Cap-2 Maneuver	-	-	-	-	710	-
Stage 1	-	-	-	-	844	-
Stage 2	-	-	-	-	888	-
Approach	EB	WB		SB		
HCM Control Delay, s	1.5	0		9.6		
HCM LOS	A					
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	
Capacity (veh/h)	1381	-	-	-	789	
HCM Lane V/C Ratio	0.012	-	-	-	0.006	
HCM Control Delay (s)	7.6	0	-	-	9.6	
HCM Lane LOS	A	A	-	-	A	
HCM 95th %tile Q(veh)	0	-	-	-	0	



Intersection												
Int Delay, s/veh	5.3											
Movement	EBL	EBT	EBR	WBL	WBT	WBR	NBL	NBT	NBR	SBL	SBT	SBR
Lane Configurations												
Traffic Vol, veh/h	21	12	11	5	35	44	21	69	7	31	58	19
Future Vol, veh/h	21	12	11	5	35	44	21	69	7	31	58	19
Conflicting Peds, #/hr	0	0	0	0	0	0	0	0	0	0	0	0
Sign Control	Stop	Stop	Stop	Stop	Stop	Stop	Free	Free	Free	Free	Free	Free
RT Channelized	-	-	None	-	-	None	-	-	None	-	-	None
Storage Length	-	-	-	-	-	-	-	-	-	-	-	-
Veh in Median Storage, #	-	0	-	-	0	-	-	0	-	-	0	-
Grade, %	-	0	-	-	0	-	-	0	-	-	0	-
Peak Hour Factor	90	90	90	90	90	90	90	90	90	90	90	90
Heavy Vehicles, %	4	4	4	9	9	9	2	2	2	2	2	2
Mvmt Flow	23	13	12	6	39	49	23	77	8	34	64	21
Major/Minor	Minor2		Minor1		Major1		Major2					
Conflicting Flow All	314	274	75	282	280	81	85	0	0	85	0	0
Stage 1	143	143	-	127	127	-	-	-	-	-	-	-
Stage 2	171	131	-	155	153	-	-	-	-	-	-	-
Critical Hdwy	7.14	6.54	6.24	7.19	6.59	6.29	4.12	-	-	4.12	-	-
Critical Hdwy Stg 1	6.14	5.54	-	6.19	5.59	-	-	-	-	-	-	-
Critical Hdwy Stg 2	6.14	5.54	-	6.19	5.59	-	-	-	-	-	-	-
Follow-up Hdwy	3.536	4.036	3.336	3.581	4.081	3.381	2.218	-	-	2.218	-	-
Pot Cap-1 Maneuver	635	630	981	656	617	960	1512	-	-	1512	-	-
Stage 1	855	775	-	860	778	-	-	-	-	-	-	-
Stage 2	826	784	-	831	758	-	-	-	-	-	-	-
Platoon blocked, %								-	-		-	-
Mov Cap-1 Maneuver	555	605	981	618	592	960	1512	-	-	1512	-	-
Mov Cap-2 Maneuver	555	605	-	618	592	-	-	-	-	-	-	-
Stage 1	841	756	-	846	766	-	-	-	-	-	-	-
Stage 2	732	771	-	787	740	-	-	-	-	-	-	-
Approach	EB		WB		NB		SB					
HCM Control Delay, s	11.1		10.5		1.6		2.1					
HCM LOS	B		B									
Minor Lane/Major Mvmt	NBL	NBT	NBR	EBLn1WBLn1	SBL	SBT	SBR					
Capacity (veh/h)	1512	-	-	639	743	1512	-	-				
HCM Lane V/C Ratio	0.015	-	-	0.077	0.126	0.023	-	-				
HCM Control Delay (s)	7.4	0	-	11.1	10.5	7.4	0	-				
HCM Lane LOS	A	A	-	B	B	A	A	-				
HCM 95th %tile Q(veh)	0	-	-	0.2	0.4	0.1	-	-				

Intersection




Int Delay, s/veh 2.4

Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	17	125	82	17	26	27
Future Vol, veh/h	17	125	82	17	26	27
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	8	8	4	4	80	80
Mvmt Flow	19	139	91	19	29	30

Major/Minor	Major1	Major2	Minor2
Conflicting Flow All	110	0	0 278 101
Stage 1	-	-	- 101 -
Stage 2	-	-	- 177 -
Critical Hdwy	4.18	-	- 7.2 7
Critical Hdwy Stg 1	-	-	- 6.2 -
Critical Hdwy Stg 2	-	-	- 6.2 -
Follow-up Hdwy	2.272	-	- 4.22 4.02
Pot Cap-1 Maneuver	1443	-	- 573 778
Stage 1	-	-	- 760 -
Stage 2	-	-	- 696 -
Platoon blocked, %		-	-
Mov Cap-1 Maneuver	1443	-	- 565 778
Mov Cap-2 Maneuver	-	-	- 565 -
Stage 1	-	-	- 749 -
Stage 2	-	-	- 696 -

Approach	EB	WB	SB
HCM Control Delay, s	0.9	0	11
HCM LOS			B

Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1
Capacity (veh/h)	1443	-	-	-	657
HCM Lane V/C Ratio	0.013	-	-	-	0.09
HCM Control Delay (s)	7.5	0	-	-	11
HCM Lane LOS	A	A	-	-	B
HCM 95th %tile Q(veh)	0	-	-	-	0.3




Intersection						
Int Delay, s/veh	2.1					
Movement	WBL	WBR	NBT	NBR	SBL	SBT
Lane Configurations						
Traffic Vol, veh/h	1	13	59	3	18	30
Future Vol, veh/h	1	13	59	3	18	30
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Stop	Stop	Free	Free	Free	Free
RT Channelized	-	None	-	None	-	None
Storage Length	0	-	-	-	-	-
Veh in Median Storage, #	0	-	0	-	-	0
Grade, %	0	-	0	-	-	0
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	2	2	2	2	2	2
Mvmt Flow	1	14	66	3	20	33

Major/Minor	Minor1	Major1	Major2		
Conflicting Flow All	141	68	0	0	69
Stage 1	68	-	-	-	-
Stage 2	73	-	-	-	-
Critical Hdwy	6.42	6.22	-	-	4.12
Critical Hdwy Stg 1	5.42	-	-	-	-
Critical Hdwy Stg 2	5.42	-	-	-	-
Follow-up Hdwy	3.518	3.318	-	-	2.218
Pot Cap-1 Maneuver	852	995	-	-	1532
Stage 1	955	-	-	-	-
Stage 2	950	-	-	-	-
Platoon blocked, %			-	-	-
Mov Cap-1 Maneuver	841	995	-	-	1532
Mov Cap-2 Maneuver	841	-	-	-	-
Stage 1	955	-	-	-	-
Stage 2	938	-	-	-	-

Approach	WB	NB	SB
HCM Control Delay, s	8.7	0	2.8
HCM LOS	A		

Minor Lane/Major Mvmt	NBT	NBRWBLn1	SBL	SBT
Capacity (veh/h)	-	-	982	1532
HCM Lane V/C Ratio	-	-	0.016	0.013
HCM Control Delay (s)	-	-	8.7	7.4
HCM Lane LOS	-	-	A	A
HCM 95th %tile Q(veh)	-	-	0	0



Intersection						
Int Delay, s/veh	0.7					
Movement	EBL	EBT	WBT	WBR	SBL	SBR
Lane Configurations						
Traffic Vol, veh/h	1	142	97	1	9	9
Future Vol, veh/h	1	142	97	1	9	9
Conflicting Peds, #/hr	0	0	0	0	0	0
Sign Control	Free	Free	Free	Free	Stop	Stop
RT Channelized	-	None	-	None	-	None
Storage Length	-	-	-	-	0	-
Veh in Median Storage, #	-	0	0	-	0	-
Grade, %	-	0	0	-	0	-
Peak Hour Factor	90	90	90	90	90	90
Heavy Vehicles, %	8	8	4	4	4	8
Mvmt Flow	1	158	108	1	10	10
Major/Minor	Major1	Major2		Minor2		
Conflicting Flow All	109	0	-	0	269	109
Stage 1	-	-	-	-	109	-
Stage 2	-	-	-	-	160	-
Critical Hdwy	4.18	-	-	-	6.44	6.28
Critical Hdwy Stg 1	-	-	-	-	5.44	-
Critical Hdwy Stg 2	-	-	-	-	5.44	-
Follow-up Hdwy	2.272	-	-	-	3.536	3.372
Pot Cap-1 Maneuver	1445	-	-	-	716	929
Stage 1	-	-	-	-	911	-
Stage 2	-	-	-	-	864	-
Platoon blocked, %		-	-	-		
Mov Cap-1 Maneuver	1445	-	-	-	715	929
Mov Cap-2 Maneuver	-	-	-	-	715	-
Stage 1	-	-	-	-	910	-
Stage 2	-	-	-	-	864	-
Approach	EB	WB		SB		
HCM Control Delay, s	0.1	0		9.6		
HCM LOS				A		
Minor Lane/Major Mvmt	EBL	EBT	WBT	WBR	SBLn1	
Capacity (veh/h)	1445	-	-	-	808	
HCM Lane V/C Ratio	0.001	-	-	-	0.025	
HCM Control Delay (s)	7.5	0	-	-	9.6	
HCM Lane LOS	A	A	-	-	A	
HCM 95th %tile Q(veh)	0	-	-	-	0.1	



## Appendix G TURN LANE ANALYSIS WORKSHEETS

### Study Area Information

County:	Hampton County	Date:	11/10/2022
SCDOT Engineering District:	District 7	Analyst:	PC
Analysis Year:	2025	Agency:	Stantec Consulting Services Inc.
Intersection:	US 21 & Salkhatchie Road		
Left Turn Movement:	Northbound Left-Turn Lane		
Right Turn Movement:	Southbound Right-Turn Lane		
Posted Speed Limit:	35	Median:	Undivided
# of Approach Lanes:	1	Urban or Rural?	Rural

### Volume Information & Calculations

#### Left Turn Lane Volume Calculations

Movement		Volume (vph)	
		AM	PM
Advancing	Left	5	21
	Through	53	69
	Right	13	7
Opposing	Left	35	31
	Through	71	58
	Right	10	19

	AM	PM
Advancing Volume:	71	97
Opposing Volume:	116	108
Left Turn Volume:	5	21

% Left Turns in Advancing Volume:	7.0%	21.6%
-----------------------------------	------	-------

#### Right Turn Lane Volume Calculations

Movement		Volume (vph)	
		AM	PM
Advancing	Left	35	31
	Through	71	58
	Right	10	19

Adjustment to Right Turn Volume <sup>1</sup>	Include?	No
--	----------	----

	AM	PM
Advancing Volume:	116	108
Right Turn Volume:	10	19

### Turn Lane Warrant Met?

Left Turn Lane Warrant		Right Turn Lane Warrant	
Applicable Warrant Chart:	Fig 9.5-G	Applicable Warrant Chart:	Fig 9.5-A
Warrant Satisfied:	No	Warrant Satisfied:	No

### Recommended Turn Lane Length

Left Turn Lane		Right Turn Lane	
Turning Truck%:	2%	Turning Truck%:	2%
Storage Length (ft):	N/A	Storage Length:	N/A
Taper Length (ft):	N/A	Taper Length:	N/A
Total Left Turn Lane (ft):	N/A	Total Left Turn Lane:	N/A


Consider providing dual-turn lanes if the turning volumes are greater than 300 vehicles per hour. A traffic analysis will be required if the turning volumes are greater than 300 vehicles per hour.

The traffic designer should review the design to determine if longer turn lane lengths are required.




# GUIDELINES FOR RIGHT-TURN LANES AT UNSIGNALIZED INTERSECTIONS ON TWO-LANE HIGHWAYS

Figure 9.5-A, (SCDOT ROADWAY DESIGN MANUAL 2021)



# VOLUME GUIDELINES FOR LEFT-TURN LANES AT UNSIGNALIZED INTERSECTIONS ON TWO-LANE HIGHWAYS (40 mph)

Figure 9.5-G, (SCDOT ROADWAY DESIGN MANUAL 2021)



### Study Area Information

County:	Hampton County	Date:	11/10/2022
SCDOT Engineering District:	District 7	Analyst:	PC
Analysis Year:	2025	Agency:	Stantec Consulting Services Inc.
Intersection: US 21 & Pine St (Project Driveway #1)			
Left Turn Movement: Eastbound Left-Turn Lane			
Right Turn Movement: Westbound Right-Turn Lane			
Posted Speed Limit:	45 mph	Median:	Undivided
# of Approach Lanes:	1	Urban or Rural?	Rural

### Volume Information & Calculations

#### Left Turn Lane Volume Calculations

Movement		Volume (vph)	
		AM	PM
Advancing	Left	21	17
	Through	61	126
	Right	0	0
Opposing	Left	0	0
	Through	98	91
	Right	20	15

	AM	PM
Advancing Volume:	82	143
Opposing Volume:	118	106
Left Turn Volume:	21	17

% Left Turns in Advancing Volume: 25.6% 11.9%

#### Right Turn Lane Volume Calculations

Movement		Volume (vph)	
		AM	PM
Advancing	Left	0	0
	Through	98	91
	Right	20	15

Adjustment to Right Turn Volume<sup>1</sup> Include? No

	AM	PM
Advancing Volume:	118	106
Right Turn Volume:	20	15

### Turn Lane Warrant Met?

<b>Left Turn Lane Warrant</b> Applicable Warrant Chart: <b>Fig 9.5-F</b> Warrant Satisfied: <b>No</b>	<b>Right Turn Lane Warrant</b> Applicable Warrant Chart: <b>Fig 9.5-A</b> Warrant Satisfied: <b>No</b>
---	--

### Recommended Turn Lane Length

Turning Truck%: 20%

Turning Truck%: 20%

<b>Left Turn Lane</b> Storage Length (ft): N/A ft Taper Length (ft): N/A ft Total Left Turn Lane (ft): N/A ft	<b>Right Turn Lane</b> Storage Length: N/A ft Taper Length: N/A ft Total Left Turn Lane: N/A ft
--	--


Consider providing dual-turn lanes if the turning volumes are greater than 300 vehicles per hour. A traffic analysis will be required if the turning volumes are greater than 300 vehicles per hour.

The traffic designer should review the design to determine if longer turn lane lengths are required.




# GUIDELINES FOR RIGHT-TURN LANES AT UNSIGNALIZED INTERSECTIONS ON TWO-LANE HIGHWAYS

Figure 9.5-A, (SCDOT ROADWAY DESIGN MANUAL 2021)



# VOLUME GUIDELINES FOR LEFT-TURN LANES AT UNSIGNALALIZED INTERSECTIONS ON TWO-LANE HIGHWAYS (45 mph)

Figure 9.5-F, (SCDOT ROADWAY DESIGN MANUAL 2021)



### Study Area Information

County:	Hampton County	Date:	11/10/2022
SCDOT Engineering District:	District 7	Analyst:	PC
Analysis Year:	2025	Agency:	Stantec Consulting Services Inc.
Intersection:	Salkhatchie Rd & Pine St (Project Driveway #2)		
Left Turn Movement:	Southbound Left-Turn Lane		
Right Turn Movement:	Northbound Right-Turn Lane		
Posted Speed Limit:	35	Median:	Undivided
# of Approach Lanes:	1	Urban or Rural?	Rural

### Volume Information & Calculations

#### Left Turn Lane Volume Calculations

Movement		Volume (vph)	
		AM	PM
Advancing	Left	8	18
	Through	46	30
	Right	0	0
Opposing	Left	0	0
	Through	39	59
	Right	1	3

	AM	PM
Advancing Volume:	54	48
Opposing Volume:	40	62
Left Turn Volume:	8	18

% Left Turns in Advancing Volume:	14.8%	37.5%
-----------------------------------	-------	-------

#### Right Turn Lane Volume Calculations

Movement		Volume (vph)	
		AM	PM
Advancing	Left	0	0
	Through	39	59
	Right	1	3

Adjustment to Right Turn Volume <sup>1</sup>	Include?	No
--	----------	----

	AM	PM
Advancing Volume:	40	62
Right Turn Volume:	1	3

### Turn Lane Warrant Met?

Left Turn Lane Warrant		Right Turn Lane Warrant	
Applicable Warrant Chart:	Fig 9.5-G	Applicable Warrant Chart:	Fig 9.5-A
Warrant Satisfied:	No	Warrant Satisfied:	No

### Recommended Turn Lane Length

Left Turn Lane		Right Turn Lane	
Turning Truck%:	80%	Turning Truck%:	80%
Storage Length (ft):	N/A	Storage Length:	N/A
Taper Length (ft):	N/A	Taper Length:	N/A
Total Left Turn Lane (ft):	N/A	Total Left Turn Lane:	N/A


Consider providing dual-turn lanes if the turning volumes are greater than 300 vehicles per hour. A traffic analysis will be required if the turning volumes are greater than 300 vehicles per hour.

The traffic designer should review the design to determine if longer turn lane lengths are required.




# GUIDELINES FOR RIGHT-TURN LANES AT UNSIGNALIZED INTERSECTIONS ON TWO-LANE HIGHWAYS

Figure 9.5-A, (SCDOT ROADWAY DESIGN MANUAL 2021)



# VOLUME GUIDELINES FOR LEFT-TURN LANES AT UNSIGNALALIZED INTERSECTIONS ON TWO-LANE HIGHWAYS (40 mph)

Figure 9.5-G, (SCDOT ROADWAY DESIGN MANUAL 2021)



### Study Area Information

County:	Hampton County	Date:	11/10/2022
SCDOT Engineering District:	District 7	Analyst:	PC
Analysis Year:	2025	Agency:	Stantec Consulting Services Inc.
Intersection: US 21 & Project Driveway #3			
Left Turn Movement: Eastbound Left-Turn Lane			
Right Turn Movement: Westbound Right-Turn Lane			
Posted Speed Limit:	45 mph	Median:	Undivided
# of Approach Lanes:	1	Urban or Rural?	Rural

### Volume Information & Calculations

#### Left Turn Lane Volume Calculations

Movement		Volume (vph)	
		AM	PM
Advancing	Left	15	1
	Through	61	142
	Right	0	0
Opposing	Left	0	0
	Through	116	97
	Right	16	1

	AM	PM
Advancing Volume:	76	143
Opposing Volume:	132	98
Left Turn Volume:	15	1

% Left Turns in Advancing Volume: 19.7% 0.7%

#### Right Turn Lane Volume Calculations

Movement		Volume (vph)	
		AM	PM
Advancing	Left	0	0
	Through	116	97
	Right	16	1

Adjustment to Right Turn Volume<sup>1</sup> Include? No

	AM	PM
Advancing Volume:	132	98
Right Turn Volume:	16	1

### Turn Lane Warrant Met?

<b>Left Turn Lane Warrant</b> Applicable Warrant Chart: <b>Fig 9.5-F</b> Warrant Satisfied: <b>No</b>	<b>Right Turn Lane Warrant</b> Applicable Warrant Chart: <b>Fig 9.5-A</b> Warrant Satisfied: <b>No</b>
---	--

### Recommended Turn Lane Length

Turning Truck%: 20%

Turning Truck%: 20%

<b>Left Turn Lane</b> Storage Length (ft): N/A ft Taper Length (ft): N/A ft Total Left Turn Lane (ft): N/A ft	<b>Right Turn Lane</b> Storage Length: N/A ft Taper Length: N/A ft Total Left Turn Lane: N/A ft
--	--


Consider providing dual-turn lanes if the turning volumes are greater than 300 vehicles per hour. A traffic analysis will be required if the turning volumes are greater than 300 vehicles per hour.

The traffic designer should review the design to determine if longer turn lane lengths are required.




# GUIDELINES FOR RIGHT-TURN LANES AT UNSIGNALIZED INTERSECTIONS ON TWO-LANE HIGHWAYS


Figure 9.5-A, (SCDOT ROADWAY DESIGN MANUAL 2021)



# VOLUME GUIDELINES FOR LEFT-TURN LANES AT UNSIGNALALIZED INTERSECTIONS ON TWO-LANE HIGHWAYS (45 mph)

Figure 9.5-F, (SCDOT ROADWAY DESIGN MANUAL 2021)





LOCATION MAP

NOTES

THIS PLAT DOES NOT CERTIFY THAT THE INFORMATION SHOWN HEREON COMPLIES WITH LOCAL ZONING REGULATIONS. THIS PLAT DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF OVERLAY DISTRICTS OR SPECIAL HAZARD AREAS SUCH AS BUT NOT LIMITED TO AIRPORT AND AICUZ ZONES.

THIS PLAT REPRESENTS CONDITIONS FOUND ON 4/1/2022 AND DOES NOT REPRESENT CONDITIONS FOUND ON ANY OTHER DATE.

THIS PLAT WAS SURVEYED BASED ON REFERENCED DOCUMENTS AND WAS NOT SURVEYED IN COORDINATION WITH A TITLE EXAMINATION. THE SURVEYOR DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF EASEMENTS.

THE AREA CALCULATIONS SHOWN HEREON WERE DETERMINED BY THE COORDINATE METHOD.

THE PRESENCE OR ABSENCE OF REGULATED NATURAL RESOURCES (SUCH AS, BUT NOT LIMITED TO, CRITICAL AREAS, FRESHWATER WETLANDS, SPECIMEN TREES, AND HISTORICALLY SIGNIFICANT SITES AND CULTURAL RESOURCES) WAS NOT DETERMINED AT THIS TIME OTHER THAN THOSE SHOWN HEREON AND ACCOMPANIED BY THE CERTIFICATION OR APPROVAL OF APPROPRIATE REGULATORY AGENCY.

THIS PLAT DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF UNDERGROUND FEATURES, (INCLUDING, BUT NOT LIMITED TO UTILITIES, STORAGE TANKS, AND SIMILAR).

THE VERTICAL DATUM FOR FLOOD ZONE INFORMATION AND TOPOGRAPHY IS NAVD 1988 AND WAS DETERMINED USING THE SC VRS NETWORK.

ZONING AND SETBACKS WERE NOT DETERMINED AT THIS TIME



AREA TABLE			
Description	Perimeter	Sq. Feet	Acres
AREA A	6,698.26	2,017,285.51	46.31
AREA B	7,818.71	1,824,771.31	41.89
AREA C	4,206.48	596,822.44	13.70
AREA D	1,380.30	108,808.70	2.50
Total		4,547,687.95	104.40

LINE	BEARING	DISTANCE
L1	S 54°02'11" W	119.41'
L2	N 38°18'44" W	245.26'
L3	S 54°42'38" E	194.73'
L4	N 43°12'39" W	208.73'
L5	S 50°45'40" W	183.01'
L6	S 60°26'56" W	50.00'
L7	S 60°26'56" W	113.82'
L8	N 48°49'06" E	209.73'
L9	N 40°27'17" W	46.59'
L10	N 40°17'13" W	188.93'
L11	S 44°28'53" E	131.17'
L12	S 49°42'44" W	278.85'
L13	N 85°17'14" W	47.50'
L14	N 40°27'17" W	28.68'
L15	N 44°27'15" W	147.62'
L16	N 43°09'46" W	270.15'
L17	N 40°17'13" W	178.04'
L18	N 60°40'02" E	63.84'
L19	N 29°20'29" W	244.09'
L20	S 29°24'03" E	243.34'
L21	N 59°36'52" E	50.25'
L22	N 29°20'15" W	146.49'
L23	N 29°33'44" W	7.70'

WETLANDS AREA TABLE			
Description	Perimeter	Sq. Feet	Acres
Ditch A	294.59	1,352.19	0.03
Ditch B	1,186.4	7,907	0.18
Ditch C	1,682.5	9,786	0.22
Ditch D	1,499.7	11,460.52	0.26
Ditch E	2,034.71	13,461.15	0.31
Wetland A	8,468.70	2,717,817.99	62.39
Wetland B	172.52	1,661.23	0.04
Wetland C	1,241.41	33,650.55	0.77
Wetland D	433.22	8,261.57	0.19
Wetland E	1,362.85	105,202.51	2.42
Wetland F	295.51	4,680.65	0.11
Total		2,916,081.36	66.92

AREA TABLE			
AREA	TOTAL ACREAGE	SQ. FEET	WETLANDS ACREAGE
A	46.31	2,017,285.51	46.31
B	33.96	1,479,297	17.00
C	12.70	553,115	2.42
D	2.50	108,809	0.00
E	1.00	43,567	0.11
F	7.98	347,487	0.19

AREA TABLE			
Description	Perimeter	Sq. Feet	Acres
AREA A	6,698.26	2,017,285.51	46.31
AREA B	7,818.71	1,824,771.31	41.89
AREA C	4,206.48	596,822.44	13.70
AREA D	1,380.30	108,808.70	2.50
Total		4,547,687.95	104.40




FLOOD ZONE DETERMINATION

FLOOD ZONE (BFE)-A (BFE=NOT DETERMINED) AND X  
COMMUNITY NAME: HAMPTON CO. UN INCORP./TOWN OF YEMASSEE  
COMMUNITY #: 450095 / 450103  
MAP #: 45049C0450C  
PANEL #: 450.0E.550  
PANEL DATE: SEPTEMBER 29, 2010  
INDEX DATE: SEPTEMBER 29, 2010

THIS FLOOD ZONE DETERMINATION IS APPROXIMATE AND SHOULD BE VERIFIED BY THE APPROPRIATE BUILDING CODES OFFICE BEFORE ANY DESIGN OR CONSTRUCTION BEGINS.

I HEREBY CERTIFY TO RAMSEY DEVELOPMENT THAT TO THE BEST OF MY KNOWLEDGE, INFORMATION, AND BELIEF, THE SURVEY SHOWN HEREON WAS MADE IN ACCORDANCE WITH THE REQUIREMENTS OF THE MINIMUM STANDARDS MANUAL FOR THE PRACTICE OF LAND SURVEYING IN SOUTH CAROLINA, AND MEETS OR EXCEEDS THE REQUIREMENTS FOR A CLASS "C" SURVEY AS SPECIFIED THEREIN. ALSO THERE ARE NO ENCROACHMENTS OR PROJECTIONS AFFECTING THE PROPERTY OTHER THAN THOSE SHOWN.



LORICK V. FANNING, PLS 19882


BOUNDARY SURVEY OF  
CORBETT TRACT  
TAX PARCELS 204-01-05-005 AND 203-00-00-046  
YEMASSEE, HAMPTON COUNTY, SOUTH CAROLINA  
PREPARED FOR RAMSEY DEVELOPMENT

JOB # 6024

FIELD BOOK:	ELECTRONIC
FIELD CREW:	LE/PW
DRAFTER:	LE/PW
DATE OF FIELDWORK:	04/01/2022
REFERENCES	PB 21 PG 417 PB 3 PG 127 DB 484 PG 261
	PB 32 PG 4 PB 14 PG 64
	PB 5 PG 96 PB 3 PG 157

LAND CONSULTING GROUP, LLC  
POST OFFICE DRAWER 1366  
BEAUFORT, SOUTH CAROLINA 29901-1366  
(843) 575-5206





LOCATION MAP

## NOTES

THIS PLAT DOES NOT CERTIFY THAT THE INFORMATION SHOWN HEREON COMPLIES WITH LOCAL ZONING REGULATIONS. THIS PLAT DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF OVERLAY DISTRICTS OR SPECIAL HAZARD AREAS SUCH AS BUT NOT LIMITED TO AIRPORT AND AICUZ ZONES.

THIS PLAT REPRESENTS CONDITIONS FOUND ON 4/1/2022 AND DOES NOT REPRESENT CONDITIONS FOUND ON ANY OTHER DATE.

THIS PLAT WAS SURVEYED BASED ON REFERENCED DOCUMENTS AND WAS NOT SURVEYED IN COORDINATION WITH A TITLE EXAMINATION. THE SURVEYOR DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF EASEMENTS.

THE AREA CALCULATIONS SHOWN HEREON WERE DETERMINED BY THE COORDINATE METHOD.

THE PRESENCE OR ABSENCE OF REGULATED NATURAL RESOURCES (SUCH AS, BUT NOT LIMITED TO, CRITICAL AREAS, FRESHWATER WETLANDS, SPECIMEN TREES, AND HISTORICALLY SIGNIFICANT SITES AND CULTURAL RESOURCES) WAS NOT DETERMINED AT THIS TIME OTHER THAN THOSE SHOWN HEREON AND ACCOMPANIED BY THE CERTIFICATION OR APPROVAL OF APPROPRIATE REGULATORY AGENCY.

THIS PLAT DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF UNDERGROUND FEATURES, (INCLUDING, BUT NOT LIMITED TO UTILITIES, STORAGE TANKS, AND SIMILAR).

THE VERTICAL DATUM FOR FLOOD ZONE INFORMATION AND TOPOGRAPHY IS NAVD 1988 AND WAS DETERMINED USING THE SC VRS NETWORK.

ZONING AND SETBACKS WERE NOT DETERMINED AT THIS TIME

AREA TABLE			
Description	Perimeter	Sq. Feet	Acres
AREA A	6,698.26	2,017,285.51	46.31
AREA B	7,818.71	1,824,771.31	41.89
AREA C	4,206.48	596,822.44	13.70
AREA D	1,380.30	108,808.70	2.50
Total		4,547,687.95	104.40

LINE	BEARING	DISTANCE
L1	S 54°02'11" W	119.41'
L2	N 38°18'44" W	245.26'
L3	S 54°42'38" E	194.73'
L4	N 43°12'39" W	208.73'
L5	S 50°45'40" W	183.01'
L6	S 60°26'56" W	50.00'
L7	S 60°26'56" W	113.82'
L8	N 48°49'06" E	209.73'
L9	N 40°27'17" W	46.59'
L10	N 40°17'13" W	188.93'
L11	S 44°28'33" E	131.17'
L12	S 49°42'44" W	278.85'
L13	N 85°17'14" W	47.50'
L14	N 40°27'17" W	28.68'
L15	N 44°27'15" W	147.62'
L16	N 43°09'46" W	270.15'
L17	N 40°17'13" W	178.04'
L18	N 60°40'02" E	63.84'
L19	N 29°20'29" W	244.09'
L20	S 29°24'03" E	243.34'
L21	N 59°36'32" E	50.25'
L22	N 29°20'15" W	146.49'
L23	N 29°33'44" W	7.70'

WETLANDS AREA TABLE			
Description	Perimeter	Sq. Feet	Acres
Ditch A	294.59	1,352.19	0.03
Ditch B	1,186.4	7,907	0.18
Ditch C	1,682.5	9,786	0.22
Ditch D	1,499.7	11,460.52	0.26
Ditch E	2,034.71	13,461.15	0.31
Wetland A	8,468.70	2,717,817.99	62.39
Wetland B	172.52	1,661.23	0.04
Wetland C	1,241.41	33,650.55	0.77
Wetland D	433.22	8,261.57	0.19
Wetland E	1,362.85	105,202.51	2.42
Wetland F	295.51	4,680.65	0.11
Total		2,916,081.36	66.92



AREA TABLE			
AREA/TOTAL	ACREAGE	SQ. FEET	WETLANDS ACREAGE
A	46.31	2,017,286	46.20
B	33.96	1,479,297	17.00
C	12.70	553,115	2.42
D	2.50	108,809	0.00
E	1.00	43,567	0.11
F	7.98	347,487	0.19

AREA TABLE			
Description	Perimeter	Sq. Feet	Acres
AREA A	6,698.26	2,017,285.51	46.31
AREA B	7,818.71	1,824,771.31	41.89
AREA C	4,206.48	596,822.44	13.70
AREA D	1,380.30	108,808.70	2.50
Total		4,547,687.95	104.40

LINE	BEARING	DISTANCE
L24	N 67°42'26" E	48.34'
L25	N 54°21'03" E	48.16'
L26	N 51°56'55" E	37.48'
L27	S 24°45'48" E	10.12'
L28	S 54°10'28" W	43.47'
L29	S 53°39'09" W	41.93'
L30	S 69°33'31" W	47.29'
L31	S 45°26'11" E	20.80'
L32	N 80°47'05" E	16.25'
L33	S 85°54'34" E	33.94'
L34	N 35°39'44" E	8.66'
L35	N 16°42'56" W	10.01'
L36	N 71°04'53" W	20.57'
L37	N 58°10'23" W	23.55'
L38	S 72°04'53" W	24.22'
L39	S 17°29'54" W	14.53'
L40	S 59°00'43" E	27.91'
L41	S 03°43'59" W	18.54'
L42	N 85°21'48" W	28.81'
L43	N 71°24'10" W	24.80'
L44	S 31°17'53" W	64.38'
L45	N 87°55'49" W	38.43'
L46	N 39°46'17" W	39.56'
L47	N 23°22'06" E	49.29'
L48	N 80°03'53" E	62.15'
L49	N 45°48'46" E	36.64'
L50	S 09°47'09" W	7.63'
L51	S 36°37'00" E	35.07'
L52	N 47°22'00" E	7.33'
L53	N 49°20'42" E	124.90'
L54	N 46°45'02" E	87.15'
L55	N 46°54'03" E	131.98'
L56	N 51°53'20" E	158.18'
L57	N 49°11'48" E	134.60'
L58	N 52°35'15" E	44.45'
L59	S 26°15'28" E	10.24'
L60	S 44°58'35" W	44.45'
L61	S 49°15'06" W	129.16'
L62	S 52°49'21" W	160.08'
L63	S 45°15'56" W	128.29'
L64	S 46°36'31" W	96.13'
L65	S 49°23'09" W	123.17'
L66	S 47°28'45" W	71.50'
L67	N 43°12'39" W	16.72'
L68	S 75°42'22" E	39.79'
L69	S 47°42'55" E	28.12'
L70	S 30°00'38" W	34.07'
L71	S 65°30'03" W	26.16'
L72	N 40°10'52" W	28.21'
L73	S 67°00'10" W	30.17'
L74	S 25°46'25" W	31.86'
L75	S 89°35'21" W	18.54'
L76	N 52°40'38" W	37.56'
L77	S 80°42'07" W	31.23'
L78	N 71°39'20" W	29.80'
L79	N 32°15'32" W	38.93'
L80	N 84°05'10" W	11.13'
L81	S 05°55'48" E	19.67'
L82	S 05°15'18" E	48.07'
L83	S 57°24'44" W	42.50'
L84	S 83°21'44" W	12.57'
L85	N 37°53'20" W	25.30'
L86	N 17°42'44" E	6.92'
L87	N 26°07'09" E	34.76'
L88	N 44°59'37" W	17.32'
L89	S 55°25'46" E	30.30'
L90	N 28°48'00" E	3.50'
L91	N 48°18'36" W	29.18'
L92	N 47°12'22" E	11.99'
L93	N 59°28'59" E	53.34'
L94	N 51°49'16" E	52.38'
L95	N 53°30'51" E	128.47'
L96	N 67°02'28" E	19.22'
L97	N 64°50'13" E	43.63'
L98	N 69°36'55" E	39.80'
L99	S 83°16'17" E	24.23'
L100	S 15°20'50" E	22.83'
L101	S 05°13'27" E	15.41'
L102	S 55°44'53" W	34.59'
L103	S 65°09'54" W	32.60'
L104	S 53°37'04" W	37.93'
L105	S 37°41'27" W	30.65'
L106	S 08°25'45" W	21.73'
L107	S 63°23'37" E	17.39'
L108	N 64°47'59" W	52.39'
L109	N 80°14'52" W	21.35'
L110	N 02°49'10" W	28.63'
L111	N 10°53'49" E	57.42'
L112	N 34°56'36" W	53.29'
L113	N 18°41'36" W	48.42'
L114	N 17°13'24" E	71.54'
L115	N 11°28'09" E	40.93'
L116	N 60°11'12" E	56.68'
L117	N 84°41'06" E	46.26'
L118	N 68°00'42" E	48.12'
L119	N 69°25'09" E	68.12'
L120	N 57°59'53" E	98.97'

LINE	BEARING	DISTANCE
L121	N 62°44'02" E	39.83'
L122	S 28°51'37" E	173.30'
L123	N 41°01'08" W	198.85'
L124	N 28°51'37" W	172.06'
L125	N 60°31'54" E	31.30'
L126	N 29°20'29" W	6.54'
L127	S 28°51'37" E	152.55'
L128	N 57°43'22" E	13.88'
L129	N 28°51'37" W	112.46'
L130	S 77°06'49" W	23.30'
L131	S 06°19'37" W	32.81'
L132	S 23°43'28" E	31.29'
L133	S 20°12'57" E	16.72'
L134	S 27°21'57" E	26.91'
L135	N 89°48'01" E	38.14'
L136	N 28°51'37" W	51.89'
L137	S 17°30'58" W	91.85'
L138	S 55°06'41" W	50.28'
L139	N 48°40'20" E	77.22'
L140	N 51°01'32" E	49.92'
L141	N 48°42'14" E	22.63'
L142	N 44°09'09" E	71.27'
L143	N 56°18'05" E	123.64'
L144	N 55°02'21" E	127.02'
L145	N 29°27'04" W	21.80'
L146	S 52°09'46" W	132.15'
L147	S 55°24'42" W	121.99'
L148	S 43°33'57" W	74.50'
L149	N 48°40'20" E	10.51'
L150	N 48°33'00" E	19.15'
L151	N 48°05'39" E	45.23'
L152	N 47°33'09" E	109.69'
L153	N 47°54'31" E	177.29'
L154	N 48°53'08" E	299.37'
L155	N 37°44'23" W	5.32'
L156	N 49°34'21" W	147.54'
L157	S 49°55'40" W	154.36'
L158	N 49°01'31" W	180.73'
L159	N 48°14'40" W	104.12'
L160	N 48°03'39" W	81.49'
L161	N 48°47'37" W	57.76'
L162	N 46°54'27" W	23.59'
L163	S 29°57'09" E	10.47'
L164	N 52°46'00" E	42.70'
L165	N 48°31'33" E	54.35'
L166	N 47°53'14" E	75.10'
L167	N 50°09'57" E	38.95'
L168	S 51°07'42" W	52.42'
L169	S 47°43'47" W	114.58'
L170	S 49°42'14" W	67.40'
L171	S 24°44'26" E	11.95'
L172	N 49°06'34" E	69.43'
L173	N 64°50'13" W	43.63'
L174	N 66°59'07" W	19.27'
L175	N 41°02'25" W	7.50'
L176	S 60°18'38" W	26.47'
L177	N 68°02'09" W	13.85'
L178	S 18°18'02" W	47.62'
L179	N 40°17'55" W	5.11'
L180	N 42°44'49" E	17.27'
L181	N 42°29'37" E	41.02'
L182	N 55°14'43" E	94.12'
L183	N 65°02'02" E	96.37'
L184	N 37°44'23" W	48.67'
L185	N 37°44'23" W	30.86'
L186	N 58°42'59" W	44.05'
L187	N 48°05'58" W	65.98'
L188	N 84°02'31" W	84.41'
L189	S 74°43'05" W	42.71'
L190	N 59°13'14" W	50.94'
L191	N 75°20'46" W	79.62'
L192	N 58°20'14" W	39.13'
L193	N 59°00'08" W	70.01'
L194	N 65°59'10" W	43.06'
L195	N 69°48'56" W	57.58'
L196	S 83°49'20" W	21.93'
L197	N 89°16'04" W	56.19'
L198	N 82°23'31" W	33.71'
L199	N 83°53'07" W	52.94'
L200	N 67°08'43" W	37.88'
L201	N 31°37'32" W	33.98'
L202	N 57°59'02" W	34.05'
L203	N 50°38'56" W	49.85'
L204	N 80°14'41" E	49.81'
L205	N 84°50'10" E	90.19'
L206	N 13°57'00" W	9.38'
L207	N 43°37'58" W	27.53'
L208	N 24°58'57" E	15.46'
L209	N 26°10'53" W	38.00'
L210	N 72°37'44" W	26.77'


LINE	BEARING	DISTANCE
L218	S 12°35'50" W	22.53'
L219	S 70°37'46" W	15.17'
L220	S 28°12'22" W	15.21'
L221	N 31°43'46" W	48.99'
L222	N 66°57'01" W	18.56'
L223	S 32°22'14" W	35.28'
L224	S 87°47'53" W	23.97'
L225	S 60°27'38" W	16.22'
L226	N 69°35'37" W	33.67'
L227	S 70°54'06" W	33.52'
L228	N 27°37'01" W	18.76'
L229	N 46°36'54" E	37.96'
L230	N 20°51'33" E	16.68'
L231	N 11°20'48" W	17.41'
L232	S 67°48'46" W	24.02'
L233	S 00°57'36" E	10.68'
L234	S 45°38'50" W	29.67'
L235	S 73°20'13" W	43.98'
L236	S 77°39'01" W	34.83'
L237	S 85°39'05" W	24.95'
L238	N 85°04'23" W	75.44'
L239	S 21°47'35" W	64.92'
L240	S 49°38'29" W	52.62'
L241	S 65°03'20" W	34.38'
L242	S 44°37'07" W	17.74'
L243	S 46°35'03" W	30.33'
L244	S 66°21'45" W	39.86'
L245	N 41°58'04" W	16.72'
L246	S 80°10'31" W	12.87'
L247	S 69°04'06" W	33.97'
L248	S 71°25'38" W	29.44'
L249	N 54°29'25" W	21.03'
L250	N 12°36'01" E	20.88'
L251	N 21°59'15" W	20.69'
L252	N 68°16'05" E	13.02'
L253	S 85°08'44" E	40.97'
L254	S 89°13'03" E	32.58'
L255	S 56°49'52" E	21.71'
L256	N 49°49'45" W	26.63'
L257	N 72°54'43" W	20.31'
L258	N 71°19'32" W	28.99'
L259	N 48°05'06" W	12.52'
L260	N 07°47'46" E	40.74'
L261	N 09°09'04" E	33.15'
L262	N 05°46'53" W	40.80'
L263	N 04°33'13" W	34.21'
L264	N 60°01'45" W	36.48'
L265	S 64°15'31" W	58.67'
L266	S 65°16'47" W	51.69'
L267	N 83°17'36" W	37.99'
L268	N 71°14'43" W	71.52'
L269	N 13°29'57" E	34.72'
L270	N 53°28'38" E	36.33'
L271	S 73°22'38" E	27.28'
L272	N 75°20'46" E	61.26'
L273	N 69°44'01" E	37.43'
L274	S 88°12'34" E	40.51'
L275	N 69°15'40" E	40.10'
L276	N 30°25'16" E	58.73'
L277	N 17°06'33" W	70.69'
L278	N 04°41'33" E	19.94'
L279	S 72°39'08" W	26.77'
L280	S 85°16'33" W	37.93'
L281	S 77°56'02" W	114.44'
L282	S 85°38'34" W	99.93'
L283	S 83°19'23" W	35.96'
L284	S 40°33'38" W	19.64'
L285	S 87°01'50" W	52.95'
L286	N 66°28'14" W	41.94'
L287	N 83°21'00" W	28.59'
L288	S 71°21'41" E	17.79'
L289	N 85°53'07" E	68.36'
L290	S 65°50'28" E	41.17'
L291	N 87°30'46" E	36.91'
L292	N 78°02'25" E	24.85'
L293	S 85°10'35" E	23.69'
L294	S 85°06'01" E	35.33'
L295	N 72°25'11" E	12.52'
L296	N 82°51'35" E	45.06'
L297	N 83°24'53" E	71.56'
L298	N 85°36'39" E	84.02'
L299	N 49°13'56" W	10.97'



FLOOD ZONE DETERMINATION

FLOOD ZONE (BFE): A (BFE=NOT DETERMINED) AND X  
COMMUNITY NAME: HAMPTON CO. UN. INCORP./TOWN OF YEMASSEE  
COMMUNITY #: 450035 / 450103  
MAP #: 4504300450C  
PANEL #: 450 OF 550  
PANEL DATE: SEPTEMBER 29, 2010  
INDEX DATE: SEPTEMBER 29, 2010  
THIS FLOOD ZONE DETERMINATION IS APPROXIMATE AND SHOULD BE VERIFIED BY THE APPROPRIATE BUILDING CODES OFFICE BEFORE ANY DESIGN OR CONSTRUCTION BEGINS.

I HEREBY CERTIFY TO RAMSEY DEVELOPMENT THAT TO THE BEST OF MY KNOWLEDGE, INFORMATION, AND BELIEF, THE SURVEY SHOWN HEREON WAS MADE IN ACCORDANCE WITH THE REQUIREMENTS OF THE MINIMUM STANDARDS MANUAL FOR THE PRACTICE OF LAND SURVEYING IN SOUTH CAROLINA, AND MEETS OR EXCEEDS THE REQUIREMENTS FOR A CLASS "C" SURVEY AS SPECIFIED THEREIN, ALSO THERE ARE NO ENCROACHMENTS OR PROJECTIONS AFFECTING THE PROPERTY OTHER THAN THOSE SHOWN.



LORICK V. FANNING, PLS 19882


WETLANDS SURVEY OF  
CORBETT TRACT  
TAX PARCELS 204-01-05-005 AND 203-00-00-046  
YEMASSEE, HAMPTON COUNTY, SOUTH CAROLINA  
PREPARED FOR RAMSEY DEVELOPMENT  
SHEET 2 OF 2

JOB # 6024

FIELD BOOK:	ELECTRONIC
FIELD CREW:	LF/PW
DRAFTER:	LF/PW
DATE OF FIELDWORK:	04/01/2022
REFERENCES	
PB 21 PG 417	PB 3 PG 127 DB 484 PG 261
PB 32 PG 4	PB 14 PG 64
PB 5 PG 96	PB 3 PG 157

LAND CONSULTING GROUP, LLC  
POST OFFICE DRAWER 1366  
BEAUFORT, SOUTH CAROLINA 29901-1366  
(843) 575-5206





LOCATION MAP

NOTES

THIS PLAT DOES NOT CERTIFY THAT THE INFORMATION SHOWN HEREON COMPLIES WITH LOCAL ZONING REGULATIONS. THIS PLAT DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF OVERLAY DISTRICTS OR SPECIAL HAZARD AREAS SUCH AS BUT NOT LIMITED TO AIRPORT AND AICUZ ZONES.

THIS PLAT REPRESENTS CONDITIONS FOUND ON 4/1/2022 AND DOES NOT REPRESENT CONDITIONS FOUND ON ANY OTHER DATE.

THIS PLAT WAS SURVEYED BASED ON REFERENCED DOCUMENTS AND WAS NOT SURVEYED IN COORDINATION WITH A TITLE EXAMINATION. THE SURVEYOR DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF EASEMENTS.

THE AREA CALCULATIONS SHOWN HEREON WERE DETERMINED BY THE COORDINATE METHOD.

THE PRESENCE OR ABSENCE OF REGULATED NATURAL RESOURCES (SUCH AS, BUT NOT LIMITED TO, CRITICAL AREAS, FRESHWATER WETLANDS, SPECIMEN TREES, AND HISTORICALLY SIGNIFICANT SITES AND CULTURAL RESOURCES) WAS NOT DETERMINED AT THIS TIME OTHER THAN THOSE SHOWN HEREON AND ACCOMPANIED BY THE CERTIFICATION OR APPROVAL OF APPROPRIATE REGULATORY AGENCY.

THIS PLAT DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF UNDERGROUND FEATURES, (INCLUDING, BUT NOT LIMITED TO UTILITIES, STORAGE TANKS, AND SIMILAR).

THE VERTICAL DATUM FOR FLOOD ZONE INFORMATION AND TOPOGRAPHY IS NAVD 1988 AND WAS DETERMINED USING THE SC VRS NETWORK.

ZONING AND SETBACKS WERE NOT DETERMINED AT THIS TIME



AREA TABLE			
Description	Perimeter	Sq. Feet	Acres
AREA A	6,698.26	2,017,285.51	46.31
AREA B	7,818.71	1,824,771.31	41.89
AREA C	4,206.48	596,822.44	13.70
AREA D	1,380.30	108,808.70	2.50
Total		4,547,687.95	104.40

LINE	BEARING	DISTANCE
L1	S 54°02'11" W	119.41'
L2	N 38°18'44" W	245.26'
L3	S 54°42'38" E	194.73'
L4	N 43°12'39" W	208.73'
L5	S 50°45'40" W	183.01'
L6	S 60°26'56" W	50.00'
L7	S 60°26'56" W	113.82'
L8	N 48°49'06" E	209.73'
L9	N 40°27'17" W	46.59'
L10	N 40°17'13" W	188.93'
L11	S 44°28'33" E	131.17'
L12	S 49°42'44" W	278.85'
L13	N 85°17'14" W	47.50'
L14	N 40°27'17" W	28.68'
L15	N 44°27'15" W	147.62'
L16	N 43°09'46" W	270.15'
L17	N 40°17'13" W	178.04'
L18	N 60°40'02" E	63.84'
L19	N 29°20'29" W	244.09'
L20	S 29°24'03" E	243.34'
L21	N 59°36'32" E	50.25'
L22	N 29°20'15" W	146.49'
L23	N 29°33'44" W	7.70'

WETLANDS AREA TABLE			
Description	Perimeter	Sq. Feet	Acres
Ditch A	294.59	1,352.19	0.03
Ditch B	1,186.4	7,907	0.18
Ditch C	1,682.5	9,786	0.22
Ditch D	1,499.7	11,460.52	0.26
Ditch E	2,034.71	13,461.15	0.31
Wetland A	8,468.70	2,717,817.99	62.39
Wetland B	172.52	1,661.23	0.04
Wetland C	1,241.41	33,650.55	0.77
Wetland D	433.22	8,261.57	0.19
Wetland E	1,362.85	105,202.51	2.42
Wetland F	295.51	4,680.65	0.11
Total		2,916,081.36	66.92

AREA TABLE			
AREA	TOTAL ACREAGE	SQ. FEET	WETLANDS ACREAGE
A	46.31	2,017,286	46.20
B	33.96	1,479,297	17.00
C	12.70	553,115	2.42
D	2.50	108,809	0.00
E	1.00	43,567	0.11
F	7.98	347,487	0.19

AREA TABLE			
Description	Perimeter	Sq. Feet	Acres
AREA A	6,698.26	2,017,285.51	46.31
AREA B	7,818.71	1,824,771.31	41.89
AREA C	4,206.48	596,822.44	13.70
AREA D	1,380.30	108,808.70	2.50
Total		4,547,687.95	104.40





THIS DOCUMENT AND ALL REPRODUCIBLE COPIES OF THIS DOCUMENT ARE THE PROPERTY OF WARD EDWARDS, INC. REPRODUCTION OR ALTERATIONS OF THIS DRAWING WITHOUT THE WRITTEN CONSENT OF WARD EDWARDS, INC. IS NOT PERMITTED.

# SITE DEVELOPMENT PLANS FOR IRONLINE METALS TOWN OF YEMASSEE, SOUTH CAROLINA

## GENERAL NOTES:

- BOUNDARY INFORMATION PROVIDED BY LIMITED TREE & TOPOGRAPHIC SURVEY OF CORBETT TRACT, DATED 04/01/22, BY LAND CONSULTING GROUP, LLC.
- TOPOGRAPHIC DATA PROVIDED BY LAND CONSULTING GROUP, LLC, DATED 04/01/22.
- APPROXIMATE LOCATION OF CERTAIN EXISTING UNDERGROUND UTILITY LINES AND STRUCTURES ARE SHOWN ON THE PLANS FOR INFORMATION ONLY. ADDITIONAL UNDERGROUND LINES OR STRUCTURES MAY EXIST THAT ARE NOT SHOWN. CALL SOUTH CAROLINA 811 AT 811 OR 1-888-721-7877 BETWEEN THE HOURS OF 7:00 AM AND 7:00 PM MONDAY THRU FRIDAY AT LEAST THREE WORKING DAYS BEFORE COMMENCING CONSTRUCTION. REQUEST UNDERGROUND UTILITIES TO BE LOCATED AND MARKED WITHIN AND NEAR THE CONSTRUCTION SITE.
- COMPLY WITH "SOUTH CAROLINA UNDERGROUND FACILITY DAMAGE PREVENTION ACT (EFFECTIVE JUNE 7, 2012). NOTIFICATION OF INTENT TO EXCAVATE MAY BE GIVEN BY CALLING THE TOLL FREE NUMBER: 1-800-922-0983.
- PROTECT BENCH MARKS AND PROPERTY MONUMENTS FROM DAMAGE DURING CONSTRUCTION OPERATIONS. REPLACE ANY BENCH MARKS OR MONUMENTS DAMAGED OR DESTROYED AS A RESULT OF CONTRACTOR'S OPERATIONS, AT NO COST TO THE OWNER, BY A LICENSED SURVEYOR IN THE STATE OF SOUTH CAROLINA.
- OFF-STREET PARKING FOR THE CONTRACTOR'S EMPLOYEES AND AUTHORIZED VISITORS TO THE SITE MUST BE PROVIDED AND MAINTAINED THROUGHOUT CONSTRUCTION.
- THE CONTRACTOR IS RESPONSIBLE FOR ADHERING TO WEIGHT LIMITS PRESCRIBED FOR ALL PUBLIC ROADS WHEN HAULING EQUIPMENT AND MATERIALS TO AND FROM THE PROJECT SITE. DAMAGES TO EXISTING PAVEMENT DUE TO THE CONTRACTOR'S CONSTRUCTION OPERATIONS OR IMPROPER TRANSPORTATION OF MATERIALS AND EQUIPMENT SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.
- AT LEAST ONE DRIVING LANE ON PUBLIC ROADS SHALL REMAIN OPEN TO TRAFFIC AT ALL TIMES. TRAFFIC LANES WILL ONLY BE CLOSED WITH THE EXPRESS WRITTEN CONSENT OF THE AGENCY HAVING JURISDICTION OVER THE ROADWAY. NOTIFY AGENCY HAVING JURISDICTION AT LEAST 5 DAYS BEFORE CLOSING ANY DRIVING LANES TO TRAFFIC. PROVIDE TRAFFIC CONTROL DEVICES, SIGNS AND FLAGMEN AS REQUIRED TO ENSURE PUBLIC SAFETY.
- CONTRACTOR SHALL COORDINATE DEMOLITION, CLEARING AND CONSTRUCTION OF IMPROVEMENTS TO MINIMIZE INTERFERENCE WITH VEHICULAR AND PEDESTRIAN TRAFFIC AND WITH OPERATIONS OF EXISTING FACILITIES.

## SITE GRADING AND DRAINAGE:

- ALL UTILITIES SHOWN ARE APPROXIMATE LOCATIONS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR PROVIDING 72-HOUR NOTICE TO ALL RESPECTIVE UTILITY COMPANIES FOR FIELD VERIFICATION OF EXISTING UTILITIES PRIOR TO CONSTRUCTION. ANY DAMAGES TO EXISTING UTILITIES DUE TO THIS CONSTRUCTION SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR.
- TEMPORARY CONTROL OF STORM WATER DRAINAGE SHALL BE THE RESPONSIBILITY OF THE CONTRACTOR. SEQUENCING AND CONSTRUCTION TECHNIQUES SHALL PREVENT OBSTRUCTION OF STORM SEWERS, PONDING IN TRAFFIC AREAS OR RISING OF WATER LEVELS WHICH WOULD ENTER ADJACENT BUILDINGS OR STRUCTURES.
- FULL WIDTH OF STREET AND ROAD RIGHTS-OF-WAY MUST BE CLEARED AND GRADED AS SHOWN IN THE DETAILS ON THE DRAWINGS.
- SUBGRADE PREPARATION: TOP SOIL SHALL BE REMOVED FROM PAVED AREAS TO A MINIMUM DEPTH AS RECOMMENDED IN THE PROJECT'S GEOTECHNICAL REPORT. ALL EXCAVATION SHALL BE TO SUBGRADE LIMITS.
- ALL UTILITY PIPE LINES, CONDUITS AND SLEEVES UNDER PAVED AREAS MUST BE IN PLACE PRIOR TO COMPLETION OF THE ROADWAY SUBGRADE COMPACTION.
- FINISH GRADING SHALL INCLUDE THE PLACEMENT OF TOPSOIL OVER ALL UNPAVED AREAS NOT OCCUPIED BY BUILDINGS OR STRUCTURES AND FINE GRADING AROUND BUILDINGS, ADJACENT TO WALKS, CURBS, GUTTERS AND STRUCTURES TO ASSURE POSITIVE DRAINAGE.

## SCDHEC/OCRM SEDIMENT AND EROSION CONTROL STANDARD NOTES (REVISED DEC-2012):

- IF NECESSARY, SLOPES, WHICH EXCEED EIGHT (8) VERTICAL FEET SHOULD BE STABILIZED WITH SYNTHETIC OR VEGETATIVE MATS. IN ADDITION TO HYDROSEEDING, IT MAY BE NECESSARY TO INSTALL TEMPORARY SLOPE DRAINS DURING CONSTRUCTION. TEMPORARY BERMS MAY BE NEEDED UNTIL THE SLOPE IS BROUGHT TO GRADE.
- STABILIZATION MEASURES SHALL BE INITIATED AS SOON AS PRACTICABLE IN PORTIONS OF THE SITE WHERE CONSTRUCTION ACTIVITIES HAVE TEMPORARILY OR PERMANENTLY CEASED, BUT IN NO CASE MORE THAN FOURTEEN (14) DAYS AFTER WORK HAS CEASED, EXCEPT AS STATED BELOW.
  - WHERE STABILIZATION BY THE 14TH DAY IS PRECLUDED BY SNOW COVER OR FROZEN GROUND CONDITIONS STABILIZATION MEASURES MUST BE INITIATED AS SOON AS PRACTICABLE.
  - WHERE CONSTRUCTION ACTIVITY ON A PORTION OF THE SITE IS TEMPORARILY CEASED, AND EARTH-DISTURBING ACTIVITIES WILL BE RESUMED WITHIN 14 DAYS, TEMPORARY STABILIZATION MEASURES DO NOT HAVE TO BE INITIATED ON THAT PORTION OF THE SITE.
- ALL SEDIMENT AND EROSION CONTROL DEVICES SHALL BE INSPECTED ONCE EVERY CALENDAR WEEK. IF PERIODIC INSPECTION OR OTHER INFORMATION INDICATES THAT A BMP HAS BEEN INAPPROPRIATELY, OR INCORRECTLY INSTALLED, THE PERMITTEE MUST ADDRESS THE NECESSARY REPLACEMENT OR MODIFICATION REQUIRED TO CORRECT THE BMP WITHIN 48 HOURS OF IDENTIFICATION.
- PROVIDE SILT FENCE AND/OR OTHER CONTROL DEVICES, AS MAY BE REQUIRED, TO CONTROL SOIL EROSION DURING UTILITY CONSTRUCTION. ALL DISTURBED AREAS SHALL BE CLEARED, GRADED, AND STABILIZED WITH GRASSING IMMEDIATELY AFTER THE UTILITY INSTALLATION. FILL, COVER, AND TEMPORARY SEEDING AT THE END OF EACH DAY ARE RECOMMENDED. IF WATER IS ENCOUNTERED WHILE TRENCHING, THE WATER SHOULD BE FILTERED TO REMOVE SEDIMENT BEFORE BEING PUMPED BACK INTO ANY WATERS OF THE STATE.
- ALL EROSION CONTROL DEVICES SHALL BE PROPERLY MAINTAINED DURING ALL PHASES OF CONSTRUCTION UNTIL THE COMPLETION OF ALL CONSTRUCTION ACTIVITIES AND ALL DISTURBED AREAS HAVE BEEN STABILIZED. ADDITIONAL CONTROL DEVICES MAY BE REQUIRED DURING CONSTRUCTION IN ORDER TO CONTROL EROSION AND/OR OFFSITE SEDIMENTATION. ALL TEMPORARY CONTROL DEVICES SHALL BE REMOVED ONCE CONSTRUCTION IS COMPLETE AND THE SITE IS STABILIZED.
- THE CONTRACTOR MUST TAKE NECESSARY ACTION TO MINIMIZE THE TRACKING OF MUD ONTO PAVED ROADWAY(S) FROM CONSTRUCTION AREAS AND THE GENERATION OF DUST. THE CONTRACTOR SHALL DAILY REMOVE MUD/SOIL FROM PAVEMENT, AS MAY BE REQUIRED.
- RESIDENTIAL SUBDIVISIONS REQUIRE EROSION CONTROL FEATURES FOR INFRASTRUCTURE AS WELL AS FOR INDIVIDUAL LOT CONSTRUCTION. INDIVIDUAL PROPERTY OWNERS SHALL FOLLOW THESE PLANS DURING CONSTRUCTION OF AN INDIVIDUAL LOT IN ACCORDANCE WITH S.C. REG. 72-300 ET SEQ. AND SCR100000.
- TEMPORARY DIVERSION BERMS AND/OR DITCHES WILL BE PROVIDED AS NEEDED DURING CONSTRUCTION TO PROTECT WORK AREAS FROM UPSLOPE RUNOFF AND/OR TO DIVERT SEDIMENT--LADEN WATER TO APPROPRIATE TRAPS OR STABLE OUTLETS.
- ALL WATERS OF THE STATE (WOS), INCLUDING WETLANDS, ARE TO BE FLAGGED OR OTHERWISE CLEARLY MARKED IN THE FIELD. A DOUBLE ROW OF SILT FENCE IS TO BE INSTALLED IN ALL AREAS WHERE A 50-FOOT BUFFER CANT BE MAINTAINED BETWEEN THE DISTURBED AREA AND ALL WOS. A 10-FOOT BUFFER SHOULD BE MAINTAINED BETWEEN THE LAST ROW OF SILT FENCE AND ALL WOS.
- LITTER, CONSTRUCTION DEBRIS, OILS, FUELS, AND BUILDING PRODUCTS WITH SIGNIFICANT POTENTIAL FOR IMPACT (SUCH AS STOCKPILES OF FRESHLY TREATED LUMBER) AND CONSTRUCTION CHEMICALS THAT COULD BE EXPOSED TO STORM WATER MUST BE PREVENTED FROM BECOMING A POLLUTANT SOURCE IN STORM WATER DISCHARGES.
- A COPY OF THE SWPPP, INSPECTIONS RECORDS, AND RAINFALL DATA MUST BE RETAINED AT THE CONSTRUCTION SITE OR A NEARBY LOCATION EASILY ACCESSIBLE DURING NORMAL BUSINESS HOURS, FROM THE DATE OF COMMENCEMENT OF CONSTRUCTION ACTIVITIES TO THE DATE THAT FINAL STABILIZATION IS REACHED.
- INITIATE STABILIZATION MEASURES ON ANY EXPOSED STEEP SLOPE (3H:1V OR GREATER) WHERE LAND-DISTURBING ACTIVITIES HAVE PERMANENTLY OR TEMPORARILY CEASED, AND WILL NOT RESUME FOR A PERIOD OF 7 CALENDAR DAYS.
- MINIMIZE SOIL COMPACTION AND, UNLESS INFEASIBLE, PRESERVE TOPSOIL.
- MINIMIZE THE DISCHARGE OF POLLUTANTS FROM EQUIPMENT AND VEHICLE WASHING, WHEEL WASH WATER, AND OTHER WASH WATERS. WASH WATERS MUST BE TREATED IN A SEDIMENT BASIN OR ALTERNATIVE CONTROL THAT PROVIDES EQUIVALENT OR BETTER TREATMENT PRIOR TO DISCHARGE.
- MINIMIZE THE DISCHARGE OF POLLUTANTS FROM DEWATERING OF TRENCHES AND EXCAVATED AREAS. THESE DISCHARGES ARE TO BE ROUTED THROUGH APPROPRIATE BMPs (SEDIMENT BASIN, FILTER BAG, ETC.).
- THE FOLLOWING DISCHARGES FROM SITES ARE PROHIBITED:
  - WASTEWATER FROM WASHOUT OF CONCRETE, UNLESS MANAGED BY AN APPROPRIATE CONTROL.
  - WASTEWATER FROM WASHOUT AND CLEANOUT OF STUCCO, PAINT, FORM RELEASE OILS, CURING COMPOUNDS AND OTHER CONSTRUCTION MATERIALS.
  - FUELS, OILS, OR OTHER POLLUTANTS USED IN VEHICLE AND EQUIPMENT OPERATION AND MAINTENANCE.
  - SOAPS OR SOLVENTS USED IN VEHICLE AND EQUIPMENT WASHING.
- AFTER CONSTRUCTION ACTIVITIES BEGIN, INSPECTIONS MUST BE CONDUCTED AT A MINIMUM OF AT LEAST ONCE EVERY CALENDAR WEEK AND MUST BE CONDUCTED UNTIL FINAL STABILIZATION IS REACHED ON ALL AREAS OF THE CONSTRUCTION SITE.
- IF EXISTING BMPs NEED TO BE MODIFIED OR IF ADDITIONAL BMPs ARE NECESSARY TO COMPLY WITH THE REQUIREMENTS OF THIS PERMIT AND/OR SC'S WATER QUALITY STANDARDS, IMPLEMENTATION MUST BE COMPLETED BEFORE THE NEXT STORM EVENT WHENEVER PRACTICABLE. IF IMPLEMENTATION BEFORE THE NEXT STORM EVENT IS IMPRACTICABLE, THE SITUATION MUST BE DOCUMENTED IN THE SWPPP AND ALTERNATIVE BMPs MUST BE IMPLEMENTED AS SOON AS REASONABLY POSSIBLE.
- A PRE-CONSTRUCTION CONFERENCE MUST BE HELD FOR EACH CONSTRUCTION SITE WITH AN APPROVED ON-SITE SWPPP PRIOR TO THE IMPLEMENTATION OF CONSTRUCTION ACTIVITIES. FOR NON-LINEAR PROJECTS THAT DISTURB 10 ACRES OR MORE THIS CONFERENCE MUST BE HELD ON-SITE UNLESS THE DEPARTMENT HAS APPROVED OTHERWISE.

## DRY UTILITY CONDUITS FOR ELECTRIC, TELEPHONE AND CABLE TV:

- ALL DRY UTILITY CONDUIT ENDS SHALL BE CAPPED AND MARKED WITH A STEEL REBAR STAKE IMBEDDED ONE (1) FOOT BELOW GROUND SURFACE.
- 48" MINIMUM BURY DEPTH FOR ALL ELECTRICAL CONDUITS.
- MAINTAIN MINIMUM 12" VERTICAL CLEARANCE WHEN CROSSING WATER, SEWER, AND STORM DRAIN LINES.
- IF BUILDING PLANS FOR THE EXACT LOCATION OF THE CONDUITS, THE CONTRACTOR MUST INSTALL ALL CONDUITS, AS SHOWN ON THE PLANS OR AS REQUIRED BY RESPECTIVE UTILITY COMPANIES. THE CONTRACTOR SHALL BE RESPONSIBLE TO ENSURE STRICT COMPLIANCE WITH ALL APPLICABLE CODES AND REGULATIONS WITH REGARDS TO THE INSTALLATION OF UTILITIES AND CONDUIT.
- LOCATIONS SHOWN ON THE PLANS FOR PROPOSED DRY UTILITY CONDUITS ARE APPROXIMATE ONLY. ALL DIMENSIONING AND STAKING SHOULD BE BASED ON ECONOMICAL AND PRACTICAL CONSTRUCTION. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COORDINATION WITH THE RESPECTIVE UTILITY REPRESENTATIVES, PRIOR TO ANY CONDUIT INSTALLATION.
- TRANSFORMER PADS SHALL BE LOCATED AS DIRECTED BY THE RESPECTIVE UTILITY REPRESENTATIVE. THE CONTRACTOR SHALL BE RESPONSIBLE FOR COMPLIANCE WITH APPLICABLE CODE REQUIREMENTS.
- NOTIFY THE ENGINEER IF CONFLICTS WITH EXISTING OR PROPOSED STRUCTURES REQUIRE PROPOSED UTILITIES BE RELOCATED.

## SITE CLEARING AND DEMOLITION:

- NO CLEARING SHALL OCCUR WITHIN DESIGNATED BUFFER ZONES, TREE PROTECTION ZONES, OUTSIDE OF THE PROPERTY LINES OR BEYOND THE CLEARING LIMITS UNLESS OTHERWISE SPECIFICALLY SHOWN ON THE PLANS.
- ONLY THOSE TREES DESIGNATED ON THE DRAWINGS FOR REMOVAL ARE TO BE REMOVED AS PART OF THE SITE CLEARING OPERATIONS. THE CONTRACTOR SHALL INSTALL A CONTINUOUS LINE OF FLAGGING OR FENCING ALONG THE LIMITS OF CLEARING PRIOR TO COMMENCING ANY CLEARING, DEMOLITION, OR CONSTRUCTION WORK ON THE PROJECT.
- EXERCISE CAUTION DURING CLEARING OPERATIONS TO AVOID FELLING TREES INTO DESIGNATED TREE PROTECTION ZONES.
- NO BURNING WILL BE ALLOWED WITHIN 50 FEET OF A TREE PROTECTION ZONE OR TREE DRIP LINE. CONTRACTOR SHALL COORDINATE ANY BURNING OPERATIONS WITH LOCAL JURISDICTION AND FIRE DEPARTMENTS.
- SELECTIVE CLEARING AREAS SHALL BE CLEARED OF ALL BRUSH AND UNDERSTORY GROWTH.


## UTILITY CONTACTS:

PAUMotu ELECTRIC	843-208-5512	1 COOPERATIVE WAY, HARDEEVILLE, SC 29927
DOMINION ENERGY	800-251-7234	PO BOX 100255 COLUMBIA, SC 29202
LOWCOUNTRY REGIONAL WATER SYSTEM	803-843-1006	513 ELM STREET WEST, SC 29924
HARGRAY COMMUNICATIONS	843-815-1675	PO BOX 3380, BLUFFTON, SC 29910
TIME WARNER CABLE	843-913-7940	11 OFFICE PARK ROAD, HILTON HEAD, SC 29928
CENTURY LINK	843-525-0044	2127 BOUNDARY ST #16, BEAUFORT, SC 29902
SANTEET COOPER	843-761-8000	1 RIVERWOOD DRIVE, MONCKS CORNER, SC 29461

## CONTRACTOR NOTE:

CONTRACTOR TO OBTAIN AND BECOME FAMILIAR WITH GEOTECHNICAL REPORT #12591408-00 PREPARED BY GH.

ALL WORK MUST CONFORM TO PROJECT TECHNICAL SPECIFICATIONS FOR IRONLINE METALS PREPARED BY WARD EDWARDS ENGINEERING. THE CONTRACTOR IS RESPONSIBLE FOR OBTAINING A COPY OF THE TECHNICAL SPECIFICATIONS IF NOT PROVIDED WITH THE DRAWINGS.



## SCHEDULE OF DRAWINGS

SHEET NO.	DESCRIPTION
C001	COVER SHEET & CONSTRUCTION NOTES
C002	SHEET INDEX
C101	EXISTING CONDITIONS PLANS
C201	INITIAL EROSION CONTROL PLANS AND DETAILS
C301	CLEARING & DEMOLITION PLANS AND DETAILS
C401	SITE LAYOUT PLANS
C501	GRADING PLANS AND DETAILS
C601	DRAINAGE PLANS AND DETAILS
C700	OVERALL UTILITY PLAN
C701	UTILITY PLANS, PROFILES AND DETAILS
C801	INTERMEDIATE EROSION CONTROL PLANS AND DETAILS
C901	PAVING PLANS, ROAD PROFILES AND DETAILS
C1001	FINAL EROSION CONTROL PLANS AND DETAILS
C1101	SCDOT SIGHT DISTANCE EXHIBIT AND SCDOT DETAILS

## RELEASE SCHEDULE

RELEASE NO.	DESCRIPTION	DATE
A.	RELEASED FOR PERMITTING	12-27-22
B.	RELEASED FOR PERMITTING	12-29-22
C.	RELEASED FOR PERMITTING	02-20-23
D.	RELEASED FOR PERMITTING	02-24-23


## SEQUENCE OF CONSTRUCTION ACTIVITIES

- ESTIMATED START DATE: 04/15/2023 ESTIMATED COMPLETION DATE: 01/01/2023
- ITEMS MUST OCCUR IN THE ORDER LISTED; ITEMS CANNOT OCCUR CONCURRENTLY UNLESS SPECIFICALLY NOTED.
- PHASE 1: (INITIAL)
- RECEIVE NPDES COVERAGE FROM DHEC.
  - HOLD PRE-CONSTRUCTION MEETING.
  - NOTIFY DHEC EOC REGIONAL OFFICE OR OCRM OFFICE 48 HOURS PRIOR TO BEGINNING LAND-DISTURBING ACTIVITIES.
  - INSTALLATION OF CONSTRUCTION ENTRANCE.
  - CLEARING & GRUBBING ONLY AS NECESSARY FOR INSTALLATION OF PERIMETER CONTROLS.
  - INSTALLATION OF PERIMETER CONTROLS (E.G. SILT FENCE).
  - INSTALL TREE PROTECTION.
  - INSTALL INLET PROTECTION.
  - INSTALL SEDIMENT TUBES.
  - CLEARING & GRUBBING ONLY IN AREAS OF BASIN.
- PHASES 2 & 3: (INTERMEDIATE & FINAL)
- INSTALLATION OF BASIN AND INSTALLATION OF DIVERSIONS TO THOSE STRUCTURES (OUTLET STRUCTURES MUST BE COMPLETELY INSTALLED AS SHOWN ON THE DETAILS BEFORE PROCEEDING TO NEXT STEP; AREAS DRAINING TO THESE STRUCTURES CANNOT BE DISTURBED UNTIL THE STRUCTURES & DIVERSIONS TO THE STRUCTURES ARE COMPLETELY INSTALLED). INSTALL SURFACE DEWATERING SKIMMER PRIOR TO MOVING TO NEXT STEP.
  - CLEARING & GRUBBING OF SITE OR DEMOLITION (SEDIMENT & EROSION CONTROL MEASURES FOR THESE AREAS MUST ALREADY BE INSTALLED).
  - ROUGH GRADING.
  - INSTALLATION OF STORM DRAIN SYSTEM AND PLACEMENT OF INLET PROTECTION AS EACH INLET IS INSTALLED.
  - INSTALL ALL REQUIRED UTILITIES AND CURBING.
  - FINE GRADING, PAVING, ETC.
  - PLACE TOPSOIL & ESTABLISH FINISH GRADES.
  - PERMEABLE PAVERS SHALL BE LAID WHEN ALL HEAVY CONSTRUCTION IS COMPLETED.
  - CLEAN-OUT OF DETENTION BASINS THAT WERE USED AS SEDIMENT CONTROL STRUCTURES AND RE-GRADING OF DETENTION POND BOTTOMS; IF NECESSARY, MODIFICATION OF SEDIMENT BASIN RISER TO CONVERT TO DETENTION BASIN OUTLET STRUCTURE.
  - INSTALL PERMANENT SEEDING.
  - FLUSH ANY SEDIMENT FROM STORM SEWER PIPES AND INLETS.
  - REMOVAL OF TEMPORARY SEDIMENT & EROSION CONTROL MEASURES (INCLUDING SKIMMER) AFTER ENTIRE AREA DRAINING TO THE STRUCTURE IS FINALLY STABILIZED (THE DEPARTMENT RECOMMENDS THAT THE PROJECT OWNER / OPERATOR HAVE THE SWPPP PREPARER OR REGISTRATION EQUIVALENT APPROVE THE REMOVAL OF TEMPORARY STRUCTURES).
  - PERFORM AS-BUILT SURVEYS OF ALL DETENTION STRUCTURES AND SUBMIT TO DHEC OR MS4 FOR ACCEPTANCE.
  - SUBMIT NOTICE OF TERMINATION (NOT) TO DHEC AS APPROPRIATE.

- NOTE: PERFORM WEEKLY SITE INSPECTIONS DURING LAND DISTURBING ACTIVITIES AND MAKE RECOMMENDATIONS FOR ADDITIONAL BMPs OR MAINTENANCE OF EXISTING BMP.
- NOTE: ALL PUMPED DEWATERING SHALL BE PERFORMED USING AN APPROPRIATELY SIZED PUMPED WATER FILTER BAG.

## SCDHEC-OCRM CERTIFICATION:

"I HAVE PLACED MY SIGNATURE AND SEAL ON THE DESIGN DOCUMENTS SUBMITTED SIGNIFYING THAT I ACCEPT RESPONSIBILITY FOR THE DESIGN OF THE SYSTEM. FURTHER, I CERTIFY TO THE BEST OF MY KNOWLEDGE AND BELIEF THAT THE DESIGN IS CONSISTENT WITH THE REQUIREMENTS OF TITLE 48, CHAPTER 14 OF THE CODE OF LAWS OF SC, 1976 AS AMENDED, PURSUANT TO REGULATION 72-300 ET SEQ. (IF APPLICABLE), AND IN ACCORDANCE WITH THE TERMS AND CONDITIONS OF SCR100000."



NO.	DESCRIPTION	PLAN REVISIONS	DATE
7			
6			
5			
4			
3			
2			
1			



IRONLINE METALS TOWN OF YEMASSEE, SOUTH CAROLINA	RAMSEY DEVELOPMENT, LLC TELL CITY, INDIANA	COVER SHEET & CONSTRUCTION NOTES
---	---	----------------------------------


VERTICAL DATUM: NAVD88	
PROJECT #:	210148
DATE:	02/24/23
DESIGNED BY:	BMT
CHECKED BY:	CPB

SHEET  
**C001**

NOT FOR CONSTRUCTION



THIS DOCUMENT AND ALL REPRODUCIBLE COPIES OF THIS DOCUMENT ARE THE PROPERTY OF WARD EDWARDS, INC. REPRODUCTION OR ALTERATIONS OF THIS DRAWING WITHOUT THE WRITTEN CONSENT OF WARD EDWARDS, INC. IS NOT PERMITTED.



WETLANDS DATA				
Description	Area (Acres)	Per Cent	Area (Acres)	Area (Acres)
Wetland A	0.0000	0.00%	0.0000	0.0000
Wetland B	0.0000	0.00%	0.0000	0.0000
Wetland C	0.0000	0.00%	0.0000	0.0000
Wetland D	0.0000	0.00%	0.0000	0.0000
Wetland E	0.0000	0.00%	0.0000	0.0000
Wetland F	0.0000	0.00%	0.0000	0.0000
Wetland G	0.0000	0.00%	0.0000	0.0000
Wetland H	0.0000	0.00%	0.0000	0.0000
Wetland I	0.0000	0.00%	0.0000	0.0000
Wetland J	0.0000	0.00%	0.0000	0.0000
Wetland K	0.0000	0.00%	0.0000	0.0000
Wetland L	0.0000	0.00%	0.0000	0.0000
Wetland M	0.0000	0.00%	0.0000	0.0000
Wetland N	0.0000	0.00%	0.0000	0.0000
Wetland O	0.0000	0.00%	0.0000	0.0000
Wetland P	0.0000	0.00%	0.0000	0.0000
Wetland Q	0.0000	0.00%	0.0000	0.0000
Wetland R	0.0000	0.00%	0.0000	0.0000
Wetland S	0.0000	0.00%	0.0000	0.0000
Wetland T	0.0000	0.00%	0.0000	0.0000
Wetland U	0.0000	0.00%	0.0000	0.0000
Wetland V	0.0000	0.00%	0.0000	0.0000
Wetland W	0.0000	0.00%	0.0000	0.0000
Wetland X	0.0000	0.00%	0.0000	0.0000
Wetland Y	0.0000	0.00%	0.0000	0.0000
Wetland Z	0.0000	0.00%	0.0000	0.0000

WARD EDWARDS, INC.  
No. 000152  
CERTIFICATE OF  
QUALIFICATION

WARD EDWARDS, INC.  
No. 22816  
No. 02/24/21  
P. L. U. I. S.

WARD EDWARDS, INC.  
No. 000152  
CERTIFICATE OF  
QUALIFICATION

WARD EDWARDS, INC.  
No. 22816  
No. 02/24/21  
P. L. U. I. S.

PLAN REVISIONS		DESCRIPTION	DATE
NO.	NO.		
7			
6			
5			
4			
3			
2			
1			

WARD EDWARDS, INC.  
ENGINEERING

P.O. BOX 381, BLUFFTON, SOUTH CAROLINA 29910  
PH (803) 837-5355 FAX (803) 837-4236  
WWW.WARDEDWARDS.COM

IRONLINE METALS  
TOWN OF YEMASSEE, SOUTH CAROLINA  
RAMSEY DEVELOPMENT, LLC  
TELL CITY, INDIANA

SHEET INDEX

IRONLINE METALS TOWN OF YEMASSEE, SOUTH CAROLINA RAMSEY DEVELOPMENT, LLC TELL CITY, INDIANA	
SHEET INDEX	


VERTICAL DATUM: NAVD88	
PROJECT #:	210148
DATE:	02/24/23
DESIGNED BY:	BMT
CHECKED BY:	CPB

SHEET  
C002

NOT FOR CONSTRUCTION



THIS DOCUMENT AND ALL REPRODUCIBLE COPIES OF THIS DOCUMENT ARE THE PROPERTY OF WARD EDWARDS, INC. REPRODUCTION OR ALTERATIONS OF THIS DRAWING WITHOUT THE WRITTEN CONSENT OF WARD EDWARDS, INC. IS NOT PERMITTED.



### LEGEND

- IPS
- 1/2" REBAR SET
- CONCRETE MONUMENT FOUND
- ⊙ PINCHTOP FOUND
- SS SANITARY SEWER MANHOLE
- Ditch B
- 1/2" REBAR FOUND
- ⊙ 1" PIPE FOUND
- T T-POST FOUND
- POWER POLE
- DRAINAGE DITCH

AREA TABLE			
Description	Perimeter	Sq. Feet	Acres
AREA A	6,698.26	2,017,285.51	46.31
AREA B	7,818.71	1,824,771.31	41.89
AREA C	4,206.48	596,822.44	13.70
Total		4,438,879.25	101.90

LINE	BEARING	DISTANCE
L1	S 54°02'11" W	119.41'
L2	N 38°18'44" W	245.26'
L3	S 54°42'38" E	194.73'
L4	N 43°12'39" W	208.73'
L5	S 50°45'40" W	183.01'
L6	S 60°26'56" W	50.00'
L7	S 60°26'56" W	113.82'
L8	N 48°49'06" E	209.73'
L9	N 40°27'17" W	46.59'
L10	N 40°17'13" W	188.93'
L11	S 44°28'33" E	131.17'
L12	S 49°42'44" W	278.85'
L13	N 85°17'14" W	47.50'
L14	N 40°27'17" W	28.68'
L15	N 44°27'15" W	147.62'
L16	N 43°09'46" W	270.15'
L17	N 40°17'13" W	178.04'
L18	N 60°40'02" E	63.84'
L19	N 29°20'29" W	244.09'
L20	S 29°24'03" E	243.34'
L21	N 59°36'32" E	50.25'
L22	N 29°20'15" W	146.49'
L23	N 29°33'44" W	7.70'

WETLANDS AREA TABLE			
Description	Perimeter	Sq. Feet	Acres
Ditch A	294.59	1,352.19	0.03
Ditch B	3,278.62	20,364.79	0.47
Ditch C	1,528.96	11,826.52	0.27
Ditch D	2,034.71	13,461.15	0.31
Wetland A	8,468.70	2,717,817.99	62.39
Wetland B	172.52	1,661.23	0.04
Wetland C	1,241.41	33,650.55	0.77
Wetland D	433.22	8,261.57	0.19
Wetland E	1,362.85	105,202.51	2.42
Wetland F	295.51	4,680.65	0.11
Total		2,918,279.15	67.00

REFERENCES  
PB 21 PG 417  
PB 32 PG 4  
PB 5 PG 96  
DB 484 PG 261

PB 3 PG 127  
PB 14 PG 64  
PB 3 PG 157

### FLOOD ZONE DETERMINATION



FLOOD ZONE (BFE): A (BFE=NOT DETERMINED) AND X  
COMMUNITY NAME: HAMPTON CO. UNINCORP./TOWN OF YEMASSEE  
COMMUNITY #: 450095/450103  
MAP #: 45049C0450C  
PANEL #: 450 OF 550  
PANEL DATE: SEPTEMBER 29, 2010  
INDEX DATE: SEPTEMBER 29, 2010

THIS FLOOD ZONE DETERMINATION IS APPROXIMATE AND SHOULD BE VERIFIED BY THE APPROPRIATE BUILDING CODES OFFICE BEFORE ANY DESIGN OR CONSTRUCTION BEGINS.

BOUNDARY SURVEY OF  
CORBETT TRACT  
TAX PARCELS 204-01-05-005 AND 203-00-00-046  
YEMASSEE, HAMPTON COUNTY, SOUTH CAROLINA  
PREPARED FOR RAMSEY DEVELOPMENT  
JOB # 6024

FIELD BOOK: ELECTRONIC  
FIELD CREW: LF/PW  
DRAFTER: LF/PW  
DATE OF FIELDWORK: 04/01/2022

LAND CONSULTING GROUP, LLC  
POST OFFICE DRAWER 1366  
BEAUFORT, SOUTH CAROLINA 29901-1366  
(843) 575-5206



THIS PLAT DOES NOT CERTIFY THAT THE INFORMATION SHOWN HEREON COMPLIES WITH LOCAL ZONING REGULATIONS. THIS PLAT DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF OVERLAY DISTRICTS OR SPECIAL HAZARD AREAS SUCH AS BUT NOT LIMITED TO AIRPORT AND AICUZ ZONES.

THIS PLAT REPRESENTS CONDITIONS FOUND ON 4/1/2022 AND DOES NOT REPRESENT CONDITIONS FOUND ON ANY OTHER DATE.

THIS PLAT WAS SURVEYED BASED ON REFERENCED DOCUMENTS AND WAS NOT SURVEYED IN COORDINATION WITH A TITLE EXAMINATION. THE SURVEYOR DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF EASEMENTS.


THE AREA CALCULATIONS SHOWN HEREON WERE DETERMINED BY THE COORDINATE METHOD.

THE PRESENCE OR ABSENCE OF REGULATED NATURAL RESOURCES (SUCH AS, BUT NOT LIMITED TO, CRITICAL AREAS, FRESHWATER WETLANDS, SPECIMEN TREES, AND HISTORICALLY SIGNIFICANT SITES AND CULTURAL RESOURCES) WAS NOT DETERMINED AT THIS TIME OTHER THAN THOSE SHOWN HEREON AND ACCOMPANIED BY THE CERTIFICATION OR APPROVAL OF APPROPRIATE REGULATORY AGENCY.

THIS PLAT DOES NOT CERTIFY TO THE PRESENCE OR ABSENCE OF UNDERGROUND FEATURES, (INCLUDING, BUT NOT LIMITED TO UTILITIES, STORAGE TANKS, AND SIMILAR).

THE VERTICAL DATUM FOR FLOOD ZONE INFORMATION AND TOPOGRAPHY IS NAVD 1988 AND WAS DETERMINED USING THE SC VRS NETWORK.

ZONING AND SETBACKS WERE NOT DETERMINED AT THIS TIME



PLAN REVISIONS	
NO.	DESCRIPTION
7	
6	
5	
4	
3	
2	
1	

**Ward Edwards**  
ENGINEERING  
P.O. BOX 381, BEAUFORT, SOUTH CAROLINA 29910  
PH (843) 575-5206 FAX (843) 575-4236  
WWW.WARDEDWARDS.COM


IRONLINE METALS  
TOWN OF YEMASSEE, SOUTH CAROLINA  
RAMSEY DEVELOPMENT, LLC  
TELL CITY, INDIANA  
EXISTING CONDITIONS PLAN

VERTICAL DATUM:  
NAVD88


PROJECT #:	210148
DATE:	02/24/23
DESIGNED BY:	BMT
CHECKED BY:	CPB

SHEET  
**C101**





IF THIS SHEET IS LESS THAN 22" X 34" IT IS A REDUCED PRINT, SCALE ACCORDINGLY



**Ward  
Edwards**  
ENGINEERING

P.O. BOX 381, BLUFFTON, SOUTH CAROLINA 29910  
PH (843) 837-5250 / FAX (843) 837-2558  
WWW.WARDEWARDS.COM

**IRONLINE METALS**  
TOWN OF YEMASSEE, SOUTH CAROLINA

**RAMSEY DEVELOPMENT, LLC**  
TELL CITY, INDIANA



**EXISTING CONDITIONS PLAN**

VERTICAL DATUM:  
NAVD88

PROJECT #:	210148
DATE:	02/24/23
DESIGNED BY:	BMT
CHECKED BY:	CPB


SHEET  
**C102**

PLAN REVISIONS		DATE
NO.	DESCRIPTION	
1		
2		
3		
4		
5		
6		
7		



NOT FOR CONSTRUCTION



THIS DOCUMENT AND ALL REPRODUCIBLE COPIES OF THIS DOCUMENT ARE THE PROPERTY OF WARD EDWARDS, INC. REPRODUCTION OR ALTERATIONS OF THIS DRAWING WITHOUT THE WRITTEN CONSENT OF WARD EDWARDS, INC. IS NOT PERMITTED.



LIMITS OF DISTURBANCE:		NPDES
EROSION PREVENTION		
LAND GRADING:	LG	OR
SURFACE ROUGHENING:		
TOPSOILING:	TS	
TEMPORARY SEEDING:	TS	
MULCHING:	M	
ECB OR TRM:	ECB	
FGM:	FGM	
BFM:	BFM	
PERMANENT SEEDING:	PS	
SODDING:	SO	
RIPRAP:		
OUTLET PROTECTION:	RIPRAP	ECB or TRM
DUST CONTROL:	DC	
POLYACRYLAMIDE (PAM):	PAM	

SEDIMENT CONTROL	
SEDIMENT BASIN:	
TEMPORARY SEDIMENT TRAP:	
ROCK SEDIMENT DIKE:	
ROCK CHECK DAM:	
SEDIMENT TUBE:	
SILT FENCE:	
REINFORCED SILT FENCE:	
TYPE A - FABRIC INLET PROTECTION:	
TYPE A - SEDIMENT TUBE INLET PROTECTION:	
TYPE B - WIRE MESH AND STONE DROP INLET PROTECTION:	
TYPE C - BLOCK AND GRAVEL INLET PROTECTION:	
TYPE D - RIGID INLET FILTERS:	
TYPE E - SURFACE COURSE CURB INLET FILTER:	
TYPE F - INLET TUBE:	
TYPE FC - FILTER BAG CURB INLET PROTECTION:	
TYPE FB - FILTER BAG GRATE INLET PROTECTION:	
CONCRETE WASHOUT:	

RUNOFF CONVEYANCE MEASURES	
VEGETATED CHANNELS:	
RIPRAP-LINED CHANNELS:	
ECB OR TRM-LINED CHANNELS:	
PAVED CHANNELS:	
PIPE SLOPE DRAINS:	
TEMPORARY STREAM CROSSING:	
TEMPORARY DIVERSION DITCH OR SWALE:	
PERMANENT DIVERSION DITCH:	
DIVERSION DIKE OR BERM:	
LEVEL SPREADER:	
SUBSURFACE DRAIN:	




PLAN REVISIONS	
NO.	DESCRIPTION
7	
6	
5	
4	
3	
2	
1	

**Ward Edwards**  
ENGINEERING  
P.O. BOX 381, BLUFFTON, SOUTH CAROLINA 29910  
PH (803) 827-5353 FAX (803) 827-2556  
WWW.WARDEDWARDS.COM

IRONLINE METALS  
TOWN OF YEMASSEE, SOUTH CAROLINA  
RAMSEY DEVELOPMENT, LLC  
TELL CITY, INDIANA  
**INITIAL EROSION CONTROL PLAN**

VERTICAL DATUM:  
NAVD88  
PROJECT #:  
210148  
DATE:  
02/24/23  
DESIGNED BY:  
BMT  
CHECKED BY:  
CPB  
**SHEET C201**

[illegible]


<b>IRONLINE METALS</b>		 <p><b>Ward Edwards</b> <b>E N G I N E E R I N G</b></p> <p>P.O. BOX 384   BLUEFONTS, SOUTH CAROLINA 29910 PH (803) 827-5250 / FAX (803) 827-2558 WWW.WARDEDWARDS.COM</p>	
TOWN OF YEMASSEE, SOUTH CAROLINA			
RAMSEY DEVELOPMENT, LLC			
TELL CITY, INDIANA			
<b>INITIAL EROSION CONTROL PLAN</b>			
VERTICAL DATUM: NAVD88			
PROJECT #:		210IL8	
DATE:		02/26/23	
DESIGNED BY:		BMT	
CHECKED BY:		CPB	
SHEET			
<b>C202</b>			









THIS DOCUMENT AND ALL REPRODUCIBLE COPIES OF THIS DOCUMENT ARE THE PROPERTY OF WARD EDWARDS, INC. REPRODUCTION OR ALTERATIONS OF THIS DRAWING WITHOUT THE WRITTEN CONSENT OF WARD EDWARDS, INC. IS NOT PERMITTED.





THIS DOCUMENT AND ALL REPRODUCIBLE COPIES OF THIS DOCUMENT ARE THE PROPERTY OF WARD EDWARDS, INC. REPRODUCTION OR ALTERATIONS OF THIS DRAWING WITHOUT THE WRITTEN CONSENT OF WARD EDWARDS, INC. IS NOT PERMITTED.



IRONLINE METALS  
TOWN OF YEMASSEE, SOUTH CAROLINA  
RAMSEY DEVELOPMENT, LLC  
TELL CITY, INDIANA

WARD  
EDWARDS  
ENGINEERING  
P.O. BOX 381, BLUFFTON, SOUTH CAROLINA 29910  
PH (803) 837-5353 FAX (803) 837-4236  
WWW.WARDEDWARDS.COM

VERTICAL DATUM:  
NAVD88

PROJECT #:  
210148

DATE:  
02/24/23

DESIGNED BY:  
BMT

CHECKED BY:  
CPB

SHEET  
C401

PLAN REVISIONS	
NO.	DESCRIPTION
7	
6	
5	
4	
3	
2	
1	


DATE

NOT FOR CONSTRUCTION

IF THIS SHEET IS LESS THAN 22" X 34" IT IS A REDUCED PRINT, SCALE ACCORDINGLY



THIS DOCUMENT AND ALL REPRODUCIBLE COPIES OF THIS DOCUMENT ARE THE PROPERTY OF WARD EDWARDS, INC. REPRODUCTION OR ALTERATIONS OF THIS DRAWING WITHOUT THE WRITTEN CONSENT OF WARD EDWARDS, INC. IS NOT PERMITTED.



GRADING LEGEND	
TOP OF PAVEMENT ELEVATION	TP: 22.50
TOP OF WALK ELEVATION	TW: 22.50
TOP OF CURB ELEVATION	TC: 22.50
FINISH GRADE	FG: 22.5
HIGH POINT	HP
LOW POINT	LP
CONTOUR	19
DITCH CENTERLINE	PD
DIRECTION OF FLOW	
DOORWAY	

Professional Engineer Seal for Ward Edwards, Inc. (No. 22816, Exp. 12/31/24) and Professional Surveyor Seal for Ward Edwards, Inc. (No. 00052, Exp. 12/31/24).

PLAN REVISIONS	
NO.	DESCRIPTION
7	
6	
5	
4	
3	
2	
1	

**Ward Edwards ENGINEERING**  
P.O. BOX 381, BLUFFTON, SOUTH CAROLINA 29910  
PH (803) 837-5355 FAX (803) 837-4236  
WWW.WARDEDWARDS.COM

**IRONLINE METALS**  
TOWN OF YEMASSEE, SOUTH CAROLINA  
**RAMSEY DEVELOPMENT, LLC**  
TELL CITY, INDIANA

VERTICAL DATUM: NAVD88	
PROJECT #:	210148
DATE:	02/24/23
DESIGNED BY:	BMT
CHECKED BY:	CPB

**SHEET C501**

NOT FOR CONSTRUCTION



**AS-BUILT SURVEY REQUIREMENTS**  
 CONTRACTOR IS RESPONSIBLE FOR PROVIDING AN AS-BUILT SURVEY TO THE OWNER. THE SURVEY SHALL CONFORM TO SCDEH AND LOCAL GOVERNMENT REQUIREMENTS. THE SURVEY SHALL INCLUDE THE FOLLOWING AS-BUILT DATA:  
 a. PROPERTY LINES  
 b. BUILDING(S) WITH FINISHED FLOOR ELEVATIONS  
 c. PAVING TO INCLUDE ELEVATIONS ALONG EDGES AND CROWN FLOW LINES  
 d. ADA-ACCESSIBLE RAMPS  
 e. CURB AND GUTTER  
 f. SIDEWALKS  
 g. SIGNAGE  
 h. STORM INLETS WITH PIPE DIAMETER(S), FRAME, AND INVERT ELEVATION  
 i. JUNCTION BOXES WITH PIPE DIAMETER(S), FRAME, AND INVERT ELEVATION  
 j. SANITARY SEWER MANHOLES WITH FRAME AND INVERT ELEVATION  
 k. PUMP STATIONS TO INCLUDE FENCING, CONTROLS, AND ELEVATIONS  
 l. DITCHES TO INCLUDE TOP OF BANK, BOTTOM OF BANK, AND ELEVATIONS  
 m. PONDS TO INCLUDE CONTOURS FROM TOP OF BANK SURFACE TO POND BOTTOM  
 n. WEIR ELEVATIONS AND DIMENSIONS  
 o. OUTLET CONTROL STRUCTURES TO INCLUDE ELEVATION AND OUTLET PIPE INVERTS AND DIAMETERS  
 p. EMERGENCY SPILLWAY DIMENSIONS AND ELEVATIONS  
 q. LOCATIONS AND INVERTS FOR ALL PIPES DISCHARGING TO A BODY OF WATER  
 r. ALL OTHER VISIBLE SITE FEATURES TO INCLUDE VALVES, PEDESTALS, SERVICE YARDS, FENCING, HVAC/MECH.

### AS-BUILT SURVEY REQUIREMENTS

CONTRACTOR IS RESPONSIBLE FOR PROVIDING AN AS-BUILT TOPOGRAPHIC SURVEY OF THE CONSTRUCTED PROJECT SITE. THE SURVEY SHALL CONFORM TO SCDHCE AND LOCAL GOVERNMENT AS-BUILT REQUIREMENTS INCLUDING, BUT NOT NECESSARILY LIMITED TO THE FOLLOWING:

THE SURVEY SHALL BE PREPARED AND SIGNED BY A SOUTH CAROLINA LICENSED LAND SURVEYOR.



A SIGNED HARD COPY AND AUTOCAD FILE SHALL BE PROVIDED TO THE ENGINEER.

ELEVATIONS SHALL BE BASED UPON THE SAME VERTICAL DATUM USED IN THE ENGINEERING PLANS.

THE DRAWING SHALL BE ON THE SC NAD83 STATE PLANE COORDINATE SYSTEM.

THE SURVEY SHALL INCLUDE THE FOLLOWING AS-BUILT INFORMATION TO INCLUDE LOCATION AND ELEVATIONS:

- a. PROPERTY LINES
- b. BUILDING(S) WITH FINISHED FLOOR ELEVATIONS
- c. PAVING TO INCLUDE ELEVATIONS ALONG EDGES AND INTERNAL RIDGES AND VALLEYS (I.E. ROAD CROWNS, INVERTED CROWN FLOW LINES)
- d. ADA-ACCESSIBLE RAMPS
- e. CURB AND GUTTER
- f. SIDEWALKS
- g. SIGNAGE
- h. STORM INLETS WITH PIPE DIAMETER(S), FRAME, AND INVERT
- i. JUNCTION BOXES WITH PIPE DIAMETER(S), FRAME, AND INVERT
- j. SANITARY SEWER MANHOLES WITH FRAME AND INVERT
- k. PUMP STATIONS TO INCLUDE FENCING, CONTROLS, DRIVEWAY, WETWELL TOP/BOTTOM ELEVATIONS
- l. DITCHES TO INCLUDE TOP OF BANK, BOTTOM OF BANK, AND CENTERLINE
- m. POND TO INCLUDE CONTOURS FROM TOP OF BANK TO WATER SURFACE AND MEASURED DEPTH FROM WATER SURFACE TO POND BOTTOM
- n. WEIR ELEVATIONS AND DIMENSIONS
- o. OUTLET CONTROL STRUCTURES TO INCLUDE ELEVATIONS AND DIMENSIONS OF ALL RISERS, GRATES, ORIFICES, WEIRS, AND OUTLET PIPE INVERTS AND DIAMETERS
- p. EMERGENCY SPILLWAY DIMENSIONS AND ELEVATIONS
- q. LOCATIONS AND INVERTS FOR ALL PIPES DISCHARGING INTO THE POND
- r. ALL OTHER VISIBLE SITE FEATURES TO INCLUDE VALVES, FDCs, HYDRANTS, TRANSFORMERS, LIGHT POLES, CLEAN-OUTS, PEDESTALS, SERVICE YARDS, FENCING, HVAC/MECHANICAL DEVICES, AND BOLLARDS.



**IRONLINE METALS**  
TOWN OF YEMASSEE, SOUTH CAROLINA

**RAMSEY DEVELOPMENT, LLC**  
TELL CITY, INDIANA


***DRAINAGE PLAN***

VERTICAL DATUM: NAVD88	
PROJECT #:	210148
DATE:	02/24/23
DESIGNED BY:	BMT
CHECKED BY:	CPB
SHEET <b>C601</b>	

IF THIS SHEET IS LESS THAN 22" X 34" IT IS A REDUCED PRINT, SCALE ACCORDINGLY


NOT FOR CONSTRUCTION

THIS DOCUMENT AND ALL REPRODUCIBLE COPIES OF THIS DOCUMENT ARE THE PROPERTY OF WARD EDWARDS, INC. REPRODUCTION OR ALTERATIONS OF THIS DRAWING WITHOUT THE WRITTEN CONSENT OF WARD EDWARDS, INC. IS NOT PERMITTED.




POND SPILLWAY DETAILS

DETAIL 02660-003




WET DETENTION BASIN WITH BERM CROSS SECTION

DETAIL 02630-033




SUBGRADE DRAIN


DETAIL 02630-014




DETAIL 02630-031



CLEANOUT DETAIL



EMBEDMENT DETAIL FOR REINFORCED CONCRETE PIPE



PLAN REVISIONS	
NO.	DESCRIPTION
7	
6	
5	
4	
3	
2	
1	



IRONLINE METALS
TOWN OF YEMASSEE, SOUTH CAROLINA
RAMSEY DEVELOPMENT, LLC
TELL CITY, INDIANA
DRAINAGE DETAILS


VERTICAL DATUM: NAVD88	
PROJECT #:	210148
DATE:	02/24/23
DESIGNED BY:	BMT
CHECKED BY:	CPB

SHEET
C602

NOT FOR CONSTRUCTION




THIS DOCUMENT AND ALL REPRODUCIBLE COPIES OF THIS DOCUMENT ARE THE PROPERTY OF WARD EDWARDS, INC. REPRODUCTION OR ALTERATIONS OF THIS DRAWING WITHOUT THE WRITTEN CONSENT OF WARD EDWARDS, INC. IS NOT PERMITTED.




STORM DRAIN MANHOLE

DETAIL: 02630-037




CURB INLET WITH FRAME AND COVER

DETAIL 02630-028




GRATE INLET


DETAIL 02630-027




- NOTES:
1. REFER TO SCDOT STD DETAIL 719-009-01 FOR REINFORCEMENT SCHEDULE
  2. ALL CATCH BASINS ARE TO BE PRECAST PRIOR TO INSTALLATION. THE USE OF PRECAST UNITS WILL NOT RELEVE THE CONTRACTOR OF THE RESPONSIBILITY OF OBTAINING SATISFACTORY INSTALLATIONS.
  3. THE BOTTOM SLAB OF THE BOX SHALL BE A MINIMUM OF 6 IN. THICK, CLASS A CONCRETE WITH A REINFORCING STEEL AREA OF 0.20 SQ. IN. PER FOOT. WIRE MESH MAY BE USED IN LIEU OF STEEL BARS PROVIDED A MINIMUM OF 0.20 SQ. IN. PER FT. IS MET.
  4. IF STRUCTURE DEPTH EXCEEDS 4'-6", METAL STEPS ARE TO BE PLACED ON THE WALL.
  5. REINFORCING STEEL SHALL BE DEFORMED AND SHALL CONFORM TO AASHTO M 31. GRADE 60. WIRE MESH SHALL CONFORM TO AASHTO M 55 AND M 221.
  6. THROAT OPENING SHALL BE 32" WIDE AND SHOULD BE AT ELEVATIONS AS SPECIFIED ON PLANS, ON THE NUMBER OF SIDES AS SPECIFIED ON PLANS.



DETAIL MODIFIED TYPE 9 WEIR OUTFALL



NO.	DESCRIPTION	DATE
7		
6		
5		
4		
3		
2		
1		



IRONLINE METALS
TOWN OF YEMASSEE, SOUTH CAROLINA
RAMSEY DEVELOPMENT, LLC
TELL CITY, INDIANA
DRAINAGE DETAILS

VERTICAL DATUM:	NAVD88
PROJECT #:	210168
DATE:	02/24/23
DESIGNED BY:	BMT
CHECKED BY:	CPB

SHEET  
**C603**

THIS DOCUMENT AND ALL REPRODUCIBLE COPIES OF THIS DOCUMENT ARE THE PROPERTY OF WARD EDWARDS, INC. REPRODUCTION OR ALTERATIONS OF THIS DRAWING WITHOUT THE WRITTEN CONSENT OF WARD EDWARDS, INC. IS NOT PERMITTED.


SHEET 2 bottom

SHEET 2 top

SHEET 1

WATER SYSTEM LEGEND	
	PROPOSED
WATER METER	□
WATER VALVE	⊙
REDUCER	▼
POST INDICATOR VALVE	⊗
FIRE HYDRANT	⊙
BLOWOFF HYDRANT	⊙
YARD HYDRANT	⊙
FIRE DEPART. CONN. (FDC)	⊙
CAP	⊙
PLUG	⊙
BACKFLOW PREVENTOR	⊙
BUTTERFLY VALVE	⊙
FITTINGS	⊙
WATER LINE	WL
SERVICE LATERAL	

SANITARY SEWER LEGEND	
	PROPOSED
SANITARY SEWER MANHOLE	⊙ MH: A1
SANITARY SEWER CLEANOUT	● CO
SANITARY SEWER WYE	⊙
CHECK VALVE IN MANHOLE	⊙
PLUG VALVE	⊙
AIR RELEASE VALVE	⊙
SEWER LINE	SS
FORCE MAIN	FM
SERVICE LATERAL	



PLAN REVISIONS	
NO.	DESCRIPTION
7	
6	
5	
4	
3	
2	
1	



**Ward Edwards**  
ENGINEERING

P.O. BOX 381, BLUFFTON, SOUTH CAROLINA 29910  
PH (803) 837-5353 FAX (803) 837-4336  
WWW.WARDEDWARDS.COM


IRONLINE METALS  
TOWN OF YEMASSEE, SOUTH CAROLINA

RAMSEY DEVELOPMENT, LLC  
TELL CITY, INDIANA

OVERALL UTILITY PLAN

VERTICAL DATUM: NAVD88	
PROJECT #:	210148
DATE:	02/24/23
DESIGNED BY:	BMT
CHECKED BY:	CPB

SHEET  
C700




IF THIS SHEET IS LESS THAN 22" X 34" IT IS A REDUCED PRINT, SCALE ACCORDINGLY

NOT FOR CONSTRUCTION



THIS DOCUMENT AND ALL REPRODUCIBLE COPIES OF THIS DOCUMENT ARE THE PROPERTY OF WARD EDWARDS, INC. REPRODUCTION OR ALTERATIONS OF THIS DRAWING WITHOUT THE WRITTEN CONSENT OF WARD EDWARDS, INC. IS NOT PERMITTED.



**Ward Edwards**  
ENGINEERING  
P.O. BOX 381, BLUFFTON, SOUTH CAROLINA 29910  
PH (803) 837-5353 FAX (803) 837-4236  
WWW.WARDEDWARDS.COM

IRONLINE METALS  
TOWN OF YEMASSEE, SOUTH CAROLINA  
RAMSEY DEVELOPMENT, LLC  
TELL CITY, INDIANA  
UTILITY PLAN

VERTICAL DATUM:  
NAVD88

PROJECT #:  
210148

DATE:  
02/24/23

DESIGNED BY:  
BMT



CHECKED BY:  
CPB

SHEET  
C701

NOT FOR CONSTRUCTION



THIS DOCUMENT AND ALL REPRODUCIBLE COPIES OF THIS DOCUMENT ARE THE PROPERTY OF WARD EDWARDS, INC. REPRODUCTION OR ALTERATIONS OF THIS DRAWING WITHOUT THE WRITTEN CONSENT OF WARD EDWARDS, INC. IS NOT PERMITTED.



IF THIS SHEET IS LESS THAN 22" X 34" IT IS A REDUCED PRINT, SCALE ACCORDINGLY

Professional Engineer  
Carol M. Edwards  
No. 22816  
SSW302/24/27

Professional Engineer  
Ward Edwards, Inc.  
No. 00052  
SSW302/24/27

WARD EDWARDS, INC.  
No. 00052  
SSW302/24/27

CERTIFICATE OF AUTHORITY

PLAN REVISIONS	
NO.	DESCRIPTION
7	
6	
5	
4	
3	
2	
1	
	DATE

WARD EDWARDS, INC.  
No. 00052  
SSW302/24/27

CERTIFICATE OF AUTHORITY

WARD EDWARDS, INC.  
No. 22816  
SSW302/24/27

Professional Engineer

WARD EDWARDS, INC.  
No. 00052  
SSW302/24/27

CERTIFICATE OF AUTHORITY


IRONLINE METALS  
TOWN OF YEMASSEE, SOUTH CAROLINA  
RAMSEY DEVELOPMENT, LLC  
TELL CITY, INDIANA

UTILITY PLAN

VERTICAL DATUM: NAVD88	
PROJECT #:	210148
DATE:	02/24/23
DESIGNED BY:	BMT
CHECKED BY:	CPB


SHEET  
C702

NOT FOR CONSTRUCTION




## SANITARY SEWER BEDDING

DETAIL 02530-00




## PRECAST CONCRETE COLLAR

DETAIL 02510-02




## BLOW OFF DETAIL

DETAIL 02510-02




### PRESSURE PIPE UNDER WET UTILITY FOR FINAL DEPTH 5' OR GREATER



### WET UTILITY CROSSING


WET UTILITY CROSSING



## TEE AND VALVES

PAUL R. MOORE  
ENGINEER  
LICENSE NO. 22816  
STATE OF NORTH CAROLINA  
02/24/12

7		
6		
5		
4		
3		
2		
1		
NO.	DESCRIPTION	DATE



**Ward  
Edwards**  
ENGINEERING

P.O. BOX 381, BLUFFTON, SOUTH CAROLINA 29910  
PH (843) 837-5250 / FAX (843) 837-2558

IRONLINE METALS

TOWN OF YEMASSEE, SOUTH CAROLINA

RAMSEY DEVELOPMENT, LLC

TELL CITY, INDIANA

UTILITY DETAILS


VERTICAL DATUM: NAVD88	
PROJECT #:	21014
DATE:	02/24/20
DESIGNED BY:	BM
CHECKED BY:	CF

SHEET  
**C703**

IF THIS SHEET IS LESS THAN 22" X 34" IT IS A REDUCED PRINT, SCALE ACCORDINGLY


**NOT FOR CONSTRUCTION**

THIS DOCUMENT AND ALL REPRODUCIBLE COPIES OF THIS DOCUMENT ARE THE PROPERTY OF WARD EDWARDS, INC. REPRODUCTION OR ALTERATIONS OF THIS DRAWING WITHOUT THE WRITTEN CONSENT OF WARD EDWARDS, INC. IS NOT PERMITTED.




PIPE TRENCH BEDDING

DETAIL 02510-004



TAPPING SLEEVE AND VALVE


DETAIL 02510-006



CONDUIT NOTES:

1. ALL CONDUIT ENDS SHALL BE CAPPED AND MARKED AS ILLUSTRATED.
2. ELECTRICAL CONDUIT: 42" BURY DEPTH, SCH 40 ELECTRICAL GRADE (N.E.C.) PVC
3. TELCO CONDUIT: 36" BURY DEPTH, SCH 40 ELECTRICAL GRADE (N.E.C.) PVC
4. IRRIGATION CONDUIT: 24" BURY DEPTH, SCH 40 PVC
5. MINIMUM 12" VERTICAL CLEARANCE WHEN CROSSING WATER, SEWER, AND DRAINAGE.
6. MINIMUM 18" HORIZONTAL CLEARANCE WHEN PARALLELING WATER, SEWER, AND DRAINAGE.
7. MINIMUM 12" HORIZONTAL SEPARATION BETWEEN CONDUIT.
8. CONDUIT MUST EXTEND BEYOND PAVEMENT, CURB, AND SIDEWALKS.
9. THE CONTRACTOR MUST INSTALL ALL CONDUITS, AS SHOWN ON THE PLANS OR AS REQUIRED BY DRY UTILITY COMPANIES. THE CONTRACTOR SHALL BE RESPONSIBLE TO ENSURE STRICT COMPLIANCE WITH ALL APPLICABLE CODES AND REGULATIONS WITH REGARDS TO THE INSTALLATION OF UTILITIES AND CONDUIT.
10. REFER TO PLANS FOR CONDUIT SIZE AND LOCATION. PLAN VIEW LOCATIONS OF CONDUIT ARE APPROXIMATE.
11. NO 90° OR 45° COUPLINGS TO BE USED ON CONDUIT.
12. CONDUIT MUST BE STRAIGHT TO ALLOW PIPE AND/OR WIRING BY UTILITY COMPANY AND IRRIGATION INSTALLER.
13. CONDUIT NOT INSTALLED AT PROPER DEPTH WILL BE REINSTALLED TO CONFORM TO DETAIL.
14. CONTRACTOR TO VERIFY CONDUIT INTEGRITY PRIOR TO FINAL PAVING.

CONDUIT DETAIL




FIELD ADJUSTMENT INSTRUCTIONS


1. REMOVE THE BODY FROM THE TOP OF THE INDICATOR POST ASSEMBLY.
2. CUT THE REQUIRED LENGTH OFF THE BOTTOM OF THE STANDPIPE FOR THE GROUND LINE TO MATCH UP WITH STANDPIPE GROUND LINE MARK.
3. CUT THE 1" SQ. EXTENSION AT A DISTANCE OF 9" ABOVE THE TOP OF THE STANDPIPE.
4. SET THE "OPEN" AND "SHUT" TARGETS FOR THE APPROPRIATE VALVE SIZE.
5. RE-ATTACH THE BODY TO THE TOP OF THE INDICATOR POST ASSEMBLY.
6. ALL POST INDICATOR VALVES SHALL BE INSTALLED WITH AN ELECTRONIC UL LISTED TAMPER SWITCH.
7. THERE SHALL BE 36" OF UNOBSTRUCTED CLEARANCE AROUND THE PERIMETER OF ALL POST INDICATOR VALVES.
8. POST INDICATOR VALVE SHALL BE LOCATED AT A MINIMUM 40-FT FROM BUILDING.

STANDARD POST INDICATOR VALVE

DETAIL 02510-032A



UTILITY CONDUIT TRENCH DETAIL




NOTES:


- ① WHERE GALVANIZED STEEL PIPE IS INSTALLED UNDERGROUND FOR FIRE DEPARTMENT CONNECTION PIPING, PIPING SHALL BE EXTERNALLY COATED AND WRAPPED INCLUDING ALL CLAMPS, TIE RODS AND BOLTED JOINT ACCESSORIES PER NFPA 13.

FREE STANDING FIRE DEPARTMENT CONNECTION DETAIL

NOT TO SCALE



NOTE: CONTRACTOR TO INSTALL TRACER WIRE OVER PIPE




TYPICAL WATER SERVICE CONNECTION

DETAIL 02510-001


NOTES:

1. ALL FIRE HYDRANT LEADS TO BE DUCTILE IRON WITH MECHANICAL JOINTS. HYDRANTS TO BE LOCATED 3' TO 10' BEHIND EDGE OF PAVEMENT OR 1' INSIDE RIGHT-OF-WAY AND ON PROPERTY LINE BETWEEN TWO LOTS. VERIFY LOCATION W/HILTON HEAD P.S.D..
2. ALL FITTINGS SHALL BE MECHANICAL JOINTS AT TEES, GATE VALVES & FIRE HYDRANTS.



FIRE HYDRANT VALVE AND TEE SETTING

DETAIL 02510-019



NO.	DESCRIPTION	DATE
7		
6		
5		
4		
3		
2		
1		




IRONLINE METALS TOWN OF YEMASSEE, SOUTH CAROLINA RAMSEY DEVELOPMENT, LLC TELL CITY, INDIANA	UTILITY DETAILS
--	-----------------

VERTICAL DATUM: NAVD88	PROJECT #: 210148
DATE: 02/24/23	DESIGNED BY: BMT
CHECKED BY:	CPB

SHEET  
**C704**






- NOTES:
1. INSTALL ASSEMBLY ON THE CUSTOMER SIDE OF THE FLEET PRIOR TO ANY BRANCH, TEE OR SERVICE CONNECTION.
  2. INSTALL ASSEMBLY IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
  3. ASSEMBLY SHALL BE SELECTED FROM LATEST EDITION OF THE SUDAS NOTIFICATION OF APPROVED BACKFLOW PREVENTION ASSEMBLIES FOR SOUTH CAROLINA AND SHALL BE IN FULL CONFORMANCE WITH AWWA C510-89.
  4. CONCRETE SLAB STABILIZES SUPPORTS BETWEEN ASSEMBLY AND GROUND.
  5. APPROPRIATE THRUST RESTRAINT AND SUPPORT MEASURES ARE TO BE DETERMINED BY THE OWNER/INSTALLER.
  6. 4" OR GREATER ASSEMBLY SHALL REQUIRE PIPE SUPPORT
  7. ASSEMBLY SHALL BE TESTED IMMEDIATELY AFTER INSTALLATION AND AT LEAST ONCE A YEAR HEREFTER BY A SCODGE-CERTIFIED TESTER.

### DOUBLE CHECK VALVE ASSEMBLY (ABOVE GROUND)

DETAIL 02510-033



- NOTES:**
2. 1" MIN. COPPER, DIP, OR BRONZE INLET AND OUTLET.
  3. BACKFLOW SLAB STABILIZES SUPPORTS BETWEEN BACKFLOW AND GROUND. SIZE ACCORDINGLY OR BY MANUFACTURER'S RECOMMENDATIONS.
  4. 4" OR GREATER BACKFLOW ASSEMBLIES SHALL REQUIRE PIPE SUPPORTS.
  5. BACKFLOW PREVENTION ASSEMBLY SHALL BE TESTED IMMEDIATELY AFTER INSTALLATION AND SHALL PASS ONE OF THE FOLLOWING TESTS: A. A SCHEC-CERTIFIED TESTER.
  6. BACKFLOW PREVENTION ASSEMBLY SHALL BE SUBJECT TO PRODUCTION TESTING OF APPROVED TYPE. TESTING SHALL BE IN ACCORDANCE WITH "LIST OF APPROVED BACKFLOW PREVENTION ASSEMBLIES FOR SOUTH CAROLINA" AND SHALL BE IN FULL COMPLIANCE WITH AWWA C511-89.
  7. BACKFLOW PREVENTION ASSEMBLY SHALL BE INSTALLED ON THE CUSTOMER'S SIDE OF THE METER PRIOR TO ANY BRANCH, TEE, OR SERVICE CONNECTION.
  8. INSTALL ASSEMBLY IN ACCORDANCE WITH MANUFACTURER'S INSTRUCTIONS.
  9. IF AN ABOVE-GROUND ENCLOSURE IS USED, PROVIDE MINIMUM 6" CLEARANCE ON ALL SIDES. PROVIDE TWO DRAIN HOLES, EQUAL IN SIZE TO RELIEF VALVE VENT OPENING, AT THE BASE OF THE ENCLOSURE.

**NOTE:**  
APPROPRIATE THRUST RESTRAINT AND  
SUPPORT MEASURES ARE TO BE DETERMINED  
BY OWNER/INSTALLER.

## REDUCED PRESSURE PRINCIPLE BACKFLOW PREVENTION ASSEMBLY

DETAIL 02510-035



**Ward  
Edwards**  
ENGINEERING

**IRONLINE METALS**  
TOWN OF YEMASSEE, SOUTH CAROLINA

---


**RAMSEY DEVELOPMENT, LLC**  
TELL CITY, INDIANA

## UTILITY DETAILS

VERTICAL DATUM  
NAVD88

PROJECT #:	210148
DATE:	02/24/23
DESIGNED BY:	BMT
CHECKED BY:	CPB


SHEET  
**C705**



**NOT FOR CONSTRUCTION**



THIS DOCUMENT AND ALL REPRODUCIBLE COPIES OF THIS DOCUMENT ARE THE PROPERTY OF WARD EDWARDS, INC. REPRODUCTION OR ALTERATIONS OF THIS DRAWING WITHOUT THE WRITTEN CONSENT OF WARD EDWARDS, INC. IS NOT PERMITTED.



LIMITS OF DISTURBANCE: NPDES

EROSION PREVENTION

LAND GRADING: LG OR

SURFACE ROUGHENING:

TOPSOILING:

TEMPORARY SEEDING: TS

MULCHING: M

ECB OR TRM:

FGM:

BFM:

PERMANENT SEEDING: PS

SODDING: SO

RIPRAP:

OUTLET PROTECTION: RIPRAP ECB OR TRM

DUST CONTROL: DC

POLYACRYLAMIDE (PAM): PAM

SEDIMENT CONTROL

SEDIMENT BASIN:

TEMPORARY SEDIMENT TRAP:

ROCK SEDIMENT DIKE:

ROCK CHECK DAM:

SEDIMENT TUBE:

SILT FENCE:

REINFORCED SILT FENCE:

TYPE A-FABRIC INLET PROTECTION:

TYPE A-SEDIMENT TUBE INLET PROTECTION:

TYPE B - WIRE MESH AND STONE DROP INLET PROTECTION:

TYPE C - BLOCK AND GRAVEL INLET PROTECTION:

TYPE D - RIGID INLET FILTERS:

TYPE E - SURFACE COURSE CURB INLET FILTER:

TYPE F - INLET TUBE:

TYPE FC - FILTER BAG CURB INLET PROTECTION:

TYPE FB - FILTER BAG GRATE INLET PROTECTION:

CONCRETE WASHOUT

RUNOFF CONVEYANCE MEASURES

VEGETATED CHANNELS:

RIPRAP-LINED CHANNELS:

ECB OR TRM-LINED CHANNELS:

PAVED CHANNELS: PC PC PC

PIPE SLOPE DRAINS:

TEMPORARY STREAM CROSSING:

TEMPORARY DIVERSION DITCH OR SWALE:

PERMANENT DIVERSION DITCH:

DIVERSION DIKE OR BERM:

LEVEL SPREADER:

SUBSURFACE DRAIN:

0 40 80 Feet

SCALE: 1"= 40'

0 40 80 Feet

SCALE: 1"= 40'

VERTICAL DATUM: NAVD88

PROJECT #: 210148

DATE: 02/24/23

DESIGNED BY: BMT

CHECKED BY: CPB

SHEET C801

IRONLINE METALS

TOWN OF YEMASSEE, SOUTH CAROLINA

RAMSEY DEVELOPMENT, LLC

TELL CITY, INDIANA

INTERMEDIATE EROSION CONTROL PLAN

WARD EDWARDS ENGINEERING

P.O. BOX 381, BLUFFTON, SOUTH CAROLINA 29910

PH (803) 837-5353 FAX (803) 837-4236

WWW.WARDEDWARDS.COM

NO. 1 2 3 4 5 6 7



DATE

DESCRIPTION

PLAN REVISIONS



THIS DOCUMENT AND ALL REPRODUCIBLE COPIES OF THIS DOCUMENT ARE THE PROPERTY OF WARD EDWARDS, INC. REPRODUCTION OR ALTERATIONS OF THIS DRAWING WITHOUT THE WRITTEN CONSENT OF WARD EDWARDS, INC. IS NOT PERMITTED.



Professional Engineer  
CAROLINA  
No. 22816  
P.L.L.C.  
WARD EDWARDS, INC.  
No. 000152  
CERTIFICATE OF QUALIFICATION

NO.	DESCRIPTION	DATE
1		
2		
3		
4		
5		
6		
7		

**Ward Edwards**  
ENGINEERING  
P.O. BOX 381, BLUFFTON, SOUTH CAROLINA 29910  
PH (803) 877-5355 FAX (843) 877-4236  
WWW.WARDEDWARDS.COM

IRONLINE METALS  
TOWN OF YEMASSEE, SOUTH CAROLINA  
RAMSEY DEVELOPMENT, LLC  
TELL CITY, INDIANA  
**INTERMEDIATE EROSION CONTROL PLAN**

VERTICAL DATUM: NAVD88	PROJECT #: 210148
DATE: 02/24/23	DESIGNED BY: BMT
CHECKED BY: CPB	

**SHEET  
C802**





## TRACKING


STANDARD DRAWING NO. EC-01 Page 1

APPROVED BY: \_\_\_\_\_ AUGUST, 200 \_\_\_\_\_  
NAME DATE

APPROVED BY: \_\_\_\_\_  
SCDHFC



PLAN SYMBOL



Type A

SEDIMENT TUBE INLET PROTECTION

STANDARD DRAWING NO. SC-07A PAGE 1 of 2


NOT TO SCALE

DATE \_\_\_\_\_

[illegible]

## TEMPORARY SEEDING - COASTAL

DETAIL 02370-011



NOTES:

1. PLACE ALL RIP RAP ON 8 OUNCE NON-WOVEN FILTER CLOTH.
2. STAKING OF FILTER CLOTH PER MANUFACTURER'S SPECIFICATIONS.
3. LENGTH OF OUTLET STABILIZATION = 8 TIMES PIPE DIA.  
TOP WIDTH OF OUTLET STABILIZATION = 3 TIMES PIPE DIA.  
BOTTOM WIDTH OF OUTLET STABILIZATION = 6 TIMES PIPE DIA.



DTES:

- LETTERS A MINIMUM OF 5" IN HEIGHT

  1. ACTUAL LAYOUT DETERMINED IN FIELD.
  2. INSTALL CONCRETE WASHOUT SIGN (24"x24", MINIMUM) WITHIN 30' OF THE TEMPORARY CONCRETE WASHOUT FACILITY.
  3. TEMPORARY WASHOUT AREA MUST BE AT LEAST 50' FROM A STORM DRAIN, CREEK BANK OR PERIMETER CONTROL.
  4. CLEAN OUT CONCRETE WASHOUT AREA WHEN 50% FULL.
  5. THE KEY TO FUNCTIONAL CONCRETE WASHOUTS IS WEEKLY INSPECTIONS, ROUTINE MAINTENANCE, AND REGULAR CLEAN OUT.
  6. SILT FENCE SHALL BE INSTALLED AROUND PERIMETER OF CONCRETE WASHOUT AREA EXCEPT FOR THE SIDE UTILIZED FOR ACCESSING THE WASHOUT.
  7. A ROCK CONSTRUCTION ENTRANCE MAY BE NECESSARY ALONG ONE SIDE OF THE WASHOUT TO PROVIDE VEHICLE ACCESS.

CONCRETE WASHOUT SIGN DETAIL

<b>South Carolina Department of Health and Environmental Control</b>	
<b>CONCRETE WASHOUT</b>	
STANDARD DRAWING NO. _____	EXCAVATED
REVISED PAGE 1 of 1	

CONCRETE WASHOUT

EXCAVATED PIT

RD DRAWING NO. RC-08 P

Page 1 of 1

## RIP RAP OUTLET STABILIZATION DETAIL

DETAIL #02370-009

7			
6			
5			
4			
3			
2			
1			
NO.	DESCRIPTION	DATE	




**IRONLINE METALS**  
TOWN OF YEMASSEE, SOUTH CAROLINA  
RAMSEY DEVELOPMENT, LLC

## INTERMEDIATE EROSION CONTROL DETAILS


VERTICAL DATUM:  
NAVD88

PROJECT #:	210148
DATE:	02/24/23
DESIGNED BY:	BMT
CHECKED BY:	CPB


SHEET  
**C803**



PAVING HATCH LEGEND	
PROPOSED CONCRETE PAVING	
PROPOSED PERVIOUS CONCRETE PAVING	
PROPOSED SIDEWALK / CONCRETE	
REINFORCED GRASS FIRE LANE	
PROPOSED AGGREGATE / STONES	
PROPOSED ASPHALT (LIGHT DUTY)	
PROPOSED ASPHALT (HEAVY DUTY)	
MILL & OVERLAY ASPHALT	
PROPOSED CONCRETE PAVERS	



7	
6	
5	
4	
3	
2	
1	
NO.	DESCRIPTION OF AN DEVIATIONS
	DATE



**Ward  
Edwards**  
ENGINEERING

P.O. BOX 381, BLUFFTON, SOUTH CAROLINA 29910  
PH (843) 837-5250 / FAX (843) 837-2558  
[WWW.WARDEDFWARDS.COM](http://WWW.WARDEDFWARDS.COM)

**IRONLINE METALS**  
TOWN OF YEMASSEE, SOUTH CAROLINA  
**RAMSEY DEVELOPMENT, LLC**  
TELL CITY, INDIANA

***PAVING PLAN***

VERTICAL DATUM: NAVD88	
PROJECT #:	210148
DATE:	02/24/23
DESIGNED BY:	BMT
CHECKED BY:	CP

SHEET  
**C901**


NOT FOR CONSTRUCTION







THIS DOCUMENT AND ALL REPRODUCIBLE COPIES OF THIS DOCUMENT ARE THE PROPERTY OF WARD EDWARDS, INC. REPRODUCTION OR ALTERATIONS OF THIS DRAWING WITHOUT THE WRITTEN CONSENT OF WARD EDWARDS, INC. IS NOT PERMITTED.



LIMITS OF DISTURBANCE: NPDES

EROSION PREVENTION

LAND GRADING:	LG OR
SURFACE ROUGHENING:	
TOPSOILING:	TS
TEMPORARY SEEDING:	TS
MULCHING:	M
ECB OR TRM:	ECB
FGM:	FGM
BFM:	BFM
PERMANENT SEEDING:	PS
SODDING:	SO
RIPRAP:	
OUTLET PROTECTION:	RIPRAP ECB or TRM
DUST CONTROL:	DC
POLYACRYLAMIDE (PAM):	PAM

SEDIMENT CONTROL

SEDIMENT BASIN:	
TEMPORARY SEDIMENT TRAP:	
ROCK SEDIMENT DIKE:	
ROCK CHECK DAM:	
SEDIMENT TUBE:	
SILT FENCE:	
REINFORCED SILT FENCE:	
TYPE A - FABRIC INLET PROTECTION:	A
TYPE A - SEDIMENT TUBE INLET PROTECTION:	
TYPE B - WIRE MESH AND STONE DROP INLET PROTECTION:	B
TYPE C - BLOCK AND GRAVEL INLET PROTECTION:	C
TYPE D - RIGID INLET FILTERS:	D
TYPE E - SURFACE COURSE CURB INLET FILTER:	E
TYPE F - INLET TUBE:	F
TYPE FC - FILTER BAG CURB INLET PROTECTION:	FC
TYPE FB - FILTER BAG GRATE INLET PROTECTION:	FB
CONCRETE WASHOUT:	CWS

RUNOFF CONVEYANCE MEASURES

VEGETATED CHANNELS:	
RIPRAP-LINED CHANNELS:	
ECB OR TRM-LINED CHANNELS:	
PAVED CHANNELS:	PC PC PC
PIPE SLOPE DRAINS:	
TEMPORARY STREAM CROSSING:	
TEMPORARY DIVERSION DITCH OR SWALE:	TD TD
PERMANENT DIVERSION DITCH:	PD PD
DIVERSION DIKE OR BERM:	DD DB
LEVEL SPREADER:	
SUBSURFACE DRAIN:	SSD SSD

FINAL EROSION CONTROL NOTE

CONTRACTOR SHALL REMOVE ALL INITIAL AND INTERMEDIATE EROSION AND SEDIMENT CONTROL MEASURES AFTER CONSTRUCTION IS COMPLETE AND ALL FINAL MEASURES HAVE BEEN SUCCESSFULLY INSTALLED AND STABILIZED.

0 40 80 Feet

SCALE: 1" = 40'

IRONLINE METALS

TOWN OF YEMASSEE, SOUTH CAROLINA

RAMSEY DEVELOPMENT, LLC

TELL CITY, INDIANA

FINAL EROSION CONTROL PLAN

VERTICAL DATUM:

NAVD88

PROJECT #:

210148

DATE:

02/24/23

DESIGNED BY:

BMT

CHECKED BY:

CPB

SHEET

C1001

WARD EDWARDS ENGINEERING



P.O. BOX 381, BLUFFTON, SOUTH CAROLINA 29910

PH (803) 837-5353 FAX (803) 837-4236

WWW.WARDEDWARDS.COM

NOT FOR CONSTRUCTION

THIS DOCUMENT AND ALL REPRODUCIBLE COPIES OF THIS DOCUMENT ARE THE PROPERTY OF WARD EDWARDS, INC. REPRODUCTION OR ALTERATIONS OF THIS DRAWING WITHOUT THE WRITTEN CONSENT OF WARD EDWARDS, INC. IS NOT PERMITTED.



Professional Engineer  
CAROLINA  
No. 22816  
P.L.U.I.

Professional Engineer  
CAROLINA  
No. 00052  
P.L.U.I.

NO.	DESCRIPTION	DATE
1		
2		
3		
4		
5		
6		
7		

**Ward Edwards**  
ENGINEERING

P.O. BOX 381, BLUFFTON, SOUTH CAROLINA 29910  
PH (803) 877-5355 FAX (843) 877-4236  
WWW.WARDEDWARDS.COM

IRONLINE METALS  
TOWN OF YEMASSEE, SOUTH CAROLINA  
RAMSEY DEVELOPMENT, LLC  
TELL CITY, INDIANA

FINAL EROSION CONTROL PLAN

VERTICAL DATUM: NAVD88	PROJECT #: 210148
DATE: 02/24/23	DESIGNED BY: BMT
CHECKED BY: CPB	

SHEET  
**C1002**

THIS DOCUMENT AND ALL REPRODUCIBLE COPIES OF THIS DOCUMENT ARE THE PROPERTY OF WARD EDWARDS, INC. REPRODUCTION OR ALTERATIONS OF THIS DRAWING WITHOUT THE WRITTEN CONSENT OF WARD EDWARDS, INC. IS NOT PERMITTED.

PERMANENT SEEDING – COASTAL

SPECIES	LBS/AC	JAN	FEB	MAR	APR	MAY	JUN	JUL	AUG	SEP	OCT	NOV	DEC
SANDY, DROUGHTY SITES													
BROWNTOP MILLET	10 LBS/AC												
BAHIAGRASS	40 LBS/AC												
BROWNTOP MILLET	10 LBS/AC												
BAHIAGRASS	30 LBS/AC												
SERICEA LESPEDEZA	40 LBS/AC												
BROWNTOP MILLET	10 LBS/AC												
ATLANTIC COASTAL PANICGRASS	15 LBS/AC												
PLS													
BROWNTOP MILLET	10 LBS/AC												
SWITCHGRASS	8 LBS/AC												
(ALAMO)	PLS												
LITTLE BLUESTEM	4 LBS/AC												
SERICEA LESPEDEZA	20 LBS/AC												
BROWNTOP MILLET	10 LBS/AC												
WEEPING LOVEGRASS	8 LBS/AC												
WELL DRAINED, CLAYEY/LOAMEY SITES													
BROWNTOP MILLET	10 LBS/AC												
BAHIAGRASS	40 LBS/AC												
RYE, GRAIN	10 LBS/AC												
BAHIAGRASS	40 LBS/AC												
CLOVER, CRIMSON (ANNUAL)	5 LBS/AC												
BROWNTOP MILLET	10 LBS/AC												
BAHIAGRASS	30 LBS/AC												
SERICEA LESPEDEZA	40 LBS/AC												
BROWNTOP MILLET	10 LBS/AC												
BERMUDA, COMMON	10 LBS/AC												
SERICEA LESPEDEZA	40 LBS/AC												
BROWNTOP MILLET	10 LBS/AC												
BERMUDA, COMMON	12 LBS/AC												
KOBE LESPEDEZA (ANNUAL)	10 LBS/AC												
BROWNTOP MILLET	10 LBS/AC												
BAHIAGRASS	20 LBS/AC												
BERMUDA, COMMON	6 LBS/AC												
SERICEA LESPEDEZA	40 LBS/AC												
BROWNTOP MILLET	10 LBS/AC												
SWITCHGRASS	8 LBS/AC												
LITTLE BLUESTEM	PLS												
INDIANGRASS	3 LBS/AC												
PLS	3 LBS/AC												
PLS													

PS

PERMANENT SEEDING - COASTAL

DETAIL 02370-010

Professional Engineer  
No. 22816  
02/24/23  
PLU 1

Professional Engineer  
No. 00052  
02/24/23  
PLU 1

WARD EDWARDS, INC.  
No. 00052  
02/24/23  
PLU 1

WARD EDWARDS, INC.  
No. 00052  
02/24/23  
PLU 1

NO.	DESCRIPTION	DATE
7		
6		
5		
4		
3		
2		
1		

Ward Edwards  
ENGINEERING

P.O. BOX 381 BLUEFORD, SOUTH CAROLINA 29910  
PH (803) 837-5350 / FAX (843) 837-2558  
WWW.WARDEDWARDS.COM

IRONLINE METALS  
TOWN OF YEMASSEE, SOUTH CAROLINA  
RAMSEY DEVELOPMENT, LLC  
TELL CITY, INDIANA

FINAL EROSION CONTROL  
DETAILS




VERTICAL DATUM: NAVD88	
PROJECT #:	210168
DATE:	02/24/23
DESIGNED BY:	BMT
CHECKED BY:	CPB

SHEET


C803

NOT FOR CONSTRUCTION









Plan View  
Scale - 1" = 25ft

# COMPREHENSIVE SWPPP (C-SWPPP)

---

## IRONLINE METALS

Prepared for Town of Yemassee  
Yemassee, South Carolina

12/21/2022



P.O. Box 381  
Bluffton, SC 29910  
843.837.5250 (T)  
843.837.2558 (F)

SWPPP Preparer:  
Paul Moore, PE  
pmoore@wardedwards.com  
WE Project: 210148



Paul Moore, PE  
South Carolina P.E. No. 22816



# Comprehensive Stormwater Pollution Prevention Plan (C-SWPPP) For Construction Activities:

## Project/Site Name:

Ironline Metals

## Primary Permittee:

Ironline Metals

### Project Owner:

Ramsey Development

706 Jefferson Street

Tell City, IN, 47586

thuber@ramseydevelopment.com

812-719-0008

### Permittee/Owner Contact:

706 Jefferson Street

Tell City, IN, 47586

thuber@ramseydevelopment.com

812-719-0008

### Project Address/Location:

Pine Street & HWY 21/17

Yemassee, South Carolina, 29945

## SWPPP Preparer:

Ward Edwards Engineering

Paul Moore, PE

PO Box 381

Bluffton, SC 29910

843.384.5266

pmoore@wardedwards.com

## Day-to-Day Operator:

To Be Determined

(Leave Blank if not known.)

## C-SWPPP Preparation Date:

12/21/2022

### Modification Dates:

Modification I: \_\_/\_\_/\_\_\_\_

Modification II: \_\_/\_\_/\_\_\_\_

# Table of Contents

## Certification Statement

### Section 1

#### PROJECT OVERVIEW

1.1 Narrative .....	4
1.2 Stormwater Management and Sediment Control .....	8
1.3 Sequence of Construction.....	17
1.4 Non-Numeric Effluent Limits .....	18
1.5 Buffer Zone Management.....	22

### Section 2

#### SITE FEATURES AND SENSITIVE AREAS

2.1 Sources of Pollution .....	24
2.2 Surface Waters.....	25
2.3 Impairments And TMDLs .....	26
Critical Areas (Coastal Zone Only).....	27

### Section 3

#### COMPLIANCE REQUIREMENTS

3.1 SWPPP Availability .....	28
3.2 Pre-Construction Conferences.....	29
3.3 Inspection Requirements.....	31
3.4 Maintenance Requirements .....	35
3.5 Record Keeping .....	37
3.6 Final Stabilization .....	38

## Appendices

#### REFERENCE MATERIAL

Appendix A - Site Maps.....	39
Appendix B - Drainage Maps .....	40
Appendix C - Additional Approvals/Certifications.....	41
Appendix D - Engineering Report (C-SWPPP* Only).....	42
Appendix E - Maintenance Agreements/Plans .....	50
Appendix F - Inspection Log and Reports (OS-SWPPP** Only) .....	51
Appendix G - Rainfall Records (OS-SWPPP** Only) .....	55
Appendix H - Additional Site Logs and Records (OS-SWPPP** Only).....	58
Appendix I - Construction General Permit (CGP) - SCR100000 .....	66

\*C-SWPPP is acronym for Comprehensive Storm Water Pollution Prevention Plan

\*\*OS-SWPPP is acronym for On-Site Storm Water Pollution Prevention Plan

## ***Certification Statement***

---

I have placed my signature and seal on the design documents submitted signifying that I accept responsibility for the design of the system. Further, I certify to the best of my knowledge and belief that the design is consistent with the requirements of Title 48, Chapter 14 of the Code of Laws of SC, 1976 as amended, pursuant to Regulation 72-300 et seq. (if applicable), and in accordance with the terms and conditions of SCR100000.



Name: Paul Moore, PE

Title: Project Manager

Date : 12/21/2022



## Section 1

### PROJECT OVERVIEW

#### 1.1 Narrative

The proposed project is located at Pine Street & HWY 21/17 in the Town of Yemassee and is identified by tax map numbers 204-01-05-013 & 204-01-05-005. The Site is bound by Pine Street to the West and US Hwy 21 to the South. Currently, the site is undeveloped, except for the existing dirt road and residence on the southern portion of the property. There will be an increase in impervious area with the proposed development, to be routed to onsite detention ponds, that will discharge along the existing outfall path at a rate less than or equal to existing conditions, to ultimately outfall to the Combahee River. See Appendix A for the site vicinity map.

Based on the soils report, the soils found onsite are Argent loamy fine sand and Emporia loamy sand, which are classified as HSG C/D and C respectively. See Appendix A, Exhibit 3 for the soils map and Appendix G, Geotechnical Report.

#### Pre-Development Conditions

The site is currently mostly undeveloped wooded area with runoff directed east towards the large wetland area, and ultimately to the Combahee River. Onsite elevations range from 10 to 30 feet, and the undeveloped portions of the site were analyzed as fair condition woods/grass combination which can be seen in Appendix D. There are two ditches bisecting the site, that drain from west to east.

To determine the pre-development runoff, the site was analyzed in the model as two drainage basins. The following table summarizes the pre-development basin input data. See Appendix A, Exhibit 5 for the basin boundaries and Appendix C for the complete TR-55 basin analysis.

Table 1 - Pre-Development Basin Information

Pre-Development Basin	Basin Area (AC)	Curve Number	Time of Concentration (min)
Pre 1	22.37	78	39
Pre 2	8.23	77	15

The following table shows the results of the pre-development runoff calculations for the four design storms. See Appendix C for the complete results.

**Table 2 - Pre-Development Runoff Results**

<b>Design Storm</b>	<b>Pre-Development Runoff (cfs)</b>
<b>2 Year</b>	28.55
<b>10 Year</b>	56.00
<b>25 Year</b>	74.22
<b>100 Year</b>	105.82

### **Post-Development Conditions**

The proposed development will include the construction of a large industrial building, associated parking, and improvements to an existing dirt road. The dirt road will be paved with asphalt to create a crowned road with curb and gutter. The front portion of the onsite parking lot will also be paved with asphalt, while the rear portion will be paved with granite aggregate. A wet detention pond will be constructed to the west of the paved road to handle stormwater attenuation and water quality treatment from the road improvements. Onsite, dry detention BMPs and a wet detention pond on the eastern portion of the site will be used for stormwater treatment from the remaining proposed development.

The two existing ditches that bisect the site will be isolated from the post-development runoff and will piped through the site to follow existing drainage flow patterns. The pipes will be sized to make sure there is no impact to the offsite, upstream property.

To analyze the post-development conditions, the site was divided into seven basins. The proposed wet and dry detention ponds were modeled in ICPR to determine the post development peak runoff and to make sure they have the capacity to meet water quality treatment and water quantity attenuation requirements. The following table summarizes the post-development basin input data.

**Table 3 - Post-Development Basin Information**

<b>Post-Development Basin</b>	<b>Basin Area (AC)</b>	<b>Curve Number</b>	<b>Time of Concentration (min)</b>
<b>Post 1</b>	11.62	77	32
<b>Post 2</b>	1.19	88	6
<b>Post 3</b>	0.60	80	13
<b>Post 4</b>	0.60	86	6
<b>Post 5</b>	1.74	94	6
<b>Post 6</b>	6.62	89	8
<b>Post 7</b>	8.23	77	15

The following table shows the results of the runoff calculations and the total post-development discharge for the design storms. It can be seen that the peak runoff for the post-development conditions will be less than or equal to the pre-development conditions. See Appendix B for the complete results.

**Table 4 - Pre-Post Runoff Comparison**

<b>Design Storm</b>	<b>Pre-Development Runoff BNDY(cfs)</b>	<b>Post-Development Discharge BNDY (cfs)</b>
<b>2 Year</b>	28.55	24.79
<b>10 Year</b>	56.00	48.69
<b>25 Year</b>	74.22	60.71
<b>100 Year</b>	105.82	93.28



The following table shows the lowest water level for the BMPs under normal conditions, the maximum stage reached during a 100-year storm, and the maximum water level allowed before over topping occurs.

**Table 5 - Water Level Stages**

<b>BMP Structure</b>	<b>BMP Starting Elevation (NWL or bottom)</b>	<b>100-Year Max Stage</b>	<b>Top of Bank</b>
<b>Dry Detention 1</b>	13	16.45	17
<b>Dry Detention 2</b>	13	16.46	17
<b>Wet Pond 1</b>	13	15.62	16
<b>Wet Pond 2</b>	11	15.64	16

All stormwater pipes were modeled using Hydraflow Storm Sewers. To assure the proposed site will not be inundated with excessive ponding of runoff, the stormwater routing model was run using the 25-yr 24 hr. design storm. The max water surface elevation, 25-year Staging Elevation ft, of the SWM facility for the 25-year storm event was used as the starting tail water. The peak water level off the storm collection system was checked against grate inlets, edged of pavement, and the building finished floor elevations to help assure these items do not see flooding or surcharging.

### **Flooding Issues**

The site can be found on FEMA Panels 45049C0450C and is located within Zone A, which are unstudied areas of with an estimated 1% risk of annual flooding. Zone A has no established base flood elevation due to being unstudied. The site naturally drains from west to east, toward the Combahee River, which is approximately 1 mile away.

Due to the topographic relief across the property and naturally sandy soils, there are no known flooding issues on this site or caused by this site.

## **1.2 Stormwater Management and Sediment Control**

### **Erosion Prevention BMPs**

As the existing site is cleared, grubbed and graded to the proposed contours shown on the construction site plans, erosion prevention BMPs shall be placed throughout the construction site to aid in the prevention of sediment-laden stormwater runoff. These BMPs shall be focused in areas with high potential of erosion, areas preceding infiltration practices, and shall be applied to all steep slopes. That is slopes equal to or greater than 3H:1V.

Each erosion prevention measure shall be selected on a site-specific basis and details have been provided on the construction site plans. The plans identify all proposed Erosion Prevention BMPs and the recommended installation, maintenance, and inspection procedures.

Examples of Erosion Prevention BMPs are, but are not limited to, surface roughening, temporary seeding, erosion control blankets, turf reinforcement mats, sodding, riprap, outlet protection, dust control, and polyacrylamide (PAM). Information on the design and proper use of Erosion Prevention BMPs can be located in the [SC DHEC's BMP Handbook](#).

### **Sediment Control BMPs**

Sediment Control BMPs are designed to remove some of the sediment accumulated within stormwater runoff, to the best extent practicable. These BMPs help prevent sediment impacts to adjacent properties and water bodies from stormwater discharges originating from construction sites.

Typically these BMPs are placed near each of the site's outfalls and are installed prior to clearing and grubbing of the site (before large areas of soil are exposed). However, these BMPs can also be located throughout the construction site and, in these circumstances, are installed after mass grading has occurred. Placement, sizing and modifications of Sediment Control BMPs should be left to the SWPPP preparer and/or the Site Engineer. Contractors must consult the SWPPP Preparer as listed at the front of this SWPPP before making any significant changes to these BMPs.

Each sediment control BMP shall be selected on a site-specific basis. Examples of Sediment Control BMPs are, but are not limited to sediment traps, sediment basins, silt fence, rock check dams, rock sediment dikes, sediment tubes, and inlet protection. Please consult [SC DHEC's BMP Handbook](#) for more information on Sediment Control BMPs.

### **Structural Control BMPs and Floodplain Placement**

This site-specific SWPPP utilizes the following structural control BMPs: dry detention ponds, wet detention ponds, and storm sewer systems. These practices have been designed to either divert flows from exposed soils, to retain/detain flows, and to otherwise limit the runoff and the discharge of pollutants from disturbed areas of the construction site.

Throughout the lifespan of the construction project these BMPs will be installed and maintained, as required by the SWPPP and the construction site plans, until final stabilization has been achieved for the areas draining to each BMP. Upon final stabilization, each structural control BMP must be modified to the post-construction conditions shown within the approved construction site plans or removed, if the structural BMP was a temporary structure.

### **Construction Entrances and Dust Control**

All access areas into and out of the limits of disturbance, as shown on the construction site plans, are required to be equipped with a construction entrance. The use of this BMP will limit the amount of sediment being transported by construction vehicles onto existing roadways or other impervious areas. Any tracked sediment, along with any attached pollutants, deposited on impervious areas could be washed downstream during the next rain event. Each construction entrance must be installed as shown in the details section of the construction site plans.

If a new entrance or exit is required, that is not shown on the plans, install the construction entrance as noted by the construction entrance detail, mark the location on the plans and make a record of this minor modification in the SWPPP's modification log, which is located within one of the appendices of the On-site SWPPP.

Each stabilized construction entrance should be used in conjunction with Street Sweeping measures if it becomes apparent that sediment is still being tracked onto adjacent impervious areas, even with the use of the construction entrance.

During extremely dry conditions, drought, and/or excessive winds, the construction site should be treated for dust control to prevent the suspension of fine sediment particles into the air, being carried offsite, and deposited on adjacent properties or surface waters. This practice may not be directly called out for on the construction site plans. A water tanker used to spray the soil down may be an effective way to prevent excessive dust at a construction site.



### **Water Quality BMPs During Construction**

Site-specific water quality BMPs (e.g., sediment basins, sediment traps, rock check dams, and rock sediment dikes) must be installed prior to the mass clearing, grubbing and grading of the site, and must be kept in functioning order throughout the lifespan of all construction activities. Each of these BMPs must be maintained and inspected until all areas draining to these BMPs have reached final stabilization, approved by the construction site inspector or the SWPPP Preparer, and recorded within the stabilization log located as an appendix of the On-site SWPPP.

The location, installation procedures, and maintenance procedures for each water quality BMP can be found within the approved construction site plans.

### **Post-Construction Water Quality**

All construction sites must be designed to treat water quality post-construction. These water quality controls must be installed and stabilized prior to terminating coverage under the CGP. These controls will require routine maintenance to remain functional; this is to be conducted by the Primary Permittee or the entity that accepts responsibility for these structures once construction has been completed. Additional information, including permanent maintenance and inspection procedures, can be found in Appendix E of the OS-SWPPP or within the construction site plans.

Upon final stabilization, each construction site will have to make the transition from temporary BMPs to permanent BMPs. This transition may include the conversion of a sediment basin to a detention basin, a sediment trap to a bioretention area, or diversion swales to permanently vegetated swales. All post-construction (permanent) water quality and water quantity BMPs are identified in the final phase of the Erosion and Sediment Control located within the construction site plans.

### **Other Stormwater Management Procedures**

All parties conducting work at this construction site must be informed of and make note of pollutant sources, both industrial and construction, at this site, and be informed of all controls and measures that will be implemented to prevent the discharge of these pollutants in stormwater runoff.

Based on the nature, conditions, and/or procedures associated with this construction site, the following items must be followed and adopted by all those conducting land disturbing activities at this site:

### **Dewatering**

Non-stormwater may not discharge from the site unless it is considered clean and uncontaminated water.

Any construction water discharging from the site must originate from a public water supply or private well approved by the State Health Department. No water used for construction that does not originate from an approved public water supply may discharge from the site.

Groundwater or surface water encountered and removed during grading and excavation must be filtered to remove sediments before discharged off-site. Surface water will be filtered with Sediment Traps as shown on the plans and details. A pump intake should have a float device or placed in a gravel filter bed to prevent dredging. Discharged water must be routed through an energy dissipater and/or sediment trap. Direct pumping to lakes, rivers and streams must be avoided.

### **Storage of Stockpiled Materials**

All construction debris must be stockpiled in designated areas, which have been provided with the proper BMPs to prevent the discharge of pollutants through stormwater runoff from building or other similar materials off-site or into surface waters.

Any additional waste material or stockpile material (i.e., soil and mulch) must also be stored in the designated areas as shown on the Construction Site Plans or as the contractor, responsible for day-day activities at this site, deems appropriate. Silt fence or an approved equal shall surround all stockpiled materials.

### **Solid Waste Disposal**

All solid wastes, including garbage, recyclables, compostable materials, and cooking grease containers, shall be collected and stored in suitable non-leaking containers. Solid waste containers shall be inspected for damage on a regular basis, and shall be replaced if they are leaking, corroded, or otherwise deteriorating. The containers shall be emptied and hauled offsite when 95% full, or as necessary, by a certified waste disposal service. Covers for the containers shall be provided as practicable, or as required, to prevent stormwater contact and pollutant discharges.

Storage areas shall be swept or cleaned frequently to collect all loose solids for proper disposal in a waste container. Any water used during cleaning operations shall be contained and properly disposed so that no wash water is discharged from the site.

Should a spill occur, it must be contained and disposed of so that the spill does not enter groundwater or discharge from the site, even if requires removal, treatment, and disposal of soil. Contaminated soil shall be buried or paved over during construction operations.

Solid waste materials shall not be buried or disposed of onsite.

### **Sanitary Facilities**

All personnel involved with construction activities must comply with state and local sanitary sewer regulations. Temporary sanitary facilities shall be provided at the site throughout the construction phase. Temporary sanitary facilities shall be used by all construction personnel and will be serviced by a licensed commercial operator.

Portable toilets must be securely anchored to prevent overturning and must not be located within 30-feet of stormwater collection systems or within 50-feet of federal, state, or locally defined protected wetlands or Waters of the State.

### **Concrete Wastes and Washouts**

Discharge of excess waste and/or wash water from concrete trucks will only be allowed within designated washout areas, in accordance with SCDHEC-OCRM details as shown on the drawings. Washout areas may be aboveground portable concrete washout containers or lined and diked areas prepared to prevent contact between the concrete waste and stormwater that will be discharged from the site.

The cured residue from concrete waste may be useful for onsite concrete products or shall be disposed of in accordance with applicable federal, state, and local regulations.

The location of concrete washout areas shall be shown on the drawings, and must not be located within 50-feet of stormwater collection systems, in accordance with SCDHEC-OCRM regulations.

### **Process Water**

Process water such as power washing and concrete cutting must be collected for treatment and disposal. It is not to be flushed into the site storm drain system.

### **Temporary On-site Storage Tanks**

On-site fueling tanks (except double walled tanks), chemicals, liquid products, petroleum products, and other materials that have the potential to pose a threat to human health or the environment shall have a secondary containment, in accordance with federal, state, and local regulations.



The secondary containment shall be capable of storing 110% of the volume of the largest tank within the containment area, and shall be constructed of materials of sufficient thickness, density, and composition so as to not be structurally weakened as a result of contact with the material stored within the tanks.

On-site storage tanks shall be in sound condition, free of rust or damage which might compromise containment. Fuel storage areas shall meet all EPA, OSHA, and other federal, state, and local requirements for signage, fire extinguisher, etc.

A Spill Prevention, Control, and Countermeasure (SPCC) Plan must be developed if the total aggregate capacity of aboveground oil storage containers is greater than 1,320 gallons, or as specified by SCDHEC for specific projects. Containers less than 55 gallons, permanently closed containers, motive power containers, or storage containers used exclusively for wastewater treatment should not be included when calculating site storage capacity.

#### **Hazardous Material Management and Spill Reporting Plan**

The Site Stormwater Representative is responsible for the implementation of spill prevention plan and control for any given project site. Where a release containing a hazardous substance or oil in an amount equal to or in excess of a reportable quantity established under either 40 CFR Part 110, 40 CFR Part 117 or 40 CFR Part 302, occurs during a 24-hour period:

1. You must notify the SCDHEC's Emergency Response Section at (803) 253-6488 and the National Response Center (NRC) (800) 424-8802 in accordance with the requirements of 40 CFR Part 110, 40 CFR Part 117 and 40 CFR Part 302 as soon as Site staff have knowledge of the discharge; and
2. You must modify the SWPPP within 14 calendar days of knowledge of the release to: provide a description of the release, the circumstances leading to the release, and the date of the release. In addition, you must review your SWPPP to identify measures to prevent the reoccurrence of such releases and to respond to such releases, and you must modify your SWPPP where appropriate.

Reportable quantities can be found in Appendix G.

This Spill Prevention and Control Plan (SPCP) as a component of the SWPPP is intended to prevent or reduce the discharge of pollutants to drainage systems or watercourses from leaks and spills by reducing the chance for spills, stopping the source of spills,

containing and cleaning up spills, and properly disposing of spill materials, and training employees.

**General:**

- To the extent that the work can be accomplished safely, spills of oil, petroleum products, and substances listed under 40 CFR parts 110,117, and 302, and sanitary and septic wastes should be contained and cleaned up immediately.
- Store hazardous materials and wastes in covered containers and protect from vandalism.
- Place a stockpile of spill cleanup materials where it will be readily accessible.
- Train employees in spill prevention and cleanup.
- Designate responsible individuals to oversee and enforce control measures.
- Spills should be covered and protected from stormwater run-off during rainfall to the extent that it doesn't compromise clean-up activities.
- Do not bury or wash spills with water.
- Store and dispose of used clean up materials, contaminated materials, and recovered spill material that is no longer suitable for the intended purpose in conformance with the provisions in applicable BMPs.
- Do not allow water used for cleaning and decontamination to enter storm drains or watercourses.
- Contain water overflow or minor water spillage and do not allow it to discharge into drainage facilities or watercourses.
- Place proper storage, cleanup, and spill reporting instructions for hazardous materials stored or used on the project site in an open, conspicuous, and accessible location.
- Keep waste storage areas clean, well-organized, and equipped with ample cleanup supplies as appropriate for the materials being stored. Perimeter controls, containment structures, covers, and liners should be repaired or replaced as needed to maintain proper function.

**Response:**

***Minor Spills***

Minor spills typically involve small quantities of oil, gasoline, paint, etc. which can be controlled by the first responder at the discovery of the spill. Use absorbent materials on small spills rather than hosing down or burying the spill. Absorbent materials should be promptly removed and disposed of properly. Follow the practice below for a minor spill:

1. Contain the spread of the spill.
2. Recover spilled materials.
3. Clean the contaminated area and properly dispose of contaminated materials.

### ***Moderate Spills***

Moderate spills still can be controlled by the first responder along with the aid of other personnel such as laborers and the foreman, etc. This response may require the cessation of all other activities. Spills should be cleaned up immediately:

1. Contain spread of the spill.
2. Notify the project foreman immediately.
3. If the spill occurs on paved or impermeable surfaces, clean up using "dry" methods (absorbent materials, cat litter and/or rags). Contain the spill by encircling with absorbent materials and do not let the spill spread widely.
4. If the spill occurs in dirt areas, immediately contain the spill by constructing an earthen dike. Dig up and properly dispose of contaminated soil.
5. If the spill occurs during rain, cover spill with tarps or other material to prevent contaminating runoff.

### ***Significant/Hazardous Spills***

For significant or hazardous spills that cannot be controlled by personnel in the immediate vicinity, the following steps should be taken:

1. Notify the local emergency response by dialing 911. In addition to 911, the contractor will notify the proper local officials. It is the contractor's responsibility to have all emergency phone numbers at the construction site.
2. Notify SCDHEC's Emergency Response Section at (803) 253-6488.
3. For spills of federal reportable quantities, in conformance with the requirements in 40 CFR parts 110,119, and 302, the contractor should notify the National Response Center at (800) 424-8802.  
Notification should first be made by telephone and followed up with a written report. The services of a spills contractor or a Haz-Mat team should be obtained immediately. Construction personnel should not attempt to clean up until the appropriate and qualified staffs have arrived at the job site.



**Spill Record Keeping:**

All spills and BMPs employed shall be documented to prevent a reoccurrence of the event. This SWPPP shall be updated as necessary to prevent the reoccurrence of a spill event according to the provisions of SWPPP updates. All spills shall be recorded on the Hazardous Substance/Oil Spill Discharge Event form and kept in Appendix H.

**Illicit Discharges**

Any additional non-stormwater discharges, as referenced in the CGP, should be eliminated or reduced to the maximum extent feasible. All unpreventable non-stormwater discharges shall be treated through the approved stormwater management system before release off-site. Following is a list of allowable non-stormwater discharges:

- Fire hydrant flushing
- Wash water without detergents
- Water used for dust control
- Potable water
- Building wash down water without detergents
- Uncontaminated pavement wash water
- Uncontaminated condensation from mechanical equipment
- Uncontaminated ground or spring water
- Water from foundation of footing drains
- Uncontaminated excavation dewatering
- Landscape irrigation
- Dechlorinated swimming pool discharges.

### **1.3    *Sequence of Construction***

The construction sequence for this project has been provided on the construction site plans. Each item/step of that construction sequence has been listed in the sequence that they should be implemented.

For additional information or questions on the sequencing please contact the SWPPP Preparer or the Permittee referenced on the cover of this SWPPP.

## **1.4 Non-Numeric Effluent Limits**

### **Stormwater Volume and Velocity Control**

During the implementation of construction activities, all parties performing work at this construction site whose work may affect the implementation of the SWPPP must be informed of and directed on how to comply with this Non-Numeric Effluent Limit, which requires the management of stormwater runoff within the construction site and at each outfall. The purpose of this requirement is to control the stormwater volume and velocity at these locations to minimize erosion.

Specifically, each responsible party should be made aware of the practices that have been or should be implemented at the construction site to accomplish these particular stormwater management practices. Below is a list of practices that may be utilized within the disturbed area and at each outfall at construction sites to control stormwater volume and velocity:

#### **Volume Control**

- Limiting the amount of disturbed area and exposed soils
- Staging and/or Phasing of the Construction Sequence;
- Sediment Basins and Sediment Traps
- Diverting off-site flow around the construction site;
- Controlling the Drainage Patterns within the Construction Site;
- Temporary Stabilization of Disturbed Areas.

#### **Velocity Control**

- Surface Roughening and/or other Slope Stabilization Practices;
- Level Spreaders, Riprap Plunge Pools and/or other Velocity Dissipation BMPS located at the Construction Site's and Sediment Basin Outfalls.
- Use of Rock Checks, Sediment Tubes, Etc. in Temporary Diversions Swales and Ditches.
- Use of Erosion Control Blankets, Turf Reinforcement Mats, and other Non-Vegetative BMPs that can be used to Quickly Stabilize Disturbed Areas.

The SWPPP Preparer/Engineer should approve any modifications (Additional BMPs or Changes to Existing BMPs) to address the management of stormwater volume and velocity prior to implementation. All approved SWPPPs that were issued coverage under the CGP should include ample BMPs and other control measures to address this specific Non-Numeric Effluent Limit.



### **Soil Exposure, Compaction and Preservation**

Throughout construction activities, the amount of soil exposed during construction should be kept to a minimum. This may be accomplished by minimizing the amount the disturbed area within the permitted Limits of Disturbance (shown on the approved construction site plans) to only that which is necessary to complete the proposed work. For areas that have already been disturbed and where construction activities will not begin for a period of 14 days or more, temporary stabilization techniques must be implemented.

Prior to implementation of any major grading activities, topsoil is to be preserved by placing it in areas designated for stockpiling until final grades are reached. Each stockpile must be equipped with proper sediment and erosion controls to preserve the topsoil and protect adjacent areas from impacts. Once final grades have been reached, the preserved topsoil should be utilized to apply to areas identified for stabilization. Topsoil contains nutrients and organisms that aid in the growth of vegetation.

The Compaction of Soil should also be minimized to the degree practicable during grading activities. This is especially important during the replacement of topsoil to aid in a quick establishment of vegetative cover. Compaction of soil may also reduce rainfall's ability to infiltrate into the soil, increasing the amount of stormwater runoff.

### **Soil Stabilization**

Throughout construction activities, soil stabilization techniques are to be initiated as soon as practicable whenever any clearing, grading, excavating, or other land-disturbing activities have permanently or temporarily ceased on any portion of the construction site and will not resume for a period exceeding 14 calendar days. For areas where initiating stabilization measures is infeasible, (e.g., where snow cover, frozen ground, or drought conditions preclude stabilization), initiate vegetative or non-vegetative stabilization measures as soon as practicable.

### **Steep Slopes (Slopes of 30% grade or greater)**

All disturbed steep slopes (30% grade, ~3H:1V, or greater), and steep slopes to be created through grading activities must be managed in a fashion that limits the potential of erosion along the slopes. All parties whose work is/was responsible for the creation/disturbance of steep slopes must comply with the following items:

- Minimize the Disturbance of all steep slopes, when possible.
- Divert Concentrated or Channelized Flows of stormwater away from and around steep slope disturbances.
- Use Specialized BMP Controls including temporary and permanent seeding

with soil binders, erosion control blankets, surface roughening, reducing continuous slope length with terracing or diversions, gradient terraces, interceptor dikes and swales, grass-lined channels, pipe slope drains, subsurface drains, level spreaders, check dams, seep berms, and triangular silt dikes to minimize erosion.

- Initiate Stabilization Measures as soon as practicable on any disturbed steep slope areas where construction activities have permanently or temporarily ceased, and will not resume for a period exceeding 7 calendar days.
- A Vegetative and/or Non-Vegetative Cover must be established within 3 working days from the time that stabilization measures were initiated.

Stabilization of steep slopes should be a priority for those performing work at the construction site. At the very least, runoff control BMPs should be implemented to transport stormwater runoff from the top of the slope to the toe of the slope. An example of this is to install diversion swales along the top of slope and direct the runoff towards pipe slope drains to transport the runoff to the toe of the slope. All pipe slope drain outlets are to be equipped proper outlet protection.

### **Sediment Discharge Minimization**

Permittees, Contractors, and all other parties responsible for conducting land-disturbing activities are required to install and maintain all erosion and sediment BMPs that are identified on the approved construction site plans. These BMPs have been designed and approved to address such factors as the amount, frequency, intensity and duration of precipitation, the nature of resulting stormwater runoff, and soil characteristics, including the range of soils particle sizes expected to be present on the construction site. Proper installation, inspection, and maintenance will allow these BMPs to operate at maximum efficiencies in order to minimize sediment discharges to the maximum extent practical.

### **Pollutant Discharge Minimization**

Permittees, Contractors, and all other parties responsible for conducting land-disturbing activities are required to install, implement, and maintain effective pollution prevention measures to minimize the discharge of pollutants. At a minimum, the following items must be implemented:

- Minimize the discharge of pollutants from dewatering trenches and excavations by managing runoff with the appropriate controls. Otherwise these discharges are prohibited;
- Minimize the discharge of pollutants from equipment and vehicle washing, wheel wash water, and other wash waters. Wash waters must be treated in a

sediment basin or alternative control that provides equivalent or better treatment prior to discharge;

- Minimize the exposure of building materials, building products, construction wastes, trash, landscape materials, fertilizers, pesticides, herbicides, detergents, sanitary waste and other materials present on the site to precipitation and to stormwater; and
- Minimize the discharge of pollutants from spills and leaks and implement chemical spill and leak prevention and response procedures.

### **Prohibited Discharges**

Permittees, Contractors, and all other responsible parties for conducting land-disturbing activities are prohibited to discharges, from the construction site, the following items:

- Wastewater from washout of concrete, unless managed by an appropriate control;
- Wastewater from washout and cleanout of stucco, paint, form release oils, curing compounds and other construction materials;
- Fuels, oils, or other pollutants used in vehicle and equipment operation and maintenance; and
- Soaps or solvents used in vehicle and equipment washing.



## **1.5 Buffer Zone Management**

Section 3.2.4.C.I of the 2012 NPDES General Permit for Stormwater Discharges from Construction Activities requires a 30-foot, natural (undisturbed) buffer zone during construction between surface waters and the outermost sediment and erosion controls of the construction site. Compliance with Section 3.2.4.C.I offers three options: maintaining the full buffer width, reducing the buffer width, and eliminating the buffer width.

The proposed development will maintain the required 30-ft natural buffer during construction.

The following information will serve as the Surface Water Protection Plan:

### **Controls:**

#### **Temporary & Permanent Grassings**

The site is proposed to be treated with both temporary and permanent seeding measures during construction.

#### **Temporary Sediment and Erosion Control Practices**

Silt fencing will be used to control sediment transport during construction. Double row silt fencing is proposed to be installed within the 30-foot buffer zone of the jurisdictional wetland.

In addition to silt fencing, there will also be inlet protection and long, overland flows utilized to prevent sediment transport.

#### **Onsite Stormwater BMPs**

Runoff from the proposed site is proposed to sheet flow across lawn areas until it is collected in an underground, piped conveyance system to the proposed onsite stormwater BMP where it will be treated for Volume Control and SCDHEC-OCRM water quality and quantity control.

**Sequence:**

- Hold Onsite Pre-Construction Conference
- Install perimeter silt fence adjacent to jurisdictional wetland line prior to land disturbing activities
- Perform weekly site inspections during land disturbing activities and make recommendations for additional BMPs or maintenance of existing BMPs
- Install site drainage features, including inlets and pipes
- Install inlet protection over proposed inlets
- Permanently seed, sod, and/or landscape areas for remaining disturbed areas
- Remove remainder of site BMPs once permanent stabilization has been achieved

## Section 2

### SITE FEATURES AND SENSITIVE AREAS

#### 2.1 Sources of Pollution

Throughout construction activities, each permittee, contractor, and person responsible for conducting work will need to ensure that sources of pollution are managed to prevent their discharge from the construction site. Expected pollution sources during construction have been identified in **Table 2.1-A (below)**, but due to the nature of construction activities, it is often tough to predict all pollution sources that may appear throughout the life of a construction project. For that reason, the following table has also been provided to help all those performing work at this construction site identify possible sources of pollution

Stormwater runoff subjected to the identified pollution sources must be treated by the appropriate BMPs as directed by this SWPPP.

In the event that any additional sources of pollution are identified during construction, the person(s) with day-to-day operational control at the site is to add the new source(s) to **Table 2.1-A** and consult with the SWPPP Preparer to properly address this source and to prevent the discharge of its pollutant through stormwater runoff.

**Table 2.1-A: Potential Sources of Pollution**

Source	Material or Chemical	Location*	Appropriate Control Measures
Loose soil exposed/disturbed during clearing, grubbing and grading activities	Sediment	All areas within the Limits of Disturbance	As directed by the construction Plans. This includes Silt Fence, sediment tubes, sediment basins, and sediment traps.
Areas where construction equipment are cleaned, a.k.a. concrete washout	Heavy Metals & pH	Located adjacent to each construction entrance	Concrete Washout Basin as shown on sheet C-8 of the plans.
Water encountered during trenching	Nutrients & Sediment	In and around any trenching activities.	Direct water into impoundments such as basins or traps to allow for the sedimentation of the listed pollutants.
Paving Operations	Sediment & Trash	All areas to be paved.	Inlet protection.
Material Delivery and Storage Areas	Nutrients, pH, Sediment, Heavy Metals, oils & grease	All areas used as storage areas	Silt fence and/or sediment dikes
Equipment fueling and maintenance areas	Metals, hydrocarbons, oils and greases	Areas surrounding fuel tanks	Provide secondary containments, locate in upland areas. Repair leaking and broken hoses.




## 2.2 Surface Waters

Stormwater runoff from the proposed construction site discharges to one location as outlined in **Figure 2.2**, leading south ultimately reaching the Combahee River.

As outlined above in Section 1.5, there are onsite wetlands. As discussed, the required 30-ft undisturbed construction buffer will be provided.

No additional Federal, State, or Local permits are required other than the SCDHEC-OCRM land disturbance permits.

**Figure 2.2: Stormwater Runoff Route**



### **2.3    *Impairments and TMDLs***

Some Waters of the State (WoS) have been identified as not meeting the State's water quality standards for recreational swimming, fish consumption, aquatic life use, and/or shellfish harvesting for one or more pollutants even after controls for point and nonpoint source pollution have been put in place. These waterbodies have been classified as "impaired." Once these waterbodies have been identified they are listed on the State's 303(d) List of Impaired Waterbodies. South Carolina lists impairments as "stations" where samples were taken along a waterbody.

The most recently-approved 303(d) list can be found at the following link:

<http://www.scdhec.gov/environment/water/tmdl/index.htm#4>

After a pre-determined period of time, DHEC is obliged to develop a Total Maximum Daily Load (TMDL) for the pollutant of concern for each impaired station listed on the 303(d) List. A TMDL is the amount of a single pollutant (such as bacteria, nutrients, metals) that can enter a waterbody on daily basis and that waterbody still meet water quality standards. "TMDL" refers to both a calculation of a pollutant entering a waterbody as well as the document containing this calculation along with source assessments, watershed and land use information, reductions and allocations information, implementation and other relevant information, maps, figures, and pictures.

Once a TMDL has been developed and approved by the EPA, the impaired WoS is removed from the 303(d) list. A separate list is maintained for WoS with approved TMDLs.

Any construction site whose discharges are released into a WoS listed on the 303(d) List or for which an EPA-approved TMDL has been developed must address the specific pollutant set forth in the TMDL and/or potential pollutants for the impairment. The SWPPP must include a description of BMPs to address these pollutants.

A TMDL has not been developed for the receiving waterbody for this project.

## **2.4 Critical Areas (CZC only)**

No Critical Areas are located within and/or directly adjacent to the proposed disturbed area and construction site.



## **Section 3**

### *Compliance Requirements*

---

#### **3.1 SWPPP Availability**

A copy of the OS-SWPPP, as defined by Section 3.1.1.H of the 2012 Construction General Permit, must be retained at the construction site or a nearby location easily accessible during normal business hours, from the date of commencement of construction activities to the date that final stabilization is reached.

If a location within the construction site is unavailable to store the On-Site SWPPP when no personnel are present, notice of the plan's location, along with any updated contact information, must be posted near the main entrance at the construction site.

Contractors and/or Builders, who have day-to-day operational control over OS-SWPPP implementation, must have a copy of this SWPPP available at a central location within the construction site for the use by all those identified as having responsibilities under the OS-SWPPP.

For linear construction of roads and utilities (i.e., electrical power lines, gas lines, main sewer trunk lines, and water distribution lines), which are not part of a LCP, where it is not practical to have the OS-SWPPP on location, the Permittee and/or Operator must upon request make the OS-SWPPP available by the end of normal business hours, or by the following business day under extenuating circumstances.

On-Site SWPPPs must be made available upon request and at the time of a construction site inspection by EPA; DHEC; a tribal or an entity delegated under Regulation 72-300; local government officials; and the Operator of a Municipal Separate Storm Sewer System (MS4) receiving discharges from the construction site to the requestor.

### **3.2 Pre-Construction Conferences**

- A. A pre-construction conference must be held for each construction project or site with an approved On-Site Stormwater Pollution Prevention Plan (OS-SWPPP). Each contractor, subcontractor, blanket utility provider, etc., who will work at a site must attend this conference in person. The primary purpose of this conference is for:

- I. The preparer of the SWPPP or someone with a registration equivalent to that of the preparer of the SWPPP; and/or
- II. The person with operational control of the plans and specifications (the Primary or Secondary Permittee) or their duly authorized representative (as defined in Section 122.22(b) of SC Regulation 61-9))

to review and explain the On-Site SWPPP (OS-SWPPP) so that all are aware of the requirements before they start performing construction-related (land disturbing) activities that may affect the implementation of the approved OS-SWPPP. This conference may be held simultaneously with all contractors and builders present or may be conducted separately with one or more contractors, subcontractors, etc. present.

- B. Linear construction of roads or utilities (such as roads and utility construction including electrical power lines, gas lines, main sewer trunk lines, and water distribution lines) that are not part of a Larger Common Plan (i.e., subdivision or other type of development) are considered to be linear construction projects or linear construction sites under this permit. Linear construction performed as a part of or within a LCP project or site, is considered to be linear construction activities under this permit and not linear construction projects or sites. (See Appendix A, Definitions.)
- C. Pre-construction conference location requirements are defined below.
- I. For non-linear construction projects/sites that disturb 10 acres or more, the preconstruction conference must be held on-site unless it is justified in the SWPPP and approved by the Department to conduct the conference off-site.
  - II. For non-linear construction projects/sites that disturb less than 10 acres, conferences may be held off-site unless specifically required in writing or as a condition of the approved OS-SWPPP by the Department or the respective MS4 to be conducted onsite.

- III. For linear construction projects/sites that are not part of a Larger Common Plan (LCP), subdivision or other type of development, conferences may be held off-site unless specifically required in writing or as a condition of the approved OS-SWPPP by the Department or the respective MS4 to be conducted on-site.
  - IV. For linear construction activities (within a LCP), conferences must be held in accordance with disturbed area ( 10 acres) criterion established for non-linear projects/sites in Items C.I and C.II above.
  - V. In addition, person(s) conducting the conference (Owner/Operator) may choose, at their discretion, to hold a conference normally held off-site, on-site.
- D. Each pre-construction conference must also specifically address Section 3.1.7, Modifications, detailing how each type of modification, Major and Minor, will be addressed and processed at the construction site to maintain compliance with this permit.
- E. Persons conducting this conference must document each contractor, subcontractor, blanket utility, etc., attending the conference. This documentation must be maintained with the On-Site SWPPP (OS-SWPPP), and include dates, locations, times, as well as, identification of those in attendance.



### **3.3 Inspection Requirements**

#### **Scope**

Construction Site Inspections are to be conducted on a routine basis, as outlined in Section 4.2.B, and must include all areas disturbed by construction activity, including perimeter BMPs and areas used for storage of materials that are exposed to precipitation.

Each Inspection must look for the evidence of, or the potential for, inefficiencies within the implemented OS-SWPPP, whether the inefficiencies are a direct result of improper design, installation or maintenance, by inspecting, at a minimum, the following:

- I. All areas of the site disturbed by construction activity and areas used for storage of materials that are exposed to precipitation;
- II. All stormwater conveyance systems for any evidence of, or the potential for, pollutants entering these systems;
- III. All BMPs identified in the OS-SWPPP;
- IV. All discharge locations to ascertain whether the implemented BMPs are effective in preventing the discharge of sediment from the site. Where discharge locations are inaccessible, nearby downstream locations must be inspected to the extent that such inspections are practicable; and
- V. Locations where vehicles enter or exit the site must be inspected for evidence of off-site sediment tracking.

If inspection responsibilities are not shared between the Primary and Secondary Permittees, each secondary permittee must provide their own inspections for the portions of the site for which their coverage includes.

#### **Frequency**

After construction activities begin, inspections must be conducted at a minimum of at least once every calendar week and must be conducted until final stabilization is reached on all areas of the construction site. An inspection is recommended within 24 hours of the end of a storm event of 0.5 inches or greater.

The Department on a case-by-case basis may require any permittee who has coverage under this CGP to conduct inspections on a more frequent basis than prescribed in this CGP. Examples include, but are not limited to, permittees who have compliance problems and permittees whose construction site's Stormwater discharges to Sensitive Waters (such as waters classified as Trout Waters, Outstanding Resource Waters, Shellfish Harvesting Waters, etc.).

Inspection frequencies for portions of the construction site that have reached temporary or final stabilization may be reduced to at least once every month, as long as the stabilization is maintained and there is no additional disturbance in these areas. Once a definable area has reached final stabilization, you may mark this on your On-Site SWPPP and no further inspection requirements apply to that portion of the Site (e.g., land-disturbing activities around one of three buildings in a complex are completed and the disturbed area has reached final stabilization, one mile of a roadway or pipeline Project is completed and the disturbed area has reached final stabilization, etc.). Inspection of common BMPs, such as sediment basins, sediment traps, may be required to resume if areas that drain to them become disturbed during future construction.

### **Linear Site Inspection Frequency**

Utility line installation, pipeline construction, and other examples of long, narrow, linear construction activities may limit the access of inspection personnel to the areas described in Section 4.2.A above. Inspection of these areas could require that vehicles compromise temporarily or even permanently stabilized areas, cause additional disturbance of soils, and increase the potential for erosion.

In these circumstances, controls must be inspected on the same frequencies as other construction Projects, but representative inspections may be performed. For representative inspections, personnel must inspect controls along the construction Site for 0.25 mile above and below each access point where a roadway, undisturbed right-of-way, or other similar feature intersects the construction Site and allows access to the areas described above.

The conditions of the controls along each inspected 0.25 mile segment may be considered as representative of the condition of controls along that reach extending from the end of the 0.25 mile segments to either the end of the next 0.25 mile inspected segment, or to the end of the construction site, whichever occurs first. Representative inspections must include any areas where Stormwater discharges to Sensitive Waters (such as waters classified as Trout Waters, Outstanding Resource Waters, Shellfish Harvesting Waters, etc.).

### Rain Gauge

Permittees shall either maintain an on-site rain gauge or use data from a certified weather record (such as a personal weather station or an airport) located within a reasonable proximity of the construction site, to record rainfall records from any significant rainfall event, 0.5 inches or greater. These recorded rainfall amounts must be maintained in a Rain Log located in the on-site SWPPP. Rainfall records for the day of an inspection and any significant rainfall events since the last inspection must be reported on each weekly inspection report.

### Inspector Qualifications

Inspections must be conducted by qualified personnel (provided by the Permittee) as outlined by the following:

- I. For Projects that disturb more than 2 acres, “Qualified personnel” means a person knowledgeable in the principles and practice of erosion and sediment controls who possesses the skills to assess conditions at the construction site that could impact Stormwater quality and to assess the effectiveness of any BMPs selected to control the quality of Stormwater discharges from the construction site.

This person must be either the preparer of the C-SWPPP or an individual who is under the direct supervision of the preparer of the approved C-SWPPP and who meets the requirements in this paragraph or an individual who has been certified through a Construction Site Inspector Certification Course that has been approved by DHEC.

Inspections may also be conducted by a person with a registration equivalent to the registration of the preparer of the C-SWPPP and who meets the qualifications of this paragraph or an individual who is under the direct supervision of the person with an equivalent registration and who meets the requirements in this paragraph.

- II. For Projects that disturb 2 acres or less, and that are not part of a Larger Common Plan, the Permittee or his designee may perform these inspections provided the preparer of the C-SWPPP or someone with a registration equivalent to that of the preparer of the C-SWPPP explains the OS-SWPPP including implementation along with the inspection requirements to the person who will be conducting the inspections.



- III. The Department and Regulated MS4s reserves the right to require that inspections be performed by an inspector meeting the requirements of 4.2.E.I for construction sites less than two acres in size that drain to Sensitive Waters, when deemed necessary.

#### **Inspection Reports**

Refer to Appendix E for an approved Inspection Report Template

#### **Monthly Reports**

DHEC may require on a case-by-case basis that the Permittee submit a monthly report summarizing the inspections at the site and any associated maintenance activity.

#### **Inspection Records**

A record of each inspection and of any actions taken in accordance with this Section must be retained as part of the On-site SWPPP for at least three years from the date that permit coverage expires or is terminated. The qualified inspector, as identified in section 4.2.E, must sign the inspection report.

#### **Primary Permittees**

Primary Permittees. Inspectors employed by the Primary Permittee retain the authority to inspect, report, and document areas of the construction site that are under direct control of the Secondary Permittee, but only when a lack of compliance by the Secondary Permittee inhibits the Primary Permittee's ability to maintain compliance with the overall OS-SWPPP or this permit.

### **3.4 Maintenance Requirements**

#### **Construction Maintenance**

All BMPs and other protective measures identified in the OS-SWPPP must be maintained in effective operating condition. If site inspections required by Section 4.2 identify BMPs that are not operating effectively, maintenance must be performed within seven (7) calendar days, before the next inspection, or as reasonably possible, and before the next storm event whenever practicable to maintain the continued effectiveness of Stormwater controls.

If periodic inspection or other information indicates that a BMP has been used inappropriately, or incorrectly, the Permittee must address the necessary replacement or modification required to correct the BMP within a time frame of 48 hours of identification.

If existing BMPs need to be modified or if additional BMPs are necessary to comply with the requirements of this permit and/or SC's Water Quality Standards, implementation must be completed before the next storm event whenever practicable. If implementation before the next storm event is impracticable, the situation must be documented in the OS-SWPPP and alternative BMPs must be implemented as soon as reasonably possible.

Sediment from sediment traps or sedimentation basins must be removed as indicated in the OS-SWPPP or when the design capacity has been reduced by 50 percent, whichever occurs first.

Sediment collected by Silt Fence, or another sediment control measure, must be removed when the deposited sediment reaches 1/3 of the height of the aboveground portion of these BMPs, or before it reaches a lower height based on the manufacturer's specifications.

#### **Permanent Maintenance**

Permanent Stormwater management structures must be routinely maintained to operate per design. The Department requires inclusion of a Permanent Stormwater Management Maintenance Agreement and a Maintenance Plan to ensure proper operation. Provide a detailed proposed maintenance plan for permanent stormwater management structures proposed for your project in the Narrative. The maintenance agreement and maintenance plan, when required, must be identified and located in the C-SWPPP.

### **Maintenance Agreements**

A copy of a notarized Maintenance Agreement in accordance with Section 4.3.C of the Construction General Permit has been provided In Appendix E.

For additional information or questions on the Maintenance Agreement please contact the SWPPP Preparer or the Permittee referenced on the cover of this SWPPP.

### **Maintenance Plans**

A copy of a Maintenance Plan in accordance with Section 4.3.D of the Construction General Permit has been provided In Appendix E.

For additional information or questions on the Maintenance Plan please contact the SWPPP Preparer or the Permittee referenced on the cover of this SWPPP.



### **3.5    *Record Keeping***

All logs necessary to track the progress, compliance, modifications and those associated with the construction site, in accordance with Section 3.1.1.H.V.(h) of the Construction General Permit, are provided in Appendices F-H.

For additional information or questions on Record Keeping please contact the SWPPP Preparer or the Permittee referenced on the cover of this SWPPP.

### **3.6 Final Stabilization**

Coverage under the Construction General Permit must be maintained until all portions of the site achieve Final Stabilization as defined in Appendix A of the Construction General Permit.

Final Stabilization means that all land-disturbing activities at the construction site have been completed and that on all areas not covered by permanent structures, either (1) a uniform (e.g., evenly distributed, without large bare areas) vegetative cover with a density of 70 percent of the natural background vegetative cover has been established excluding areas where no natural background vegetative cover is possible (e.g., on a beach), or (2) equivalent permanent stabilization measures (such as the use of landscaping mulch, riprap, pavement, and gravel) have been implemented to provide effective cover for exposed portions of the construction site not stabilized with vegetation.

All temporary structural BMPs must be removed after Final Stabilization has been accomplished.

Once Final Stabilization has been achieved on all portions of the construction site, a Notice of Termination (NOT) may be submitted.

No post-construction discharges that originate from the construction site after land-disturbing activities have been completed and the site has achieved Final Stabilization are permitted.

## ***Appendix A***

### *Site Maps*

---

To develop a site-specific SWPPP for a construction map, an assortment of site maps must be used in addition to an on-site assessment to develop an effective stormwater sediment and erosion control plan. The maps located in this appendix have been obtained from various sources, or have been developed by the SWPPP Preparer. Listed below are the type of maps found within this Appendix.


**Site Vicinity Map**

**USGS Quad Map**

**Soils Maps**

**Floodway Maps**





P.O. BOX 381, BLUFFTON, SOUTH CAROLINA 29910  
PH (843) 837-5250 / FAX (843) 837-2558  
[WWW.WARDEDWARDS.COM](http://WWW.WARDEDWARDS.COM)


## VICINITY MAP

### PINE STREET DEVELOPMENT

LOCATION: YEMASSEE, SC  
DATE: 10/25/2022  
PROJECT #: 210148

SCALE: 1"=1,000'





P.O. BOX 381, BLUFFTON, SOUTH CAROLINA 29910  
PH (843) 837-5250 / FAX (843) 837-2558  
WWW.WARDEDWARDS.COM

## QUAD MAP


### PINE STREET DEVELOPMENT

LOCATION: YEMASSEE, SC  
DATE: 10/25/2022  
PROJECT #: 210148

SCALE: 1"=2000'



# Custom Soil Resource Report Soil Map





# National Flood Hazard Layer FIRMette



80°50'44"W 32°42'26"N



0 250 500 1,000 1,500 2,000 Feet 1:6,000

Basemap: USGS National Map: Orthoimagery: Data refreshed October, 2020

## Legend

SEE FIS REPORT FOR DETAILED LEGEND AND INDEX MAP FOR FIRM PANEL LAYOUT

SPECIAL FLOOD HAZARD AREAS		Without Base Flood Elevation (BFE) Zone A, V, A99
		With BFE or Depth Zone AE, AO, AH, VE, AR
		Regulatory Floodway
OTHER AREAS OF FLOOD HAZARD		0.2% Annual Chance Flood Hazard, Areas of 1% annual chance flood with average depth less than one foot or with drainage areas of less than one square mile Zone X
		Future Conditions 1% Annual Chance Flood Hazard Zone X
		Area with Reduced Flood Risk due to Levee. See Notes. Zone X
		Area with Flood Risk due to Levee Zone D
OTHER AREAS		NO SCREEN Area of Minimal Flood Hazard Zone X
		Effective LOMRs
GENERAL STRUCTURES		Area of Undetermined Flood Hazard Zone D
		Channel, Culvert, or Storm Sewer
OTHER FEATURES		Levee, Dike, or Floodwall
		Cross Sections with 1% Annual Chance Water Surface Elevation
OTHER FEATURES		Coastal Transect
		Base Flood Elevation Line (BFE)
OTHER FEATURES		Limit of Study
		Jurisdiction Boundary
OTHER FEATURES		Coastal Transect Baseline
		Profile Baseline
OTHER FEATURES		Hydrographic Feature
		Digital Data Available
MAP PANELS		No Digital Data Available
		Unmapped



The pin displayed on the map is an approximate point selected by the user and does not represent an authoritative property location.

This map complies with FEMA's standards for the use of digital flood maps if it is not void as described below. The basemap shown complies with FEMA's basemap accuracy standards

The flood hazard information is derived directly from the authoritative NFHL web services provided by FEMA. This map was exported on **10/27/2022 at 5:25 PM** and does not reflect changes or amendments subsequent to this date and time. The NFHL and effective information may change or become superseded by new data over time.

This map image is void if the one or more of the following map elements do not appear: basemap imagery, flood zone labels, legend, scale bar, map creation date, community identifiers, FIRM panel number, and FIRM effective date. Map images for unmapped and unmodernized areas cannot be used for regulatory purposes.

## **Appendix B**

### *Drainage Maps*

---

Drainage maps become an essential tool when both developing and reviewing hydrology models of a construction site during the various phases of developing such a site (i.e. pre-development conditions, construction conditions, and post-development conditions). Typically these maps are enhanced site maps that add the features of drainage basins outlines and their respective outfall markers. Each SWPPP must contain, at a minimum, a pre-development and a post-development drainage map for the entire on-site area and adjacent off-site areas that contribute runoff to any of the marked outfall locations.

Additional drainage maps should also be included for any sediment control BMP in which sediment trapping efficiency calculations are required to be submitted. A drainage map for “During Construction” conditions should also be included if the basin and subbasin drainage patterns differ from both the pre-development and post-development patterns.


All provided drainage maps must clearly correspond to any calculations submitted for review, the outfall locations chosen for comparing runoff rates and the total drainage area analyzed (from pre- to post-development conditions) may not change. However, the immediate drainage areas contributing to each outfall location may shift.

Each Drainage Map should be provide on an 11x17 sheet and must show the contours for the specific stage of construction each map represents.

#### **Pre-Development Drainage Area Map**

#### **Post-Development Drainage Area Map**





PRE-1  
AREA: 30.66 AC  
Cn: 32  
Tc: 0.53 MIN

BNDY-PRE

VICINITY MAP  
Not To Scale

**PRE DEVELOPMENT  
DRAINAGE EXHIBIT**

**IRONLINE METALS**  
TOWN OF YEMASSEE, SOUTH CAROLINA

PREPARED FOR:  
**RAMSEY DEVELOPMENT, LLC**  
TELL CITY, INDIANA

**LEGEND**


PROPERTY BOUNDARY ———

DRAINAGE BASIN AREA ———

ANALYSIS POINT ○

FLOW ———

DOCUMENT IS CONCEPTUAL AND SUBJECT TO CHANGE.  
WARD EDWARDS INC. ASSUMES NO LIABILITY FOR  
ACCURACY OR DECISIONS MADE BY THE USER BASED UPON  
INFORMATION CONTAINED HEREIN.




 **Ward  
Edwards**  
ENGINEERING

P.O. BOX 381, BLUFFTON, SOUTH CAROLINA 29910  
PH (843) 837-5250 / FAX (843) 837-2558  
WWW.WARDEDWARDS.COM

PROJECT #:	210148
DATE:	12/05/22
PREPARED BY:	BMT
SHEET NUMBER:	I OF I





VICINITY MAP  
Not To Scale

**POST DEVELOPMENT  
DRAINAGE EXHIBIT**


**IRONLINE METALS**  
TOWN OF YEMASSEE, SOUTH CAROLINA

PREPARED FOR:  
**RAMSEY DEVELOPMENT, LLC**  
TELL CITY, INDIANA


**LEGEND**

PROPERTY BOUNDARY  
DRAINAGE BASIN AREA  
ANALYSIS POINT  
FLOW

DOCUMENT IS CONCEPTUAL AND SUBJECT TO CHANGE.  
WARD EDWARDS INC. ASSUMES NO LIABILITY FOR  
ACCURACY OR DECISIONS MADE BY THE USER BASED UPON  
INFORMATION CONTAINED HEREIN.



0 100 200  
SCALE: 1" = 100'  
Feet



P.O. BOX 381, BLUFFTON, SOUTH CAROLINA 29910  
PH (843) 837-5250 / FAX (843) 837-2558  
WWW.WARDEDWARDS.COM

PROJECT #:	210148
DATE:	12/05/22
PREPARED BY:	BMT
SHEET NUMBER:	1 OF 1

## ***Appendix C***

### *Additional Approvals/Certifications*

---

This appendix has been provided as a catchall to store any additional correspondences that may be required to either obtain coverage under the current CGP or to implement land-disturbing activities at a construction.

#### **Coastal Zone Consistency Certification**



## Appendix D

### Engineering Reports

---

#### Hydrologic Analysis

Each hydrologic analysis was performed in a manner consistent with SC Regulations 72-300 and the SC DHEC Stormwater Management BMP Handbook. Each analysis, at a minimum, meets the following requirements or guidelines:

- Analysis Points (Outfalls) for comparing runoff rates and the total drainage area analyzed do not change from pre- to post-development conditions (although the immediate drainage areas contributing to each analysis point may shift);
- Post-development and Construction runoff peak discharges are less than Pre-Development peak discharges at each outfall for the following design storms:
  - 2-year, 24 hour (4.2-inches)
  - 10-year, 24 hour (6.4-inches)
  - 25-year, 24 hour (7.8-inches)
  - 100-year, 24 hour (10.2-inches)
- Post-development runoff rate for the 100-yr 24 hr. design storm (10.2-inches) to ensure adequate freeboard;
- Each analysis was performed using a SCS Type III 24-hour storm event using an SCS Peaking Factor of 323;
- TR-55 methodology was utilized to determine the runoff index (curve number – CN) and the time of concentration (Tc);
- The composite curve number for each Basin was determined using the most prevalent hydrologic soil type.



## Detention Analysis

Each detention structure analysis was performed using the Advanced Interconnected Channel and Pond Routing (ICPR) computer model by Streamline Technologies. If a rating curve for the outlet structure had to be generated externally from the modeling software, the data and equations used to rate the outlet structure are included in the appendix.

## Water Quality Analysis

To ensure compliance with State and Local Water Quality Requirements, the following analyses were performed:

- SCDHEC First Flush
- Event of Excess of Design Storm

The proposed stormwater BMPs will handle water quality treatment in addition to the water quantity attenuation.

The water quality analysis for this project involves addressing the SCDHEC first flush requirements. The proposed BMPs will handle water quality treatment in addition to the water quantity attenuation. The following tables summarize the stage-area relationships for the proposed BMPs.

**Table 6a – Pond 1 Stage Volume Relationship**

<b>Wet Pond 1</b>				
<b>Stage (ft)</b>	<b>Elevation (ft)</b>	<b>Area (ft<sup>2</sup>)</b>	<b>Volume (ft<sup>3</sup>)</b>	<b>Σ Volume (ft<sup>3</sup>)</b>
0	13	5,362	0	0
1	14	6,180	5,771	5,771
2	15	7,113	6,647	12,418
3	16	8,101	7,607	20,025

**Table 6b – Pond 2 Stage Volume Relationship**

<b>Wet Pond 2</b>				
<b>Stage (ft)</b>	<b>Elevation (ft)</b>	<b>Area (ft<sup>2</sup>)</b>	<b>Volume (ft<sup>3</sup>)</b>	<b>Σ Volume (ft<sup>3</sup>)</b>
0	11	13,937	0	0
1	12	15,503	14,720	14,720
2	13	17,125	16,314	31,034
3	14	18,804	17,965	48,999
4	15	20,540	19,672	67,671
5	16	22,333	21,436	90,107

**Table 6c – Dry Pond 1 Stage Volume Relationship**

<b>Dry Pond 1</b>				
<b>Stage (ft)</b>	<b>Elevation (ft)</b>	<b>Area (ft<sup>2</sup>)</b>	<b>Volume (ft<sup>3</sup>)</b>	<b>Σ Volume (ft<sup>3</sup>)</b>
0	13	1,380	0	0
1	14	4,175	2,778	2,778
2	15	6,032	5,104	7,882
3	16	7,946	6,989	14,871

**Table 6d – Dry Pond 2 Stage Volume Relationship**

<b>Dry Pond 2</b>				
<b>Stage (ft)</b>	<b>Elevation (ft)</b>	<b>Area (ft<sup>2</sup>)</b>	<b>Volume (ft<sup>3</sup>)</b>	<b>Σ Volume (ft<sup>3</sup>)</b>
0	14	1,097	0	0
1	15	5,683	3,390	3,390
2	16	8,222	6,953	10,343
3	17	10,818	9,520	19,863

For each BMP, the low-flow drawdown weir was set to the bottom or normal water level. The low-flow drawdown will retain the first flush volume and draw it down over 24-hours.

### SCDHEC First Flush Analysis

*The following SCDHEC Water Quality Analysis applies to the entirety of the site*

Section 72-307.C.5 of the standards for Stormwater Management and Sediment Reduction, implemented as part of the Stormwater Management and Sediment Reduction Act, requires the following:

- a) Permanent water quality ponds having a permanent pool shall be designed to store and release the first ½ inch of runoff from the site over a 24-hour period. The storage volume shall be designed to accommodate, at least, ½ inch of runoff from the entire site. For the purposes of this calculation, the offsite, undeveloped areas were excluded from the “Project Site”. The following calculations are for the basin areas draining to Pond 1 & Pond 2.

**Pond 1:**

$$(0.5 \text{ in}) \times (\text{Area of Project Site draining to the BMP})$$

$$(0.5 \text{ in}) \times (1.19 \text{ ac}) \times (43,560 \text{ sf/ac}) \times (1 \text{ ft}/12 \text{ in}) = \mathbf{2,160 \text{ ft}^3}$$

Please note the initial outfall weir is set at elevation 14.0. The volume within the pond at this elevation is 5,771 CF, which is larger than the required First Flush volume outlined above. This volume will be discharged through a low-flow 3” wide weir over the course of 24 hours, as shown in the attached drawdown graph.

Pond 2:

$(0.5 \text{ in}) \times (\text{Area of Project Site draining to the BMP})$

$(0.5 \text{ in}) \times (8.96 \text{ ac}) \times (43,560 \text{ sf/ac}) \times (1 \text{ ft}/12 \text{ in}) = \mathbf{16,262 \text{ ft}^3}$

Please note the initial outfall weir is set at elevation 12.1. The volume within the pond at this elevation is 16,351 CF, which is larger than the required First Flush volume outlined above. Although the dry-detention basins have additional volume capacity, they ultimately drain through Pond-2 and are incorporated in the 8.96 ac area. This volume will be discharged through a low-flow 4" wide weir over the course of 24 hours, as shown in the attached drawdown graph.

### SCDHEC Trapping Efficiency Calculation

Appendix B of the South Carolina Stormwater Management and Sediment Control Handbook for Land Disturbance Activities (Aug 2003) states that land disturbing activities which disturb ten acres or more must have a sediment basin designed to meet a removal efficiency of 80 percent for suspended solids, or 0.5 ML/L peak settleable concentration, whichever is less. The project will disturb 12.5 acres. As such, this report will analyze sediment calculations to ensure the two wet detention ponds capable of serving as sediment basins for the site. The smallest soil particle size on-site was used within each basin area in order to provide the required trapping efficiency for the most limiting site condition.

According to the settling velocity and trapping efficiency graphs attached, both ponds will provide a trapping efficiency greater than the required 80% prior to discharging.

Additional sediment control measures are shown on the construction plans and include the following:

- A. Construction entrance/exit will be used to minimize the effects of sediment movement due to construction traffic, and
- B. Silt fencing will be used around the perimeter of the site to allow for sediment control during construction.
- C. Inlet protection for all existing and proposed drainage structures.
- D. Sediment Tubes will be placed in the swales.
- E. Rip-rap outlet protection will be used at all pipe ends.
- F. Temporary and permanent seeding for all disturbed areas.



### **Event of Excess of Design Storm**

To assure the proposed site will not be inundated with excessive ponding of runoff, the stormwater routing model was run using the 100-yr 24 hr. design storm. The peak water level to the pond during the 100 year event was checked against grate inlet, edge of pavements, and building finished floor elevations to assure these items would not overtop. The proposed emergency overflow was adjusted appropriately to control the peak water elevation. See Appendix C for the model results.

## ***Appendix E***

### *Maintenance Agreements/Plans*

---

**Attachment 1: ICPR Model Input**

**Attachment 2: TR-55 Curve Number and Tc Determination**

**Attachment 3: ICPR Link Node Map**

**Attachment 4: ICPR Hydrology – Basin Summary**

**Attachment 5: ICPR Hydraulics Output**

**Attachment 6: ICPR WQ Drawdown Graphs**

**Attachment 7: Sedimentology Graphs**

**Attachment 8: Geotechnical Report**

## =====

## ==== Basins =====

## =====

Name: PRE-2	Node: Pre BNDY	Status: Onsite
Group: BASE	Type: SCS Unit Hydrograph CN	
Unit Hydrograph: Uh323	Peaking Factor: 323.0	
Rainfall File: Scsiii	Storm Duration(hrs): 24.00	
Rainfall Amount(in): 0.000	Time of Conc(min): 15.00	
Area(ac): 8.230	Time Shift(hrs): 0.00	
Curve Number: 77.00	Max Allowable Q(cfs): 999999.000	
DCIA(%): 0.00		

Name: PRE1	Node: Pre BNDY	Status: Onsite
Group: BASE	Type: SCS Unit Hydrograph CN	
Unit Hydrograph: Uh323	Peaking Factor: 323.0	
Rainfall File: Scsiii	Storm Duration(hrs): 24.00	
Rainfall Amount(in): 0.000	Time of Conc(min): 39.00	
Area(ac): 22.370	Time Shift(hrs): 0.00	
Curve Number: 78.00	Max Allowable Q(cfs): 999999.000	
DCIA(%): 0.00		

Name: PST-1	Node: DB-1	Status: Onsite
Group: BASE	Type: SCS Unit Hydrograph CN	
Unit Hydrograph: Uh323	Peaking Factor: 323.0	
Rainfall File: Scsiii	Storm Duration(hrs): 24.00	
Rainfall Amount(in): 0.000	Time of Conc(min): 32.00	
Area(ac): 11.620	Time Shift(hrs): 0.00	
Curve Number: 77.00	Max Allowable Q(cfs): 999999.000	
DCIA(%): 0.00		

Name: PST-2	Node: Pond 1	Status: Onsite
Group: BASE	Type: SCS Unit Hydrograph CN	
Unit Hydrograph: Uh323	Peaking Factor: 323.0	
Rainfall File: Scsiii	Storm Duration(hrs): 24.00	
Rainfall Amount(in): 0.000	Time of Conc(min): 6.00	
Area(ac): 1.190	Time Shift(hrs): 0.00	
Curve Number: 88.00	Max Allowable Q(cfs): 999999.000	
DCIA(%): 0.00		

Name: PST-3	Node: Ditch A	Status: Onsite
Group: BASE	Type: SCS Unit Hydrograph CN	
Unit Hydrograph: Uh323	Peaking Factor: 323.0	
Rainfall File: Scsiii	Storm Duration(hrs): 24.00	
Rainfall Amount(in): 0.000	Time of Conc(min): 13.00	
Area(ac): 0.600	Time Shift(hrs): 0.00	



---

Curve Number: 80.00      Max Allowable Q(cfs): 999999.000  
DCIA(%): 0.00

---

Name: PST-4      Node: Dry Detention 2      Status: Onsite  
Group: BASE      Type: SCS Unit Hydrograph CN

Unit Hydrograph: Uh323      Peaking Factor: 323.0  
Rainfall File: Scsiii      Storm Duration(hrs): 24.00  
Rainfall Amount(in): 0.000      Time of Conc(min): 6.00  
Area(ac): 0.600      Time Shift(hrs): 0.00  
Curve Number: 86.00      Max Allowable Q(cfs): 999999.000  
DCIA(%): 0.00

---

Name: PST-5      Node: Dry Detention 1      Status: Onsite  
Group: BASE      Type: SCS Unit Hydrograph CN

Unit Hydrograph: Uh323      Peaking Factor: 323.0  
Rainfall File: Scsiii      Storm Duration(hrs): 24.00  
Rainfall Amount(in): 0.000      Time of Conc(min): 6.00  
Area(ac): 1.740      Time Shift(hrs): 0.00  
Curve Number: 94.00      Max Allowable Q(cfs): 999999.000  
DCIA(%): 0.00

---

Name: PST-6      Node: Pond 2      Status: Onsite  
Group: BASE      Type: SCS Unit Hydrograph CN

Unit Hydrograph: Uh323      Peaking Factor: 323.0  
Rainfall File: Scsiii      Storm Duration(hrs): 24.00  
Rainfall Amount(in): 0.000      Time of Conc(min): 8.00  
Area(ac): 6.620      Time Shift(hrs): 0.00  
Curve Number: 89.00      Max Allowable Q(cfs): 999999.000  
DCIA(%): 0.00

---

Name: PST-7      Node: Post BNDY      Status: Onsite  
Group: BASE      Type: SCS Unit Hydrograph CN

Unit Hydrograph: Uh323      Peaking Factor: 323.0  
Rainfall File: Scsiii      Storm Duration(hrs): 24.00  
Rainfall Amount(in): 0.000      Time of Conc(min): 15.00  
Area(ac): 8.230      Time Shift(hrs): 0.00  
Curve Number: 77.00      Max Allowable Q(cfs): 999999.000  
DCIA(%): 0.00

---

==== Nodes =====

Name: DB-1      Base Flow(cfs): 0.000      Init Stage(ft): 15.000  
Group: BASE      Warn Stage(ft): 22.000

---

Type: Stage/Area

Stage(ft)	Area(ac)
15.000	0.1000
16.000	0.2500
17.000	0.3700
18.000	0.6200
19.000	1.0200
20.000	1.4500
21.000	1.9100
22.000	2.2600

---

Name: Ditch A	Base Flow(cfs): 0.000	Init Stage(ft): 12.000
Group: BASE		Warn Stage(ft): 16.000
Type: Stage/Area		

Stage(ft)	Area(ac)
-----------	----------

---

Name: Dry Detention 1	Base Flow(cfs): 0.000	Init Stage(ft): 13.000
Group: BASE		Warn Stage(ft): 16.000
Type: Stage/Area		

Stage(ft)	Area(ac)
13.000	0.0320
14.000	0.0960
15.000	0.1380
16.000	0.1820

---

Name: Dry Detention 2	Base Flow(cfs): 0.000	Init Stage(ft): 14.000
Group: BASE		Warn Stage(ft): 17.000
Type: Stage/Area		

Stage(ft)	Area(ac)
14.000	0.0250
15.000	0.1300
16.000	0.1890
17.000	0.2480

---

Name: Pond 1	Base Flow(cfs): 0.000	Init Stage(ft): 13.000
Group: BASE		Warn Stage(ft): 16.000
Type: Stage/Area		

Stage(ft)	Area(ac)
13.000	0.1230

---

Pine Street Development

14.000	0.1420
15.000	0.1630
16.000	0.1860

-----  
Name: Pond 2                      Base Flow(cfs): 0.000                      Init Stage(ft): 11.000  
Group: BASE                              Warn Stage(ft): 16.000  
Type: Stage/Area

Stage(ft)	Area(ac)
11.000	0.3200
12.000	0.3560
13.000	0.3930
14.000	0.4320
15.000	0.4720
16.000	0.5130

-----  
Name: Post BNDY                      Base Flow(cfs): 0.000                      Init Stage(ft): 11.000  
Group: BASE                              Warn Stage(ft): 14.000  
Type: Time/Stage

Time(hrs)	Stage(ft)
0.00	11.000
24.00	11.000

-----  
Name: Pre BNDY                      Base Flow(cfs): 0.000                      Init Stage(ft): 11.000  
Group: BASE                              Warn Stage(ft): 14.000  
Type: Time/Stage

Time(hrs)	Stage(ft)
0.00	11.000
30.00	11.000

==== Pipes =====  
=====

Name: Ditch A-BNDY	From Node: Ditch A	Length(ft): 1289.00
Group: BASE	To Node: Post BNDY	Count: 1
		Friction Equation: Automatic
		Solution Algorithm: Most Restrictive
UPSTREAM	DOWNSTREAM	Flow: Both
Geometry: Circular	Circular	Entrance Loss Coef: 0.00
Span(in): 36.00	36.00	Exit Loss Coef: 1.00
Rise(in): 36.00	36.00	Bend Loss Coef: 0.00
Invert(ft): 13.200	12.000	Outlet Ctrl Spec: Use dc or tw
Manning's N: 0.013000	0.013000	Inlet Ctrl Spec: Use dc
Top Clip(in): 0.000	0.000	Stabilizer Option: None
Bot Clip(in): 0.000	0.000	

Upstream FHWA Inlet Edge Description:  
Circular Concrete: Square edge w/ headwall

Pine Street Development



Downstream FHWA Inlet Edge Description:  
Circular Concrete: Square edge w/ headwall

```
-----
Name: POST 1:BNDY      From Node: DB-1      Length(ft): 1508.00
Group: BASE            To Node: Post BNDY      Count: 1
                        Friction Equation: Automatic
                        Solution Algorithm: Most Restrictive
                        Flow: Both
UPSTREAM              DOWNSTREAM
Geometry: Circular    Circular
Span(in): 24.00       24.00
Rise(in): 24.00       24.00
Invert(ft): 15.000    12.000
Manning's N: 0.013000 0.013000
Top Clip(in): 0.000   0.000
Bot Clip(in): 0.000   0.000
Entrance Loss Coef: 0.00
Exit Loss Coef: 1.00
Bend Loss Coef: 0.00
Outlet Ctrl Spec: Use dc or tw
Inlet Ctrl Spec: Use dc
Stabilizer Option: None
-----
```

Upstream FHWA Inlet Edge Description:  
Circular Concrete: Square edge w/ headwall

Downstream FHWA Inlet Edge Description:  
Circular Concrete: Square edge w/ headwall

```
=====
==== Channels =====
=====
```

```
Name:                From Node:      Length(ft): 0.00
Group: BASE          To Node:          Count: 1
                        Friction Equation: Automatic
                        Solution Algorithm: Automatic
                        Flow: Both
UPSTREAM              DOWNSTREAM
Geometry: Trapezoidal Trapezoidal
Invert(ft): 0.000     0.000
TClpInitZ(ft): 9999.000 9999.000
Manning's N: 0.000000 0.000000
Top Clip(ft): 0.000   0.000
Bot Clip(ft): 0.000   0.000
Main XSec:           Outlet Ctrl Spec: Use dc or tw
AuxElev1(ft):        Inlet Ctrl Spec: Use dc
Aux XSec1:           Stabilizer Option: None
AuxElev2(ft):
Aux XSec2:
Top Width(ft):
Depth(ft):
Bot Width(ft): 0.000   0.000
LtSdSlp(h/v): 0.00    0.00
RtSdSlp(h/v): 0.00    0.00
Contraction Coef: 0.100
Expansion Coef: 0.300
Entrance Loss Coef: 0.000
Exit Loss Coef: 0.000
-----
```

```
==== Drop Structures =====
=====
```

```
Name: Dry1-Pond2      From Node: Dry Detention 1  Length(ft): 750.00
Group: BASE          To Node: Pond 2      Count: 1
UPSTREAM              DOWNSTREAM      Friction Equation: Automatic
-----
```

Pine Street Development

Geometry: Circular	Circular	Solution Algorithm: Most Restrictive
Span(in): 36.00	36.00	Flow: Both
Rise(in): 36.00	36.00	Entrance Loss Coef: 0.000
Invert(ft): 10.000	7.000	Exit Loss Coef: 1.000
Manning's N: 0.013000	0.013000	Outlet Ctrl Spec: Use dc or tw
Top Clip(in): 0.000	0.000	Inlet Ctrl Spec: Use dc
Bot Clip(in): 0.000	0.000	Solution Incs: 10

Upstream FHWA Inlet Edge Description:  
Circular Concrete: Square edge w/ headwall

Downstream FHWA Inlet Edge Description:  
Circular Concrete: Square edge w/ headwall

\*\*\* Weir 1 of 1 for Drop Structure Dry1-Pond2 \*\*\*

TABLE

Count: 1	Bottom Clip(in): 0.000
Type: Horizontal	Top Clip(in): 0.000
Flow: Both	Weir Disc Coef: 3.200
Geometry: Rectangular	Orifice Disc Coef: 0.600
Span(in): 24.00	Invert(ft): 13.500
Rise(in): 24.00	Control Elev(ft): 13.500

-----  
Name: Dry2-Pond2      From Node: Dry Detention 2      Length(ft): 850.00  
Group: BASE      To Node: Pond 2      Count: 1

UPSTREAM	DOWNSTREAM	Friction Equation: Automatic
Geometry: Circular	Circular	Solution Algorithm: Most Restrictive
Span(in): 36.00	36.00	Flow: Both
Rise(in): 36.00	36.00	Entrance Loss Coef: 0.000
Invert(ft): 10.260	7.000	Exit Loss Coef: 1.000
Manning's N: 0.013000	0.013000	Outlet Ctrl Spec: Use dc or tw
Top Clip(in): 0.000	0.000	Inlet Ctrl Spec: Use dc
Bot Clip(in): 0.000	0.000	Solution Incs: 10

Upstream FHWA Inlet Edge Description:  
Circular Concrete: Square edge w/ headwall

Downstream FHWA Inlet Edge Description:  
Circular Concrete: Square edge w/ headwall

\*\*\* Weir 1 of 1 for Drop Structure Dry2-Pond2 \*\*\*

TABLE

Count: 1	Bottom Clip(in): 0.000
Type: Horizontal	Top Clip(in): 0.000
Flow: Both	Weir Disc Coef: 3.200
Geometry: Rectangular	Orifice Disc Coef: 0.600
Span(in): 24.00	Invert(ft): 14.500
Rise(in): 24.00	Control Elev(ft): 14.500

-----  
Name: Pond 2-BNDY      From Node: Pond 2      Length(ft): 34.00  
Group: BASE      To Node: Post BNDY      Count: 1

UPSTREAM	DOWNSTREAM	Friction Equation: Automatic
----------	------------	------------------------------

Pine Street Development

Geometry: Circular	Circular	Solution Algorithm: Most Restrictive
Span(in): 36.00	36.00	Flow: Both
Rise(in): 36.00	36.00	Entrance Loss Coef: 0.000
Invert(ft): 11.000	11.000	Exit Loss Coef: 1.000
Manning's N: 0.013000	0.013000	Outlet Ctrl Spec: Use dc or tw
Top Clip(in): 0.000	0.000	Inlet Ctrl Spec: Use dc
Bot Clip(in): 0.000	0.000	Solution Incs: 10

Upstream FHWA Inlet Edge Description:  
Circular Concrete: Square edge w/ headwall

Downstream FHWA Inlet Edge Description:  
Circular Concrete: Square edge w/ headwall

## \*\*\* Weir 1 of 3 for Drop Structure Pond 2-BNDY \*\*\*

TABLE

Count: 1	Bottom Clip(in): 0.000
Type: Horizontal	Top Clip(in): 0.000
Flow: Both	Weir Disc Coef: 3.200
Geometry: Rectangular	Orifice Disc Coef: 0.600
Span(in): 36.00	Invert(ft): 15.000
Rise(in): 36.00	Control Elev(ft): 15.000

## \*\*\* Weir 2 of 3 for Drop Structure Pond 2-BNDY \*\*\*

TABLE

Count: 1	Bottom Clip(in): 0.000
Type: Vertical: Mavis	Top Clip(in): 0.000
Flow: Both	Weir Disc Coef: 3.200
Geometry: Rectangular	Orifice Disc Coef: 0.600
Span(in): 4.00	Invert(ft): 11.000
Rise(in): 13.20	Control Elev(ft): 11.000

## \*\*\* Weir 3 of 3 for Drop Structure Pond 2-BNDY \*\*\*

TABLE

Count: 1	Bottom Clip(in): 0.000
Type: Vertical: Mavis	Top Clip(in): 0.000
Flow: Both	Weir Disc Coef: 3.200
Geometry: Rectangular	Orifice Disc Coef: 0.600
Span(in): 15.00	Invert(ft): 12.100
Rise(in): 34.80	Control Elev(ft): 12.100

-----	
Name: Pond1-BNDY	From Node: Pond 1
Group: BASE	To Node: Post BNDY
	Length(ft): 1858.00
	Count: 1
UPSTREAM	DOWNSTREAM
Geometry: Circular	Circular
Span(in): 18.00	18.00
Rise(in): 18.00	18.00
Invert(ft): 13.200	12.000
Manning's N: 0.013000	0.013000
Top Clip(in): 0.000	0.000
Bot Clip(in): 0.000	0.000
	Friction Equation: Automatic
	Solution Algorithm: Most Restrictive
	Flow: Both
	Entrance Loss Coef: 0.000
	Exit Loss Coef: 1.000
	Outlet Ctrl Spec: Use dc or tw
	Inlet Ctrl Spec: Use dc
	Solution Incs: 10

Upstream FHWA Inlet Edge Description:  
Circular Concrete: Square edge w/ headwall

Downstream FHWA Inlet Edge Description:

Pine Street Development



---

Circular Concrete: Square edge w/ headwall

## \*\*\* Weir 1 of 3 for Drop Structure Pond1-BNDY \*\*\*

Count: 1	Bottom Clip(in): 0.000
Type: Horizontal	Top Clip(in): 0.000
Flow: Both	Weir Disc Coef: 3.200
Geometry: Rectangular	Orifice Disc Coef: 0.600
Span(in): 36.00	Invert(ft): 15.000
Rise(in): 36.00	Control Elev(ft): 15.000

TABLE

## \*\*\* Weir 2 of 3 for Drop Structure Pond1-BNDY \*\*\*

Count: 1	Bottom Clip(in): 0.000
Type: Vertical: Mavis	Top Clip(in): 0.000
Flow: Both	Weir Disc Coef: 3.200
Geometry: Rectangular	Orifice Disc Coef: 0.600
Span(in): 3.00	Invert(ft): 13.000
Rise(in): 12.00	Control Elev(ft): 13.000

TABLE

## \*\*\* Weir 3 of 3 for Drop Structure Pond1-BNDY \*\*\*

Count: 1	Bottom Clip(in): 0.000
Type: Vertical: Mavis	Top Clip(in): 0.000
Flow: Both	Weir Disc Coef: 3.200
Geometry: Rectangular	Orifice Disc Coef: 0.600
Span(in): 12.00	Invert(ft): 14.000
Rise(in): 12.00	Control Elev(ft): 14.000

TABLE

=====  
==== Weirs =====  
=====

Name: Pond2-BNDY-W	From Node: Pond 2
Group: BASE	To Node: Post BNDY
Flow: Both	Count: 1
Type: Vertical: Fread	Geometry: Trapezoidal

Bottom Width(ft): 15.00  
Left Side Slope(h/v): 3.00  
Right Side Slope(h/v): 3.00  
Invert(ft): 15.250  
Control Elevation(ft): 15.250  
Struct Opening Dim(ft): 9999.00

TABLE

Bottom Clip(ft): 0.000
Top Clip(ft): 0.000
Weir Discharge Coef: 3.200
Orifice Discharge Coef: 0.600

=====  
==== Hydrology Simulations =====  
=====

Name: 002  
Filename: O:\Data\Projects\210148-Pine Street Development\2-Design\2-Reports\Stormwater\ICPR\210148-Hydrology Simulation.R32

---

Pine Street Development

Override Defaults: Yes  
Storm Duration(hrs): 24.00  
Rainfall File: Scsiii  
Rainfall Amount(in): 4.20

Time(hrs)	Print Inc(min)
30.000	5.00

-----  
Name: 010  
Filename: O:\Data\Projects\210148-Pine Street Development\2-Design\2-Reports\Stormwater\ICPR\10.R32

Override Defaults: Yes  
Storm Duration(hrs): 24.00  
Rainfall File: Scsiii  
Rainfall Amount(in): 6.40

Time(hrs)	Print Inc(min)
30.000	5.00

-----  
Name: 025  
Filename: O:\Data\Projects\210148-Pine Street Development\2-Design\2-Reports\Stormwater\ICPR\25.R32

Override Defaults: Yes  
Storm Duration(hrs): 24.00  
Rainfall File: Scsiii  
Rainfall Amount(in): 7.80

Time(hrs)	Print Inc(min)
30.000	5.00

-----  
Name: 050  
Filename: O:\Data\Projects\210148-Pine Street Development\2-Design\2-Reports\Stormwater\ICPR\50.R32

Override Defaults: Yes  
Storm Duration(hrs): 24.00  
Rainfall File: Scsiii  
Rainfall Amount(in): 9.00

Time(hrs)	Print Inc(min)
30.000	5.00

-----  
Name: 100  
Filename: O:\Data\Projects\210148-Pine Street Development\2-Design\2-Reports\Stormwater\ICPR\100.R32

Override Defaults: Yes  
Storm Duration(hrs): 24.00  
Rainfall File: Scsiii  
Rainfall Amount(in): 10.20

Time(hrs)	Print Inc(min)
30.000	5.00

-----  
Name: 95th

---

Pine Street Development

---

Filename: O:\Data\Projects\210148-Pine Street Development\2-Design\2-Reports\Stormwater\ICPR\95th.R32

Override Defaults: Yes  
Storm Duration(hrs): 24.00  
Rainfall File: Scsiii  
Rainfall Amount(in): 1.95

Time(hrs)	Print Inc(min)
30.000	5.00

==== Routing Simulations =====

Name: 002 Hydrology Sim: 002  
Filename: O:\Data\Projects\210148-Pine Street Development\2-Design\2-Reports\Stormwater\ICPR\002.I32

Execute: Yes Restart: No Patch: No  
Alternative: No

Max Delta Z(ft): 1.00	Delta Z Factor: 0.00500
Time Step Optimizer: 10.000	
Start Time(hrs): 0.000	End Time(hrs): 24.00
Min Calc Time(sec): 0.5000	Max Calc Time(sec): 60.0000
Boundary Stages:	Boundary Flows:

Time(hrs)	Print Inc(min)
999.000	15.000

Group	Run
BASE	Yes

-----  
Name: 010 Hydrology Sim: 010  
Filename: O:\Data\Projects\210148-Pine Street Development\2-Design\2-Reports\Stormwater\ICPR\010.I32

Execute: Yes Restart: No Patch: No  
Alternative: No

Max Delta Z(ft): 1.00	Delta Z Factor: 0.00500
Time Step Optimizer: 10.000	
Start Time(hrs): 0.000	End Time(hrs): 24.00
Min Calc Time(sec): 0.5000	Max Calc Time(sec): 60.0000
Boundary Stages:	Boundary Flows:

Time(hrs)	Print Inc(min)
999.000	15.000

Group	Run
BASE	Yes

-----  
Name: 025 Hydrology Sim: 025

---

Pine Street Development



---

Filename: O:\Data\Projects\210148-Pine Street Development\2-Design\2-Reports\Stormwater\ICPR\025.I32

Execute: Yes            Restart: No            Patch: No  
Alternative: No

Max Delta Z(ft): 1.00            Delta Z Factor: 0.00500  
Time Step Optimizer: 10.000  
Start Time(hrs): 0.000            End Time(hrs): 24.00  
Min Calc Time(sec): 0.5000        Max Calc Time(sec): 60.0000  
Boundary Stages:            Boundary Flows:

Time(hrs)            Print Inc(min)  
-----  
999.000            15.000

Group            Run  
-----  
BASE            Yes

-----  
Name: 050            Hydrology Sim: 050  
Filename: O:\Data\Projects\210148-Pine Street Development\2-Design\2-Reports\Stormwater\ICPR\050.I32

Execute: Yes            Restart: No            Patch: No  
Alternative: No

Max Delta Z(ft): 1.00            Delta Z Factor: 0.00500  
Time Step Optimizer: 10.000  
Start Time(hrs): 0.000            End Time(hrs): 24.00  
Min Calc Time(sec): 0.5000        Max Calc Time(sec): 60.0000  
Boundary Stages:            Boundary Flows:

Time(hrs)            Print Inc(min)  
-----  
999.000            15.000

Group            Run  
-----  
BASE            Yes

-----  
Name: 100            Hydrology Sim: 100  
Filename: O:\Data\Projects\210148-Pine Street Development\2-Design\2-Reports\Stormwater\ICPR\100.I32

Execute: Yes            Restart: No            Patch: No  
Alternative: No

Max Delta Z(ft): 1.00            Delta Z Factor: 0.00500  
Time Step Optimizer: 10.000  
Start Time(hrs): 0.000            End Time(hrs): 24.00  
Min Calc Time(sec): 0.5000        Max Calc Time(sec): 60.0000  
Boundary Stages:            Boundary Flows:

Time(hrs)            Print Inc(min)  
-----  
999.000            15.000

---

Pine Street Development

Group	Run
-----	-----
BASE	Yes

-----

Name: 95th	Hydrology Sim: 95th	
Filename: O:\Data\Projects\210148-Pine Street Development\2-Design\2-Reports\Stormwater\ICPR\95th.I32		
Execute: Yes	Restart: No	Patch: No
Alternative: No		
Max Delta Z(ft): 1.00	Delta Z Factor: 0.00500	
Time Step Optimizer: 10.000		
Start Time(hrs): 0.000	End Time(hrs): 24.00	
Min Calc Time(sec): 0.5000	Max Calc Time(sec): 60.0000	
Boundary Stages:	Boundary Flows:	

Time(hrs)	Print Inc(min)
-----	-----
999.000	15.000

Group	Run
-----	-----
BASE	Yes

# WinTR-55 Current Data Description

## --- Identification Data ---

User: BMT Date: 12/22/2022  
 Project: Pine Street Development Units: English  
 SubTitle: 210148 Areal Units: Acres  
 State: South Carolina  
 County: Beaufort  
 Filename: O:\Data\Projects\210148-Pine Street Development\2-Design\2-Reports\Stormwater\TR-55\210148-TR55

## --- Sub-Area Data ---

Name	Description	Reach	Area (ac)	RCN	Tc
PRE 1			22.37	78	.648
POST DB 1			11.62	77	.54
POST DB 2			1.19	88	0.1
POST DB 3			0.6	80	.224
POST DB 4			0.6	86	0.1
POST DB 5			1.74	94	0.1
POST DB 6			6.62	89	.136
POST DB 7			8.23	77	.254
PRE-2			8.23	77	.254

Total area: 61.20 (ac)

## --- Storm Data --

### Rainfall Depth by Rainfall Return Period

2-Yr (in)	5-Yr (in)	10-Yr (in)	25-Yr (in)	50-Yr (in)	100-Yr (in)	1-Yr (in)
4.5	5.9	6.8	7.8	8.8	10.0	3.7

Storm Data Source: Beaufort County, SC (NRCS)  
 Rainfall Distribution Type: Type III  
 Dimensionless Unit Hydrograph: <standard>



BMT

Pine Street Development  
210148  
Beaufort County, South Carolina

Storm Data

Rainfall Depth by Rainfall Return Period

2-Yr (in)	5-Yr (in)	10-Yr (in)	25-Yr (in)	50-Yr (in)	100-Yr (in)	1-Yr (in)
4.5	5.9	6.8	7.8	8.8	10.0	3.7

Storm Data Source: Beaufort County, SC (NRCS)  
Rainfall Distribution Type: Type III  
Dimensionless Unit Hydrograph: <standard>

BMT

Pine Street Development  
210148  
Beaufort County, South Carolina

Sub-Area Summary Table

Sub-Area Identifier	Drainage Area (ac)	Time of Concentration (hr)	Curve Number	Receiving Reach	Sub-Area Description
PRE 1	22.37	0.648	78		
POST DB 1	11.62	0.540	77		
POST DB 2	1.19	0.100	88		
POST DB 3	.60	0.224	80		
POST DB 4	.60	0.100	86		
POST DB 5	1.74	0.100	94		
POST DB 6	6.62	0.136	89		
POST DB 7	8.23	0.254	77		
PRE-2	8.23	0.254	77		
-----					
Total Area:	61.20 (ac)				

BMT

Pine Street Development  
210148  
Beaufort County, South Carolina

Sub-Area Time of Concentration Details

Sub-Area Identifier/	Flow Length (ft)	Slope (ft/ft)	Mannings's n	End Area (sq ft)	Wetted Perimeter (ft)	Velocity (ft/sec)	Travel Time (hr)
-----							
PRE 1							
SHEET	100	0.0130	0.400				0.359
SHALLOW	1915	0.0130	0.050				0.289
					Time of Concentration		.648
							=====
POST DB 1							
SHEET	100	0.0120	0.400				0.370
SHALLOW	480	0.0193	0.050				0.059
CHANNEL	800				2.000		0.111
					Time of Concentration		.54
							=====
POST DB 2							
SHEET	100	0.0400	0.011				0.013
SHALLOW	374	0.0211	0.025				0.035
					Time of Concentration		0.1
							=====
POST DB 3							
SHEET	100	0.0080	0.150				0.199
SHALLOW	138	0.0092	0.050				0.025
					Time of Concentration		.224
							=====
POST DB 4							
SHEET	100	0.1200	0.011				0.008
SHALLOW	30	0.0923	0.050				0.002
					Time of Concentration		0.1
							=====
POST DB 5							
SHEET	100	0.0500	0.011				0.012
SHALLOW	58	0.0316	0.050				0.006
					Time of Concentration		0.1
							=====
POST DB 6							
SHEET	100	0.0100	0.011				0.022
SHALLOW	957	0.0132	0.025				0.114
					Time of Concentration		.136
							=====
POST DB 7							
SHEET	100	0.0350	0.240				0.160
SHALLOW	300	0.0302	0.050				0.030
SHALLOW	500	0.0180	0.050				0.064
					Time of Concentration		.254
							=====
PRE-2							
SHEET	100	0.0350	0.240				0.160
SHALLOW	500	0.0180	0.050				0.064

15000.000302

SHALLOW

500

0.0180

0.050

0.050

1

12/23/2022

0.0300:47 PM



BMT

Pine Street Development  
210148  
Beaufort County, South Carolina

Sub-Area Time of Concentration Details (continued)

Sub-Area Identifier/	Flow Length (ft)	Slope (ft/ft)	Mannings's n	End Area (sq ft)	Wetted Perimeter (ft)	Velocity (ft/sec)	Travel Time (hr)
-----							
						Time of Concentration	.254
							=====

BMT

Pine Street Development  
210148  
Beaufort County, South Carolina

Sub-Area Land Use and Curve Number Details

Sub-Area Identifier	Land Use		Hydrologic Soil Group	Sub-Area Area (ac)	Curve Number
PRE 1	Open space; grass cover > 75%	(good)	D	2.525	80
	Paved parking lots, roofs, driveways		D	.15	98
	Dirt (w/ right-of-way)		D	.629	89
	Woods	(good)	D	19.07	77
	Total Area / Weighted Curve Number			22.37	78
				=====	==
POST DB 1	Dirt (w/ right-of-way)		D	.306	89
	Woods	(good)	D	11.314	77
	Total Area / Weighted Curve Number			11.62	77
				=====	==
POST DB 2	Open space; grass cover > 75%	(good)	D	.663	80
	Paved parking lots, roofs, driveways		D	.527	98
	Total Area / Weighted Curve Number			1.19	88
				=====	==
POST DB 3	Open space; grass cover > 75%	(good)	D	.6	80
	Total Area / Weighted Curve Number			.6	80
				=====	==
POST DB 4	Open space; grass cover > 75%	(good)	D	.396	80
	Paved parking lots, roofs, driveways		D	.204	98
	Total Area / Weighted Curve Number			.6	86
				=====	==
POST DB 5	Open space; grass cover > 75%	(good)	D	.433	80
	Paved parking lots, roofs, driveways		D	1.307	98
	Total Area / Weighted Curve Number			1.74	94
				=====	==
POST DB 6	Open space; grass cover > 75%	(good)	D	3.157	80
	Paved parking lots, roofs, driveways		D	3.463	98
	Total Area / Weighted Curve Number			6.62	89
				=====	==
POST DB 7	Woods - grass combination	(good)	D	1.79	79
	Woods	(good)	D	6.44	77
	Total Area / Weighted Curve Number			8.23	77
				=====	==
PRE-2	Woods - grass combination	(good)	D	1.79	79
	Woods	(good)	D	6.44	77
	Total Area / Weighted Curve Number			8.23	77
				=====	==

## 210148-Node Map

### Nodes


A Stage/Area  
V Stage/Volume  
T Time/Stage  
M Manhole

### Basins

O Overland Flow  
U SCS Unit CN  
S SBUH CN  
Y SCS Unit GA  
Z SBUH GA

### Links

P Pipe  
W Weir  
C Channel  
D Drop Structure  
B Bridge  
R Rating Curve  
H Breach  
E Percolation  
F Filter  
X Exfil Trench







Name: PRE-2 Group: BASE  Unit Hydrograph: Uh323 Rainfall File: Scsiii Rainfall Amount(in): 0.000 Area(ac): 8.230 Curve Number: 77.00 DCIA(%): 0.00	Node: Pre BNDY Type: SCS Unit Hydrograph CN  Peaking Factor: 323.0 Storm Duration(hrs): 24.00 Time of Conc(min): 15.00 Time Shift(hrs): 0.00 Max Allowable Q(cfs): 999999.000	Status: Onsite
-----		
Name: PRE1 Group: BASE  Unit Hydrograph: Uh323 Rainfall File: Scsiii Rainfall Amount(in): 0.000 Area(ac): 22.370 Curve Number: 78.00 DCIA(%): 0.00	Node: Pre BNDY Type: SCS Unit Hydrograph CN  Peaking Factor: 323.0 Storm Duration(hrs): 24.00 Time of Conc(min): 39.00 Time Shift(hrs): 0.00 Max Allowable Q(cfs): 999999.000	Status: Onsite
-----		
Name: PST-1 Group: BASE  Unit Hydrograph: Uh323 Rainfall File: Scsiii Rainfall Amount(in): 0.000 Area(ac): 11.620 Curve Number: 77.00 DCIA(%): 0.00	Node: DB-1 Type: SCS Unit Hydrograph CN  Peaking Factor: 323.0 Storm Duration(hrs): 24.00 Time of Conc(min): 32.00 Time Shift(hrs): 0.00 Max Allowable Q(cfs): 999999.000	Status: Onsite
-----		
Name: PST-2 Group: BASE  Unit Hydrograph: Uh323 Rainfall File: Scsiii Rainfall Amount(in): 0.000 Area(ac): 1.190 Curve Number: 88.00 DCIA(%): 0.00	Node: Pond 1 Type: SCS Unit Hydrograph CN  Peaking Factor: 323.0 Storm Duration(hrs): 24.00 Time of Conc(min): 6.00 Time Shift(hrs): 0.00 Max Allowable Q(cfs): 999999.000	Status: Onsite
-----		
Name: PST-3 Group: BASE  Unit Hydrograph: Uh323 Rainfall File: Scsiii Rainfall Amount(in): 0.000 Area(ac): 0.600 Curve Number: 80.00 DCIA(%): 0.00	Node: Ditch A Type: SCS Unit Hydrograph CN  Peaking Factor: 323.0 Storm Duration(hrs): 24.00 Time of Conc(min): 13.00 Time Shift(hrs): 0.00 Max Allowable Q(cfs): 999999.000	Status: Onsite

Name: PST-4 Group: BASE	Node: Dry Detention 2 Type: SCS Unit Hydrograph CN	Status: Onsite
Unit Hydrograph: Uh323 Rainfall File: Scsii Rainfall Amount(in): 0.000 Area(ac): 0.600 Curve Number: 86.00 DCIA(%): 0.00	Peaking Factor: 323.0 Storm Duration(hrs): 24.00 Time of Conc(min): 6.00 Time Shift(hrs): 0.00 Max Allowable Q(cfs): 999999.000	
Name: PST-5 Group: BASE	Node: Dry Detention 1 Type: SCS Unit Hydrograph CN	Status: Onsite
Unit Hydrograph: Uh323 Rainfall File: Scsii Rainfall Amount(in): 0.000 Area(ac): 1.740 Curve Number: 94.00 DCIA(%): 0.00	Peaking Factor: 323.0 Storm Duration(hrs): 24.00 Time of Conc(min): 6.00 Time Shift(hrs): 0.00 Max Allowable Q(cfs): 999999.000	
Name: PST-6 Group: BASE	Node: Pond 2 Type: SCS Unit Hydrograph CN	Status: Onsite
Unit Hydrograph: Uh323 Rainfall File: Scsii Rainfall Amount(in): 0.000 Area(ac): 6.620 Curve Number: 89.00 DCIA(%): 0.00	Peaking Factor: 323.0 Storm Duration(hrs): 24.00 Time of Conc(min): 8.00 Time Shift(hrs): 0.00 Max Allowable Q(cfs): 999999.000	
Name: PST-7 Group: BASE	Node: Post BNDY Type: SCS Unit Hydrograph CN	Status: Onsite
Unit Hydrograph: Uh323 Rainfall File: Scsii Rainfall Amount(in): 0.000 Area(ac): 8.230 Curve Number: 77.00 DCIA(%): 0.00	Peaking Factor: 323.0 Storm Duration(hrs): 24.00 Time of Conc(min): 15.00 Time Shift(hrs): 0.00 Max Allowable Q(cfs): 999999.000	

Name	Group	Simulation	Max Time Stage hrs	Max Stage ft	Warning Stage ft	Max Delta Stage ft	Max Surf Area ft2	Max Time Inflow hrs	Max Inflow cfs	Max Time Outflow hrs	Max Outflow cfs
DB-1	BASE	002	12.89	16.51	22.00	0.0031	14896	12.42	11.10	12.89	7.25
Ditch A	BASE	002	12.36	13.69	16.00	-1.2000	1468	12.25	0.97	12.36	0.88
Dry Detention 1	BASE	002	12.25	13.82	16.00	0.0034	3684	12.25	4.70	12.25	4.66
Dry Detention 2	BASE	002	12.26	14.64	17.00	0.0023	4004	12.25	1.38	12.26	1.30
Pond 1	BASE	002	12.57	14.10	16.00	0.0025	6273	12.25	2.87	12.57	0.70
Pond 2	BASE	002	12.50	13.59	16.00	0.0050	18113	12.25	21.84	12.50	8.51
Post BNDY	BASE	002	0.00	11.00	14.00	0.0000	172	12.36	24.61	0.00	0.00
Pre BNDY	BASE	002	0.00	11.00	14.00	0.0000	0	12.42	28.55	0.00	0.00
DB-1	BASE	010	13.27	17.83	22.00	-0.0049	25547	12.42	21.90	13.27	9.53
Ditch A	BASE	010	12.34	13.87	16.00	-1.2000	1649	12.25	1.79	12.34	1.68
Dry Detention 1	BASE	010	12.45	14.62	16.00	-0.0032	5311	12.25	7.35	12.03	6.33
Dry Detention 2	BASE	010	12.26	14.70	17.00	0.0024	4281	12.25	2.32	12.26	2.26
Pond 1	BASE	010	12.42	14.61	16.00	0.0027	6746	12.25	4.73	12.42	1.93
Pond 2	BASE	010	12.45	14.58	16.00	0.0050	19837	12.12	31.63	12.45	15.82
Post BNDY	BASE	010	0.00	11.00	14.00	0.0000	172	12.33	48.55	0.00	0.00
Pre BNDY	BASE	010	0.00	11.00	14.00	0.0000	0	12.33	56.00	0.00	0.00
DB-1	BASE	025	13.47	18.55	22.00	-0.0050	36934	12.42	29.05	13.47	10.48
Ditch A	BASE	025	12.34	13.96	16.00	-1.2000	1725	12.25	2.33	12.34	2.19
Dry Detention 1	BASE	025	12.44	15.09	16.00	0.0037	6191	12.25	9.02	11.96	6.44
Dry Detention 2	BASE	025	12.45	15.05	17.00	0.0024	5792	12.25	2.91	12.17	2.73
Pond 1	BASE	025	12.41	14.91	16.00	0.0029	7020	12.25	5.90	12.41	2.42
Pond 2	BASE	025	12.43	15.04	16.00	0.0050	20631	12.18	37.50	12.43	19.96
Post BNDY	BASE	025	0.00	11.00	14.00	0.0000	172	12.33	60.56	0.00	0.00
Pre BNDY	BASE	025	0.00	11.00	14.00	0.0000	0	12.33	74.22	0.00	0.00
DB-1	BASE	050	13.60	19.06	22.00	-0.0050	45897	12.42	35.24	13.60	11.14
Ditch A	BASE	050	12.33	14.04	16.00	-1.2000	1776	12.25	2.79	12.33	2.64
Dry Detention 1	BASE	050	12.40	15.41	16.00	0.0043	6798	12.25	10.45	11.94	6.22
Dry Detention 2	BASE	050	12.41	15.32	17.00	0.0031	6487	12.25	3.42	12.10	3.01
Pond 1	BASE	050	12.44	15.18	16.00	0.0029	7283	12.25	6.89	12.44	2.61
Pond 2	BASE	050	12.39	15.31	16.00	0.0050	21108	12.13	41.73	12.39	28.18
Post BNDY	BASE	050	0.00	11.00	14.00	0.0000	172	12.33	75.21	0.00	0.00
Pre BNDY	BASE	050	0.00	11.00	14.00	0.0000	0	12.33	89.99	0.00	0.00
DB-1	BASE	100	13.72	19.51	22.00	-0.0050	54323	12.42	41.46	13.72	11.73
Ditch A	BASE	100	12.33	14.11	16.00	-1.2000	1819	12.25	3.25	12.33	3.08
Dry Detention 1	BASE	100	12.37	15.66	16.00	0.0040	7282	12.25	11.87	12.42	6.49
Dry Detention 2	BASE	100	12.37	15.50	17.00	0.0029	6939	12.25	3.92	12.04	3.20
Pond 1	BASE	100	12.46	15.45	16.00	0.0029	7550	12.25	7.89	12.46	2.80
Pond 2	BASE	100	12.35	15.48	16.00	0.0050	21411	12.25	46.79	12.35	38.77
Post BNDY	BASE	100	0.00	11.00	14.00	0.0000	172	12.33	93.90	0.00	0.00
Pre BNDY	BASE	100	0.00	11.00	14.00	0.0000	0	12.33	105.81	0.00	0.00
DB-1	BASE	95th	13.22	15.51	22.00	0.0028	8986	12.50	1.98	13.22	1.14
Ditch A	BASE	95th	12.45	13.42	16.00	-1.2000	1063	12.33	0.22	12.45	0.17
Dry Detention 1	BASE	95th	12.25	13.68	16.00	0.0050	3280	12.25	1.94	12.25	1.90
Dry Detention 2	BASE	95th	14.52	14.51	17.00	0.0029	3434	12.25	0.44	14.52	0.04
Pond 1	BASE	95th	14.57	13.43	16.00	0.0020	5715	12.25	0.98	14.57	0.08
Pond 2	BASE	95th	13.26	12.07	16.00	0.0050	15615	12.25	7.40	13.26	0.99
Post BNDY	BASE	95th	0.00	11.00	14.00	0.0000	172	12.34	3.17	0.00	0.00
Pre BNDY	BASE	95th	0.00	11.00	14.00	0.0000	0	12.50	5.26	0.00	0.00








**Pond-1**

V15 = 0.008 ft/s  
q = 1.0 cfs  
A = 0.12 acres  
q/(AV) = 1,042

**Pond-2**


V15 = 0.008 ft/s  
q = 7.4 cfs  
A = 0.32 acres  
q/(AV) = 2,891



**DESIGN AID FOR ESTIMATING TRAPPING EFFICIENCY  
FOR SEDIMENT BASINS LOCATED IN LOW LYING  
AREAS AND/OR HAVING A HIGH WATER TABLE**



**FIGURE SV-1  
CHARACTERISTIC SETTLING VELOCITY AS A  
FUNCTION OF ERODED PARTICLE DIAMETER**



Emporia D15 K = 0.0098mm

Argent D15 K = 0.0057mm

Our ref: 12591408-00 | Pine Street Industrial Building

October 06, 2022

Mr. Tim Huber  
Ironline LLC  
300 Technology Drive  
Walterboro, South Carolina 29488

## Report of Subsurface Exploration and Geotechnical Evaluation

Dear Mr. Huber:

**GHD** is pleased to present the results of our subsurface exploration and geotechnical evaluation for the above-referenced project. Our services were performed in general accordance with our Proposal No. 12591408 dated August 10, 2022.

### 1. Site Description / Project Understanding

GHD has received project information via email correspondence with you beginning July 29, 2022. Project information provided to us and referenced in our evaluation includes a preliminary site plan drawing titled 'Conceptual Plan for Pine Street Residential' prepared by Witmer-Jones-Keefer, Ltd. and dated July 7, 2022.

The subject property is an approximately rectangular shaped parcel located in the northeast quadrant of the intersection of Highway 17/21 and Pine Street in Yemassee, South Carolina. The south approximate half (2.5 acres) of the property is identified by street address as 311 US Highway 21 and includes an existing single multi-family residence structure fronting on Highway 17/21 in the southwest corner, a concrete parking slab adjacent to the highway right-of-way in the central portion, and the balance is cleared of significant vegetation with visual evidence of widespread past ground disturbance. Multiple small piles of miscellaneous household debris, multiple abandoned vehicles, and several used vehicle tires were observed at widespread locations throughout this south portion of the overall property. In addition, review of historic aerial images available through Google Earth reveals that the concrete parking slab adjacent to the highway (described above) was associated with a structure (visible in a 1994 aerial image) that has been demolished and removed in the past. Further, it is our understanding that it has been reported that there may be buried debris within the south portion of the subject property.

The north portion of the subject property was observed to be vegetated with moderate density mature trees and moderate to dense underbrush. Two approximately parallel southwest/northeast oriented drainage ditches cross the subject property diagonally, one separating the south and north approximate halves and the second, further north, subdividing the northern portion into approximately equal halves. In addition, the two ditches detailed above are connected by a generally north/south oriented ditch in the central portion of the overall site.

We observed that the property is generally flat but with multiple isolated lower elevated areas throughout much of both the south and north portions. At the time of our clearing for drill rig access and excavation of the test pits, as well as at the time our soil test borings were performed, we observed significant flow of water within the drainage ditches described above as well as ponded surface water within the isolated lower elevated areas.

The conceptual site plan provided to us indicates that the existing multi-unit residence structure is to be removed and that new development is to include an industrial building having initial footprint dimensions of 200 feet by 500 feet and with an anticipated future expansion along the east side of an additional width of approximately 100 feet. As requested, our evaluation addresses the entire anticipated 300 feet by 500 feet footprint of the future building. The conceptual plan also indicates that the development will include paved entrances, drives and parking along the north, west and south sides of the proposed building.

Details of the proposed new structure have not been provided to us for reference in our analyses and evaluation. It is our assumption, and our evaluation is based upon our assumption, that the structure will be of some conventional combination of concrete masonry unit (CMU), steel frame, and/or wood frame design and that the preferred foundation system will be conventional shallow spread column/continuous wall footings and soil supported concrete floor slabs. We have assumed, as stated in our proposal to perform these services, for the purpose of our analyses, that the maximum design loads for isolated column footings and/or continuous strip foundations will not exceed 60 kips and 3.5 kips per linear foot, respectively. Further, we anticipate fill thicknesses of not greater than approximately 18 inches will be required in order to bring the building floor slab to the desired elevation.

With regard to paved access drives and parking areas, we anticipate that heavy duty pavements will be required for the main entrances and access drives and that light duty pavements will be sufficient for the parking areas.

It is our understanding that the purposes of this geotechnical site investigation are generally to explore and evaluate the underlying in situ soils and groundwater conditions to provide site preparation and shallow foundation design recommendations for the proposed new structure (including potential 'static' settlement estimates, seismic design parameters, and potential liquefaction induced settlement estimates) as well as site preparation and preliminary cross-section design recommendations for conventional asphalt pavements.

## 2. Subsurface Exploration

Our scope of services has included eight (8) soil test borings at widely dispersed locations throughout the footprint area of the proposed new structure and four (4) hand-auger borings at widely dispersed locations throughout the paved portions of the site as indicated on the preliminary conceptual site plan provided to us, as well as test pit excavations at thirteen (13) locations within the south portion of the property.

The locations of the soil test borings, hand-auger borings, and test pit excavations in **Figure 1**. A GHD professional positioned the explorations in the field utilizing a hand-held GPS device. Given the method of locating the explorations in the field, the locations indicated on **Figure 1** should be considered approximate.

### 2.1 SPT Soil Test Borings

The eight soil test borings (designated B-1 through B-8) were performed on September 14 and 15, 2022. Current International Building Code (IBC) requirements dictate that the geotechnical evaluation/foundation design process include a seismic analysis; which requires at least one boring be performed to sufficient depth to provide the necessary subsurface soils parameter information. Therefore, one of the borings (B-6) was advanced to a depth of 50 feet below the existing ground surface. The other borings were each advanced to a depth of 25 feet. The borings were advanced utilizing mud-rotary drilling equipment/methods. Closely spaced soil sampling was performed in the upper ten feet and at five-foot intervals thereafter in each boring. During the sampling procedure, Standard Penetration Tests (SPT's) were conducted in general accordance with ASTM D1586 to obtain the standard penetration value of the soil. The standard penetration value (N) is defined as the number of blows of a 140-pound hammer, falling thirty inches, required to advance the split spoon sampler one foot. The sampler is lowered to the bottom of the drill hole and the number of blows



recorded for each of three successive increments of six inches penetration. The “N” value is obtained by adding the second and third incremental values. The “N” values are reported on each boring log. The results of the SPT testing indicate the relative density and comparative consistency of the soils, and thereby provide a basis for estimating relative strength and compressibility of the soil profile components. The logs of each of the soil test borings are presented as **Appendix A, Soil Test Boring Logs**.

## 2.2 Hand-auger Borings

The four (4) hand-auger borings (designated HA-1 through HA-4) were performed on September 20, 2022. Each hand-auger boring was manually advanced to a depth of approximately 4 feet below the existing ground surface using a steel auger. The soils encountered were examined by retrieving samples of the auger cuttings at regular depth intervals during boring advancement. Our personnel visually classified the soils encountered in the field. The logs of the hand-auger borings are presented as **Appendix B, Hand-Auger Boring Logs**.

## 2.3 Test Pits

The test pit excavations (designated TP-1 through TP-13, but with five (A – E) excavations in close proximity to each other at location TP-3 and three (A-C) at TP-9) were performed on September 7, 2022 to depths varying from approximately 3.5 to 11 feet below the existing ground surface. The soils encountered at each test pit location were examined and visually classified during the excavation of each test pit and representative samples of the various strata encountered were collected. The logs of the test pits are presented as **Appendix C, Test Pit Logs**.

## 2.4 Soil Sample Handling

The soils from each soil boring sample/SPT test, selected hand-auger boring cuttings, and the representative test pit excavation samples were placed in individual containers, properly sealed and marked for identification, and transported to our laboratory for analysis and/or final classification by a GHD staff professional in accordance with the Unified Soil Classification System (USCS).

## 2.5 Laboratory Analyses

Selected samples of the soils obtained from the test pit excavations were tested in our laboratory to determine their percent fines (ASTM D1140) and natural moisture content (ASTM D2216). The laboratory data was used to aid in the classification of the soils in accordance with ASTM D2487 and to determine their engineering characteristics. The laboratory test results are included in the logs of test pit excavations in **Appendix C**.

# 3. Subsurface Stratigraphy/Conditions Encountered

A GHD professional developed the final boring log and test pit excavation log information from the field logs and visual review of the soil samples delivered to our laboratory. Similar soils were grouped into strata, with each stratum described in general accordance with the nomenclature used in ASTM D2487. Although indicated on the boring and test pit logs as distinct changes, the transition from one soil type or stratum to another may be gradual or may occur at slightly differing elevations than indicated between soil samples. Soil conditions may also vary from our findings at locations in areas of the site not explored.

The following discussion of the subsurface conditions encountered highlights the generalized major subsurface stratification encountered during our fieldwork. For more detailed descriptions of the subsurface conditions encountered at each location, please refer to the **Appendices A, B and C** to this report. The logs include the SPT “N” values (soil test borings), Unified Soil Classification System (USCS) symbols and groundwater levels at the time of our study.

### **3.1 Subsurface Soil Stratigraphy**

The specific soil types, stratifications and consistencies encountered varied significantly both with depth within individual explorations and between the exploration locations. However, a generalized description of the soil profile encountered throughout the majority of the overall property includes a thin surface veneer of organic topsoil, a surficial layer of clayey to very clayey fine sand (SC), sometimes including fine roots, to depths of approximately 1.5 to 2.5 feet, then varied strata of clays with varying fine sand content and fine sands of varying clay content (CL, CH, SC, SP-SC, SP) through the depth of the explorations.

Within the south portion of the property that had been previously cleared of significant vegetation, and from within which a previous structure had apparently been removed, our test pit excavations identified as TP-3 (A – E), TP-9 (A- C), and TP-11 all encountered significant quantities of miscellaneous household and/or construction debris to depths varying from approximately 1.5 to 3.5 feet below the existing ground surface, abandoned shallow concrete foundations, and an undocumented sewer pipe. The deeper soils at those three locations generally consisted of fine very sandy clay (CL). Within the remainder of the south portion of the property the explorations encountered surficial grass root mass and/or topsoil underlain by a shallow layer of clayey fine sand (SC) then fine very sandy clay (CL) or underlain directly by the fine very sandy clay.

### **3.2 Groundwater**

The depth to groundwater in the soil test borings measured after a stabilization period in excess of 24 hours varied from approximately 1 to 3 feet below the existing ground surface. No groundwater was encountered at the hand-auger locations. At test pit location TP-1, although moist soils were encountered beginning at depths of approximately 7 to 9 feet below the existing ground surface, no significant water inflow was observed.

The soil conditions observed at the exploration locations generally consisted of relatively permeable surficial and shallow subgrade soils having moderate clay content directly underlain by much less permeable very sandy clay or very clayey sand. These soil conditions are conducive to development of a ‘perched’ water condition within the near surface soils. A ‘perched’ condition occurs when surface water is not readily drained from the site and becomes ponded and/or permeates an upper more permeable soil strata while an underlying relatively impervious stratum prevents any further downward migration of the water, thus creating the ‘perched’ condition. The magnitude of ‘perched’ water is related to surficial soil permeability, lateral surface drainage onto and across the subject site, and the amount and duration of recent precipitation. The ‘perched groundwater’ may often be non-existent.

In general, we believe the variation in depth to stabilized groundwater levels in our soil test borings can be somewhat correlated to the topographic variation across the site. Also, there are a number of possible reasons why the groundwater depths vary, including localized perching within surficial sandy soils above clayey soils with low permeability and the effects of drainage feature installations and ground surface grading modifications within and/or in the vicinity of the site. We also expect groundwater levels will fluctuate depending upon the season, recent rainfall quantities in the area, and other factors.

## **4. Conclusions and Recommendations**

### **4.1 General**

The following conclusions and recommendations are based on the project characteristics previously described, the data obtained in our field explorations, and our experience with similar subsurface conditions and development projects. If the final design grades are to be significantly different from our understanding as stated earlier, or if subsurface conditions different from those disclosed by the soil test borings, hand-auger borings, and/or test pit excavations are encountered during site preparation, we should be notified so that we

might review the following preliminary recommendations in light of such additional information and/or changed conditions.

In general, it is our opinion that the subsurface conditions encountered by the soil test borings are suitable for support of the proposed structures using conventional shallow foundations following implementation of the site preparation and design recommendations discussed in the following sections of this report.

Further, our analyses indicate that, if liquefaction did occur, the magnitude of potential total settlement of the subgrade soils within the site could be on the order of 1 inch or less. Therefore, 'improvement' of the subsurface soils to a degree sufficient to reduce the magnitude of potential liquefaction induced settlement of the proposed structure to a lesser magnitude would likely not be warranted.

## **4.2 Site Preparation Recommendations**

### **4.2.1 Moisture Control**

Our explorations encountered moisture sensitive clayey soils at or very near the existing ground surface throughout the proposed structure/pavement areas. Strict moisture control will need to be maintained to avoid destabilization of the surficial and/or shallow subgrade soils during site preparation in these areas. Failure to control moisture in clayey soils may result in the need for removal and replacement of otherwise stable soils. Moisture control methods should also be implemented even where more favourable soils are located within the upper two feet. Moisture control methods should include, but are not necessarily be limited to:

- Staging the work to avoid excessive exposure to inclement weather;
- Installing drainage features such as ditches and ponds prior to initiating site clearing and grubbing;
- Maintaining positive drainage at the end of each work day or prior to inclement weather;
- Using a smooth drum roller or bulldozer to seal areas to facilitate runoff;
- And minimizing/limiting rubber-tired vehicle traffic by utilizing low contact pressure or tracked equipment whenever possible across the work area.

We highly recommend that surface water across the area be managed prior to, during and after stripping and grubbing operations to avoid excessive surface moisture which can lead to an unstable working surface and thus, undue mixing of the organic debris with the underlying soils. Therefore, it may be necessary to drain ponded surface water and to reduce the moisture content of the surficial and shallow subgrade soils prior to initiating general site preparation procedures.

### **4.2.2 Stripping and Grubbing / Uncontrolled Fill/Backfill Removal**

Site preparation should include the complete clearing, stripping and removal of all vegetation (including trees, underbrush, grasses/weeds, etc.), surficial topsoil, surficial and subgrade soils containing organic material and/or other debris, and other deleterious materials from within and to a minimum distance of five (5) feet beyond the perimeter of the structure footprints and pavement areas.

The depth to which topsoil, organic laden soils, miscellaneous debris, abandoned foundations and utilities, etc. was encountered at our exploration locations was generally on the order of a few inches to approximately 3.5 feet. It should be anticipated that the required depth of removal of deleterious materials and/or abandoned structures/utilities may be greater within un-explored portions of the site. During site clearing and earthwork operations, and while excavating for site utilities and foundations, the excavated and exposed soils should be observed for the presence of excessive organic and/or deleterious materials and debris that could be detrimental to building foundations, floor slabs and/or pavements. We recommend that an experienced soils engineering technician be present on site during the stripping, grubbing and uncontrolled fill/backfill removal process in order to determine which surficial and/or subgrade soils must be removed and replaced.



### 4.2.3 Exposed Subgrade Soils Proofrolling

After stripping and grubbing, and removal of debris/deleterious materials where necessary, GHD should inspect the disturbed surficial soils in structural (building and pavement) areas. Where practical, structural areas of the site should be proofrolled utilizing a loaded tri-axle dump truck, or other heavily loaded construction equipment. The purpose of the proofrolling will be to detect any areas where unstable soils are present. Materials that yield excessively during the proofrolling should be investigated via shallow test pits to verify the absence of organic laden soils, debris, or other deleterious materials. Where deleterious materials are not present, prior to fill placement, the soils should be over-excavated and replaced with structural fill soils meeting the material type and compaction requirements as outlined herein. GHD can recommend the nature and extent of any such remedial work.

### 4.2.4 Backfill/Fill Placement

#### 4.2.4.1 Building Footprint Areas

All fill within the proposed building footprint area should be inorganic, granular soils (clean to silty/clayey sands) with a maximum of 25 percent silt and/or clay. Backfill/fill should be placed in level lifts not to exceed 12 inches loose thickness and compacted to a minimum of 95 percent of the soil's "Modified" Proctor maximum dry density as determined by ASTM D1557.

#### 4.2.4.2 Conventional (Non-Permeable) Pavement Areas

Below 24 inches of Subgrade Elevation: All backfill/fill placed in conventional non-permeable paved parking and access drive areas at depths of 24 inches or deeper below pavement base should be inorganic, granular soils (clean to silty/clayey sands) with a maximum of 30 percent passing the No. 200 sieve. All backfill placed in undercut areas deeper than 24 inches below the pavement base course should be placed in level lifts not to exceed 12 inches in loose thickness and should be compacted to a minimum of 95 percent of the soil's maximum dry density as determined by ASTM D1557.

Upper 24 inches of Subgrade: Fill/backfill for the upper 24 inches in conventional non-permeable paved parking and access drive areas should be inorganic, granular soil (clean to silty / clayey sands) with a maximum of 20 percent passing the No. 200 sieve. Backfill/Fill within the upper 24 inches of the subgrade should be placed in level lifts not to exceed 12 inches in loose thickness and should be compacted to a minimum of 98 percent of the soil's maximum dry density as determined by ASTM D1557.

#### 4.2.4.3 General

In-place density tests should be performed on each lift by an experienced engineering technician working under the direction of a licensed geotechnical engineer to verify that the recommended degree of compaction has been achieved.

The top surface of the fill should extend a minimum of 3 feet beyond the perimeters of the structures/pavements and fill slopes should not exceed 2 horizontal to 1 vertical to prevent possible erosion or undermining of slabs, shallow footings and/or pavements. Shallower slopes may be dictated by site grading requirements.

## 4.3 Shallow Foundation / Floor Slab Design and Construction

### 4.3.1 Foundation Design / Dimensioning

When structural loads comply with the earlier stated assumed criteria, the footings may be proportioned for a maximum allowable bearing pressure of 2000 pounds per square foot (psf). To provide an adequate factor of

safety against a shearing failure in the subsoils: (1) all foundations should be founded at a depth of not less than 18 inches below the adjacent ground surface or floor slab elevation; (2) continuous footings should be at least 18 inches wide; and (3) isolated foundations should not be less than 24 inches in their least dimension.

### **4.3.2 Foundation Construction**

All foundation elements should be excavated, formed if necessary, and have their concrete cast in the dry. Care should also be taken when scheduling the excavation of foundations to avoid inclement weather as rain will make it necessary to control stormwater and/or 'perched' water that may infiltrate the exposed bearing soils. Any sandy soils at the bottom of the foundation excavations disturbed during the excavation process should be re-densified prior to placement of reinforcement steel. Any disturbed and/or softened clayey/silty soils should be removed and replaced with properly compacted structural fill or graded aggregate prior to placement of reinforcement steel. If this issue is encountered during construction, the geotechnical engineer should be consulted to evaluate the field conditions and to determine the extent of the required undercutting and appropriate alternatives for backfill. We also recommend that probing and/or dynamic cone penetrometer (DCP) testing be performed in the foundation excavations where the footings bear in or just above in-situ soils.

### **4.3.3 Floor Slab Design Recommendations**

A modulus of subgrade reaction of 200 psi/inch may be used for design of the floor slabs bearing on properly compacted structural fill. We recommend the placement of a vapor barrier below the floor slab(s). We suggest the use of polyethylene sheeting of at least 10-mil thickness for this purpose. Nevertheless, selection of the vapor barrier should consider the anticipated moisture conditions, flooring types and other applicable considerations.

The structural fill soils as specified herein for use in constructing the building pad are considered to be relatively free-draining soils. It is our opinion that these soils would be classified as "drainable" and that an additional aggregate material to act as a capillary barrier immediately below the floor slab would not be required.

Note that all downspouts/roof drains should be positioned such that stormwater is directed away from the structure and that the site should be constructed to meet the construction grading requirements.

### **4.3.4 Settlement**

Column and continuous wall foundations designed and constructed in the recommended manner are estimated to be subject to a maximum potential total settlement of less than about 0.5 inch, in the absence of a significant seismic event.

## **4.4 Seismic Considerations**

### **4.4.1 Liquefaction Potential**

The subject property is located within an active seismic zone with its center in the Charleston, South Carolina area. Although the area has not experienced significant earthquake events in the recent past, evidence of seismic event induced liquefaction has been found and geologists have mapped this area as having the potential for recurrence(s) of such an event. Considerable research is ongoing to better determine which local soils are truly liquefiable and the magnitude of settlement that might occur as a result of their liquefaction during a significant seismic event.

Based on our review of soil and groundwater conditions at the subject site, we believe there is a risk for liquefaction settlement to occur during a significant seismic event. Utilizing 'LiquefyPro' modelling software, we have performed a liquefaction analysis of the subject site considering the 'general' subsurface soil and groundwater conditions encountered and, in reference to the 2018 International Building Code (2018 IBC),

utilizing the Maximum Considered Earthquake Geometric Mean ( $MCE_G$ ) and Peak Ground Acceleration ( $PGAM$ ) which considers the soil characteristics of the site (Site Class effects). As previously stated, our analysis of the potential magnitude of settlement due to liquefaction indicates that following completion of the site preparation recommendations detailed above, settlement would be on the order of 1.0 inch or less within the area of the proposed structure. The potential liquefaction induced settlement would be due generally to the consolidation of the loose to medium dense saturated sand soils below the water table encountered at various depths below the existing ground surface. Due to the depth below the ground surface to the upper boundary of liquefiable soils, we estimate that differential liquefaction induced settlement within the building footprint would be on the order of 25 percent or less of the total.

#### 4.4.2 Seismic Design Parameters

Based upon the soil conditions encountered, our procedure for determining the site specific seismic design parameters follows that which is outlined in the 2018 International Building Code with reference to ASCE 7-16 for a default Seismic Site Class “D”. Values for Spectral Response Acceleration for short periods (0.2 seconds),  $S_s$ , and for long periods (1 second),  $S_1$ , were obtained from the Applied Technology Council (ATC) ‘Hazards by Location’ online tool which queries the United States Geological Survey (USGS) web servers and retrieves the seismic design variables in a report format. The values are expressed as a multiple of the acceleration of gravity. The design parameters generated are presented in **Appendix D, Seismic Design Parameters**.

### 4.5 Pavement Recommendations

The following pavement design guidelines are made without the benefit of specific traffic information and/or reference to any local minimum section standards, and are intended as a general guide for the design engineer’s evaluation. Site design decisions may dictate alterations to certain aspects of these guidelines.

#### 4.5.1 Conventional (Non-Pervious) Pavements

The following recommendations assume that site preparation procedures, including removal and replacement of unsuitable near surface soils/debris and proper proofrolling of subgrade soils detailed in earlier sections of this report, will have been completed where necessary. All conventional asphalt pavements and base courses should be constructed in accordance with the guidelines of the latest applicable South Carolina Department of Transportation Specifications.

**Entrance Drives & Truck Corridors:** We recommend an asphalt pavement section consisting of 3½ inches of asphaltic concrete (2 inches intermediate course + 1½ inches surface course) over 8 inches of graded aggregate base course. The pavement section should be underlain by a 24-inch sand subbase (with a maximum of 20 percent by weight passing the No. 200 sieve).

**Personal Vehicle Corridors & Parking Areas:** We recommend an asphalt pavement section consisting of 2 inches of asphaltic concrete (Type C) over 6 inches of graded aggregate base course. The pavement section should be underlain by a 24-inch sand subbase (with a maximum of 20 percent by weight passing the No. 200 sieve).

**Suitability of In Situ Soils:** Beneath the surficial organic debris/topsoil and shallow subgrade soils consisting of fine sand of varying clay content and/or very sandy clay, our explorations generally encountered unsuitable clay of varying fine sand content and/or very clayey fine sand at depths of less than 24 inches below the existing ground surface. These unsuitable soils will require removal and replacement with suitable select fill as detailed above to the depths necessary to provide the 24-inch sand subbase included in the recommended pavement section.



## 5. Limitations

*This report: has been prepared by GHD for Ironline LLC and may only be used and relied on by Ironline LLC and their selected consultants for the purposes agreed between GHD and Ironline LLC as set out in this report.*

*GHD otherwise disclaims responsibility to any person other than Ironline LLC arising in connection with this report. GHD also excludes implied warranties and conditions, to the extent legally permissible.*

*The services undertaken by GHD in connection with preparing this report were limited to those specifically detailed in the report and are subject to the scope limitations set out in the report.*

*The opinions, conclusions and any recommendations in this report are based on conditions encountered and information reviewed at the date of preparation of the report. GHD has no responsibility or obligation to update this report to account for events or changes occurring subsequent to the date that the report was prepared.*

*The opinions, conclusions and any recommendations in this report are based on assumptions made by GHD described in this report). GHD disclaims liability arising from any of the assumptions being incorrect.*

*GHD's scope of work for this project has not included investigation, detection, or evaluation related to the presence of any biological pollutants. The term 'biological pollutants' includes, but is not limited to, mold, fungi, spores, bacteria, and viruses, and the by products of any such biological organisms. Further, evaluation or review to determine compliance with State and/or Federal regulatory requirements, assessment of potential contamination migration from or onto the subject site, and/or any similar environmental analyses were beyond the scope of this study.*

*This report has been prepared with the intent that it not be separated. Information from this report should not be distributed or made available to designers or contractors in partial form. This report should be made available to prospective contractors for information only, and not as a warranty of subsurface conditions.*

## 6. Closure

We appreciate the opportunity to work with you on this project. We trust that the information provided in the report is clear and understandable. Should it require any clarification or amplification, however, please contact us at (843) 815-5120.

Regards

  
W. Chuck Rushing, P.E.  
843.815.0263  
Chuck.Rushing@ghd.com



  
Sean M. McCubbins, LEED® AP  
843.815.0268  
Sean.McCubbins@ghd.com

# Appendix A

## **Soil Test Boring Logs**

# Key to Soil Classification

## Correlation of Penetration Resistance with Relative Density and Consistency

<u>Sands and Gravels</u>		<u>Silts and Clays</u>	
No. of <u>Blows, N</u>	Relative <u>Density</u>	No. of <u>Blows, N</u>	Relative <u>Density</u>
0 – 4	Very loose	0 – 2	Very soft
5 – 10	Loose	3 – 4	Soft
11 – 30	Medium dense	5 – 8	Firm
31 – 50	Dense	9 – 15	Stiff
Over 50	Very dense	16 – 30	Very stiff
		31 – 50	Hard
		Over 50	Very hard

## Particle Size Identification (Unified Classification System)

Boulders:	Diameter exceeds 8 inches
Cobbles:	3 to 8 inches diameter
Gravel:	<b>Coarse</b> - 3/4 to 3 inches diameter <b>Fine</b> - 4.76 mm to 3/4 inch diameter
Sand:	<b>Coarse</b> - 2.0 mm to 4.76 mm diameter <b>Medium</b> - 0.42 mm to 2.0 mm diameter <b>Fine</b> - 0.074 mm to 0.42 mm diameter
Silt and Clay:	Less than 0.07 mm (particles cannot be seen with naked eye)



## Modifiers



The modifiers provide our estimate of the amount of silt, clay or sand size particles in the soil sample.



Approximate Content	Modifiers
≤ 5%:	Trace
5% to 12%:	Slightly silty, slightly clayey, slightly sandy
12% to 30%:	Silty, clayey, sandy
30% to 50%:	Very silty, very clayey, very sandy

Field Moisture Description	
Saturated:	Usually liquid; very wet, usually from below the groundwater table
Wet:	Semisolid; requires drying to attain optimum moisture
Moist:	Solid; at or near optimum moisture
Dry:	Requires additional water to attain optimum moisture












PROJECT:  <i>Pine Street Industrial Building</i>								LOG OF BORING:  B-1		
DATE DRILLED: <i>September 14, 2022</i>					DRILLER: <i>A. Nelson</i>			GROUND ELEVATION:		
DRILLING METHOD: <i>Mud Rotary</i>					BORING DEPTH: <i>25.00 Feet</i>			Notes:		
WATER LEVEL:					WATER LEVEL (24-HRS): <i>3'</i>					
ANALYSIS					Depth feet	BLOW COUNTS	GROUND WATER	GRAPHIC LOG	USCS	GEOLOGIC DESCRIPTION
Moisture Content	% Passing 200 Sieve	Organic Content	Liquid Limit	Plasticity Index						
					0					4" Topsoil
					1.4	11			SC	Medium dense tan to tan orange and brown clayey fine SAND
					2.8	7			CL	Firm gray orange tan and brown fine very sandy CLAY with soft lense at 4' - 5.5'
					4.2					
					5.6	3				
					7	8				
					8.4					
					9.8	3			CH	Soft light gray CLAY
					11.2					
					12.6				SP	Medium dense tan fine to medium SAND
					14					
					15.4	19				
					16.8					
					18.2					
					19.6	9			SP-SC	Loose tannish gray slightly clayey fine SAND
					21					
					22.4					
					23.8				SC	Loose dark gray very clayey fine SAND
					25.2	5				Boring terminated at 25 feet
					26.6					
					28					
					29.4					
					30.8					
					32.2					
					33.6					
					35					
					36.4					
					37.8					
					39.2					
					40.6					
					42					
					43.4					
					44.8					
					46.2					
					47.6					
					49					
					50.4					
					51.8					
					53.2					



PROJECT:  <i>Pine Street Industrial Building</i>										LOG OF BORING:  B-2	
DATE DRILLED: <i>September 14, 2022</i>						DRILLER: <i>A. Nelson</i>				GROUND ELEVATION:	
DRILLING METHOD: <i>Mud Rotary</i>						BORING DEPTH: <i>25.00 Feet</i>				Notes:	
WATER LEVEL:						WATER LEVEL (24-HRS): <i>2.5'</i>					
ANALYSIS					Depth feet	BLOW COUNTS	GROUND WATER	GRAPHIC LOG	USCS	GEOLOGIC DESCRIPTION	
Moisture Content	% Passing 200 Sieve	Organic Content	Liquid Limit	Plasticity Index							
					0					4" Topsoil	
					1.4	6			SC	Loose gray and dark gray clayey fine SAND with fine roots	
					2.8	8			CL	Firm gray tan and orange fine very sandy CLAY	
					4.2	8			SC	Loose gray very clayey fine SAND	
					5.6	8					
					7	20			SC	Medium dense light gray and tan clayey fine SAND	
					8.4	11					
					9.8						
					11.2						
					12.6						
					14						
					15.4	11					
					16.8						
					18.2				SC	Loose dark gray very clayey fine SAND	
					19.6	5					
					21						
					22.4				SC	Medium dense dark gray and gray clayey fine SAND	
					23.8						
					25.2	12				Boring terminated at 25 feet	
					26.6						
					28						
					29.4						
					30.8						
					32.2						
					33.6						
					35						
					36.4						
					37.8						
					39.2						
					40.6						
					42						
					43.4						
					44.8						
					46.2						
					47.6						
					49						
					50.4						
					51.8						
					53.2						

PROJECT:  <i>Pine Street Industrial Building</i>								LOG OF BORING:  B-3			
DATE DRILLED: <i>September 14, 2022</i>					DRILLER: <i>A. Nelson</i>			GROUND ELEVATION:			
DRILLING METHOD: <i>Mud Rotary</i>					BORING DEPTH: <i>25.00 Feet</i>			Notes:			
WATER LEVEL:					WATER LEVEL (24-HRS): <i>2.5'</i>						
ANALYSIS					Depth feet	BLOW COUNTS	GROUND WATER	GRAPHIC LOG	USCS	GEOLOGIC DESCRIPTION	
Moisture Content	% Passing 200 Sieve	Organic Content	Liquid Limit	Plasticity Index							
					0					4" Topsoil	
					1.4	5			SC	Loose dark gray and brown clayey fine SAND with decayed organics	
					2.8	8			CL		
					4.2						Firm brown gray and orange fine very sandy CLAY
					5.6	7					
					7	8					
					8.4				CH	Firm light gray CLAY with thin clayey fine sand seams	
					9.8	6					
					11.2						
					12.6						
					14						
					15.4	5					
					16.8						
					18.2				SC	Loose to medium dense dark gray slightly clayey fine SAND	
					19.6	10					
					21						
					22.4						
					23.8						
					25.2	15				Boring terminated at 25 feet	
					26.6						
					28						
					29.4						
					30.8						
					32.2						
					33.6						
					35						
					36.4						
					37.8						
					39.2						
					40.6						
					42						
					43.4						
					44.8						
					46.2						
					47.6						
					49						
					50.4						
					51.8						
					53.2						











PROJECT:  <i>Pine Street Industrial Building</i>										LOG OF BORING:  B-4	
DATE DRILLED: <i>September 15, 2022</i>						DRILLER: <i>A. Nelson</i>				GROUND ELEVATION:	
DRILLING METHOD: <i>Mud Rotary</i>						BORING DEPTH: <i>25.00 Feet</i>				Notes:	
WATER LEVEL:						WATER LEVEL (24-HRS): <i>2.5'</i>					
ANALYSIS					Depth feet	BLOW COUNTS	GROUND WATER	GRAPHIC LOG	USCS	GEOLOGIC DESCRIPTION	
Moisture Content	% Passing 200 Sieve	Organic Content	Liquid Limit	Plasticity Index							
					0						
					1.4	5			SC	4" Topsoil	
					2.8	13			CL	Loose gray tan orange and brown very clayey fine SAND with fine roots	
					4.2					Stiff brown tan and orange fine very sandy CLAY	
					5.6	9					
					7	33			SC	Dense gray light gray orange and tan very clayey fine SAND	
					8.4				CH	Stiff gray CLAY with thin clayey fine sand seams	
					9.8	15					
					11.2						
					12.6						
					14						
					15.4	9					
					16.8						
					18.2				CH	Stiff greenish gray CLAY	
					19.6	9					
					21						
					22.4				SC	Medium dense dark gray very clayey fine SAND	
					23.8						
					25.2	12				Boring terminated at 25 feet	
					26.6						
					28						
					29.4						
					30.8						
					32.2						
					33.6						
					35						
					36.4						
					37.8						
					39.2						
					40.6						
					42						
					43.4						
					44.8						
					46.2						
					47.6						
					49						
					50.4						
					51.8						
					53.2						

PROJECT:  Pine Street Industrial Building									LOG OF BORING:  B-5	
DATE DRILLED: September 15, 2022					DRILLER: A. Nelson				GROUND ELEVATION:	
DRILLING METHOD: Mud Rotary					BORING DEPTH: 25.00 Feet				Notes:	
WATER LEVEL:					WATER LEVEL (24-HRS): 3'					
ANALYSIS					Depth feet	BLOW COUNTS	GROUND WATER	GRAPHIC LOG	USCS	GEOLOGIC DESCRIPTION
Moisture Content	% Passing 200 Sieve	Organic Content	Liquid Limit	Plasticity Index						
					0					6" Topsoil
					1.4	4			SC	Very loose gray tan orange and light gray clayey fine SAND
					2.8	10			SC	Loose gray tan and orange very clayey fine SAND
					4.2					
					5.6	12			CL	Stiff to very stiff gray and tan fine very sandy CLAY
					7	21				
					8.4				SC	Medium dense tan and orange clayey fine SAND
					9.8	14				
					11.2					
					12.6					
					14					
					15.4	11				
					16.8					
					18.2				SC	Loose to medium dense gray and dark gray clayey fine SAND
					19.6	9				
					21					
					22.4					
					23.8					
					25.2	16				
					26.6					Boring terminated at 25 feet
					28					
					29.4					
					30.8					
					32.2					
					33.6					
					35					
					36.4					
					37.8					
					39.2					
					40.6					
					42					
					43.4					
					44.8					
					46.2					
					47.6					
					49					
					50.4					
					51.8					
					53.2					

PROJECT:  <i>Pine Street Industrial Building</i>									LOG OF BORING:  B-6	
DATE DRILLED: <i>September 15, 2022</i>					DRILLER: <i>A. Nelson</i>				GROUND ELEVATION:	
DRILLING METHOD: <i>Mud Rotary</i>					BORING DEPTH: <i>50.00 Feet</i>				Notes:	
WATER LEVEL:					WATER LEVEL (24-HRS): <i>3'</i>					
ANALYSIS					Depth feet	BLOW COUNTS	GROUND WATER	GRAPHIC LOG	USCS	GEOLOGIC DESCRIPTION
Moisture Content	% Passing 200 Sieve	Organic Content	Liquid Limit	Plasticity Index						
					0					6" Topsoil
					1.4	4			SC	Very loose gray brown and tan very clayey fine SAND with fine roots
					2.8	9			SC	
					4.2					Loose to medium dense gray tan orange and red very clayey fine SAND
					5.6	7				
					7	17				
					8.4	10			CL	Stiff greenish gray fine very sandy CLAY
					9.8					
					11.2					
					12.6				SP-SC	Medium dense light gray and tan slightly clayey fine SAND
					14	11			SC	Loose gray and dark gray very clayey fine SAND
					15.4					
					16.8					
					18.2					
					19.6	9				
					21					
					22.4				SC	Medium dense dark greenish gray very clayey fine SAND with thin clay seams
					23.8					
					25.2	12				
					26.6					
					28					
					29.4					
					30.8	14				
					32.2					
					33.6				SC	Medium dense dark gray clayey fine SAND
					35	17				Medium dense dark gray very clayey fine SAND
					36.4					
					37.8					
					39.2					
					40.6	15				
					42					
					43.4				SC	
					44.8	12				
					46.2					
					47.6					
					49					
					50.4	17				Boring terminated at 50 feet
					51.8					
					53.2					



PROJECT:  <i>Pine Street Industrial Building</i>									LOG OF BORING:  B-7	
DATE DRILLED: <i>September 15, 2022</i>					DRILLER: <i>A. Nelson</i>				GROUND ELEVATION:	
DRILLING METHOD: <i>Mud Rotary</i>					BORING DEPTH: <i>25.00 Feet</i>				Notes:	
WATER LEVEL:					WATER LEVEL (24-HRS): <i>1'</i>					
ANALYSIS					Depth feet	BLOW COUNTS	GROUND WATER	GRAPHIC LOG	USCS	GEOLOGIC DESCRIPTION
Moisture Content	% Passing 200 Sieve	Organic Content	Liquid Limit	Plasticity Index						
					0					4" Topsoil
					1.4	6			SC	Loose gray light gray tan orange and red clayey fine SAND with fine roots
					2.8	15			CL	
					4.2					Stiff to firm gray orange and red fine very sandy CLAY
					5.6	8				
					7	18			CH	Very stiff light gray and gray CLAY with thin clayey fine sand seams
					8.4				SC	Medium dense light gray and tan clayey fine SAND
					9.8	22				
					11.2					
					12.6				SC	Medium dense gray very clayey fine SAND
					14	14				
					15.4					
					16.8					
					18.2				SC	Medium dense dark gray clayey fine SAND
					19.6	12				
					21					
					22.4					
					23.8					
					25.2	12				Boring terminated at 25 feet
					26.6					
					28					
					29.4					
					30.8					
					32.2					
					33.6					
					35					
					36.4					
					37.8					
					39.2					
					40.6					
					42					
					43.4					
					44.8					
					46.2					
					47.6					
					49					
					50.4					
					51.8					
					53.2					

PROJECT:  <i>Pine Street Industrial Building</i>								LOG OF BORING:  B-8			
DATE DRILLED: <i>September 15, 2022</i>					DRILLER: <i>A. Nelson</i>			GROUND ELEVATION:			
DRILLING METHOD: <i>Mud Rotary</i>					BORING DEPTH: <i>25.00 Feet</i>			Notes:			
WATER LEVEL:					WATER LEVEL (24-HRS): <i>2'</i>						
ANALYSIS					Depth feet	BLOW COUNTS	GROUND WATER	GRAPHIC LOG	USCS	GEOLOGIC DESCRIPTION	
Moisture Content	% Passing 200 Sieve	Organic Content	Liquid Limit	Plasticity Index							
					0				SC	4" Topsoil	
						Loose gray tan and orange very clayey fine SAND					
					1.4	10			CL	Very stiff to stiff gray tan and red fine sandy CLAY	
					2.8	19					
					4.2	14			SP- SC	Medium dense light gray and tan slightly clayey fine SAND	
					5.6	16					
					7	12					
					8.4						
					9.8	12			SP	Medium dense gray fine to medium SAND with thin slightly clayey fine sand seams	
					11.2						
					12.6						
					14	12					
					15.4				SC	Loose to medium dense gray and dark gray clayey fine SAND	
					16.8						
					18.2						
					19.6	8					
					21						Boring terminated at 25 feet
					22.4						
					23.8						
					25.2	18					
					26.6						
					28						
					29.4						
					30.8						
					32.2						
					33.6						
					35						
					36.4						
					37.8						
					39.2						
40.6											
42											
43.4											
44.8											
46.2											
47.6											
49											
50.4											
51.8											
53.2											

# Appendix B

## **Hand-auger Boring Logs**



## B-1 Log of Hand-Auger Borings

Project: Pine Street Industrial Building

Date: September 20, 2022

Personnel: C. Rushing

Reference No: 12591408-00

Location: See Figure

Location	Depth Below Ground Surface	Soil Description
HA-1	0 – 6"	Topsoil
	6" – 14"	Gray and brown slightly clayey fine SAND (SP-SC)
	14" – 22"	Gray orange and tan very clayey fine SAND (SC)
	22" – 48"	Gray orange tan and red fine very sandy CLAY (CL)
HA-2	0 – 14"	Topsoil and roots
	14" – 18"	Gray orange and tan very clayey fine SAND (SC)
	18" – 48"	Gray orange tan and red fine very sandy CLAY (CL)
HA-3	0 – 4"	Topsoil
	4" – 8"	Tan clayey fine SAND (SC)
	8" – 14"	Gray orange and tan very clayey fine SAND (SC)
	14" – 48"	Gray orange tan and red fine very sandy CLAY (CL)
HA-4	0 – 3"	Topsoil
	3" – 8"	Gray orange and tan very clayey fine SAND (SC)
	8" – 48"	Gray orange tan and red fine very sandy CLAY (CL)

Comments: \_\_\_\_\_

# Appendix C

## **Test Pit Excavation Logs**

## C-1 Log of Test Pits

Project: Pine Street Industrial Building

Date: September 7, 2022

Personnel: C. Rushing

Reference No: 12591408-00

Location: See Figure 1

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-1	0 – 2"	Topsoil		
	2" – 14"	Gray to tan slightly clayey fine SAND (SP-SC)		
	14" – 32"	Gray and tan very clayey fine SAND (SC)		
	32" – 8.5'	Gray orange and tan fine very sandy CLAY (CL) <Water inflow at 8.5'>	35.1	67.9
	8.5' – 11'	Light gray and tan clayey fine AND (SC)	23.6	16.8
Test pit terminated at 11'				

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-2	0 – 4"	Topsoil		
	4" – 4'	Gray orange and tan fine very sandy CLAY (CL)		
Test pit terminated at 4'				



## C-1 Log of Test Pits

Project: Pine Street Industrial Building

Date: September 7, 2022

Personnel: C. Rushing

Reference No: 12591408-00

Location: See Figure 1

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-3 (A-E)	0 – 6"	Topsoil		
	6" – 2.5'	Gray and tan slightly clayey fine SAND (SP-SC) and debris (shingles/metal/PVC/bricks)		
	2.5' – 6'	Gray orange and tan fine very sandy CLAY (CL)		
Test pit terminated at 6'				

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-4	0 – 4"	Topsoil		
	4" – 4'	Gray orange and tan fine very sandy CLAY (CL)		
Test pit terminated at 4'				

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-5	0 – 3"	Topsoil		
	3" – 10"	Gray slightly clayey fine SAND (SP-SC)		
	10" – 4'	Gray orange and tan fine very sandy CLAY (CL)	30.6	65.4
Test pit terminated at 4'				

## C-1 Log of Test Pits

Project: Pine Street Industrial Building

Date: September 7, 2022

Personnel: C. Rushing

Reference No: 12591408-00

Location: See Figure 1

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-6	0 – 4"	Topsoil		
	4" – 14"	Gray to tan slightly clayey fine SAND (SP-SC)		
	14" – 3'	Gray and tan very clayey fine SAND (SC)		
	3' – 5'	Gray orange and tan fine very sandy CLAY (CL)		
Test pit terminated at 5'				

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-7	0 – 5"	Topsoil		
	5" – 14"	Gray slightly clayey fine SAND (SP-SC)		
	14" – 4'	Gray orange and tan fine very sandy CLAY (CL)		
Test pit terminated at 4'				

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-8	0 – 8"	Topsoil and debris (bricks/plastic/gravel)		
	8" – 16"	Gray slightly clayey fine SAND (SP-SC)		
	16" – 4'	Gray orange and tan fine very sandy CLAY (CL)		
Test pit terminated at 4'				

## C-1 Log of Test Pits

Project: Pine Street Industrial Building

Date: September 7, 2022

Personnel: C. Rushing

Reference No: 12591408-00

Location: See Figure 1

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-9 (A-C)	0 – 14"	Topsoil and debris (bricks/plastic/gravel/clay pipe/strip foundation)		
	14" – 20"	Gray slightly clayey fine SAND (SP-SC)		
	20" – 4'	Gray orange and tan fine very sandy CLAY (CL)		
Test pit terminated at 4'				

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-10	0 – 4"	Topsoil		
	4" – 14"	Gray slightly clayey fine SAND (SP-SC) with few bricks and roots		
	14" – 3'	Gray orange and tan fine very sandy CLAY (CL)	33.8	66.0
Test pit terminated at 4'				
<i>Note: Test pit located under current debris pile</i>				

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-11	0 – 4"	Topsoil		
	4" – 16"	Gray and tan slightly clayey fine SAND (SP-SC)		
	16" – 3.5'	Gray orange and tan fine very sandy CLAY (CL)		
Test pit terminated at 3.5'				
<i>Note: Encountered cast iron pipe oriented parallel to highway at 3.5'</i>				



## C-1 Log of Test Pits

Project: Pine Street Industrial Building

Date: September 7, 2022

Personnel: C. Rushing

Reference No: 12591408-00

Location: See Figure 1

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-12	0 – 2"	Topsoil		
	2" – 14"	Tan slightly clayey fine SAND (SP-SC)		
	14" – 4'	Gray orange and tan fine very sandy CLAY (CL)		
Test pit terminated at 4'				

Location	Depth Below Ground Surface	Soil Description	Natural Moisture Content (%)	Percent Finer than #200 Sieve
TP-13	0 – 2"	Topsoil		
	2" – 16"	Tan slightly clayey fine SAND (SP-SC)		
	16" – 4'	Gray orange and tan fine very sandy CLAY (CL)		
Test pit terminated at 4'				

# Appendix D

## **Seismic Design Parameters**

⚠ This is a beta release of the new ATC Hazards by Location website. Please [contact us](#) with feedback.

ℹ The ATC Hazards by Location website will not be updated to support ASCE 7-22. [Find out why.](#)



## Hazards by Location

### Search Information

**Address:** 311 US-17 ALT, Yemassee, SC 29945, USA

**Coordinates:** 32.6985622, -80.84510920000001

**Elevation:** 16 ft

**Timestamp:** 2022-10-05T17:46:28.305Z

**Hazard Type:** Seismic


**Reference Document:** ASCE7-16

**Risk Category:** II


**Site Class:** D-default



### MCER Horizontal Response Spectrum



### Design Horizontal Response Spectrum



### Basic Parameters

Name	Value	Description
$S_S$	0.587	MCE <sub>R</sub> ground motion (period=0.2s)
$S_1$	0.184	MCE <sub>R</sub> ground motion (period=1.0s)
$S_{MS}$	0.781	Site-modified spectral acceleration value
$S_{M1}$	0.41	Site-modified spectral acceleration value
$S_{DS}$	0.52	Numeric seismic design value at 0.2s SA
$S_{D1}$	0.273	Numeric seismic design value at 1.0s SA

### Additional Information

Name	Value	Description
SDC	D	Seismic design category



$F_a$	1.331	Site amplification factor at 0.2s
$F_v$	2.233	Site amplification factor at 1.0s
$CR_S$	0.899	Coefficient of risk (0.2s)
$CR_1$	0.908	Coefficient of risk (1.0s)
PGA	0.344	$MCE_G$ peak ground acceleration
$F_{PGA}$	1.256	Site amplification factor at PGA
$PGA_M$	0.432	Site modified peak ground acceleration
$T_L$	8	Long-period transition period (s)
SsRT	0.587	Probabilistic risk-targeted ground motion (0.2s)
SsUH	0.653	Factored uniform-hazard spectral acceleration (2% probability of exceedance in 50 years)
SsD	1.5	Factored deterministic acceleration value (0.2s)
S1RT	0.184	Probabilistic risk-targeted ground motion (1.0s)
S1UH	0.202	Factored uniform-hazard spectral acceleration (2% probability of exceedance in 50 years)
S1D	0.6	Factored deterministic acceleration value (1.0s)
PGAd	0.5	Factored deterministic acceleration value (PGA)

*The results indicated here DO NOT reflect any state or local amendments to the values or any delineation lines made during the building code adoption process. Users should confirm any output obtained from this tool with the local Authority Having Jurisdiction before proceeding with design.*

*Please note that the ATC Hazards by Location website will not be updated to support ASCE 7-22. [Find out why.](#)*


## Disclaimer




Hazard loads are provided by the U.S. Geological Survey [Seismic Design Web Services](#).

While the information presented on this website is believed to be correct, ATC and its sponsors and contributors assume no responsibility or liability for its accuracy. The material presented in the report should not be used or relied upon for any specific application without competent examination and verification of its accuracy, suitability and applicability by engineers or other licensed professionals. ATC does not intend that the use of this information replace the sound judgment of such competent professionals, having experience and knowledge in the field of practice, nor to substitute for the standard of care required of such professionals in interpreting and applying the results of the report provided by this website. Users of the information from this website assume all liability arising from such use. Use of the output of this website does not imply approval by the governing building code bodies responsible for building code approval and interpretation for the building site described by latitude/longitude location in the report.

# Appendix E

**Figure**



- |   |   |   |
|---|---|---|
|  <b>B-#</b> Designation / approximate location of Standard Penetration Test (SPT) Boring |  <b>HA-#</b> Designation / approximate location of Hand-Auger Boring |  <b>TP-#</b> Designation / approximate location of Test Pit Excavation |
|---|---|---|

# Figure 1: Location Plan

Pine Street Industrial Building



## Appendix F

### Inspection Log and Reports

SWPPP Inspection Log			
Name of Construction Site	Location of Construction Site		
Date of Inspection	Inspector Name	Does Inspection Report require maintenance of installed BMPs?	
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No

SWPPP Inspection Log (Continued)			
Date of Inspection	Inspector Name	Does Inspection Report require maintenance of installed BMPs?	
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No
		<input type="checkbox"/> Yes	<input type="checkbox"/> No

## ***Appendix G***

---

*Rainfall Log and Reports*



SWPPP Rainfall Records (January - June)										Year:	
January	Rainfall	February	Rainfall	March	Rainfall	April	Rainfall	May	Rainfall	June	Rainfall
1		1		1		1		1		1	
2		2		2		2		2		2	
3		3		3		3		3		3	
4		4		4		4		4		4	
5		5		5		5		5		5	
6		6		6		6		6		6	
7		7		7		7		7		7	
8		8		8		8		8		8	
9		9		9		9		9		9	
10		10		10		10		10		10	
11		11		11		11		11		11	
12		12		12		12		12		12	
13		13		13		13		13		13	
14		14		14		14		14		14	
15		15		15		15		15		15	
16		16		16		16		16		16	
17		17		17		17		17		17	
18		18		18		18		18		18	
19		19		19		19		19		19	
20		20		20		20		20		20	
21		21		21		21		21		21	
22		22		22		22		22		22	
23		23		23		23		23		23	
24		24		24		24		24		24	
25		25		25		25		25		25	
26		26		26		26		26		26	
27		27		27		27		27		27	
28		28		28		28		28		28	
29		29		29		29		29		29	

30				30		30		30		30	
31				31		31		31		31	
SWPPP Rainfall Records (Jul - December)										Year:	
July	Rainfall	August	Rainfall	September	Rainfall	October	Rainfall	November	Rainfall	December	Rainfall
1		1		1		1		1		1	
2		2		2		2		2		2	
3		3		3		3		3		3	
4		4		4		4		4		4	
5		5		5		5		5		5	
6		6		6		6		6		6	
7		7		7		7		7		7	
8		8		8		8		8		8	
9		9		9		9		9		9	
10		10		10		10		10		10	
11		11		11		11		11		11	
12		12		12		12		12		12	
13		13		13		13		13		13	
14		14		14		14		14		14	
15		15		15		15		15		15	
16		16		16		16		16		16	
17		17		17		17		17		17	
18		18		18		18		18		18	
19		19		19		19		19		19	
20		20		20		20		20		20	
21		21		21		21		21		21	
22		22		22		22		22		22	
23		23		23		23		23		23	
24		24		24		24		24		24	
25		25		25		25		25		25	

26		26		26		26		26		26	
27		27		27		27		27		27	
28		28		28		28		28		28	
29		29		29		29		29		29	
30		30		30		30		30		30	
31		31				31				31	





## SWPPP Pre-Construction Conference Attendance Log (Continued)

[illegible]

<b>SWPPP Contractor &amp; Sub-Contractor Log</b>		
Name of Construction Site		Location of Construction Site
Company/Individual Name	Work Responsibilities	
1.)		
Start Date:		
Completion Date:		
2.)		
Start Date:		
Completion Date:		
3.)		
Start Date:		
Completion Date:		
4.)		
Start Date:		
Completion Date:		
5.)		
Start Date:		
Completion Date:		
6.)		
Start Date:		
Completion Date:		
7.)		
Start Date:		
Completion Date:		
8.)		
Start Date:		
Completion Date:		
9.)		
Start Date:		
Completion Date:		
10.)		
Start Date:		
Completion Date:		



<b>SWPPP Contractor &amp; Sub-Contractor Log (Continued)</b>		
11.)		
Start Date:		
Completion Date:		
12.)		
Start Date:		
Completion Date:		
13.)		
Start Date:		
Completion Date:		
14.)		
Start Date:		
Completion Date:		
15.)		
Start Date:		
Completion Date:		
16.)		
Start Date:		
Completion Date:		
17.)		
Start Date:		
Completion Date:		
18.)		
Start Date:		
Completion Date:		
19.)		
Start Date:		
Completion Date:		
20.)		
Start Date:		
Completion Date:		
21.)		
Start Date:		
Completion Date:		

<b>SWPPP Modification Log</b>				
Name of Construction Site		Location of Construction Site		
<b>Type of Modification</b>		<b>Description of Modification</b>		<b>Location of Modification</b>
<input type="checkbox"/> Major <input type="checkbox"/> Minor				
Start Date:				
Completion Date:				
Reason for Modifications:			Approved/Implemented By:	
<b>Type of Modification</b>		<b>Description of Modification</b>		<b>Location of Modification</b>
<input type="checkbox"/> Major <input type="checkbox"/> Minor				
Start Date:				
Completion Date:				
Reason for Modifications:			Approved/Implemented By:	
<b>Type of Modification</b>		<b>Description of Modification</b>		<b>Location of Modification</b>
<input type="checkbox"/> Major <input type="checkbox"/> Minor				
Start Date:				
Completion Date:				
Reason for Modifications:			Approved/Implemented By:	
<b>Type of Modification</b>		<b>Description of Modification</b>		<b>Location of Modification</b>
<input type="checkbox"/> Major <input type="checkbox"/> Minor				
Start Date:				
Completion Date:				
Reason for Modifications:			Approved/Implemented By:	
<b>Type of Modification</b>		<b>Description of Modification</b>		<b>Location of Modification</b>
<input type="checkbox"/> Major <input type="checkbox"/> Minor				
Start Date:				
Completion Date:				
Reason for Modifications:			Approved/Implemented By:	

<b>SWPPP Modification Log (Continued)</b>				
Name of Construction Site		Location of Construction Site		
<b>Type of Modification</b>		<b>Description of Modification</b>		<b>Location of Modification</b>
<input type="checkbox"/> Major <input type="checkbox"/> Minor				
Start Date:				
Completion Date:				
Reason for Modifications:			Approved/Implemented By:	
<b>Type of Modification</b>		<b>Description of Modification</b>		<b>Location of Modification</b>
<input type="checkbox"/> Major <input type="checkbox"/> Minor				
Start Date:				
Completion Date:				
Reason for Modifications:			Approved/Implemented By:	
<b>Type of Modification</b>		<b>Description of Modification</b>		<b>Location of Modification</b>
<input type="checkbox"/> Major <input type="checkbox"/> Minor				
Start Date:				
Completion Date:				
Reason for Modifications:			Approved/Implemented By:	
<b>Type of Modification</b>		<b>Description of Modification</b>		<b>Location of Modification</b>
<input type="checkbox"/> Major <input type="checkbox"/> Minor				
Start Date:				
Completion Date:				
Reason for Modifications:			Approved/Implemented By:	
<b>Type of Modification</b>		<b>Description of Modification</b>		<b>Location of Modification</b>
<input type="checkbox"/> Major <input type="checkbox"/> Minor				
Start Date:				
Completion Date:				
Reason for Modifications:			Approved/Implemented By:	



<b>SWPPP Soil Stabilization Log</b>				
Name of Construction Site		Location of Construction Site		
<b>Type of Stabilization</b>		<b>Description of Stabilization</b>		<b>Location of Stabilization</b>
<input type="checkbox"/> <b>Final</b> <input type="checkbox"/> <b>Temporary</b>				
Initiate Date:				
Completion Date:				
Additional work proposed for this area:			Inspection Frequency for Stabilized Area:	
<b>Type of Stabilization</b>		<b>Description of Stabilization</b>		<b>Location of Stabilization</b>
<input type="checkbox"/> <b>Final</b> <input type="checkbox"/> <b>Temporary</b>				
Initiate Date:				
Completion Date:				
Additional work proposed for this area:			Inspection Frequency for Stabilized Area:	
<b>Type of Stabilization</b>		<b>Description of Stabilization</b>		<b>Location of Stabilization</b>
<input type="checkbox"/> <b>Final</b> <input type="checkbox"/> <b>Temporary</b>				
Initiate Date:				
Completion Date:				
Additional work proposed for this area:			Inspection Frequency for Stabilized Area:	
<b>Type of Stabilization</b>		<b>Description of Stabilization</b>		<b>Location of Stabilization</b>
<input type="checkbox"/> <b>Final</b> <input type="checkbox"/> <b>Temporary</b>				
Initiate Date:				
Completion Date:				
Additional work proposed for this area:			Inspection Frequency for Stabilized Area:	
<b>Type of Stabilization</b>		<b>Description of Stabilization</b>		<b>Location of Stabilization</b>
<input type="checkbox"/> <b>Final</b> <input type="checkbox"/> <b>Temporary</b>				
Initiate Date:				
Completion Date:				
Additional work proposed for this area:			Inspection Frequency for Stabilized Area:	

<b>SWPPP Modification Log (Continued)</b>				
Name of Construction Site		Location of Construction Site		
<b>Type of Stabilization</b>		<b>Description of Stabilization</b>		<b>Location of Stabilization</b>
<input type="checkbox"/> <b>Final</b> <input type="checkbox"/> <b>Temporary</b>				
Initiate Date:				
Completion Date:				
Additional work proposed for this area:			Inspection Frequency for Stabilized Area:	
<b>Type of Stabilization</b>		<b>Description of Stabilization</b>		<b>Location of Stabilization</b>
<input type="checkbox"/> <b>Final</b> <input type="checkbox"/> <b>Temporary</b>				
Initiate Date:				
Completion Date:				
Additional work proposed for this area:			Inspection Frequency for Stabilized Area:	
<b>Type of Stabilization</b>		<b>Description of Stabilization</b>		<b>Location of Stabilization</b>
<input type="checkbox"/> <b>Final</b> <input type="checkbox"/> <b>Temporary</b>				
Initiate Date:				
Completion Date:				
Additional work proposed for this area:			Inspection Frequency for Stabilized Area:	
<b>Type of Stabilization</b>		<b>Description of Stabilization</b>		<b>Location of Stabilization</b>
<input type="checkbox"/> <b>Final</b> <input type="checkbox"/> <b>Temporary</b>				
Initiate Date:				
Completion Date:				
Additional work proposed for this area:			Inspection Frequency for Stabilized Area:	
<b>Type of Stabilization</b>		<b>Description of Stabilization</b>		<b>Location of Stabilization</b>
<input type="checkbox"/> <b>Final</b> <input type="checkbox"/> <b>Temporary</b>				
Initiate Date:				
Completion Date:				
Additional work proposed for this area:			Inspection Frequency for Stabilized Area:	

## ***Appendix I***

*Construction General Permit SCR100000*

---


***A copy of the NPDES General Permit for Stormwater Discharges from Construction Activities (SCR100000) can be found at the following address:***

***<http://www.scdhec.gov/environment/water/swater/docs/CGP-permit.pdf>***












SCALE: N.T.S.



SCALE: N.T.S.



## SCALE: N.T.S.



## SCALE: N.T.S.

**NOTES:**

1. APPLY MULCH IN A  $\pm 5'$  DIAMETER WHERE PROPOSED TREE PLANTINGS OCCUR IN SOD OR SEEDED AREAS.

## SCALE: N.T.S.

© 2022 WJK LTD.  
DESIGN CONCEPTS, DRAWING, SHEET  
LOGOS, SPECIFICATIONS, DETAIL  
WRITTEN MATERIAL SHALL NOT BE USED  
OR REPRODUCED IN WHOLE OR IN PART  
IN ANY FORM WITHOUT PRIOR WRITTEN  
CONSENT OF WJK LTD.  
THIS SHEET TO SCALE AT: 30"X42"

# TE DEVELOPMENT PLANS FOR IRONLINE YEMASSEE, SOUTH CAROLINA

DATE:	MAR. 01, 2023
PROJECT NO.:	22024.01
DRAWN BY:	MC
CHECKED BY:	DK

PRELIMINARY  
SUBMITTAL PLAN  
NOT FOR  
CONSTRUCTION

REVISIONS:

DRAWING TITLE

**PLANT SCHEDULE AND  
DETAILS**

DRAWING NUMBER

# L50 1



Colin J Moore

*Mayor*

Peggy Bing-O'Banner

*Mayor Pro Tempore*

Matthew Garnes

*Town Administrator*



***Council Members***

Alfred Washington

Stacy Pinckney

David Paul Murray

**Town of Yemassee Administration Department  
Rezoning Analysis (ZONE-03-23-1023)  
203-00-00-046, 204-01-05-013 & 204-01-05-046 (Hampton County)  
Meeting Date: March 14, 2023**

**Applicant:** Ironline Metals, LLC.

**Owner:** Ironline Metals, LLC.

**Address(es):** Jinks St & U.S. Highway 17A

**Tax Map Number(s):** 203-00-00-046, 204-01-05-013 & 204-01-05-046

**County:** Hampton

**Site Description:** The three parcels total approximately 104.4 acres located northwest of the intersection of U.S. Highway 17A and Jinks Street while the southern portion of the tract is directly north of Lacey Street.

**Present Zoning and Existing Conditions:**

Currently each parcel has a different zoning designation:

204-01-05-005 - Current Zoning: Residential ¼ Acre

204-01-05-013 - Current Zoning: Office Commercial District

203-00-00-046 - Current Zoning: Conservation Preservation District

Portions of parcels 204-01-05-005 & 204-01-05-013 abut U.S. Highway 17A and accordingly, portions of the properties are within the boundaries of the Highway Corridor Overlay District (HCOD) and are currently subjected to the requirements outlined in the Yemassee Zoning Ordinance pertaining to the HCOD.

**Land Use Compatibility:** The eastern border of the property is adjacent to U.S. Highway 17A, a north/south artery that traverses the Beaufort and Hampton County portions of the Town of Yemassee before crossing the Combahee River and entering Colleton County. The applicant is seeking to construct a 100,000sqft manufacturing operation near the intersection of U.S.

Highway 17A and Jinks Street - adjacent to the main thoroughfare. The applicant is seeking an encroachment permit from SCDOT to add a deceleration lane for truck access into the property heading southbound, roughly 500ft north of the existing Jinks Rd intersection. The existing Jinks Road would be improved and side roads leading to residential neighborhoods.

**Environmental Issues:** The project is adjacent to the Ace Basin Wildlife Refuge and a significant portion of parcel 203-00-00-046 is wetland and within a floodplain which is non-conducive to development. The balance of the property towards Lacey Street is uplands with an assortment of trees. The applicant will employ stormwater BMP's and a series of detention ponds to handle runoff.

**Public Service Issues:** None noted.

**Letters were sent by certified mail to all adjacent property owners to the development advising them of the application.**

**Staff Review:** Overall, Staff support the proposed rezoning to PUD which would allow a mix of housing units and a manufacturing operation which would bring an influx of jobs into the Town. Staff have no objection to the four requested modifications deviating from current zoning ordinances within the existing zoning ordinance. The Traffic Impact Analysis was reviewed and projected trips would not warrant a traffic control device at this time.



### Town of Yemassee Public Hearing

NOTICE IS HEREBY GIVEN that the Town of Yemassee Planning Commission will hold a Public Hearing on Tuesday, April 4, 2023, at 3:00 PM at the Yemassee Municipal Complex, 101 Town Cir, Yemassee, SC 29945, for the purpose of soliciting input on the following:

**ZONE-03-23-1023** by Ironline Metals, LLC., for a request for a Zoning Map Amendment for three parcels of land totaling approximately 104.40 acres of land located at the northwest corner of U.S. Highway 17A and Jinks Street, Hampton County from their current zoning designations to a designation of Planned Unit Development. The subject parcels are further identified by Hampton County Tax Map Number(s): 204-01-05-013, 204-01-05-005 & 203-00-00-046.

Persons with comments or questions should contact the Town of Yemassee Administration Department at (843) 589-2565 Ext. 3. Persons requiring special services to attend the meeting should call to make arrangements.



**THANK YOU for your legal submission!**

Your legal has been submitted for publication. Below is a confirmation of your legal placement. You will also receive an email confirmation.

**ORDER DETAILS**

**Order Number:**  
IPL0113606  
**Parent Order #:**  
IPL0101153  
**Order Status:**  
Submitted  
**Classification:**  
Legals & Public Notices  
**Package:**  
HHI - Legal Ads  
**Final Cost:**  
55.62  
**Payment Type:**  
Account Billed  
**User ID:**  
IPL0026087

**ACCOUNT INFORMATION**

TOWN OF YEMASSEE IP  
101 Town Cir  
YEMASSEE, SC 29945-3363  
803-589-2565  
mattgarnes@townofyemassee.org  
TOWN OF YEMASSEE

**TRANSACTION REPORT**

**Date**  
March 9, 2023 4:18:18 PM EST  
**Amount:**  
55.62

**SCHEDULE FOR AD NUMBER IPL01136060**

March 12, 2023  
The Island Packet (Hilton Head)

**PREVIEW FOR AD NUMBER IPL01136060****Town of Yemassee Public Hearing**

NOTICE IS HEREBY GIVEN that the Town of Yemassee Planning Commission will hold a Public Hearing on Tuesday, April 4, 2023, at 3:00 PM at the Yemassee Municipal Complex, 101 Town Cir, Yemassee, SC 29945, for the purpose of soliciting input on the following:

**ZONE-03-23-1023** by Ironline Metals, LLC., for a request for a Zoning Map Amendment for three parcels of land totaling approximately 104.40 acres of land located at the northwest corner of U.S. Highway 17A and Jinks Street, Hampton County from their current zoning designations to a designation of Planned Unit Development. The subject parcels are further identified by Hampton County Tax Map Number(s): 204-01-05-013, 204-01-05-005 & 203-00-00-046.

Persons with comments or questions should contact the Town of Yemassee Administration Department at (843) 589-2565 Ext. 3. Persons requiring special services to attend the meeting should call to make arrangements.

W00000000

Publication Dates

[<< Click here to print a printer friendly version >>](#)



2020 1810 0001 1932 6465  
2020 1810 0001 1932 6533  
2020 1810 0001 1932 6472  
2020 1810 0001 1932 6496  
2020 1810 0001 1932 6458  
2020 1810 0001 1932 6519

U.S. Postal Service™  
**CERTIFIED MAIL® RECEIPT**  
Domestic Mail Only

For delivery information, visit our website at [www.usps.com](http://www.usps.com)®.

Yemassee, SC 29945

**OFFICIAL USE**

Certified Mail Fee	\$4.15	0796 03
Extra Services & Fees (check box, add fee as appropriate)	\$7.75	
<input type="checkbox"/> Return Receipt (hardcopy)	\$0.00	
<input type="checkbox"/> Return Receipt (electronic)	\$0.00	
<input type="checkbox"/> Certified Mail Restricted Delivery	\$0.00	
<input type="checkbox"/> Adult Signature Required	\$0.00	
<input type="checkbox"/> Adult Signature Restricted Delivery	\$0.00	
Postage	\$0.63	
Total Postage and Fees	\$8.13	03/10/2023

Sent To  
Brenda A. High  
25 Ponderosa Cir  
City, State, ZIP+4®  
Yemassee, SC 29945-3321

PS Form 3800, June 2015

U.S. Postal Service™  
**CERTIFIED MAIL® RECEIPT**  
Domestic Mail Only

For delivery information, visit our website at [www.usps.com](http://www.usps.com)®.

Yemassee, SC 29945

**OFFICIAL USE**

Certified Mail Fee	\$4.15	0796 03
Extra Services & Fees (check box, add fee as appropriate)	\$7.75	
<input type="checkbox"/> Return Receipt (hardcopy)	\$0.00	
<input type="checkbox"/> Return Receipt (electronic)	\$0.00	
<input type="checkbox"/> Certified Mail Restricted Delivery	\$0.00	
<input type="checkbox"/> Adult Signature Required	\$0.00	
<input type="checkbox"/> Adult Signature Restricted Delivery	\$0.00	
Postage	\$0.63	
Total Postage and Fees	\$8.13	03/10/2023

Sent To  
Richard A. Hagan  
279 U.S. Highway 17A  
City, State, ZIP+4®  
Yemassee, SC 29945-5066

PS Form 3800, June 2015

U.S. Postal Service™  
**CERTIFIED MAIL® RECEIPT**  
Domestic Mail Only

For delivery information, visit our website at [www.usps.com](http://www.usps.com)®.

Hilton Head Island, SC 29926

**OFFICIAL USE**

Certified Mail Fee	\$4.15	0796 03
Extra Services & Fees (check box, add fee as appropriate)	\$7.75	
<input type="checkbox"/> Return Receipt (hardcopy)	\$0.00	
<input type="checkbox"/> Return Receipt (electronic)	\$0.00	
<input type="checkbox"/> Certified Mail Restricted Delivery	\$0.00	
<input type="checkbox"/> Adult Signature Required	\$0.00	
<input type="checkbox"/> Adult Signature Restricted Delivery	\$0.00	
Postage	\$0.63	
Total Postage and Fees	\$8.13	03/10/2023

Sent To  
Dewayne Crosby  
3 Cardinal Ct, Unit 365  
City, State, ZIP+4®  
Hilton Head Island, SC 29926-3411

PS Form 3800, June 2015

U.S. Postal Service™  
**CERTIFIED MAIL® RECEIPT**  
Domestic Mail Only

For delivery information, visit our website at [www.usps.com](http://www.usps.com)®.

Hollywood, SC 29449

**OFFICIAL USE**

Certified Mail Fee	\$4.15	0796 03
Extra Services & Fees (check box, add fee as appropriate)	\$7.75	
<input type="checkbox"/> Return Receipt (hardcopy)	\$0.00	
<input type="checkbox"/> Return Receipt (electronic)	\$0.00	
<input type="checkbox"/> Certified Mail Restricted Delivery	\$0.00	
<input type="checkbox"/> Adult Signature Required	\$0.00	
<input type="checkbox"/> Adult Signature Restricted Delivery	\$0.00	
Postage	\$0.63	
Total Postage and Fees	\$8.13	03/10/2023

Sent To  
USA Secretary of Interior  
P.O. Box 848  
City, State, ZIP+4®  
Hollywood, SC 29449

PS Form 3800, June 2015

U.S. Postal Service™  
**CERTIFIED MAIL® RECEIPT**  
Domestic Mail Only

For delivery information, visit our website at [www.usps.com](http://www.usps.com)®.

Yemassee, SC 29945

**OFFICIAL USE**

Certified Mail Fee	\$4.15	0796 03
Extra Services & Fees (check box, add fee as appropriate)	\$7.75	
<input type="checkbox"/> Return Receipt (hardcopy)	\$0.00	
<input type="checkbox"/> Return Receipt (electronic)	\$0.00	
<input type="checkbox"/> Certified Mail Restricted Delivery	\$0.00	
<input type="checkbox"/> Adult Signature Required	\$0.00	
<input type="checkbox"/> Adult Signature Restricted Delivery	\$0.00	
Postage	\$0.63	
Total Postage and Fees	\$8.13	03/10/2023

Sent To  
Daniel Dziadaszek  
52 Lacey St  
City, State, ZIP+4®  
Yemassee, SC 29945-5038

PS Form 3800, June 2015

U.S. Postal Service™  
**CERTIFIED MAIL® RECEIPT**  
Domestic Mail Only

For delivery information, visit our website at [www.usps.com](http://www.usps.com)®.

Yemassee, SC 29945

**OFFICIAL USE**

Certified Mail Fee	\$4.15	0796 03
Extra Services & Fees (check box, add fee as appropriate)	\$7.75	
<input type="checkbox"/> Return Receipt (hardcopy)	\$0.00	
<input type="checkbox"/> Return Receipt (electronic)	\$0.00	
<input type="checkbox"/> Certified Mail Restricted Delivery	\$0.00	
<input type="checkbox"/> Adult Signature Required	\$0.00	
<input type="checkbox"/> Adult Signature Restricted Delivery	\$0.00	
Postage	\$0.63	
Total Postage and Fees	\$8.13	03/10/2023

Sent To  
Edith G. Lane Trustee  
P.O. Box 428  
City, State, ZIP+4®  
Yemassee, SC 29945-0428

PS Form 3800, June 2015

U.S. Postal Service™  
**CERTIFIED MAIL® RECEIPT**  
Domestic Mail Only

For delivery information, visit our website at [www.usps.com](http://www.usps.com)®.

Louisville, KY 40223

**OFFICIAL USE**

Certified Mail Fee	\$4.15	0796 03
Extra Services & Fees (check box, add fee as appropriate)	\$7.75	
<input type="checkbox"/> Return Receipt (hardcopy)	\$0.00	
<input type="checkbox"/> Return Receipt (electronic)	\$0.00	
<input type="checkbox"/> Certified Mail Restricted Delivery	\$0.00	
<input type="checkbox"/> Adult Signature Required	\$0.00	
<input type="checkbox"/> Adult Signature Restricted Delivery	\$0.00	
Postage	\$0.63	
Total Postage and Fees	\$8.13	03/10/2023

Sent To  
Ironline Metals, LLC.  
1515 Ormsby Station Ct  
City, State, ZIP+4®  
Louisville, KY 40223-5032

PS Form 3800, June 2015

U.S. Postal Service™  
**CERTIFIED MAIL® RECEIPT**  
Domestic Mail Only

For delivery information, visit our website at [www.usps.com](http://www.usps.com)®.

Yemassee, SC 29945

**OFFICIAL USE**

Certified Mail Fee	\$4.15	0796 03
Extra Services & Fees (check box, add fee as appropriate)	\$7.75	
<input type="checkbox"/> Return Receipt (hardcopy)	\$0.00	
<input type="checkbox"/> Return Receipt (electronic)	\$0.00	
<input type="checkbox"/> Certified Mail Restricted Delivery	\$0.00	
<input type="checkbox"/> Adult Signature Required	\$0.00	
<input type="checkbox"/> Adult Signature Restricted Delivery	\$0.00	
Postage	\$0.63	
Total Postage and Fees	\$8.13	03/10/2023

Sent To  
Randy & Anna Lunsford  
37 Poston Dr  
City, State, ZIP+4®  
Yemassee, SC 29945-3330

PS Form 3800, June 2015



7019 2970 0000 1588 3439

U.S. Postal Service™  
**CERTIFIED MAIL® RECEIPT**  
Domestic Mail Only

For delivery information, visit our website at [www.usps.com](http://www.usps.com)®.

Yemassee, SC 29945

**OFFICIAL USE**

Certified Mail Fee	\$4.15	0796
Extra Services & Fees (check box, add fee as appropriate)	\$3.35	03
<input type="checkbox"/> Return Receipt (hardcopy)	\$0.00	
<input type="checkbox"/> Return Receipt (electronic)	\$0.00	
<input type="checkbox"/> Certified Mail Restricted Delivery	\$0.00	
<input type="checkbox"/> Adult Signature Required	\$0.00	
<input type="checkbox"/> Adult Signature Restricted Delivery	\$0.00	
Postage	\$0.63	
Total P	\$8.13	03/10/2023

Sent To: Annie M. Reeves  
Street: P.O. Box 1074  
City, St: Yemassee, SC 29945-1074  
PS For: Instructions

7020 1810 0001 1932 6540

U.S. Postal Service™  
**CERTIFIED MAIL® RECEIPT**  
Domestic Mail Only

For delivery information, visit our website at [www.usps.com](http://www.usps.com)®.

Brooklyn, NY 11238

**OFFICIAL USE**

Certified Mail Fee	\$4.15	0796
Extra Services & Fees (check box, add fee as appropriate)	\$3.35	03
<input type="checkbox"/> Return Receipt (hardcopy)	\$0.00	
<input type="checkbox"/> Return Receipt (electronic)	\$0.00	
<input type="checkbox"/> Certified Mail Restricted Delivery	\$0.00	
<input type="checkbox"/> Adult Signature Required	\$0.00	
<input type="checkbox"/> Adult Signature Restricted Delivery	\$0.00	
Postage	\$0.87	
Total P	\$8.37	03/10/2023

Sent To: Irene Smith Estate of  
Street: 309 Lafayette Ave, Apt 9M  
City, St: Brooklyn, NY 11238-1268  
PS For: Instructions

7019 2970 0000 1588 3408

U.S. Postal Service™  
**CERTIFIED MAIL® RECEIPT**  
Domestic Mail Only

For delivery information, visit our website at [www.usps.com](http://www.usps.com)®.

Hampton, SC 29924

**OFFICIAL USE**

Certified Mail Fee	\$4.15	0796
Extra Services & Fees (check box, add fee as appropriate)	\$3.35	03
<input type="checkbox"/> Return Receipt (hardcopy)	\$0.00	
<input type="checkbox"/> Return Receipt (electronic)	\$0.00	
<input type="checkbox"/> Certified Mail Restricted Delivery	\$0.00	
<input type="checkbox"/> Adult Signature Required	\$0.00	
<input type="checkbox"/> Adult Signature Restricted Delivery	\$0.00	
Postage	\$0.87	
Total P	\$8.37	03/10/2023

Sent To: Lowcountry Regional Water System  
Street: Attn: Brian Burgess General Manager  
City, St: 513 Elm St W  
Hampton, SC 29924-3101  
PS For: Instructions

7020 1810 0001 1932 6557

U.S. Postal Service™  
**CERTIFIED MAIL® RECEIPT**  
Domestic Mail Only

For delivery information, visit our website at [www.usps.com](http://www.usps.com)®.

Hampton, SC 29924

**OFFICIAL USE**

Certified Mail Fee	\$4.15	0796
Extra Services & Fees (check box, add fee as appropriate)	\$3.35	03
<input type="checkbox"/> Return Receipt (hardcopy)	\$0.00	
<input type="checkbox"/> Return Receipt (electronic)	\$0.00	
<input type="checkbox"/> Certified Mail Restricted Delivery	\$0.00	
<input type="checkbox"/> Adult Signature Required	\$0.00	
<input type="checkbox"/> Adult Signature Restricted Delivery	\$0.00	
Postage	\$0.87	
Total P	\$8.37	03/10/2023

Sent To: Hampton County Building Department  
Street: Attn: Randy Crews  
City, St: 201 Jackson Ave W  
Hampton, SC 29924-3256  
PS For: Instructions

7019 2970 0000 1588 3415

U.S. Postal Service™  
**CERTIFIED MAIL® RECEIPT**  
Domestic Mail Only

For delivery information, visit our website at [www.usps.com](http://www.usps.com)®.

Yemassee, SC 29945

**OFFICIAL USE**

Certified Mail Fee	\$4.15	0796
Extra Services & Fees (check box, add fee as appropriate)	\$3.35	03
<input type="checkbox"/> Return Receipt (hardcopy)	\$0.00	
<input type="checkbox"/> Return Receipt (electronic)	\$0.00	
<input type="checkbox"/> Certified Mail Restricted Delivery	\$0.00	
<input type="checkbox"/> Adult Signature Required	\$0.00	
<input type="checkbox"/> Adult Signature Restricted Delivery	\$0.00	
Postage	\$0.87	
Total P	\$8.37	03/10/2023

Sent To: Frances Kay Reebe  
Street: P.O. Box 733  
City, St: Yemassee, SC 29945-0733  
PS For: Instructions

7019 2970 0000 1588 3422

U.S. Postal Service™  
**CERTIFIED MAIL® RECEIPT**  
Domestic Mail Only

For delivery information, visit our website at [www.usps.com](http://www.usps.com)®.

Charleston, SC 29406

**OFFICIAL USE**

Certified Mail Fee	\$4.15	0796
Extra Services & Fees (check box, add fee as appropriate)	\$3.35	03
<input type="checkbox"/> Return Receipt (hardcopy)	\$0.00	
<input type="checkbox"/> Return Receipt (electronic)	\$0.00	
<input type="checkbox"/> Certified Mail Restricted Delivery	\$0.00	
<input type="checkbox"/> Adult Signature Required	\$0.00	
<input type="checkbox"/> Adult Signature Restricted Delivery	\$0.00	
Postage	\$0.87	
Total P	\$8.37	03/10/2023

Sent To: Providence Solutions, LLC.  
Street: 7087 Rivers Ave  
City, St: North Charleston, SC 29406-4622  
PS For: Instructions

7019 2970 0000 1588 3446

U.S. Postal Service™  
**CERTIFIED MAIL® RECEIPT**  
Domestic Mail Only

For delivery information, visit our website at [www.usps.com](http://www.usps.com)®.

Yemassee, SC 29945

**OFFICIAL USE**

Certified Mail Fee	\$4.15	0796
Extra Services & Fees (check box, add fee as appropriate)	\$3.35	03
<input type="checkbox"/> Return Receipt (hardcopy)	\$0.00	
<input type="checkbox"/> Return Receipt (electronic)	\$0.00	
<input type="checkbox"/> Certified Mail Restricted Delivery	\$0.00	
<input type="checkbox"/> Adult Signature Required	\$0.00	
<input type="checkbox"/> Adult Signature Restricted Delivery	\$0.00	
Postage	\$0.87	
Total P	\$8.37	03/10/2023

Sent To: Mary M. Youmans  
Street: P.O. Box 128  
City, St: Yemassee, SC 29945-0128  
PS For: Instructions

7020 1810 0001 1932 6526

U.S. Postal Service™  
**CERTIFIED MAIL® RECEIPT**  
Domestic Mail Only

For delivery information, visit our website at [www.usps.com](http://www.usps.com)®.

Early Branch, SC 29916

**OFFICIAL USE**

Certified Mail Fee	\$4.15	0796
Extra Services & Fees (check box, add fee as appropriate)	\$3.35	03
<input type="checkbox"/> Return Receipt (hardcopy)	\$0.00	
<input type="checkbox"/> Return Receipt (electronic)	\$0.00	
<input type="checkbox"/> Certified Mail Restricted Delivery	\$0.00	
<input type="checkbox"/> Adult Signature Required	\$0.00	
<input type="checkbox"/> Adult Signature Restricted Delivery	\$0.00	
Postage	\$0.63	
Total P	\$8.13	03/10/2023

Sent To: Clay T. Bishop  
Street: 2281 Ficken Rd  
City, St: Early Branch, SC 29916-3325  
PS For: Instructions



## **TOWN OF YEMASSEE**

Ordinance No. 23-09

### **AN ORDINANCE TO APPROVE AN AMENDMENT TO THE TOWN OF YEMASSEE ZONING MAP TO DESIGNATE CERTAIN REAL PROPERTY OWNED BY IRONLINE METALS, LLC., THE SAME CONTAINING APPROXIMATELY 104.4 ACRES, MORE OR LESS, LOCATED AT THE NORTHWEST CORNER OF THE INTERSECTION OF U.S. HIGHWAY 17 A & JINKS STREET, AND BEARING HAMPTON COUNTY TAX MAP NUMBERS: 203-00-00-046, 204-01-05-013 & 204-01-05-046 AS PLANNED UNIT DEVELOPMENT PURSUANT TO THE TOWN OF YEMASSEE ZONING ORDINANCE**

**WHEREAS**, THE Town of Yemassee has received a request from the applicant (Ironline Metals, LLC.) for a Zoning Map Amendment for three parcels of land that it is the One Hundred percent (100%) owner of, within the Town of Yemassee; and

**WHEREAS**, the Town of Yemassee Planning Commission reviewed a request for a Planned Unit Development (PUD) Concept Plan at their January 3, 2023, meeting. The plan included a proposed development of up to two hundred thousand (200,000) square feet of industrial occupancy and up to one hundred and seven (107), single family residences; and

**WHEREAS**, the Planning Commission voted to recommend approval of the PUD Concept Plan with the condition that a Traffic Impact Analysis be conducted to determine the potential impacts of traffic on surrounding roadways at full buildout; and

**WHEREAS**, the Town Council of the Town of Yemassee reviewed the request and recommendation of the Planning Commission at their January 10, 2023, meeting and approved the PUD Concept Plan application with the recommendations forwarded from the Planning Commission, and scheduled a Public Hearing; and

**WHEREAS**, the Town Council of the Town of Yemassee conducted a Public Hearing on the PUD Concept Plan at their February 17, 2023 Town Council Meeting to gather public input; and

**WHEREAS**, the applicant submitted a PUD Master Plan Application and a Preliminary Development Plan Application which were reviewed and approval recommended at the March 7, 2023 Planning Commission meeting; and

**WHEREAS**, concurrently the applicant submitted a Zoning Map Amendment for the subject parcels which was reviewed at the March 7, 2023, Planning Commission meeting with an approval to advance the application, schedule a Public Hearing and forward to Town Council; and

**WHEREAS**, a Public Hearing is set for the Zoning Map Amendment Application at the April 4, 2023, Planning Commission meeting to gather public input; and



**WHEREAS**, the Town Council of the Town of Yemassee concur with the Planning Commission's recommendations; and

**WHEREAS**, the Town Council of the Town of Yemassee finds it to be in the Town's best interest to amend the Zoning Map and designate the Properties as "Planned Unit Development".

**NOW THEREFORE, BE IT ENACTED BY THE TOWN COUNCIL OF THE TOWN OF YEMASSEE, SOUTH CAROLINA:**

The Town of Yemassee, South Carolina hereby amends the Zoning Map and designates that certain property owned by Ironline Metals, LLC., the same consisting of a total of 104.4 acres, more or less, being described as Hampton County Tax Map Numbers: 203-00-00-046, 204-01-05-013 & 204-01-05-046, as Planned Unit Development pursuant to the Town of Yemassee's Zoning Ordinance with the usage and densities listed below permitted within the PUD.

- I. Up to two-hundred thousand (200,000) square feet of industrial / manufacturing occupancies in the areas designated on the Master Plan map.
- II. Up to one-hundred-seven (107) single-family dwelling units with a minimum lot size of 6,000 square feet per dwelling unit, a minimum front yard setback of ten (10) feet from the street right-of-way line and a minimum side yard setback of five (5) feet from the lot lines.
- III. Said manufacturing use is entitled to any use currently permitted within the Light Industrial District chapter of the Town of Yemassee Zoning Ordinance and is permitted to conduct operations including the manufacturing of light gauge steel framing products including steel studs for residential and commercial buildings.
- IV. The minimum distance required between entrances for areas of the PUD within the Highway Corridor Overlay District is four hundred (400) feet between all access points to the corridor, including private driveways, roads, and public right-of-way. Spacing will be measured from the midpoint of each driveway. If the existence of jurisdictional wetlands precludes compliance with this provision, the Planning Commission shall have discretion as to the placing of an alternative access point; however, no additional curb cuts on the subject parcel should result from having the alternative access point.
- V. The minimum lot width at the building setback line for newly created parcels shall be a distance of one hundred fifty (150) feet. Newly created parcels are subject to the four hundred (400) foot distance requirement between access points from the highway.
- VI. Newly created subdivisions are subject to the four hundred (400) foot distance requirement between access points from the highway. No subdivision of land which would create parcels fronting on the highway shall be approved unless it is established prior to subdivision approval how access will be provided to each parcel in compliance with the four hundred (400) distance requirement, (i.e., frontage roads, shared access drives, and others);
- VII. Prior to any phase of development commencing, the applicant shall have submitted a Final Development Plan for the respective Phase and receive a Development Permit for the respective Phase. Each Development Permit granted is valid for two (2) years from the date of issue.

DONE, RATIFIED AND ENACTED THIS \_\_\_\_\_ DAY OF \_\_\_\_\_, 2023.

This Ordinance was read and passed at First Reading on: \_\_\_\_\_

\_\_\_\_\_  
Colin J. Moore, Mayor

\_\_\_\_\_  
ATTEST: Matthew E. Garnes, Town Administrator

\_\_\_\_\_  
Peggy O'Banner, Mayor Pro Tem

\_\_\_\_\_  
David Paul Murray, Councilmember

\_\_\_\_\_  
Alfred Washington, Council Member

\_\_\_\_\_  
Stacy Pinckney, Councilmember

A Public Hearing on this Ordinance was held on: \_\_\_\_\_

\_\_\_\_\_  
Colin J. Moore, Mayor

\_\_\_\_\_  
ATTEST: Matthew E. Garnes, Town Administrator

This Ordinance was read and passed at Second and Final Reading held on: \_\_\_\_\_

\_\_\_\_\_  
Colin J. Moore, Mayor

\_\_\_\_\_  
ATTEST: Matthew E. Garnes, Town Administrator

\_\_\_\_\_  
Peggy O'Banner, Mayor Pro Tem

\_\_\_\_\_  
David Paul Murray, Councilmember

\_\_\_\_\_  
Alfred Washington, Council Member

\_\_\_\_\_  
Stacy Pinckney, Councilmember

(seal)

***Recommended Motion***

***(Zoning Map Amendment – Ironline)***

***“I move to approve the first reading of the Zoning Map Amendment and to schedule a Public Hearing for three parcels of land owned by Ironline Metals, LLC., located at the intersection of U.S. Highway 17A & Jinks Street in Hampton County, and identified by Tax Map Numbers: 203-00-00-046, 204-01-05-013 & 204-01-05-046 from their current zoning designations to a Zoning Designation of Planned Unit Development pursuant to the Town of Yemassee Zoning Ordinance with conditions and entitlements listed in Ordinance 23-09 which include:***

***I. Up to two-hundred thousand (200,000) square feet of industrial / manufacturing occupancies in the areas designated on the Master Plan map.***

***II. Up to one-hundred-seven (107) single-family dwelling units with a minimum lot size of 6,000 square feet per dwelling unit, a minimum front yard setback of ten (10) feet from the street right-of-way line and a minimum side yard setback of five (5) feet from the lot lines.***

***III. Said manufacturing use is entitled to any use currently permitted within the Light Industrial District chapter of the Town of Yemassee Zoning Ordinance and is permitted to conduct***



***operations including the manufacturing of light gauge steel framing products including steel studs for residential and commercial buildings.***

***IV. The minimum distance required between entrances for areas of the PUD within the Highway Corridor Overlay District is four hundred (400) feet between all access points to the corridor, including private driveways, roads, and public right-of-way. Spacing will be measured from the midpoint of each driveway. If the existence of jurisdictional wetlands precludes compliance with this provision, the Planning Commission shall have discretion as to the placing of an alternative access point;***

***however, no additional curb cuts on the subject parcel should result from having the alternative access point.***

***V. The minimum lot width at the building setback line for newly created parcels shall be a distance of one hundred fifty (150) feet. Newly created parcels are subject to the four hundred (400) foot distance requirement between access points from the highway.***

***VI. Newly created subdivisions are subject to the four hundred (400) foot distance requirement between access points from the highway. No subdivision of land which would create parcels fronting on the highway shall be approved***

***unless it is established prior to subdivision approval how access will be provided to each parcel in compliance with the four hundred (400) distance requirement, (i.e., frontage roads, shared access drives, and others);***

***VII. Prior to any phase of development commencing, the applicant shall have submitted a Final Development Plan for the respective Phase and receive a Development Permit for the respective Phase. Each Development Permit granted is valid for two (2) years from the date of issue.”***



**THANK YOU for your legal submission!**

Your legal has been submitted for publication. Below is a confirmation of your legal placement. You will also receive an email confirmation.

**ORDER DETAILS**

**Order Number:**  
IPL0113606  
**Parent Order #:**  
IPL0101153  
**Order Status:**  
Submitted  
**Classification:**  
Legals & Public Notices  
**Package:**  
HHI - Legal Ads  
**Final Cost:**  
55.62  
**Payment Type:**  
Account Billed  
**User ID:**  
IPL0026087

**ACCOUNT INFORMATION**

TOWN OF YEMASSEE IP  
101 Town Cir  
YEMASSEE, SC 29945-3363  
803-589-2565  
mattgarnes@townofyemassee.org  
TOWN OF YEMASSEE

**TRANSACTION REPORT**

**Date**  
March 9, 2023 4:18:18 PM EST  
**Amount:**  
55.62

**SCHEDULE FOR AD NUMBER IPL01136060**

March 12, 2023  
The Island Packet (Hilton Head)

**PREVIEW FOR AD NUMBER IPL01136060****Town of Yemassee Public Hearing**

NOTICE IS HEREBY GIVEN that the Town of Yemassee Planning Commission will hold a Public Hearing on Tuesday, April 4, 2023, at 3:00 PM at the Yemassee Municipal Complex, 101 Town Cir, Yemassee, SC 29945, for the purpose of soliciting input on the following:

**ZONE-03-23-1023** by Ironline Metals, LLC., for a request for a Zoning Map Amendment for three parcels of land totaling approximately 104.40 acres of land located at the northwest corner of U.S. Highway 17A and Jinks Street, Hampton County from their current zoning designations to a designation of Planned Unit Development. The subject parcels are further identified by Hampton County Tax Map Number(s): 204-01-05-013, 204-01-05-005 & 203-00-00-046.

Persons with comments or questions should contact the Town of Yemassee Administration Department at (843) 589-2565 Ext. 3. Persons requiring special services to attend the meeting should call to make arrangements.

W00000000

Publication Dates

[<< Click here to print a printer friendly version >>](#)



Colin J. Moore

Mayor

Peggy Bing-O'Banner

Mayor Pro Tempore

Matthew Garnes

Town Administrator



***Council Members***

Alfred Washington

Stacy Pinckney

David Paul Murray

## Planning Commission Agenda Item

**Subject:** A request for a recommendation of approval for the annexation of an approximately 1.39-acre parcel located off Cochran Street, Hampton County, and further identified by Hampton County Tax Map Number: 198-00-00-095.

**Meeting Date:** April 4, 2023

**Submitted by:** Matthew Garnes, Town Administrator

### **Attachments:**

	Draft Ordinance		Resolution		Other
√	Support Documents		Motion		

---

**Summary:** Staff received a petition for annexation for a single parcel of land totaling 1.39 acres of land located off Cochran Street. The parcel is undeveloped and has no current plans for development. The applicant is seeking a zoning designation of General Residential per the Town of Yemassee Zoning Ordinance.

**Recommended Action:** Recommend advancing petition and scheduling a public hearing.

---

### **Commission Action:**

- ☐ Approved as Recommended
- ☐ Approved with Modifications
- ☐ Disapproved
- ☐ Tabled to Time Certain
- ☐ Other



Colin J Moore


*Mayor*

Peggy Bing-O'Banner

*Mayor Pro Tempore*

Matthew Garnes

*Town Administrator*



*Council Members*

Alfred Washington

Stacy Pinckney

David Paul Murray

**Town of Yemassee Administration Department  
Annexation Analysis (ANNX-03-23-1026)  
Smith Tract, Cochran St (Hampton County)**

**Applicant:** Rosalyn Smith

**Owner:** Roslyn Smith

**Address(es):** Unaddressed parcel on Cochran Street

**Tax Map Number(s):** 198-00-00-095

**County:** Hampton

**Site Description:** This project contains a single parcel of uplands on the west side Cochran Street and just east of Interstate 95. The property is a rectangular parcel of land totaling 1.39 acres of land. If developed, access would be off Solomon Street which would require an extension.

**Present Zoning and Existing Conditions:** The parcel is undeveloped with no improvements. As the parcel is currently located within unincorporated Hampton County, the parcel is subject to the Hampton County Zoning Ordinance. These parcels are currently zoned "General Development" under the County code. The applicant is requesting a zoning designation of General Residential (GR) under the Yemassee Zoning Ordinance. The Town of Yemassee Zoning Ordinance defines its General Residential District as to be "designed to provide for a variety of residential uses, including single-family, two (2) family, and mobile home dwellings. The intent of the district is to provide areas primarily for residential uses, and to discourage any encroachment by uses which may be incompatible with such residential use."

The surrounding properties were annexed in July 2018 with the Cochran / Bing / Riley Street residential annexations. The property owner was originally contacted to notify them of the surrounding annexations and inviting them to complete an application in 2018, however a response was not received by Staff. This has created the existing donut hole involving this parcel and four more adjacent properties.

### Zoning Comparison:

	General Development Hampton County	General Residential (GR) Town of Yemassee
<b>Maximum Density:</b>	One (1) Dwelling unit per acre	Three (3) Dwelling unit per acre
<b>Permitted Uses:</b>	<ul style="list-style-type: none"> <li>• Forestry</li> <li>• Clearcutting</li> <li>• Agricultural Support Services</li> <li>• Automobile Service station and/or Garage</li> <li>• Cemetery</li> <li>• Church</li> <li>• Community and Child Care Centers</li> <li>• Dwelling including mobile homes.</li> <li>• Family Day Care Home</li> <li>• Home Occupation</li> <li>• Schools</li> <li>• Equestrian uses</li> <li>• Flea Markets</li> <li>• Outdoor Recreation</li> <li>• Retail Store</li> <li>• Roadside stand</li> <li>• Recreational Vehicle Park</li> <li>• Automotive Racetrack</li> <li>• Public Utilities</li> <li>• Stockyards</li> <li>• Landfills</li> <li>• Recycling Centers</li> <li>• Marinas &amp; Piers</li> </ul>	<ul style="list-style-type: none"> <li>• Single-Family Dwelling (Stick-Built home)</li> <li>• Two (2) Family Dwelling</li> <li>• Mobile Home Dwelling</li> <li>• Church, Civic or Institutional Use</li> <li>• Home Occupation</li> <li>• Family Day Care Home</li> </ul>
<b>Minimum Lot Size:</b>	Not listed in Zoning Ordinance	14,520sqft
<b>Maximum Building Height:</b>	Not listed in Zoning Ordinance	35ft
<b>Setbacks:</b>	Not listed in Zoning Ordinance	Front Yard: Five (5) ft Side & Rear: Five (5)

## Utilities / Public Services:

Should the property be developed, the property would be served by the following utilities and public services:

- **Electric:** Dominion Energy
- **Telecommunications:** Century Link and Comcast/Xfinity
- **Fire Protection:** Hampton County Fire District
- **Emergency Medical Services:** Hampton County Emergency Medical Services
- **Law Enforcement:** Currently Hampton County Sheriff's Office, upon annexation primary response would become the Town of Yemassee Police Department while Hampton County Sheriff's Office would be utilized on an as needed, mutual-aid basis.
- **Water/Wastewater:** Lowcountry Regional Water System (LRWS) is the franchised water and wastewater provider within the Town of Yemassee and upon annexation the parcel would be theoretically served by LRWS if there was infrastructure in the area. Preliminary review indicates water available on Cochran Street, but infrastructure would need to be established prior to servicing the parcel. There is currently no sewer available on Cochran Street and a private septic permitted through SC DHEC would be required.

## Analysis:

The following analysis has been conducted on the parcels petitioning annexation:

### **1. Is the application in the best interests of the Town of Yemassee and its residents?**

- a. **Finding:** The application will expand the footprint of the Town which directly affects funding and representation for the Town at state and federal levels. Any vehicles or personal/business property taxed by Hampton County will be subjected to the town tax rate imposed for FY2023 which is 74.00 mills in Hampton County. Additionally, the parcel will close a donut hole within the Cochran Street community.

### **2. Does the Annexation have the potential to create a tax burden or measurably reduce the level of service(s) provided to existing services and property owners?**

- a. **Finding:** Based on the current use of the property and the maximum allowed development under the proposed zoning of



General Residential, a tax burden is not created and a reduction in the level of service is not anticipated.

3. ***Has the full impact of the proposed Annexation on Law Enforcement been considered?***

- a. **Finding:** Administration Staff have consulted with Chief Alexander who advised annexation of this parcel will not have a negative impact on services offered by the Yemassee Police Department. Upon annexation, the primary response agency for law enforcement issues would be the Yemassee Police Department, with backup provided on an as-needed basis from the Hampton County Sheriff's Office. This parcel would fall within Zone A for police response.

4. ***Does the Petitioner understand all potential costs & benefits associated with the Annexation?***


- a. **Finding:** The applicant has been provided with an estimated tax bill for the year following annexation. As of this report, there has been no additional questions from the petitioner regarding the information provided.


**Adjacent Properties and Jurisdictions:**

Direction	Tax Map Number / Owner & Address	Jurisdiction
West	Hampton County / 198-00-00-112 783 Riley St St. Jude Church	Town of Yemassee
North	Hampton County / 198-00-00-101 000 Oliver Dr Frances Parker	Town of Yemassee
East	Hampton County / 198-00-00-252 000 Cochran St Jalil E. Muhammed	Hampton County
South	Hampton County / 198-00-00-094 000 Cochran St Alfred Miles Jr ETAL	Hampton County

**Staff Review:** Staff have reviewed the application and requested zoning and concur with the request of General Residential.

**Staff Recommendation:** Staff request approval of the annexation.

	<p style="text-align: center;"><b>General Residential (GR) Zoning District</b></p> <p>The General Residential District is designed to provide for a variety of residential uses, including single-family, two (2) family and mobile home dwellings. The intent of the district is to provide areas primarily for residential uses, and to discourage any encroachment by uses which may be incompatible with such residential use.</p> <p style="text-align: center;"><b>Section 5.5, Town of Yemassee Zoning Ordinance</b></p>
<p><b>Standards for the GR District 5.5.1</b></p>	
<ul style="list-style-type: none"> <li>• Maximum Density: Three (3) dwelling units per acre</li> <li>• Minimum Lot Size: 14,520 square feet per dwelling unit.</li> <li>• Maximum building height: Thirty-Five (35') feet or three (3) stories, whichever is less; excluding church spires, belfries, cupolas, monuments, chimneys, or flagpoles</li> <li>• Minimum front yard setback: Five (5) feet from the street right-of-way line.</li> <li>• Minimum side and rear yard setbacks: Five (5) feet from lot lines</li> </ul>	
<p><b>Permitted Uses for the GR District 5.5.2</b></p>	
<ul style="list-style-type: none"> <li>• Single-Family dwelling (Stick built home)</li> <li>• Mobile Home dwelling (provided the home is under skirted around its base with an appropriate material sufficient to provide a visual screen for the underpinnings of the mobile home.</li> <li>• Church, Civic or Institutional use</li> <li>• Home Occupations are permitted if there is no exterior evidence of the home occupation.</li> <li>• Family Day Care Home (Consult Town of Yemassee Zoning Ordinance, Article X, Definitions)</li> <li>• Two (2) family dwelling</li> </ul>	
<p><b>Prohibited Uses for the GR District 5.3.3</b></p>	
<ul style="list-style-type: none"> <li>• Adult Entertainment Establishments</li> <li>• Any business, person, entity, or service offering Adult Entertainment</li> </ul>	







## Hampton County, SC

## Summary

Parcel Number	198-00-00-095.
Tax District	County (District N)
Location Address	
Town Code	
Class Code (NOTE: Not Zoning Info)	206-Residential Lot Vacant
Acres	1.39
Description	
Record Type	Residential
Town Code / Neighborhood	
Owner Occupied	

[View Map](#)

Note: Acres will not display correctly if any or all of the parcel is classed as exempt. (Exempt acreage will not calculate in total acreage.)

## Owners

SMITH ROSALYN  
1280 CLARK STREET  
RAHWAY NJ  
07065

## 2022 Value Information

Land Market Value	\$10,500
Improvement Market Value	\$0
Total Market Value	\$10,500
Taxable Value	\$7,700
Total Assessment Market	\$460

Note: Values will not display correctly if any or all of the parcel is classed as exempt. (Exempt building values will not display nor calculate in totals.)

## Sales Information

Sale Date	Price	Deed Book	Plat Book	Grantor
7/11/1996	\$5	194 327	20 701	MCCLENDON MAE C
5/26/1970	Not Available	59 230	Not Available	Not Available

No data available for the following modules: Building Information, Lot Size Information (Dimensions in Feet).

Hampton County makes every effort to produce the most accurate information possible. No warranties, expressed or implied, are provided for the data herein, its use or interpretation. The assessment information is from the last certified taxroll. All data is subject to change before the next certified taxroll.

[User Privacy Policy](#)[GDPR Privacy Notice](#)[Last Data Upload: 4/2/2023, 6:52:50 AM](#)

Developed by




Version 2.3.254

# Town of Yemassee

## Flood Zone Report - Hampton

2 Apr 2023



### Parcels Hampton


**TMS:** 198-00-00-095.  
**Owner City State ZIP Code:** RAHWAY NJ 07065  
**Owner:** SMITH ROSALYN  
**Owner Street Address:** 1280 CLARK STREET RAHWAY NJ  
**Parcel Street Address:**

### Flood Zones 2010

Count Zone and Subtype		Overlapping Quantities
1.	2 A	121,027.1sf (2.78acres)



Rosalyn Smith



### Legend

- ◆ Address Points Beaufort
- Parcels Beaufort
- ◆ Address Points Hampton
- Parcels Hampton
- ◆ Address Points Jasper
- Parcels Jasper
- Road Names
- Roads
- Major Roads
- Interstate
- Road Names Jasper
- Roads Jasper
- Roads
- Major Roads
- Interstate
- ✕ Railroads
- County Boundary Beaufort
- County Boundary Hampton
- County Boundary Jasper
- Yemassee Boundary

2 Apr, 2023

**Note:**  
Area map with satellite view.



This map is a user generated static output from rightspot.spateng.com website and is for reference use only. Data layers that appear on this map may or may not be accurate, current, or otherwise reliable.

**THIS MAP IS NOT TO BE USED FOR NAVIGATION**





Rosalyn Smith



### Legend

- ◆ Address Points Beaufort
- Parcels Beaufort
- ◆ Address Points Hampton
- Parcels Hampton
- ◆ Address Points Jasper
- Parcels Jasper

### Zoning

- Office Commercial District
- Conservation Preservation District
- General Residential
- Residential 1 Acre
- Residential 1/2 Acre
- Residential 1/3 Acre
- Residential 1/4 Acre
- Village Commercial District
- Mixed Use
- Light Industrial District
- Agricultural
- Telecommunications Tower
- Transitional
- Utility
- General Residential Townhouse
- Regional Commercial District
- Planned Unit Development
- To Be Determined

### Road Names

#### Roads

- Roads
- Major Roads
- Interstate

### Road Names Jasper

#### Roads Jasper

- Roads
- Major Roads
- Interstate

...

**Note:**  
Zoning of surrounding parcels

This map is a user generated static output from rightspot.spateng.com website and is for reference use only. Data layers that appear on this map may or may not be accurate, current, or otherwise reliable.

**THIS MAP IS NOT TO BE USED FOR NAVIGATION**

2 Apr, 2023





Rosalyn Smith



### Legend

- ◆ Address Points Beaufort
- Parcels Beaufort
- ◆ Address Points Hampton
- Parcels Hampton
- ◆ Address Points Jasper
- Parcels Jasper
- Annexations 2005
- Annexations 2012
- Annexations 2015
- Annexations 2016
- Annexations 2017
- Annexations 2018
- Annexations 2019
- Annexations 2020
- Annexations 2021
- Annexations 2022
- Road Names

### Roads

- Roads
- Major Roads
- Interstate

### Road Names Jasper

- Roads
- Major Roads
- Interstate

### Railroads

- County Boundary Beaufort
- County Boundary Hampton
- County Boundary Jasper
- Yemassee Boundary

2 Apr, 2023

**Note:**  
Surrounding parcels Annexation History



This map is a user generated static output from rightspot.spateng.com website and is for reference use only. Data layers that appear on this map may or may not be accurate, current, or otherwise reliable.

**THIS MAP IS NOT TO BE USED FOR NAVIGATION**





Rosalyn Smith



### Legend

- ◆ Address Points Beaufort
- Parcels Beaufort
- ◆ Address Points Hampton
- Parcels Hampton
- ◆ Address Points Jasper
- Parcels Jasper
- Road Names
- Roads
- Major Roads
- Interstate
- Road Names Jasper
- Roads Jasper
- Roads
- Major Roads
- Interstate
- ✕ Railroads
- County Boundary Beaufort
- County Boundary Hampton
- County Boundary Jasper
- Yemassee Boundary
- Contour Labels Hampton
- Contours Hampton
- Major
- Minor

2 Apr, 2023



Note:  
Elevation Contours

This map is a user generated static output from rightspot.spateng.com website and is for reference use only. Data layers that appear on this map may or may not be accurate, current, or otherwise reliable.  
**THIS MAP IS NOT TO BE USED FOR NAVIGATION**





Rosalyn Smith



### Legend

- ◆ Address Points Beaufort
- Parcels Beaufort
- ◆ Address Points Hampton
- Parcels Hampton
- ◆ Address Points Jasper
- Parcels Jasper
- Road Names

#### Roads

- Roads
- Major Roads
- Interstate

#### Road Names Jasper

- Roads
- Major Roads
- Interstate

#### Railroads

- County Boundary Beaufort
- County Boundary Hampton
- County Boundary Jasper

#### Yemassee Boundary

#### Flood Line

#### Base Flood Elevations

#### Flood Zones 2010

- 1% Annual Chance Flood Hazard
  - Zones A, AE, A99, AO, AH, AR, V, VE
- Regulatory Floodway
  - Zone AE
- 0.2% Annual Chance Flood Hazard
  - Zone X
- Future Conditions 1% Annual Chance Flood Hazard
  - Zone X
- Area with Reduced Risk Due to Levee
  - Zone X
- Area of Minimal Flood Hazard
  - Zone X

2 Apr, 2023

Note:  
FEMA Floodplains


This map is a user generated static output from rightspot.spateng.com website and is for reference use only. Data layers that appear on this map may or may not be accurate, current, or otherwise reliable.

THIS MAP IS NOT TO BE USED FOR NAVIGATION





Rosalyn Smith



### Legend

- ◆ Address Points Beaufort
- Parcels Beaufort
- ◆ Address Points Hampton
- Parcels Hampton
- ◆ Address Points Jasper
- Parcels Jasper

2 Apr, 2023

**Note:**  
Surrounding parcels police patrol grids



This map is a user generated static output from [rightspot.spateng.com](https://rightspot.spateng.com) website and is for reference use only. Data layers that appear on this map may or may not be accurate, current, or otherwise reliable.

**THIS MAP IS NOT TO BE USED FOR NAVIGATION**





Rosalyn Smith



### Legend

- ◆ Address Points Beaufort
- Parcels Beaufort
- ◆ Address Points Hampton
- Parcels Hampton
- ◆ Address Points Jasper
- Parcels Jasper
- ▣ Highway Corridor Overlay District
- Road Names**
- Roads**
- Roads
- Major Roads
- Interstate
- Road Names Jasper**
- Roads Jasper**
- Roads
- Major Roads
- Interstate
- ✕ Railroads
- County Boundary Beaufort
- County Boundary Hampton
- County Boundary Jasper
- Yemassee Boundary

2 Apr, 2023


**Note:**  
**Highway Corridor Overlay District**

This map is a user generated static output from rightspot.spateng.com website and is for reference use only. Data layers that appear on this map may or may not be accurate, current, or otherwise reliable.  
**THIS MAP IS NOT TO BE USED FOR NAVIGATION**





Rosalyn Smith



### Legend

- ◆ Address Points Beaufort
- Parcels Beaufort
- ◆ Address Points Hampton
- Parcels Hampton
- ◆ Address Points Jasper
- Parcels Jasper
- Sewer Lift Stations

### Sewer Lines

- Service
- Main
- Force main

### Fire Hydrants

- Water Meters

### Water Lines

- Water Main Line
- Water Service Line
- Water Fire Line

### Road Names

### Roads

- Roads
- Major Roads
- Interstate

### Road Names Jasper

### Roads Jasper

- Roads
- Major Roads
- Interstate

### Railroads

- County Boundary Beaufort
- County Boundary Hampton
- County Boundary Jasper
- Yemassee Boundary

2 Apr, 2023

### Note:

Water and wastewater infrastructure near property


This map is a user generated static output from rightspot.spateng.com website and is for reference use only. Data layers that appear on this map may or may not be accurate, current, or otherwise reliable.

THIS MAP IS NOT TO BE USED FOR NAVIGATION





Rosalyn Smith



### Legend


- ◆ Address Points Beaufort
- Parcels Beaufort
- ◆ Address Points Hampton
- Parcels Hampton
- ◆ Address Points Jasper
- Parcels Jasper
- Road Names
- Roads
  - Roads
  - Major Roads
  - Interstate
- Road Names Jasper
- Roads Jasper
  - Roads
  - Major Roads
  - Interstate
- Railroads
- County Boundary Beaufort
- County Boundary Hampton
- County Boundary Jasper
- Yemassee Boundary
- NWI
  - Estuarine and Marine Deepwater
  - Estuarine and Marine Wetland
  - Freshwater Emergent Wetland
  - Freshwater Forested/Shrub Wetland
  - Freshwater Pond
  - Lake
  - Other
  - Riverine

2 Apr, 2023

**Note:**  
National Wetland Inventory

This map is a user generated static output from [rightspot.spateng.com](https://rightspot.spateng.com) website and is for reference use only. Data layers that appear on this map may or may not be accurate, current, or otherwise reliable.  
**THIS MAP IS NOT TO BE USED FOR NAVIGATION**





### Legend

- ◆ Address Points Beaufort
- Parcels Beaufort
- ◆ Address Points Hampton
- Parcels Hampton
- ◆ Address Points Jasper
- Parcels Jasper

### Police Patrol Zones

- Zone A
- Zone B
- Zone C - Yemassee Core
- Zone C - Sheldon
- Zone D

### Road Names

#### Roads

- Roads
- Major Roads
- Interstate

### Road Names Jasper

#### Roads Jasper

- Roads
- Major Roads
- Interstate

### Railroads

- County Boundary Beaufort
- County Boundary Hampton
- County Boundary Jasper
- Yemassee Boundary



**Note:**  
Surrounding parcels police patrol zones

This map is a user generated static output from [rightspot.spateng.com](https://rightspot.spateng.com) website and is for reference use only. Data layers that appear on this map may or may not be accurate, current, or otherwise reliable.

**THIS MAP IS NOT TO BE USED FOR NAVIGATION**



Rosalyn Smith



### Legend

- ◆ Address Points Beaufort
- Parcels Beaufort
- ◆ Address Points Hampton
- Parcels Hampton
- ◆ Address Points Jasper
- Parcels Jasper
- Road Names
- Roads
  - Roads
  - Major Roads
  - Interstate
- Road Names Jasper
- Roads Jasper
  - Roads
  - Major Roads
  - Interstate
- Railroads
- County Boundary Beaufort
- County Boundary Hampton
- County Boundary Jasper
- Yemassee Boundary

2 Apr, 2023

Note:  
Soil Classifications

This map is a user generated static output from rightspot.spateng.com website and is for reference use only. Data layers that appear on this map may or may not be accurate, current, or otherwise reliable.  
**THIS MAP IS NOT TO BE USED FOR NAVIGATION**



Colin J. Moore

*Mayor*

Peggy Bing-O'Banner

*Mayor Pro Tempore*

Matthew Garnes

*Town Administrator*



***Council Members***

Alfred Washington

Stacy Pinckney

David Paul Murray

## Planning Commission Agenda Item

**Subject:** Comprehensive Plan Update

**Meeting Date:** April 4, 2023

**Submitted by:** Matthew Garnes, Town Administrator

### **Attachments:**

<input type="checkbox"/>	Draft Ordinance	<input type="checkbox"/>	Resolution	<input type="checkbox"/>	Other
<input checked="" type="checkbox"/>	Support Documents	<input type="checkbox"/>	Motion	<input type="checkbox"/>	

---

**Summary:** Town Council accepted a proposal from MRB Group for drafting of the Town of Yemassee Comprehensive Plan. The Town Administrator will present an update.

### **Recommended Action:**

---

#### **Commission Action:**

- ☐ Approved as Recommended
- ☐ Approved with Modifications
- ☐ Disapproved
- ☐ Tabled to Time Certain
- ☐ Other





## Town of Yemassee

**Proposal For Services:**  
Comprehensive Plan Update

**Prepared for:**  
Town of Yemassee  
Matthew Garnes, Town Clerk  
101 Town Circle  
Yemassee, SC 29945-3363

March 8, 2023



March 2, 2023

Matthew Garnes  
Town Clerk  
Town of Yemassee  
101 Town Circle  
Yemassee, SC 29945-3363

Dear Mr. Garnes,

By way of the RFP for the Comprehensive Plan Update, the Town of Yemassee has demonstrated a commitment to the future of Yemassee. A strong comprehensive plan should provide strategic guidance in all areas of operations-economic and community development, healthy neighborhoods, sound infrastructure, managed growth, and access to valued community services. Refocusing the framework of this plan regularly presents the opportunity to enhance quality of life and economic vitality through a stronger focus on economic revitalization, infrastructure investment, and sound planning practices. A refreshed comprehensive plan will synthesize these clear priorities, create actionable strategies to advance you toward your vision, and identify initial policy and investment decisions to continue moving your community forward.

MRB Group, and our local government services team, represent a collection of practitioners in the field of local government—former County Administrators, City Managers, Planners, Economic Developers, and elected officials. We build plans with an intense focus on implementation—ensuring that our recommendations result in actionable strategies for Yemassee to drive progress for the next decade.


Headquartered in Rochester, New York, MRB Group has spent decades working across New York State supporting communities in their infrastructure and community development needs. Building our presence in South Carolina since 2020, we bring this wealth of experience to a team of professionals with Lowcountry roots who themselves have contributed years of experience to the economic and municipal development of communities, identifying challenges and capitalizing on opportunities facing South Carolina's towns and cities.

Our Senior Planning Associate Riccardo Giani will serve as the project manager for this effort. He and his team will execute this project from our office in Charleston. Riccardo can be reached at any time via email ([riccardo.giani@mrbgroup.com](mailto:riccardo.giani@mrbgroup.com)) or by phone (843-608-1913). We are excited to support this project and look forward to discussing the opportunity further.

Sincerely,



Heather Simmons Jones  
Director of Southeast Operations



David M. Doyle, P.E.  
Vice President





# Table of Contents

	PAGE
Project Team .....	1
Understanding & Approach .....	10
Schedule & Fees .....	14
Relevant Experience .....	16





1

## Project Team



### Introduction and Qualifications

MRB Group's long-range planning team specializes in providing comprehensive and strategic planning, implementation, and related advisement services to communities. Behind our planning and economic practitioners the rest of the team - over 160 multi-disciplined professionals and support staff with specialized expertise - stand ready to assist every day.

Many of our staff members have worked as municipal administrators, which gives them a deep understanding of the operational, financial, and logistical challenges that towns face on a regular basis. This team of practitioners provides recommendations that are tailored to implementation, giving town officials what they need to properly execute their plans.

### Working with S.C. Local Governments

Matt Horn is an experienced community leader. He has facilitated the development of community vision and values in support of long-range planning in numerous communities. As former Assistant City Manager of Beaufort, SC, Matt oversaw the planning and implementation of a 4,000 acre annexation plan where he assisted in the development of "smart growth" zoning strategies, ultimately providing for the conservation of thousands of acres of Intercoastal Waterway shoreline.

Heather Simmons Jones is a known entity in economic development of the Southeast, and a Hampton County native. Her experience as an administrator in both urban and rural S.C. areas provides her with a unique perspective into the challenges and opportunities ahead of Yemassee. Her former roles included serving as Executive Director of the Greater Beaufort-Hilton Head Economic Partnership, Allendale County Administrator, Anderson County Assistant County Administrator, McCormick County Director of Economic Development, CEO of Greenwood Partnership Alliance.

Ms. Simmons Jones has worked on key



*Hillsboro, TX, Strategic Plan Public Engagement Session*

projects in South Carolina including:

- Connect SC - Broadband Planning, Statewide
- Medical Innovation District Creation, Land Use, and Strategic Planning - Greenwood, SC
- Sustainable Economic Development Planning - Sustain SC (formerly Palmetto Green)

MRB Group has most recently been engaged in development work across Beaufort County on projects such as:

- City of Beaufort- Assessment & Planning Transition Services, Municipal Executive Searches, City, Interim Planning Services, Site Development Regulations
- Port Royal- grant services and organizational assessment
- Hilton Head- economic development services, grant services, and code writing services
- Local Option Sales Tax Referendum- county-wide public education campaign



Communities in the process of implementing comprehensive plans face numerous challenges the MRB Group team of South Carolina has been able to answer.

In following pages outlining MRB Group's 'Relevant Experience' you will find details of our in-depth work with local S.C. communities in drafting, updating, and advancing comprehensive plans, particularly in the Town of Clover. But our depth of knowledge and breadth of service goes beyond the confines of the comprehensive plan to include the detailed implementation of those key opportunities.

In the Town of Chapin, the comprehensive plan informed the process of defining a Unified Development Ordinance (UDO)-throughout 2022 MRB Group engaged the chartering committee, key stakeholders, and general public through a formalized process to draft an ordinance that answered multiple


needs in promoting the public health, safety, convenience, order, appearance, prosperity, and general welfare of Chapin residents and businesses,

And currently, MRB Group is at work in Anderson County's Town of Pendleton, a community of approximately 3,500 residents, where we are developing another Unified Zoning & Development Ordinance. This work will precede a comprehensive plan effort, where the process of defining goals, deliverables, stakeholders, and branding is expected to facilitate the next community-wide undertaking.

MRB Group stands ready, with all of this experience in supporting the planning efforts of South Carolina communities and more, to continue our record of reliable service to energize and unite the Town of Yemassee into the future.



*MRB Group led community engagement session*



Heather has spent 20 years in South Carolina's rural communities and urbanized multi-county regions working as strategic advisor, public administrator, non-profit leader, and economic development practitioner. A vast majority of Heather's experience is in start-up, stand-up, and funding strategies for public-private partnerships and community organizations for economic and workforce development.

She provides value-added, actionable leadership on how to create viable growth strategies, sustain healthy organizations, and facilitates community-wide conversations on what is required for communities to thrive amongst the competition.



## Experience

**Community Development** – Heather has led cultural programming development, streetscape projects, façade improvements, and transportation infrastructure development and enhancement. As a trained, skilled facilitator and consensus builder, Heather has pulled together communities around polarizing topics to yield positive outcomes.

## Key Projects

### **Sustainable Economic Development Planning — Sustain SC (formerly Palmetto Green)\***

- As a strategic advisor to this non-profit organization, guided its transition from a volunteer board to a formal board structure that allowed for committees with a peer-to-peer membership base. Contributed to all aspects of this transition, including amendment of key documents and the creation of job descriptions, committee missions, and marketing plans.
- Played a leading role in successfully relaunching the organization under a new name and brand, heightening statewide understanding of the need for Sustain SC's critical work at the intersection of commerce and sustainability, and resulting in an increased donor and membership base as well as publicity.

### **Broadband Planning — Connect SC\***

- Developed and managed a federally-funded statewide initiative to assess broadband connectivity in each of South Carolina's counties, creating over 40 data-driven local technology action plans.
- Built consensus among a broad base of stakeholder groups, many of which had not worked together, facilitating the development of common goals and a unified vision.
- Led evaluation, mapping, and planning for broadband services, which in several communities brought funding and internet connectivity to businesses whose productivity was hampered by inadequate access, and to previously underserved residents, with the attendant benefits in such areas as education, employment, and health outcomes.

## Education

M.A. Human Resources Development, Clemson University

B.A., Clemson University

## Professional Affiliations

South Carolina Certified Economic Developer

South Carolina Economic Developers Association

SC Executive Institute, Harvard Business School

Diversity Leaders Initiative, Furman University

Local Government Leadership Institute (SC)—Advanced Programming

*\*Projects listed performed by Ms. Jones under former employment.*



Former City Manager and municipal operations expert with a strong background in infrastructure planning, strategic development, and community engagement. Extensive experience in municipal budgeting and finance, collaborative service delivery, comprehensive planning, downtown revitalization and economic development.

Municipal consulting background includes internal process auditing, public relations assistance and guidance, and development of local government management capacity, as well as long-term strategic planning for community growth.



## Experience

### **Community Planning/Enhanced Management Capacity** –

As former municipal consultant for Washington-based local government support services firm, worked closely with the International City-County Managers Association, National League of Cities, and other government leadership associations. Supported community development efforts and developed strategic plans to address service delivery challenges, public works and aging infrastructure, parks and recreation services, and public safety, as well as other critical municipal services for more than 50 clients.

**Strategic Development** – Engaged with client communities to conduct a range of studies and identify best practices and implement solutions to address challenges and support long-term community sustainability. Developed feasible implementation plans for innovative approaches, based on direct knowledge of municipal operations and unique familiarity with local government fiscal constraints, regulatory requirements, labor impacts, and statutory guidelines.

**Regional/Shared Services Approaches** – As City Manager, worked to establish collaborative relationships and develop a shared-services approach to municipal and community service needs. Coordinator of data-driven implementation of integrated staffing and program management, including completion of workflow analysis and workload assessment.

### **Hands-on Municipal Management/Innovative Leadership** –

Worked directly with municipal officials to implement community goals through strong team leadership and successful management of personnel across departments and disciplines.

## Key Projects

### **Innovation in Infrastructure Financing**

- Utilized public-private partnerships and developed a performance-based contracting model
- Facilitated data-driven facilities and infrastructure analysis, developed detailed scopes of work
- Engaged City Council in infrastructure management processes including finance deliberations and performance contract reviews

## Education

BS, Public Administration;  
Public Management  
Concentration

Political Science Minor,  
James Madison University

## Professional Affiliations

Credentialed Manager,  
International City-County  
Managers Association

Named to 2016-2017 "Top  
100 Local Government  
Influencers"; Engaging  
Government Leaders

Member, Local Leaders  
Council, Smart Growth  
America

- Reduced first-floor vacancies from 50% to less than 15% in just five years
- Facilitated public and business engagement, and established a multi-year, grass roots redevelopment effort for the central business district

#### **Innovation in Infrastructure Financing**

- Utilized public-private partnerships and developed a performance-based contracting model
- Facilitated data-driven facilities and infrastructure analysis, developed detailed scopes of work
- Engaged City Council in infrastructure management processes including finance deliberations and performance contract reviews

#### **Permit and Financial Software Review**

- Facilitated conversion of City's financial, planning and permitting software from legacy and proprietary systems to a single source provider with a unified, comprehensive database and open software architecture, reducing customization and update costs
- Coordinated workflow analysis in impacted departments, developed system specifications, facilitated selection and procurement, coordinated deployment, adaptation and personnel training

#### **Comprehensive Plans**

- Town of Fayette, NY- Comprehensive Plan
- Town of Lyons, NY- Comprehensive Plan
- Town of Ontario, NY- Comprehensive Plan
- Village of Clyde, NY- Comprehensive Plan
- Village of Geneseo, NY- Comprehensive Plan Update

#### **Economic Development**

- Town of Bristol, NH- Economic Development Consulting
- City of Geneva, NY- Economic Development Services
- Livingston County, NY- Economic Development (Econ. Dev. and Tourism Plan)
- Village of Perry, NY- Economic Resilience Plan--New York Main Street
- Village of West Carthage, NY- Economic Resilience Plan
- Canandaigua Local Development Corporation, NY- Economic Development Services/Executive Management
- Geneva Local Development Corporation, NY - Economic Development Services FY2022
- City of Greenville, SC- Land Management Ordinance Update

Offers a passion for planning rooted in a desire to see natural and man-made systems form a sustainable and cohesive relationship. Advancement and innovative use of the built environment to provide dynamic solutions to complex issues relating to social, economic, and environment needs.

Knowledgeable of real estate development and planning practices, with the ability to comprehend and solve complex development related issues. Demonstrated proficiency in streamlining processes and creating synergies between historic preservation and economic development.



### Experience

**Planning and Zoning** - Approximately 10 years of planning and zoning experience including over 5 years as Director of Planning and Zoning for the City of Natchez, Mississippi. Provided streamlined and constructive oversight to hundreds of applications involving public hearings and administrative reviews. Instrumental to the implementation of multiple new and revised ordinances, city-issued RFPs and software applications.

**Master Planning** - Facilitated numerous stakeholder meetings during visioning sessions for a downtown revitalization planning effort, that led to identification of multiple code constraints. Held hearings before the Planning Commission and Board of Alderman to adopt Downtown Revitalization Plan. Utilized the adopted plan to push for code revisions and tax abatement incentives to reduce vacancy in Downtown Natchez.

**Code Revision** - Due to the update to the existing Comprehensive Plan for the Downtown District, significant rewrite to the City's Development Code was needed. Created a concise and easy-to-read table format. Worked to modernize the City with the revisions of existing and implementations of new codes and processes, including ordinances for the "Go-Cup" district and Mobile Food Vending, a waste collection RFP for the reestablishment of recycling in the community, and the implementation of cloud-based permitting software.

### Education

B.S. Urban Planning, Minor in Sustainability, Arizona State University

### Professional Affiliations

American Planning Association, member



Strategic advisor, executive, and economic development practitioner. Michael is a nationally-recognized expert on economic development trends and programs, and has supported communities in over half of the states in the U.S., across a range of community typography, from diverse, multi-county regions to individual rural villages. With experience in private sector real estate development, Michael brings a unique insight to our client-communities—providing valuable, actionable advice on how best to diversify the local economy, and facilitating communitywide conversations on development.



### Experience

**Target Industry and Cluster Analysis** – Developed and analyzed critical data supporting communities in attraction, expansion, and retention activities for targeted industries, and provided clients with a roadmap toward economic development objectives.

**Real Estate Development and Reuse** – Supported public and private sector clients in development of feasibility and development/reuse planning analyses to address goals associated with economic productivity of specific, targeted real estate assets. Provided competitiveness analysis and recommended uses and prospects for prospective sites and evaluation of incentives offered.

**Economic / Fiscal Impact Analysis** – Evaluated specific projects and general sectors for impacts associated with attraction, expansion, and/or retention of key employers and other economic assets. Provided cost-benefit analysis for incentives and other programs.

### Education

M.P.A., Maxwell School,  
Syracuse University

B.A. University of Minnesota,  
Morris

### Professional Affiliations

Certified Economic  
Developer, International  
Economic Development  
Council

New York State Economic  
Development Council

### Key Projects

#### **Economic and Fiscal Impact Studies—Industrial Development Agencies**

- Provided expert analysis of the economic and fiscal impacts of potential projects seeking incentive programs from IDAs for over a decade
- Created a standardized cost-benefit analysis model for use by the majority of IDAs across New York State

#### **Comprehensive and Strategic Planning**

- Supported development of an Organizational Strategic Plan for the New York State Economic Development Council; encouraging a pivot toward the organization's embracing of integration of traditional and non-traditional economic development approaches
- Developed Comprehensive Economic Development Strategies (CEDs) for North Central Region of New Jersey, GO Virginia Region 8, the Central Texas Council of Governments and other regional organizations.

Senior Civil Engineer with experience in designing and managing large civil infrastructure projects and associated project teams. Areas of expertise includes all aspects of planning, designing, construction oversight, and commissioning of projects up to \$200 million. Design experience includes water distribution and wastewater conveyance, civil site design associated with land development, aviation terminal layout and design, airfield pavements, building layout and design, and MEP coordination.



## Experience

### Civil Engineering

Consulting Engineer of Record for commercial, industrial, and municipal projects. Areas of expertise include water and wastewater design as well as civil site design associated with land development. Additional duties include, permitting, project management, client management, billing and oversight of staff engineers.

### Project Programming

Extensive knowledge of planning and programming of infrastructure projects, including facilitating design charrettes, preliminary planning, gathering stakeholder input, alternative analysis, cost estimating, and evaluating contract executing strategies. Planning and programming experience includes establishing project requirements, gathering stakeholder input, alternative analysis, and contract execution strategies.

## Key Projects

### Municipal Site Planning/Design

- South Carolina State Ports Authority, Container Yard Modifications, Charleston, SC (Project Manager)
- South Carolina State Ports Authority, Reefer Facilities- Charleston, SC (Project Manager)
- South Carolina State Ports Authority Columbus Street Terminal Water Service Addition- Charleston, SC (Project Manager, Construction Management)
- South Carolina State Ports Authority, Building 311 Electrical Service- Charleston, SC (Project Manager)
- South Carolina State Ports Authority, Installation of Yard Management System- Charleston, SC (Project Manager)
- South Carolina State Ports Authority, Security Improvements to Georgetown Terminal- Georgetown, SC (Project Manager)

## Education

M.S., Civil Engineering,  
Clemson University, 2002

B.S., Civil Engineering, The  
Citadel, 2001

## Professional License

Professional Engineer:  
South Carolina 25068  
Georgia PE049748  
Florida 95695









## Project Understanding

The Town of Yemassee is within the heart of South Carolina's Lowcountry, an environment with rich history and diverse ecosystems. Our firm has a strong history within the region working with adjacent communities; we understand how critical this plan will be for the future of the Town and the implications in the region.

## Why Plan?

A comprehensive plan is a multi-year road map, designed to support a community in managing growth and development, and ensuring that local government operations are designed to support an overarching community vision.

No matter where you are, communities are experiencing market pressures. In many communities, the pressures are downward—population and investment loss. In more fortunate communities, development pressure means addressing a high level of investor interest and significant demand relative to population growth.

In both cases (and everywhere in between), communities must be intentional. Great places don't happen by accident. A strong comprehensive plan will identify the assets and challenges ahead of your community, and outline a set of strategies to deal with whatever market pressure you are facing.

## Comprehensive Plan Pillars

The MRB Group planning approach stands on three critical planning pillars:

- **A Strong Base of Data:** A plan that is built on strong, reliable data is already halfway home to achieving its vision. MRB Group invests heavily in demographic and market data sets to provide the community with clarity around market position and demographic trends.
- **Shaped by Public Engagement:** Authentic, robust, meaningful public engagement will create plan champions in the community, and make implementation efforts smooth and effective.
- **A Relentless Focus on Implementation:** The MRB Group team is practitioner based—which is to say that we have been in decision making seats for most of our careers. We are former local government managers, planners, economic developers, finance officers, and elected officials. With every recommendation, we ask ourselves—“how will the community get this done at the ground level?” Our team of experienced community planners and local government practitioners will facilitate the update of the comprehensive plan by performing the Scope of Services detailed below.

### VISION

An authentic but aspirational statement about the ideal condition of the community spanning years into the future.

### CORE VALUES

A set of measures by which you will evaluate all future projects, programs, and investments. The community's DNA.

### KEY INITIATIVES

Priority policy areas that require the most focus during implementation.



## Our Approach

The MRB Group general approach to comprehensive planning leans on the experience of our team who understands the operational, financial, and logistical challenges local governments face. Recommendations are tailored to implementation, providing for the specific needs of the community.

### PROJECT CHARTERING

Create a charter to serve as a guide for the project to include: schedule, key milestones, deliverable descriptions, communication plan, and steering committee matrix.

### INVENTORY & ANALYSIS

Collect demographic and market data, review recent and other relevant plans, interview key stakeholders, and gain Town leadership perspectives.

### PUBLIC ENGAGEMENT

Develop a public engagement plan to include: community surveying, digital/social media platforms, public forums, public events, and an app for instant input.

### VISION & VALUES

Identify a unified vision for the future of the Town and identify core values against which leadership can assess future opportunities.

### STRATEGIES & KEY INITIATIVES

Develop overarching strategies to address key initiatives identified by the Town.

### IMPLEMENTATION STRATEGY

Identify specific policies, programs, and projects that can be initiated in the first five years of the planning horizon, creating initial momentum.

### INITIAL DRAFT PLAN

Assemble elements from prior tasks to create a draft plan, host a public forum to showcase plan elements and catalogue any public feedback.

### FINAL DRAFT PLAN

Synthesize comments from Town leadership to prepare the final plan for adoption.

## Scope of Services

As outlined in the RFP, MRB Group proposes the following Scope of Services.

### A. Project Chartering

The successful execution of any planning effort is built upon a shared set of expectations relative to project delivery. The project chartering effort is designed to familiarize the entire project team with the project approach and to gain an agreement amongst all project partners on how to proceed.

#### **Deliverables:**

1. Kickoff Meeting: Project chartering will commence with a virtual kickoff meeting of the project stakeholders, including key Town staff, Town Officials and representatives of the MRB project team.
2. Steering Committee: With the help of the Town staff, MRB Group will facilitate the formation of project Steering Committee, if desired by the Town. Town Staff or the selected Steering Committee will be the primary point of contact and recipient of project deliverables.

### B. Inventory and Analysis

Our team of local government management professionals will work with Town Staff to compile all relevant documents, past plans, and current data for the community to develop a clear picture of current conditions in the Town of Yemassee.

#### **Deliverables:**

1. Planning Foundations Report: Our team will perform a review of the local and regional long-range planning documents mentioned above to develop a picture of congruence with development goals outlined in the Town of Yemassee's current Comprehensive Plan.

### C. Public Engagement Session

We will work with Town Staff to identify a convenient, accessible space to schedule one (1) public engagement session with a visioning component. We will work with the Town to advertise the session through multiple mediums so the largest sample of the population is engaged. The information gained at this in-person community meeting will provide us with an expansive data set from which the challenges, issues, opportunities, goals and objectives will be envisioned within a Comprehensive Plan.

#### **Deliverables:**

1. Public Forum: MRB Group has developed a broad catalogue of public engagement exercises which we will review with Town staff. At the public engagement session, MRB staff will detail the objectives of the session and engage the public in exercises to solicit feedback from the public.
2. Visioning Session: During the public forum, a visioning session will be conducted, as key stakeholders, town officials, staff, and the general public will be able to voice the most urgent community issues and challenges. At that time the public will be encouraged to come and learn about how the Comprehensive Plan will affect them and how their voice is valuable in the process.
3. Public Engagement Session Report: Included with the Comprehensive Plan and drafts will be a report based on information gained during the public engagement portion of this project. This report will include the main issues and recommendations gathered at the public forum. Each issue and recommendation will be accompanied by an assessment by MRB staff to gauge its merit and applicability.

#### **D. Initial Development of Plan Elements**

We will synthesize the recommendations and comments received by Town staff, Town Council, Steering Committee, and the public engagement and visioning sessions, to develop the initial drafts for the Comprehensive Plan.

##### ***Deliverables:***

1. Comprehensive Plan Draft: Using information and data gained from previous steps, our team will compose a draft plan that complies with the South Carolina Local Government Comprehensive Enabling Act of 1994 and latest legislative requirements. The draft plan will provide a statement of needs, goals, and objectives; implementation strategies; and timelines for the following elements:

- Executive Summary
- Overview and brief history of the Town of Yemassee
- Inventory of existing conditions
- Population
- Economic Development
- Natural Resources
- Cultural Resources
- Community Facilities
- Housing
- Land Use
- Transportation
- Priority Investment
- Resiliency

#### **E. Refining Drafts**

Working with the Steering Committee, we will refine the draft plan so that current issues and opportunities are addressed and the Comprehensive Plan paints a vision that reflects the goals and objectives of the community.

##### ***Deliverables:***

1. Second Draft of Comprehensive Plan: The second draft will be a synthesized version, encapsulating all applicable inputs of data and recommendations. The text, visuals, and data will be organized in a manner that can be understood by planning professionals, as well as the general public.

2. Final Edits: After review of the second draft, any additional revisions to the document will be done and submitted to staff to be reviewed and approved by the Town.

#### **Additional Services**

The following items, not included in the above services can be provided on a personnel time-charge basis, but would only be performed upon receipt of your authorization.

- A. Adoption support (Visits to Yemassee)
- B. Drafting amendments to zoning ordinances
- C. Town Council or Commission training
- D. Additional public engagement sessions







**Inventory &  
Analysis****Months 1-3**

A deep study of the demographic and market data that will help establish a starting point from which to plan.

**Community  
Visioning****Months 4-5**

Creating a clear, unified picture of where the community should be ten years into the future.

**Key Initiative  
Development****Months 6-7**

A series of larger, policy area goals on which the community should focus to accelerate you toward realizing your vision.

**Implementation  
Strategy****Month 8**

The what, who, and when—what you should do, who should lead the effort, and when should it be achieved.

**Adoption****Months 9-11**

Getting the plan formally on the books and ready for implementation.



Task	Cost
<b>1. Project Chartering</b>	
Kick-off Meeting Steering Committee Formation	\$2,285
<b>2. Inventory and Analysis</b>	
Review of all agreements, current land use plans, local tax structure, and any other documents relevant to current conditions Planning Foundations Report	\$3,975
<b>3. Public Engagement Session</b>	
Public Forum Visioning Session Public Engagement Sessions Report	\$16,390
<b>4. Initial Development of Plan Elements</b>	
Comprehensive Plan Draft	\$12,060
<b>5. Refining Drafts</b>	
Second Draft of Comprehensive Plan Final Edits	\$5,290
<b>Total Compensation</b>	<b>\$40,000</b>

The cost figures shown above represent our lump sum amount. Any additional work beyond this fee and outside the scope of this proposal would be reviewed with the Client. MRB Group shall submit monthly statements for services rendered during each invoicing period based on the efforts performed during that period. MRB Group Standard Rates are subject to annual adjustment.







## TOWN OF CLOVER, SC



### Description

MRB Group has been selected (January 2023) to partner with the Town of Clover to update the Housing and Land Use Elements of the Town of Clover Comprehensive Plan. Our team of experienced community planners and local government practitioners will facilitate the update through tasks that include reviewing conditions and previous planning efforts, organizing public participation, developing the required plan elements, and providing deliverables in tandem with efforts of the Catawba Regional Council of Governments.

Specific services will include:

- Project Chartering- kickoff meetings, steering committee formation
- Inventory and Analysis- planning foundation reports
- Public Engagement Sessions- public forums, charette sessions, public engagements sessions report, regulatory strategy report
- Initial Development of Plan Efforts- housing element draft, land use element draft (including second drafts)
- Delivery and Adoption Support- final edits and presentation to Town Council

### Client Contact

Allison Harvey, Town  
Administrator  
E: [aharvey@cloversc.org](mailto:aharvey@cloversc.org)  
P: 803-222-9495

## VILLAGE OF HILTON, NY



## Description

MRB Group's familiarity and long-standing relationship with the Village of Hilton made our professional staff uniquely qualified to assist in updating the Village's Comprehensive Plan.

Village leadership identified a critical need to update the community's Comprehensive Plan, adopted in the late 1970's. MRB Group's local government services team worked with a special steering committee to design a process for updating the Village's Comprehensive Plan; providing a shared vision for the future of the community.

The Village of Hilton Comprehensive Plan process developed a clear course for Hilton's future. The planning framework consisted of a strong vision and core values supported by realistic principles, goals, and objectives.

A central component of the plan includes targeted area plans – detailed plans for five different locations in the village that the community would like to see re-envisioned. These spaces included neighborhood village mixed-use, trail corridors, infill redevelopment, and streetscape design. Each area plan was featured on a project page with supporting narrative, graphics, description of key elements, and timeline for implementation.



## ENVISION HILTON 2030 (CONTINUED)

The Village engaged residents throughout the life of the planning process. As part of the community engagement process, the Steering Committee and MRB Group developed a robust Public Participation Plan to ensure community participation in establishing a community vision and long-range plan for all aspects of community development.

The comprehensive plan update process, guided by a diverse representation of the community, and supported by MRB Group's robust planning, engineering, and local government operations expertise, successfully:

- Identified key community stakeholders to ensure strong engagement throughout development of the plan;
- Created a set of feedback loops, including a dedicated project website, interactive community forums, and a community survey specifically designed to support this project;
- Facilitated a community visioning process that identifies a unified, long-range vision for the community, a set of core values to guide decision making, and a series of key area plans to ensure progress toward the community vision;
- Developed a StoryMap – a visual journey of the planning process, targeted area plans, and outcomes.

**ONLINE PLAN:** [www.hiltonny.org](http://www.hiltonny.org)

### Client Contact

Shari Pierce, Village Administrator  
Ph: (585) 392-4144  
[envisionhilton2030.org](http://envisionhilton2030.org)

### Services

- Comprehensive Plan
- Public Engagement
- Strategic Planning



## TOWN OF OVID, NY

MRB Group was selected to assist the Town of Ovid in developing a new Comprehensive Plan for the community. In partnership with Environmental Design and Research (EDR), a firm specializing in waterfront resources, MRB Group continues to work closely with a Steering Committee appointed by the Town Board.

In hopes of addressing a decade-long debate among residents over the proposed use of zoning in the Town, the plan's community outreach revealed a near-even split in public opinion. Ultimately, it was determined that the community was not yet ready to embrace zoning as a means of regulating land use.

MRB Group's clear process path facilitated creation of implementable goals and objectives. Deliverables included public presentations, and a multi-media outreach plan, including a dedicated webpage and communication portal for enhanced participation.

## RESULTS

The plan was adopted by the Town in the fall of 2018. The process provided:

- Consensus on community character, and a clear understanding of core values and strengths.
- A vision for the future of Ovid, helping the community attract and encourage development.
- Examination of existing land use, infrastructure capacity, and current challenges, along with recommendations for:

- a mechanism for notification to Town personnel regarding proposed development
- attention to the Town's most significant assets (waterfronts along both Cayuga Lake and Seneca Lake)
- support for Smart Growth principles

- Recommendations to explore local government initiatives and potential external funding resources to encourage community investment.
- A concise, understandable, dynamic Comprehensive Plan document – that will serve as a “litmus test” for Town and Planning Board decision-making, and a marketing tool for future development.



## Client Contact

Joseph Borst,  
Town Councilman  
Ph: (607) 882-1102  
[www.townofovidcomprehensiveplan.org](http://www.townofovidcomprehensiveplan.org)



## CITY OF HILLSBORO, TX

## Description

Located in the Heart of Texas, the City of Hillsboro continues to grow. Its location on the I-35 corridor and proximity to larger cities and amenities makes Hillsboro sought after by people looking to move away from larger metropolitan areas. Because the City recognized the importance of being proactive in managing the impact of this new growth, it partnered with MRB Group to write and facilitate the City's first Strategic Plan.

MRB led a planning effort that reflected a community-driven process which was the backbone for developing the Plan and, ultimately, the actions that the City will use to carry it forward. Using the community's input, MRB worked with Council and Staff Leadership to develop a consensus on a three-to-five-year Plan that establishes the purpose of the City, its vision for the future, how it does business, and citywide goals.

- *Community Snapshot.* MRB conducted a **market analysis** for the City to determine current economic conditions and a **subsequent workshop** with Staff Leadership to discuss current issues that they encounter during day-to-day operations. Finally, they developed a cohesive direction as a leadership team.
- *Community Survey and Public Meetings.* The Team distributed a **community survey** allowing citizens to provide feedback on various topics, including their vision for Hillsboro, their values, and the strengths and weaknesses of the City. **The purpose of this meeting was to communicate the strategic planning process and receive input from the community.** In addition, the Team held a second public meeting to report the results from the survey and the first meeting and provide another opportunity for their input.
- *Council and Staff Leadership Workshops.* MRB facilitated two workshops with the Council and Staff Leadership where the City reviewed the input from the community and worked together to develop a **Vision and Mission Statement**, identify **Core Values**, and discuss **Goals, Strategies**, and **Actions**. The City also collaborated to **prioritize and develop a consensus** on the Plan's strategies and actions.

The City adopted the Plan on June 21, 2022.

## Client Contact

Megan Henderson, City Manager  
P: 254-582-3271

## Services

- Targeted Market Analysis
- Public Engagement
- Strategic Planning



## CITY OF BEAUFORT, SC

**DESCRIPTION**

The City of Beaufort offers residents an attractive quality of life, and a vibrant commercial landscape within a notable historical district. A magnet for families, military, and retirees alike, Beaufort is a noted destination for business, living, and recreation, and the operations of their municipal services supports this continued appeal.

With the loss of the Community Development Director, the City wanted to take a measured approach to selecting the right candidate, but did not have the luxury of losing the capacity of service, as there were also other vacancies in the department. MRB Group was able to offer a solution in filling this critical staff role of Community Development Director while also supporting a thorough search for qualified applicants to the positions of both the Director and Senior Planner.

Fulfilling a contract for 'Interim Planning Services,' one of MRB Group's Senior Planning Associates acts as the Administrator, performing duties as laid out in the Beaufort City Code and supporting normal day-to-day operations of the Planning Department which includes, but is not limited to:

- Implementation of key long-range planning principles, goals, and objectives in the City's Civic Master Plan, Strategic Plan, and Comprehensive Plan.
- Coordinating with the daily onsite department supervisor.
- Acting as Administrator on pending and incoming projects.
- Reviewing staff reports for technical accuracy.
- Attend committee, board, and commission meetings either virtually or in person as required, keeping the City Manager and Deputy fully informed of any recommendations.

**Client Contact**

Reece Bertholf,  
Deputy City Manager  
City of Beaufort  
Ph: 843-379-7525

**Services**

- Interim Administrative Duties
- Transition Assistance



March 28, 2023

Matthew Garnes, Town Administrator  
Town of Yemassee  
101 Town Circle  
Yemassee, SC 29945

**RE: TOWN OF YEMASSEE – PROJECT SCHEDULE  
MRB GROUP PROJECT NO. 3950.23005.000**

Mr. Garnes:

To set clear expectations and ensure that the project stays on track, this letter includes a project schedule. The draft schedule is as follows below.

Project Step	Deliverable(s)	Deadline Date
Kick-off Meeting	Project Schedule	4/3/23
Inventory and Analysis	Planning Foundations Report	5/31/23
Public Engagement	Public Engagement	July 2023 (Exact date TBD)
Analysis of Public Engagement	Analysis of Charrette Sessions	August 2023
Initial Draft of Plan Elements	Draft Plan Elements	September – November 2023
Refining of Plan Elements	Second Draft of Plan Elements	November – December 2023
Delivery and Adoption Support	Final Plan Elements	January – February 2024

MRB Group understands that the development of these critical documents takes careful planning, review and consideration. The deadlines and dates are subject to change, but only upon a mutual agreement between the MRB Group Project Manager and Town Staff.





Matthew Garnes, Town Administrator

**TOWN OF YEMASSEE - PROJECT SCHEDULE**

March 28, 2023

Page 2 of 2

If you have any questions or comments about the project schedule or any other information, please reach out to us.

Sincerely,

Riccardo Giani  
Senior Planning Associate

c: Heather Simmons Jones – Director of Southeast Operations